202 Accepted Notebook (2026 - 2027)

Mục lục

1 Math 1
- 1.1 Sequences . . . 1
- 1.2 Combinatoric . . . 2
- 1.3 Number of spanning tree . . . 2
- 1.4 Series . . . 2
- 1.5 Geometry . . . 2
- 1.6 Pick's Theorem . . . 3
- 1.7 Erdos Gallai Theorem . . . 3

2 Programming 3
- 2.1 Pragma . . . 3

3 Flow and Matching 3
- 3.1 Maximum Flow (Dinic) . . . 3
- 3.2 Dinic (Template by Tran Khoi Nguyen) . . . 3
- 3.3 Min Cut (Template by Tran Khoi Nguyen) . . . 3
- 3.4 Maximum Matching (HopCroft - Karp) . . . 4
- 3.5 Maximum Matching (Template by Tran Khoi Nguyen) . . . 4
- 3.6 Maximum Matching ($O(n^2)$) . . . 5
- 3.7 Min Cost Flow . . . 5
- 3.8 Min Cost Flow (Template by Tran Khoi Nguyen) . . . 6
- 3.9 General Graph Matching . . . 6

4 Geometry 7
- 4.1 Smallest Circle - Emo Welzl (Contain all points) . . . 7
- 4.2 Closest pair of points in set . . . 7
- 4.3 Manhattan MST . . . 8
- 4.4 Geometry with real number . . . 8

5 Numerical algorithms 10
- 5.1 SQRT For Loop . . . 10
- 5.2 Rabin Miller - Prime Checker . . . 10
- 5.3 Chinese Remain Theorem . . . 10
- 5.4 Pollard Rho - Factorialize . . . 10
- 5.5 FFT . . . 11
- 5.6 FFT (Mod 998244353) . . . 11
- 5.7 FFT Mod (Template by Tran Khoi Nguyen) . . . 11
- 5.8 Fast Walsh-Hadamard Transform (FWHT) . . . 12
- 5.9 Fast Walsh-Hadamard Transform (FWHT Base m) . . . 12
- 5.10 Count Primes . . . 12
- 5.11 Interpolation (Mod a prime) . . . 12
- 5.12 Bignum . . . 13
- 5.13 Bignum with FFT multiplication . . . 13
- 5.14 Tonelli Shanks (Find square root modulo prime) . . . 14
- 5.15 Discrete Logarithm (Find x that $a^x \equiv b \ (mod\ m)$) . . . 14
- 5.16 Primitive Root (Exist k that $g^k \equiv a \ (mod\ n)$ for all a) . . . 14
- 5.17 Discrete Root (Find x that $x^k \equiv a \ (mod\ n)$, n is a prime) . . . 15
- 5.18 Super Sieve of Primes (Code by RR) . . . 15

6 Graph algorithms 15
- 6.1 Twosat (2-SAT) . . . 15
- 6.2 Eulerian Path . . . 16
- 6.3 Biconnected Component Tree . . . 16

7 String 16
- 7.1 Palindrome Tree . . . 16
- 7.2 Suffix Array . . . 16
- 7.3 Suffix Array (Template by Tran Khoi Nguyen) . . . 17
- 7.4 Aho Corasick - Extended KMP . . . 18
- 7.5 Aho Corasick (Template by Tran Khoi Nguyen) . . . 18
- 7.6 Suffix Tree (Template by Tran Khoi Nguyen) . . . 19
- 7.7 Z Function . . . 19

8 Data structures 19
- 8.1 Ordered Set . . . 19
- 8.2 Fenwick Tree (With Walk on tree) . . . 19
- 8.3 Convex Hull Trick (Min) . . . 19
- 8.4 Dynamic Convex Hull Trick (Min) . . . 20
- 8.5 SPlay Tree . . . 20
- 8.6 Hashing (Template by Tran Khoi Nguyen) . . . 21
- 8.7 BIT 2D (Template by Tran Khoi Nguyen) . . . 21
- 8.8 Wavelet Tree . . . 21

1 Math

1.1 Sequences

Catalan Numbers (OEIS A000108)

$$C_n = \frac{1}{n+1}\binom{2n}{n} = \frac{(2n)!}{(n+1)!n!}, \quad C_0 = 1$$

Recurrence:

$$C_{n+1} = \sum_{i=0}^{n} C_i\, C_{n-i}$$

.

Generating function:

$$C(x) = \frac{1-\sqrt{1-4x}}{2x}$$

.

Applications (exact meanings):

- Number of valid parenthesis expressions with n pairs.
- Number of monotonic lattice paths from $(0,0)$ to (n,n) staying below the diagonal.
- Number of triangulations of a convex polygon with $n+2$ vertices.
- Number of full binary trees with $n+1$ leaves.
- Number of noncrossing partitions of an n-element set.

—

Bernoulli Numbers (OEIS A027641)

$$\frac{x}{e^x-1} = \sum_{n=0}^{\infty} B_n \frac{x^n}{n!}, \quad B_0 = 1,\ B_1 = -\frac{1}{2},\ B_{2m+1} = 0\ (m \geq 1)$$

Key formulas:

$$\sum_{k=1}^{n} k^p = \frac{1}{p+1}\sum_{j=0}^{p}\binom{p+1}{j} B_j n^{p+1-j}$$

$$\zeta(2m) = (-1)^{m+1}\frac{(2\pi)^{2m}}{2(2m)!}B_{2m}$$

Applications (precise uses):

- Compute closed-form sums of powers up to degree p.
- Evaluate Riemann zeta at even positive integers.
- Correct high-order error in Euler–Maclaurin summation for n-term truncation.

—

Stirling Numbers of the First Kind (signed) (OEIS A048994)

$$f_n(x) = x(x-1)\cdots(x-n+1) = \sum_{k=0}^{n} s(n,k)\, x^k$$

Recurrence:

$$s(n,k) = s(n-1,k-1) - (n-1)s(n-1,k),\ s(0,0) = 1$$

Applications:

- $|s(n,k)|$: number of permutations of n elements with exactly k cycles.
- Convert falling factorial basis $f_n(x)$ to power basis x^k for degree n polynomials.

—

Stirling Numbers of the Second Kind (OEIS A008277)

$$x^n = \sum_{k=0}^{n} S(n,k)\, f_k(x), \quad S(n,k) = kS(n-1,k) + S(n-1,k-1), \quad S(0,0) = 1$$

Closed form:

$$S(n,k) = \frac{1}{k!}\sum_{j=0}^{k}(-1)^{k-j}\binom{k}{j} j^n$$

Applications:

- Number of ways to partition an n-element labeled set into k nonempty unlabeled blocks.
- Number of surjective functions from n elements onto k labeled elements ($= k!S(n,k)$).
- Coefficients when expanding monomials x^n into falling factorial basis $f_k(x)$.

—

Bell Numbers (OEIS A000110)

$$B_n = \sum_{k=0}^{n} S(n,k), \quad \sum_{n=0}^{\infty}\frac{B_n}{n!}x^n = e^{e^x-1}$$

Dobinski's formula:

$$B_n = \frac{1}{e}\sum_{m=0}^{\infty}\frac{m^n}{m!}$$

Applications:

- Number of all set partitions of an n-element set.
- Number of equivalence relations on an n-element set.
- Number of ways to cluster n labeled objects into any number of groups.

—

Eulerian Numbers (OEIS A173018)

Let $A(n,k)$ = number of permutations of $\{1,\ldots,n\}$ with exactly k ascents.
Recurrence:

$$A(n,k) = (n-k)A(n-1,k-1) + (k+1)A(n-1,k), \quad A(1,0) = 1$$

Exponential generating function:

$$\sum_{n,k\geq 0} A(n,k)\frac{t^n}{n!}x^k = \frac{1-x}{1-xe^{t(1-x)}}$$

Applications:

- $A(n,k)$: number of permutations of length n with exactly k descents.
- Coefficients of Eulerian polynomial $A_n(x) = \sum_{k=0}^{n-1} A(n,k)x^k$.
- Expected number of descents in random permutation of length n: $(n-1)/2$.

—

Computation notes:

- Catalan: compute via factorials mod p.
- Stirling (1st/2nd): dynamic programming in $O(n^2)$.
- Bell: sum $S(n,k)$ over k.
- Eulerian: DP with recurrence above.
- Bernoulli: Akiyama–Tanigawa algorithm for small n.

1.2 Combinatoric

Basic: Binomial & Multinomial

$$(1-x)^{-a} = \sum_{k=0}^{\infty} \binom{a+k-1}{k} x^k \ (|x|<1).$$

$$\binom{-a}{k} = (-1)^k \binom{a+k-1}{k},$$

$$\sum_{k=0}^{n} \binom{n}{k} = 2^n, \quad \sum_{k=0}^{n} k\binom{n}{k} = n\,2^{n-1}, \quad \sum_{k=0}^{n} k^2\binom{n}{k} = n(n+1)2^{n-2}.$$

Hockey-stick (Christmas stocking)

$$\sum_{i=r}^{n} \binom{i}{r} = \binom{n+1}{r+1} \qquad (0 \le r \le n).$$

Vandermonde (binomial convolution)

$$\sum_{k} \binom{r}{k}\binom{s}{n-k} = \binom{r+s}{n} \qquad (n \in \mathbb{Z}).$$

Notable corollary: $\sum_{k=0}^{n} \binom{n}{k}^2 = \binom{2n}{n}$.

Chu–Vandermonde (negative coefficients form)

$$\sum_{k=0}^{n} \binom{a}{k}\binom{b}{n-k} = \binom{a+b}{n} \quad (a,b \in \mathbb{R}),$$

use $\binom{-m}{k} = (-1)^k\binom{m+k-1}{k}$ to handle "selection with replacement".

Multinomial polynomial

$$(x_1 + \cdots + x_m)^n = \sum_{k_1+\cdots+k_m=n} \binom{n}{k_1,\ldots,k_m} \prod_{i=1}^{m} x_i^{k_i},$$

$$\binom{n}{k_1,\ldots,k_m} = \frac{n!}{\prod_i k_i!}, \qquad \sum_{k_1+\cdots+k_m=n} \binom{n}{k_1,\ldots,k_m} = m^n.$$

Binomial transform

$$g_n = \sum_{k=0}^{n} \binom{n}{k} f_k \iff f_n = \sum_{k=0}^{n} (-1)^{n-k}\binom{n}{k} g_k.$$

Power form: $\sum_{k=0}^{n} (-1)^k \binom{n}{k} k^m = 0$ for $0 \le m < n$.

Power sum via Bernoulli (Faulhaber)

$$\sum_{k=1}^{N} k^p = \frac{1}{p+1} \sum_{j=0}^{p} \binom{p+1}{j} B_j \, N^{p+1-j},$$

B_j is Bernoulli.
Special cases for small n:

$$1 + 2 + 3 + \cdots + n = \frac{n(n+1)}{2}$$

$$1^2 + 2^2 + 3^2 + \cdots + n^2 = \frac{n(2n+1)(n+1)}{6}$$

$$1^3 + 2^3 + 3^3 + \cdots + n^3 = \frac{n^2(n+1)^2}{4}$$

$$1^4 + 2^4 + 3^4 + \cdots + n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$

Permutations with fixed points

$$\left|\bigcup_{i=1}^{m} A_i\right| = \sum_{j\ge 1} (-1)^{j-1} \sum_{1\le i_1<\cdots<i_j\le m} |A_{i_1} \cap \cdots \cap A_{i_j}|.$$

Derangements (permutations with zero fixed points):

$$!\,0 = 1, \quad !\,1 = 0, \quad !\,m = (m-1)\big(!\,(m-1) + !\,(m-2)\big),$$

and the inclusion–exclusion form

$$!\,m = m! \sum_{i=0}^{m} \frac{(-1)^i}{i!}.$$

Count of permutations $\pi \in S_n$ with exactly k fixed points:

$$R(n,k) = \binom{n}{k} !\,(n-k),$$

Related to Stirling

Let $f_n(x) = x(x-1)\cdots(x-n+1)$.

$$f_n(x) = \sum_{k=0}^{n} s(n,k) x^k, \qquad x^n = \sum_{k=0}^{n} S(n,k)\, f_k(x).$$

Number of surjective maps $[n] \twoheadrightarrow [k]$: $k!\,S(n,k) = \sum_{j=0}^{k} (-1)^j \binom{k}{j} (k-j)^n$.

Some common alternating sums

$$\sum_{k=0}^{n} (-1)^k \binom{n}{k} = 0 \ (n \ge 1), \quad \sum_{k=0}^{n} (-1)^k \binom{r+k}{k} = (-1)^n \binom{r}{n}.$$

Central coefficient & approximation

$$\binom{2n}{n} = \sum_{k=0}^{n} \binom{n}{k}^2, \qquad \binom{2n}{n} \sim \frac{4^n}{\sqrt{\pi n}}.$$

1.3 Number of spanning tree

Create an $N \times N$ matrix `mat`, and for each edge $a \to b \in G$, do `mat[a][b]--`, `mat[b][b]++` (and `mat[b][a]--`, `mat[a][a]++` if G is undirected). Remove the ith row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).

1.4 Series

Basic Series (Maclaurin/Taylor around 0)

$$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!} \quad (\forall x), \qquad \ln(1+x) = \sum_{n=1}^{\infty} \frac{(-1)^{n-1}x^n}{n} \quad (|x|<1)$$

$$\frac{1}{1-x} = \sum_{n=0}^{\infty} x^n \quad (|x|<1), \qquad \frac{1}{1+x} = \sum_{n=0}^{\infty} (-1)^n x^n \quad (|x|<1)$$

$$(1+x)^\alpha = \sum_{n=0}^{\infty} \binom{\alpha}{n} x^n, \quad \binom{\alpha}{n} = \frac{\alpha(\alpha-1)\cdots(\alpha-n+1)}{n!} \quad (|x|<1)$$

Trigonometric & Hyperbolic

$$\sin x = \sum_{n=0}^{\infty} (-1)^n \frac{x^{2n+1}}{(2n+1)!}, \quad \cos x = \sum_{n=0}^{\infty} (-1)^n \frac{x^{2n}}{(2n)!} \quad (\forall x)$$

$$\sinh x = \sum_{n=0}^{\infty} \frac{x^{2n+1}}{(2n+1)!}, \quad \cosh x = \sum_{n=0}^{\infty} \frac{x^{2n}}{(2n)!} \quad (\forall x)$$

Use Bernoulli to quickly remember fractional series:

$$\tan x = \sum_{m=1}^{\infty} \frac{(-1)^{m-1} 2^{2m}(2^{2m}-1) B_{2m}}{(2m)!} x^{2m-1} \quad (|x| < \tfrac{\pi}{2})$$

$$x\cot x = 1 - \sum_{m=1}^{\infty} \frac{2^{2m} B_{2m}}{(2m)!} x^{2m} \quad (0 < |x| < \pi)$$

Inverse Trigonometric & Logarithmic

$$\arctan x = \sum_{n=0}^{\infty} \frac{(-1)^n x^{2n+1}}{2n+1} \quad (|x| \le 1,\ x \ne \pm i)$$

$$\arcsin x = \sum_{n=0}^{\infty} \frac{\binom{2n}{n}}{4^n(2n+1)} x^{2n+1} \quad (|x|<1), \quad \arccos x = \frac{\pi}{2} - \arcsin x$$

$$\ln(1-x) = -\sum_{n=1}^{\infty} \frac{x^n}{n} \quad (|x|<1), \qquad \ln\frac{1+x}{1-x} = 2\sum_{n=0}^{\infty} \frac{x^{2n+1}}{2n+1} \quad (|x|<1)$$

Generating Series & Fast Combinatorics

$$\frac{1}{(1-x)^\alpha} = \sum_{n=0}^{\infty} \binom{\alpha+n-1}{n} x^n \quad (|x|<1)$$

$$\ln\frac{1}{1-x} = \sum_{n=1}^{\infty} \frac{x^n}{n} \quad (|x|<1), \qquad \frac{x}{1-e^{-x}} = \sum_{n=0}^{\infty} \frac{B_n}{n!} x^n \quad (|x|<2\pi)$$

Infinite Products (useful for checking/transformation)

$$\sin(\pi x) = \pi x \prod_{n=1}^{\infty} \left(1 - \frac{x^2}{n^2}\right), \qquad \frac{\sinh(\pi x)}{\pi x} = \prod_{n=1}^{\infty} \left(1 + \frac{x^2}{n^2}\right)$$

1.5 Geometry

Distance from a point to a line

Given a point $P(x_0, y_0)$ and a line $d:\ ax + by + c = 0$:

$$\mathrm{d}(P,d) = \frac{|ax_0 + by_0 + c|}{\sqrt{a^2+b^2}}.$$

Distance between two lines

Two parallel lines: $d_1:\ ax + by + c_1 = 0$, $d_2:\ ax + by + c_2 = 0$:

$$\mathrm{d}(d_1,d_2) = \frac{|c_1 - c_2|}{\sqrt{a^2+b^2}}.$$

1.6 Pick's Theorem

Pick's Theorem relates the area of a polygon with integer coordinates: Let S = area of polygon, I = number of integer points inside polygon, B = number of integer points on polygon boundary
Then: $S = I + \frac{B}{2} - 1$

1.7 Erdos Gallai Theorem

A simple graph with node degrees $d_1 \geq \cdots \geq d_n$ exists iff $d_1 + \cdots + d_n$ is even and for every $k = 1 \ldots n$:

$$\sum_{i=1}^{k} d_i \leq k(k-1) + \sum_{i=k+1}^{n} \min(d_i, k).$$

2 Programming

2.1 Pragma

```
#pragma GCC optimize("O3,unroll-loops")
#pragma GCC target("avx2,bmi,bmi2,popcnt,lzcnt")
```

3 Flow and Matching

3.1 Maximum Flow (Dinic)

```
// In case we need to find Maximum flow of network with both
     minimum capacity and maximum capacity, let s* and t* be
     virtual source and virtual sink.

/*
Then, each edge (u->v) with lower cap l and upper cap r will be
     changed in to 3 edge:

- u->v whit capacity r-l
- u->t* with capacity l
- s*->v with capacity l
*/

// We need add one other edge t->s with capacity Inf
// Maximum Flow on original graph is the Maximum Flow on new graph
     : s*->t*

struct Edge
{
    int u, v;
    ll c;
    Edge() {}
    Edge(int u, int v, ll c)
    {
        this->u = u;
        this->v = v;
        this->c = c;
    }
};
struct Dinic
{
    const ll Inf = 1e17;
    vector<vector<int>> adj;
    vector<vector<int>::iterator> cur;
    vector<Edge> s;
    vector<int> h;
    int sink, t;
    int n;
    Dinic(int n)
    {
        this->n = n;
        adj.resize(n + 1);
        h.resize(n + 1);
        cur.resize(n + 1);
        s.reserve(n);
    }
    void AddEdge(int u, int v, ll c)
    {
        s.emplace_back(u, v, c);
        adj[u].push_back(s.size() - 1);
        s.emplace_back(v, u, 0);
        adj[v].push_back(s.size() - 1);
    }
    bool BFS()
    {
        fill(h.begin(), h.end(), n + 2);
        queue<int> pq;
        h[t] = 0;
        pq.emplace(t);
        while (pq.size())
        {
            int c = pq.front();
            pq.pop();
            for (auto i : adj[c])
                if (h[s[i ^ 1].u] == n + 2 && s[i ^ 1].c != 0)
                {
                    h[s[i ^ 1].u] = h[c] + 1;
                    if (s[i ^ 1].u == sink)
                        return true;
                    pq.emplace(s[i ^ 1].u);
                }
        }
        return false;
    }
    ll DFS(int v, ll flowin)
    {
        if (v == t)
            return flowin;
        ll flowout = 0;
        for (; cur[v] != adj[v].end(); ++cur[v])
        {
            int i = *cur[v];
            if (h[s[i].v] + 1 != h[v] || s[i].c == 0)
                continue;
            ll q = DFS(s[i].v, min(flowin, s[i].c));
            flowout += q;
            if (flowin != Inf)
                flowin -= q;
            s[i].c -= q;
            s[i ^ 1].c += q;
            if (flowin == 0)
                break;
        }
        return flowout;
    }
    void BlockFlow(ll &flow)
    {
        for (int i = 1; i <= n; ++i)
            cur[i] = adj[i].begin();
        flow += DFS(sink, Inf);
    }
    ll MaxFlow(int s, int t)
    {
        this->sink = s;
        this->t = t;
        ll flow = 0;
        while (BFS())
            BlockFlow(flow);
        return flow;
    }
};
```

3.2 Dinic (Template by Tran Khoi Nguyen)

```
struct Edge
{
    int u, v;
    ll cap, flow;
    Edge() {}
    Edge(int u, int v, ll cap) : u(u), v(v), cap(cap), flow(0) {}
};

struct Dinic
{
    int N;
    vector<Edge> E;
    vector<vector<int>> g;
    vector<int> d, pt;
    map<ll, map<ll, ll>> mp;
    Dinic(int N) : N(N), E(0), g(N), d(N), pt(N) {}

    void AddEdge(int u, int v, ll cap)
    {
        if (u != v)
        {
            E.emplace_back(u, v, cap);
            g[u].emplace_back(E.size() - 1);
            E.emplace_back(v, u, 0);
            g[v].emplace_back(E.size() - 1);
        }
    }

    bool BFS(int S, int T)
    {
        queue<int> q({S});
        fill(d.begin(), d.end(), N + 1);
        d[S] = 0;
        while (!q.empty())
        {
            int u = q.front();
            q.pop();
            if (u == T)
                break;
            for (int k : g[u])
            {
                Edge &e = E[k];
                if (e.flow < e.cap && d[e.v] > d[e.u] + 1)
                {
                    d[e.v] = d[e.u] + 1;
                    q.emplace(e.v);
                }
            }
        }
        return d[T] != N + 1;
    }

    ll DFS(int u, int T, ll flow = -1)
    {
        if (u == T || flow == 0)
            return flow;
        for (int &i = pt[u]; i < g[u].size(); ++i)
        {
            Edge &e = E[g[u][i]];
            Edge &oe = E[g[u][i] ^ 1];
            if (d[e.v] == d[e.u] + 1)
            {
                ll amt = e.cap - e.flow;
                if (flow != -1 && amt > flow)
                    amt = flow;
                if (ll pushed = DFS(e.v, T, amt))
                {
                    e.flow += pushed;
                    oe.flow -= pushed;
                    return pushed;
                }
            }
        }
        return 0;
    }

    ll MaxFlow(int S, int T)
    {
        ll total = 0;
        while (BFS(S, T))
        {
            fill(pt.begin(), pt.end(), 0);
            while (ll flow = DFS(S, T))
                total += flow;
        }
        return total;
    }
};
```

3.3 Min Cut (Template by Tran Khoi Nguyen)

```cpp
typedef long long LL;

struct Edge
{
    int u, v;
    LL cap, flow;
    Edge() {}
    Edge(int u, int v, LL cap) : u(u), v(v), cap(cap), flow(0) {}
};

bool chk[maxn];
vector<pll> mincut;
struct Dinic
{
    int N;
    vector<Edge> E;
    vector<vector<int>> g;
    vector<int> d, pt;

    Dinic(int N) : N(N), E(0), g(N), d(N), pt(N) {}

    void AddEdge(int u, int v, LL cap)
    {
        //  cout <<u<<" "<<v<<" "<<cap<<endl;
        if (u != v)
        {
            E.emplace_back(u, v, cap);
            g[u].emplace_back(E.size() - 1);
            E.emplace_back(v, u, 0);
            g[v].emplace_back(E.size() - 1);
        }
    }

    bool BFS(int S, int T)
    {
        queue<int> q({S});
        fill(d.begin(), d.end(), N + 1);
        d[S] = 0;
        while (!q.empty())
        {
            int u = q.front();
            q.pop();
            if (u == T)
                break;
            for (int k : g[u])
            {
                Edge &e = E[k];
                if (e.flow < e.cap && d[e.v] > d[e.u] + 1)
                {
                    d[e.v] = d[e.u] + 1;
                    q.emplace(e.v);
                }
            }
        }
        return d[T] != N + 1;
    }

    LL DFS(int u, int T, LL flow = -1)
    {
        if (u == T || flow == 0)
            return flow;
        for (int &i = pt[u]; i < g[u].size(); ++i)
        {
            Edge &e = E[g[u][i]];
            Edge &oe = E[g[u][i] ^ 1];
            if (d[e.v] == d[e.u] + 1)
            {
                LL amt = e.cap - e.flow;
                if (flow != -1 && amt > flow)
                    amt = flow;
                if (LL pushed = DFS(e.v, T, amt))
                {
                    e.flow += pushed;
                    oe.flow -= pushed;
                    return pushed;
                }
            }
        }
        return 0;
    }
    void dfs1(ll u)
    {
        // cout <<u<<endl;
        chk[u] = 1;
        for (int k : g[u])
        {
            Edge e = E[k];
            if (e.cap - e.flow > 0)
            {
                ll nxt = e.v;
                if (!chk[nxt])
                    dfs1(nxt);
            }
        }
    }
    void find_mincut(ll S)
    {
        dfs1(S);
        for (int i = 0; i < E.size(); i += 2)
        {
            auto p = E[i];
            if (chk[p.u] && !chk[p.v])
            {
                mincut.pb(make_pair(p.u, p.v));
            }
        }
    }

    LL MaxFlow(int S, int T)
    {
        LL total = 0;
        while (BFS(S, T))
        {
            fill(pt.begin(), pt.end(), 0);
            while (LL flow = DFS(S, T))
                total += flow;
        }
        return total;
    }
};
```

3.4 Maximum Matching (HopCroft - Karp)

```cpp
// Trace to find vertex cover and independence set
/*
        Y* = Set of vertices y such that exist an argument path
             from y to a vertex x which isn't matched
        X* = Set of matched vertices x that x isn't matched with a
             vertex in Y*

        (X* v Y*) is vertex cover
*/

struct HopCroft_Karp
{
    const int NoMatch = -1;
    vector<int> h, S, match;
    vector<vector<int>> adj;
    int nx, ny;
    bool found;
    HopCroft_Karp(int nx = 0, int ny = 0)
    {
        this->nx = nx;
        this->ny = ny;
        S.reserve(nx);
        h.resize(ny + 5);
        adj.resize(nx + 5);
        match.resize(ny + 5, NoMatch);
    }
    void Clear()
    {
        for (int i = 1; i <= nx; ++i)
            adj[i].clear();
        S.clear();
        fill(match.begin(), match.end(), NoMatch);
    }
    void AddEdge(int x, int y)
    {
        adj[x].emplace_back(y);
    }
    bool BFS()
    {
        fill(h.begin(), h.end(), 0);
        queue<int> q;
        for (auto x : S)
            for (auto i : adj[x])
                if (h[i] == 0)
                {
                    q.emplace(i);
                    h[i] = 1;
                }
        while (q.size())
        {
            int x, ypop = q.front();
            q.pop();
            if ((x = match[ypop]) == NoMatch)
                return true;
            for (auto i : adj[x])
                if (h[i] == 0)
                {
                    h[i] = h[ypop] + 1;
                    q.emplace(i);
                }
        }
        return false;
    }
    void dfs(int v, int lv)
    {
        for (auto i : adj[v])
            if (h[i] == lv + 1)
            {
                if (match[i] == NoMatch)
                    found = 1;
                else
                    dfs(match[i], lv + 1);
                if (found)
                {
                    match[i] = v;
                    return;
                }
            }
    }
    int MaxMatch()
    {
        int ans(0);
        for (int i = 1; i <= nx; ++i)
            S.emplace_back(i);
        while (BFS())
        {
            for (int i = S.size() - 1; ~i; --i)
            {
                found = 0;
                dfs(S[i], 0);
                if (found)
                {
                    ++ans;
                    S[i] = S.back();
                    S.pop_back();
                }
            }
        }
        return ans;
    }

};
```

3.5 Maximum Matching (Template by Tran Khoi Nguyen)

```cpp
struct bipartite_graph
{
    int nx, ny;
    vector<vector<int>> gr;
```

```
vector<int> match, x_not_matched;

vector<int> level;

bool found;

void init(int _nx, int _ny)
{
    nx = _nx;
    ny = _ny;
    gr.assign(nx, vector<int>());
    x_not_matched.resize(nx);
    for (int i = 0; i < nx; ++i)
        x_not_matched[i] = i;
    match.assign(ny, -1);
    level.resize(ny);
}

void add_edge(int x, int y)
{
    gr[x].push_back(y);
}

bool bfs()
{
    fill(level.begin(), level.end(), 0);
    queue<int> q;
    for (auto &x : x_not_matched)
        for (auto &y : gr[x])
            if (level[y] == 0)
            {
                level[y] = 1;
                q.push(y);
            }
    while (!q.empty())
    {
        int ypop = q.front();
        q.pop();
        int x = match[ypop];
        if (x == -1)
            return true;
        for (auto &y : gr[x])
            if (level[y] == 0)
            {
                level[y] = level[ypop] + 1;
                q.push(y);
            }
    }
    return false;
}

void dfs(int x, int lv)
{
    for (auto &y : gr[x])
        if (level[y] == lv + 1)
        {
            level[y] = 0;
            if (match[y] == -1)
                found = true;
            else
                dfs(match[y], lv + 1);
            if (found)
            {
                match[y] = x;
                return;
            }
        }
}

int max_matching()
{
    int res = 0;
    while (bfs())
    {
        for (int i = sz(x_not_matched) - 1; i >= 0; --i)
        {
            found = false;
            dfs(x_not_matched[i], 0);
            if (found)
            {
                ++res;
                x_not_matched[i] = x_not_matched.back();
                x_not_matched.pop_back();
            }
        }
    }
    return res;
}
} man;
```

3.6 Maximum Matching ($O(n^2)$)

```
// start from 1
// O(n^2)
struct Maximum_matching
{
    int nx, ny, t;
    vector<int> Visited, match;
    vector<vector<int>> a;

    Maximum_matching(int nx = 0, int ny = 0)
    {
        Assign(nx, ny);
    }

    void Assign(int nx, int ny)
    {
        this->nx = nx;
        this->ny = ny;
        t = 0;
        Visited.assign(nx + 5, 0);
        match.assign(ny + 5, 0);
        a.resize(nx + 5, {});
    }

    void AddEdge(int x, int y)
    {
        a[x].emplace_back(y);
    }

    bool visit(int u)
    {
        if (Visited[u] != t)
            Visited[u] = t;
        else
            return false;

        for (int i = 0; i < a[u].size(); i++)
        {
            int v = a[u][i];
            if (!match[v] || visit(match[v]))
            {
                match[v] = u;
                return true;
            }
        }
        return false;
    }

    int MaxMatch()
    {
        int ans(0);

        for (int i = 1; i <= nx; i++)
        {
            t++;
            ans += visit(i);
        }

        return ans;
    }
};
```

3.7 Min Cost Flow

```
struct Edge
{
    int u, v;
    ll c, w;
    Edge(const int &u, const int &v, const ll &c, const ll &w) : u
        (u), v(v), c(c), w(w) {}
};
struct MaxFlowMinCost
{
    const ll Inf = 1e17;
    int n, source, sink;
    vector<ll> d;
    vector<int> par;
    vector<bool> inqueue;
    vector<Edge> s;
    vector<vector<int>> adj;
    MaxFlowMinCost(int n)
    {
        this->n = n;
        s.reserve(n * 2);
        d.resize(n + 5);
        inqueue.resize(n + 5);
        par.resize(n + 5);
        adj.resize(n + 5);
    }
    void AddEdge(int u, int v, ll c, ll w)
    {
        s.emplace_back(u, v, c, w);
        adj[u].emplace_back(s.size() - 1);
        s.emplace_back(v, u, 0, -w);
        adj[v].emplace_back(s.size() - 1);
    }
    bool SPFA()
    {
        fill(d.begin(), d.end(), Inf);
        fill(par.begin(), par.end(), s.size());
        fill(inqueue.begin(), inqueue.end(), 0);
        d[sink] = 0;
        queue<int> q;
        q.emplace(sink);
        inqueue[sink] = 1;
        while (q.size())
        {
            int c = q.front();
            inqueue[c] = 0;
            q.pop();
            for (auto i : adj[c])
                if (s[i ^ 1].c > 0 && d[s[i].v] > d[c] + s[i ^ 1].
                    w)
                {
                    par[s[i].v] = i ^ 1;
                    d[s[i].v] = d[c] + s[i ^ 1].w;
                    if (!inqueue[s[i].v])
                    {
                        q.emplace(s[i].v);
                        inqueue[s[i].v] = 1;
                    }
                }
        }
        return (d[source] < Inf);
    }
    pair<ll, ll> MaxFlow(int so, int t, ll k)
    {
        source = so;
        sink = t;
        ll Flow(0), cost(0);
        while (k && SPFA())
        {
            ll q(Inf);
            int v = source;
            while (v != sink)
            {
                q = min(q, s[par[v]].c);
                v = s[par[v]].v;
            }

            q = min(q, k);
```

```
            cost += d[source] * q;
            Flow += q;
            k -= q;

            v = source;
            while (v != sink)
            {
                s[par[v]].c -= q;
                s[par[v] ^ 1].c += q;
                v = s[par[v]].v;
            }
        }
        return {Flow, cost};
    }
};
```

3.8 Min Cost Flow (Template by Tran Khoi Nguyen)

```
namespace MIN_COST_MAX_FLOW
{

#define REP(i, n) for (int i = 0, i##_len = (n); i < i##_len; ++i)
#define EACH(i, c) for (__typeof((c).begin()) i = (c).begin(), i##
     _end = (c).end(); i != i##_end; ++i)
    template <class T>
    inline void amin(T &x, const T &y)
    {
        if (y < x)
            x = y;
    }
    template <class T>
    inline void amax(T &x, const T &y)
    {
        if (x < y)
            x = y;
    }
    typedef vector<int> VI;
    typedef ll Flow;
    typedef ll Cost;
    const Flow FLOW_INF = 1LL << 60;
    const Cost COST_INF = 1LL << 60;

    const int SIZE = 65;
    vector<pair<Cost, int>> B[SIZE];
    Cost last;
    int sz;

    int bsr(Cost c)
    {
        if (c == 0)
            return 0;
        return __lg(c) + 1;
    }

    void init()
    {
        last = sz = 0;
        REP(i, SIZE)
        B[i].clear();
    }

    void push(Cost cst, int v)
    {
        assert(cst >= last);
        sz++;
        B[bsr(cst ^ last)].emplace_back(cst, v);
    }

    pair<Cost, int> pop_min()
    {
        assert(sz);
        if (B[0].empty())
        {
            int k = 1;
            while (k < SIZE && B[k].empty())
                k++;
            assert(k < SIZE);
            last = B[k][0].first;
            EACH(e, B[k])
            amin(last, e->first);
            EACH(e, B[k])
            B[bsr(e->first ^ last)].push_back(*e);
            B[k].clear();
        }
        assert(B[0].size());
        pair<Cost, int> ret = B[0].back();
        B[0].pop_back();
        sz--;
        return ret;
    }

    struct MinCostMaxFlow
    {
        struct Edge
        {
            int dst;
            Cost cst;
            Flow cap;
            int rev;
        };
        typedef vector<vector<Edge>> Graph;
        Graph G;
        bool negative_edge;
        MinCostMaxFlow(int N) : G(N)
        {
            negative_edge = false;
        }

        void add_edge(int u, int v, Cost x, Flow f)
        {
            if (u == v)
                return;
            if (x < 0)
                negative_edge = true;
            G[u].push_back((Edge){
                v, x, f, (int)G[v].size()});
            G[v].push_back((Edge){
                u, -x, 0, (int)G[u].size() - 1});
        }

        void bellman_ford(int s, vector<Cost> &h)
        {
            fill(h.begin(), h.end(), COST_INF);
            vector<bool> in(G.size());
            h[s] = 0;
            in[s] = true;
            VI front, back;
            front.push_back(s);
            while (1)
            {
                if (front.empty())
                {
                    if (back.empty())
                        return;
                    swap(front, back);
                    reverse(front.begin(), front.end());
                }
                int v = front.back();
                front.pop_back();
                in[v] = false;
                EACH(e, G[v])
                if (e->cap)
                {
                    int w = e->dst;
                    if (h[w] > h[v] + e->cst)
                    {
                        h[w] = h[v] + e->cst;
                        if (!in[w])
                        {
                            back.push_back(w);
                            in[w] = true;
                        }
                    }
                }
            }
        }

        Flow flow;
        Cost cost;
        Flow solve(int s, int t, Flow limit = FLOW_INF)
        {
            flow = 0;
            cost = 0;
            vector<Cost> len(G.size()), h(G.size());
            if (negative_edge)
                bellman_ford(s, h);

            vector<int> prev(G.size()), prev_num(G.size());
            while (limit > 0)
            {
                init();
                push(0, s);
                fill(len.begin(), len.end(), COST_INF);
                fill(prev.begin(), prev.end(), -1);
                len[s] = 0;
                while (sz)
                {
                    pair<Cost, int> p = pop_min();
                    Cost cst = p.first;
                    int v = p.second;
                    if (cst > len[v])
                        continue;
                    for (int i = 0; i < (int)G[v].size(); i++)
                    {
                        const Edge &f = G[v][i];
                        Cost tmp = len[v] + f.cst + h[v] - h[f.dst
                            ];
                        if (f.cap > 0 && len[f.dst] > tmp)
                        {
                            len[f.dst] = tmp;
                            push(tmp, f.dst);
                            prev[f.dst] = v;
                            prev_num[f.dst] = i;
                        }
                    }
                }

                if (prev[t] == -1)
                    return flow;
                for (int i = 0; i < (int)G.size(); i++)
                    h[i] += len[i];

                Flow f = limit;
                for (int v = t; v != s; v = prev[v])
                    f = min(f, G[prev[v]][prev_num[v]].cap);
                for (int v = t; v != s; v = prev[v])
                {
                    Edge &e = G[prev[v]][prev_num[v]];
                    e.cap -= f;
                    G[e.dst][e.rev].cap += f;
                }
                limit -= f;
                flow += f;
                cost += f * h[t];
            }
            return flow;
        }
    };
};
using MinCostMaxFlow = MIN_COST_MAX_FLOW::MinCostMaxFlow;
```

3.9 General Graph Matching

```
const int N = 514, E = (2e5) * 2;
struct Graph{
  int to[E],bro[E],head[N],e;
  int lnk[N],vis[N],stp,n;
  void init( int _n ){
    stp = 0; e = 1; n = _n;
    for( int i = 1 ; i <= n ; i ++ )
      lnk[i] = vis[i] = 0;
  }
```

```
  void add_edge(int u,int v){
    to[e]=v,bro[e]=head[u],head[u]=e++;
    to[e]=u,bro[e]=head[v],head[v]=e++;
  }
  bool dfs(int x){
    vis[x]=stp;
    for(int i=head[x];i;i=bro[i]){
      int v=to[i];
      if(!lnk[v]){
        lnk[x]=v,lnk[v]=x;
        return true;
      }else if(vis[lnk[v]]<stp){
        int w=lnk[v];
        lnk[x]=v,lnk[v]=x,lnk[w]=0;
        if(dfs(w)){
          return true;
        }
        lnk[w]=v,lnk[v]=w,lnk[x]=0;
      }
    }
    return false;
  }
  int solve(){
    int ans = 0;
    for(int i=1;i<=n;i++)
      if(!lnk[i]){
        stp++; ans += dfs(i);
      }
    return ans;
  }
} graph;
```

4 Geometry

4.1 Smallest Circle - Emo Welzl (Contain all points)

```
#include <bits/stdc++.h>
using namespace std;
using ld = double;

typedef pair<ld, ld> point;
typedef pair<point, ld> circle;
#define X first
#define Y second

// O(n)
// Remember to change size of set points
// All point must be save in array a[] below

namespace emowelzl
{
    const int N = 100005; // Size of set points
    int n;
    point a[N];

    point operator+(point a, point b)
    {
        return point(a.X + b.X, a.Y + b.Y);
    }
    point operator-(point a, point b) { return point(a.X - b.X, a.
        Y - b.Y); }
    point operator/(point a, ld x) { return point(a.X / x, a.Y / x
        ); }
    ld abs(point a) { return sqrt(a.X * a.X + a.Y * a.Y); }

    point center_from(ld bx, ld by, ld cx, ld cy)
    {
        ld B = bx * bx + by * by, C = cx * cx + cy * cy, D = bx *
            cy - by * cx;
        return point((cy * B - by * C) / (2 * D), (bx * C - cx * B
            ) / (2 * D));
    }

    circle circle_from(point A, point B, point C)
    {
        point I = center_from(B.X - A.X, B.Y - A.Y, C.X - A.X, C.Y
            - A.Y);
        return circle(I + A, abs(I));
    }

    circle f(int n, vector<point> T)
    {
        if (T.size() == 3 || n == 0)
        {
            if (T.size() == 0)
                return circle(point(0, 0), -1);
            if (T.size() == 1)
                return circle(T[0], 0);
            if (T.size() == 2)
                return circle((T[0] + T[1]) / 2, abs(T[0] - T[1])
                    / 2);
            return circle_from(T[0], T[1], T[2]);
        }
        random_shuffle(a + 1, a + n + 1);
        circle Result = f(0, T);
        for (int i = 1; i <= n; i++)
            if (abs(Result.X - a[i]) > Result.Y + 1e-9)
            {
                T.push_back(a[i]);
                Result = f(i - 1, T);
                T.pop_back();
            }
        return Result;
    }
};

int main()
{
    cin >> emowelzl::n;

    for (int i = 1; i <= emowelzl::n; ++i)
        cin >> emowelzl::a[i].X >> emowelzl::a[i].Y;

    cout << emowelzl::f(emowelzl::n, {}).Y * 2;
}
```

4.2 Closest pair of points in set

```
// Find pair of points that have closest distance

#include <iostream>
#include <cstdio>
#include <algorithm>
#include <iomanip>
#include <cmath>
#include <vector>

using namespace std;

using ll = long long;
using ld = long double;

const int N = 5e4 + 2;
const ll Inf = 1e17;
#define sq(x) ((x) * (x))

struct Point
{
    ll x, y;
    int id;

    Point(const ll &x = 0, const ll &y = 0) : x(x), y(y) {}

    Point operator-(const Point &a) const
    {
        return Point(x - a.x, y - a.y);
    }
    ll len()
    {
        return x * x + y * y;
    }
};

namespace ClosestPoint
{
    int n, xa, ya;
    ll ans;
    Point a[N];

    ll Bruteforce(int l, int r)
    {
        for (; l < r; ++l)
            for (int i = l + 1; i <= r; ++i)
                if (ans > (a[l] - a[i]).len())
                {
                    ans = (a[l] - a[i]).len();
                    xa = a[l].id;
                    ya = a[i].id;
                }
        return ans;
    }

    void Brute(vector<int> &s)
    {
        sort(s.begin(), s.end(), [&](const int &x, const int &y)
             { return a[x].y < a[y].y; });
        for (int i = 0; i < s.size(); ++i)
            for (int j = i + 1; j < s.size() && sq(abs(a[s[i]].y -
                 a[s[j]].y)) <= ans; ++j)
                if (ans > (a[s[i]] - a[s[j]]).len())
                {
                    ans = (a[s[i]] - a[s[j]]).len();
                    xa = a[s[i]].id;
                    ya = a[s[j]].id;
                }
    }

    void DAC(int l, int r)
    {
        if (r - l <= 3)
        {
            Bruteforce(l, r);
            return;
        }
        int mid = (l + r) / 2;

        DAC(l, mid);
        DAC(mid + 1, r);

        vector<int> s;
        for (int i = l; i <= r; ++i)
            if (sq(a[i].x - a[mid].x) <= ans)
                s.push_back(i);

        Brute(s);
    }

    void calc()
    {
        sort(a + 1, a + n + 1, [&](const Point &a, const Point &b)
             { return a.x < b.x || (a.x == b.x && a.y < b.y); });
        ans = Inf;

        DAC(1, n);

        if (xa > ya)
            swap(xa, ya);

        cout << xa << " " << ya << "\n";
        cout << fixed << setprecision(6) << sqrt((ld)ans);
    }
};

Point a[N];
int n;

void Read()
{
    cin >> n;
    for (int i = 1; i <= n; ++i)
    {
        cin >> a[i].x >> a[i].y;
```

```
        a[i].id = i;
    }
}

void Solve()
{
    ClosestPoint::n = n;
    for (int i = 1; i <= n; ++i)
        ClosestPoint::a[i] = a[i];

    ClosestPoint::calc();
}

int32_t main()
{
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    cout.tie(0);
    Read();
    Solve();
}
```

4.3 Manhattan MST

```
// Idea is to reduce number of edges which are candidates to be in
      the MST
// Then apply Kruskal algorithm to find MST

#include <bits/stdc++.h>
using namespace std;
using ll = long long;

constexpr int N = 2e5 + 2;
constexpr ll Inf = 1e17;

namespace manhattanMST
{
    /// disjoint set union
    struct dsu
    {
        int par[N];
        dsu()
        {
            memset(par, -1, sizeof par);
        }

        int findpar(int v)
        {
            return par[v] < 0 ? v : par[v] = findpar(par[v]);
        }

        bool Merge(int u, int v)
        {
            u = findpar(u);
            v = findpar(v);
            if (u == v)
                return false;

            if (par[u] < par[v])
                swap(u, v);

            par[v] += par[u];
            par[u] = v;

            return true;
        }
    };

    // Fenwick Tree Min

    struct FenwickTreeMin
    {
        pair<ll, int> a[N];
        int n;

        FenwickTreeMin(int n = 0)
        {
            Assign(n);
        }

        void Assign(int n)
        {
            this->n = n;
            fill(a, a + n + 1, make_pair(Inf, -1));
        }

        void Update(int p, pair<ll, int> v)
        {
            for (; p <= n; p += p & -p)
                a[p] = min(a[p], v);
        }

        pair<ll, int> Get(int p)
        {
            pair<ll, int> ans({Inf, -1});

            for (; p; p -= p & -p)
                ans = min(ans, a[p]);
            return ans;
        }
    };

    struct Edge
    {
        int u, v;
        ll w;
        Edge(const int &u = 0, const int &v = 0, const ll &w = 0)
            : u(u), v(v), w(w) {}
        bool operator<(const Edge &a) const
        {
            return w < a.w;
        }
    };

    int n;
    ll x[N], y[N];
    vector<Edge> edges;

    ll dist(int i, int j)
    {
        return abs(x[i] - x[j]) + abs(y[i] - y[j]);
    }

#define Find(x, v) (lower_bound(x.begin(), x.end(), v) - x.begin()
      + 1)
    void createEdge(int a1, int a2, int b1, int b2, int c1, int c2
         )
    {
        vector<array<ll, 4>> v;
        vector<ll> s;

        for (int i = 1; i <= n; i++)
        {
            v.push_back({a1 * x[i] + a2 * y[i],
                         b1 * x[i] + b2 * y[i],
                         c1 * x[i] + c2 * y[i],
                         i});
            s.emplace_back(b1 * x[i] + b2 * y[i]);
        }
        sort(s.begin(), s.end());
        s.resize(unique(s.begin(), s.end()) - s.begin());
        sort(v.begin(), v.end());

        FenwickTreeMin f(n);

        for (auto [num1, num2, cost, idx] : v)
        {
            num2 = Find(s, num2);

            int res = f.Get(num2).second;
            if (res != -1)
                edges.emplace_back(res, idx, dist(res, idx));

            f.Update(num2, make_pair(cost, idx));
        }
    }

    void calc()
    {
        edges.clear();

        createEdge(1, -1, -1, 0, 1, 1);  // R1
        createEdge(-1, 1, 0, -1, 1, 1);  // R2
        createEdge(-1, -1, 0, 1, 1, -1); // R3
        createEdge(1, 1, -1, 0, 1, -1);  // R4
        createEdge(-1, 1, 1, 0, -1, -1); // R5
        createEdge(1, -1, 0, 1, -1, -1); // R6
        createEdge(1, 1, 0, -1, -1, 1);  // R7
        createEdge(-1, -1, 1, 0, -1, 1); // R8

        dsu f;

        sort(edges.begin(), edges.end());
        vector<pair<int, int>> res;
        ll ans(0);

        for (auto i : edges)
            if (f.Merge(i.u, i.v))
            {
                ans += i.w;
                res.emplace_back(i.u, i.v);
            }

        cout << ans << "\n";

        for (auto i : res)
            cout << i.first << " " << i.second << "\n";
    }
};

int32_t main()
{
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    cout.tie(0);

    cin >> manhattanMST::n;

    for (int i = 1; i <= manhattanMST::n; ++i)
        cin >> manhattanMST::x[i] >> manhattanMST::y[i];

    manhattanMST::calc();
}
```

4.4 Geometry with real number

```
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
        typedef Point P;
        T x, y;
        explicit Point(T x=0, T y=0) : x(x), y(y) {}
        bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y)
             ; }
        bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y)
             ; }
        P operator+(P p) const { return P(x+p.x, y+p.y); }
        P operator-(P p) const { return P(x-p.x, y-p.y); }
        P operator*(T d) const { return P(x*d, y*d); }
        P operator/(T d) const { return P(x/d, y/d); }
        T dot(P p) const { return x*p.x + y*p.y; }
        T cross(P p) const { return x*p.y - y*p.x; }
        T cross(P a, P b) const { return (a-*this).cross(b-*this);
             }
        T dist2() const { return x*x + y*y; }
        double dist() const { return sqrt((double)dist2()); }
        // angle to x-axis in interval [-pi, pi]
        double angle() const { return atan2(y, x); }
        P unit() const { return *this/dist(); } // makes dist()=1
        P perp() const { return P(-y, x); } // rotates +90 degrees
        P normal() const { return perp().unit(); }
```

```
        // returns point rotated 'a' radians ccw around the origin
        P rotate(double a) const {
                return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
        friend ostream& operator<<(ostream& os, P p) {
                return os << "(" << p.x << "," << p.y << ")"; }
};

/* On Segment: p is on segment from s to e */
template<class P> bool onSegment(P s, P e, P p) {
        return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}

/* Segment Intersection */
template<class P> vector<P> segInter(P a, P b, P c, P d) {
        auto oa = c.cross(d, a), ob = c.cross(d, b),
             oc = a.cross(b, c), od = a.cross(b, d);
        // Checks if intersection is single non-endpoint point.
        if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
                return {(a * ob - b * oa) / (ob - oa)};
        set<P> s;
        if (onSegment(c, d, a)) s.insert(a);
        if (onSegment(c, d, b)) s.insert(b);
        if (onSegment(a, b, c)) s.insert(c);
        if (onSegment(a, b, d)) s.insert(d);
        return {all(s)};
}

/**
 * Apply the linear transformation (translation, rotation and
      scaling) which takes line p0-p1 to line q0-q1 to point r.
 */
typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1,
                const P& q0, const P& q1, const P& r) {
        P dp = p1-p0, dq = q1-q0, num(dp.cross(dq), dp.dot(dq));
        return q0 + P((r-p0).cross(num), (r-p0).dot(num))/dp.dist2
             ();
}

/**
 * Computes the pair of points at which two circles intersect.
 */
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,pair<P, P>* out) {
        if (a == b) { assert(r1 != r2); return false; }
        P vec = b - a;
        double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
               p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 - p*p*
                    d2;
        if (sum*sum < d2 || dif*dif > d2) return false;
        P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0, h2) /
             d2);
        *out = {mid + per, mid - per};
        return true;
}

/**
 * Finds the tangents of two circles, external if r2 > 0, internal
       if r2 < 0.
 */
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2, double r2) {
        P d = c2 - c1;
        double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr * dr;
        if (d2 == 0 || h2 < 0)  return {};
        vector<pair<P, P>> out;
        for (double sign : {-1, 1}) {
                P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
                out.push_back({c1 + v * r1, c2 + v * r2});
        }
        if (h2 == 0) out.pop_back();
        return out;
}

/**
 * Returns the area of the intersection of a circle with a ccw
      polygon.
 */
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
        auto tri = [&](P p, P q) {
                auto r2 = r * r / 2;
                P d = q - p;
                auto a = d.dot(p)/d.dist2(), b = (p.dist2()-r*r)/d
                     .dist2();
                auto det = a * a - b;
                if (det <= 0) return arg(p, q) * r2;
                auto s = max(0., -a-sqrt(det)), t = min(1., -a+
                     sqrt(det));
                if (t < 0 || 1 <= s) return arg(p, q) * r2;
                P u = p + d * s, v = q + d * (t-1);
                return arg(p,u) * r2 + u.cross(v)/2 + arg(v,q) *
                     r2;
        };
        auto sum = 0.0;
        rep(i,0,sz(ps))
                sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
        return sum;
}
/**
 * The circumcirle of a triangle is the circle intersecting all
      three vertices.
 *  ccRadius returns the radius of the circle going through points
       A, B and C and ccCenter returns the center of the same
      circle.
 */
typedef Point<double> P;
double ccRadius(const P& A, const P& B, const P& C) {
        return (B-A).dist()*(C-B).dist()*(A-C).dist()/
                        abs((B-A).cross(C-A))/2;
}
P ccCenter(const P& A, const P& B, const P& C) {
        P b = C-A, c = B-A;
        return A + (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}

/**
 * Computes the minimum circle that encloses a set of points.
 */
typedef Point<double> P;
pair<P, double> mec(vector<P> ps) {
        shuffle(all(ps), mt19937(time(0)));
        P o = ps[0];
        double r = 0, EPS = 1 + 1e-8;
        rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r * EPS) {
                o = ps[i], r = 0;
                rep(j,0,i) if ((o - ps[j]).dist() > r * EPS) {
                        o = (ps[i] + ps[j]) / 2;
                        r = (o - ps[i]).dist();
                        rep(k,0,j) if ((o - ps[k]).dist() > r *
                             EPS) {
                                o = ccCenter(ps[i], ps[j], ps[k]);
                                r = (o - ps[i]).dist();
                        }
                }
        }
        return {o, r};
}

/**
 * Returns true if p lies within the polygon.
 * If strict is true, it returns false for points on the boundary.
 * The algorithm uses products in intermediate steps so watch out
      for overflow.
 */
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict = true) {
        int cnt = 0, n = sz(p);
        rep(i,0,n) {
                P q = p[(i + 1) % n];
                if (onSegment(p[i], q, a)) return !strict;
                //or: if (segDist(p[i], q, a) <= eps) return !
                     strict;
                cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.cross(p[i],
                     q) > 0;
        }
        return cnt;
}

/**
 * Returns the center of mass for a polygon.
 */
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
        P res(0, 0); double A = 0;
        for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
                res = res + (v[i] + v[j]) * v[j].cross(v[i]);
                A += v[j].cross(v[i]);
        }
    return res / A / 3;
}

/**
 * Returns a vector with the vertices of a polygon with everything
       to the left of the vector going from s to e cut away.
 */
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
        vector<P> res;
        rep(i,0,sz(poly)) {
                P cur = poly[i], prev = i ? poly[i-1] : poly.back
                     ();
                auto a = s.cross(e, cur), b = s.cross(e, prev);
                if ((a < 0) != (b < 0))
                        res.push_back(cur + (prev - cur) * (a / (a
                             - b)));
                if (a < 0)
                        res.push_back(cur);
        }
        return res;
}

/**
 * Line-convex polygon intersection. The polygon must be ccw and
      have no collinear points. lineHull(line, poly) returns a
      pair describing the intersection of a line with the polygon:
 *  \begin{itemize*}
 *    \item $(-1, -1)$ if no collision,
 *    \item $(i, -1)$ if touching the corner $i$,
 *    \item $(i, i)$ if along side $(i, i+1)$,
 *    \item $(i, j)$ if crossing sides $(i, i+1)$ and $(j, j+1)$.
 *  \end{itemize*}
 */
#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
        int n = sz(poly), lo = 0, hi = n;
        if (extr(0)) return 0;
        while (lo + 1 < hi) {
                int m = (lo + hi) / 2;
                if (extr(m)) return m;
                int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
                (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi :
                     lo) = m;
        }
        return lo;
}

#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
        int endA = extrVertex(poly, (a - b).perp());
        int endB = extrVertex(poly, (b - a).perp());
        if (cmpL(endA) < 0 || cmpL(endB) > 0)
                return {-1, -1};
        array<int, 2> res;
        rep(i,0,2) {
                int lo = endB, hi = endA, n = sz(poly);
                while ((lo + 1) % n != hi) {
                        int m = ((lo + hi + (lo < hi ? 0 : n)) /
                             2) % n;
                        (cmpL(m) == cmpL(endB) ? lo : hi) = m;
                }
```

```
                res[i] = (lo + !cmpL(hi)) % n;
                swap(endA, endB);
        }
        if (res[0] == res[1]) return {res[0], -1};
        if (!cmpL(res[0]) && !cmpL(res[1]))
                switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly
                      )) {
                        case 0: return {res[0], res[0]};
                        case 2: return {res[1], res[1]};
                }
        return res;
}
```

5 Numerical algorithms

5.1 SQRT For Loop

```
// Calculate n/1 + n/2 + ... + n/n

#define Cal(a, b) ((b) - (a) + 1)

ll calc(ll n)
{
    ll ans = 0;

    for (ll i = 1; i <= n / i; ++i)
        ans += Cal(n / (i + 1) + 1, n / i) * i;

    for (ll i = 1; i < n / i; ++i)
        ans += n / i;

    return ans;
}
```

5.2 Rabin Miller - Prime Checker

```
// There is another version of Rabin Miller using random in the
     implementation of Pollard Rho

ll mul(ll a, ll b, ll mod)
{
    a %= mod;
    b %= mod;
    ll q = (ld)a * b / mod;
    ll r = a * b - q * mod;
    return (r % mod + mod) % mod;
}
ll pow(ll a, ll n, ll m)
{
    ll result = 1;
    a %= m;
    while (n > 0)
    {
        if (n & 1)
            result = mul(result, a, m);
        n >>= 1;
        a = mul(a, a, m);
    }
    return result;
}
pair<ll, ll> factor(ll n)
{
    ll s = 0;
    while ((n & 1) == 0)
    {
        s++;
        n >>= 1;
    }
    return {s, n};
}
bool test(ll s, ll d, ll n, ll witness)
{
    if (n == witness)
        return true;
    ll p = pow(witness, d, n);
    if (p == 1)
        return true;
    for (; s > 0; s--)
    {
        if (p == n - 1)
            return true;
        p = mul(p, p, n);
    }
    return false;
}
bool miller(ll n)
{
    if (n < 2)
        return false;
    if ((n & 1) == 0)
        return n == 2;
    ll s, d;
    tie(s, d) = factor(n - 1);
    return test(s, d, n, 2) && test(s, d, n, 3) && test(s, d, n,
         5) &&
           test(s, d, n, 7) && test(s, d, n, 11) && test(s, d, n,
                13) &&
           test(s, d, n, 17) && test(s, d, n, 19) && test(s, d, n,
                23);
}
```

5.3 Chinese Remain Theorem

```
pair<ll, ll> exteuclid(ll a, ll b){
    if(b == 0) return {1, 0};
    pair<ll, ll> q = gcd(b, a % b);
    return {q.second, q.first - q.second * (a / b)};
}

/**
 * x % m1 == x1
 * x % m2 == x2
 * => x % lcm(m1, m2) == res
 */
ll solve(ll x1, ll m1, ll x2, ll m2) {
    ll g = __gcd(m1, m2);
    if((x2 - x1) % g) return -1;// no sol
    m1 /= g; m2 /= g;
    pair<ll,ll> p = exteuclid(m1, m2);
    ll lcm = m1 * m2 * g;
    ll res = p.first * (x2 - x1) * m1 + x1;
    return (res % lcm + lcm) % lcm;
}
```

5.4 Pollard Rho - Factorialize

```
// You can change code Rabin-Miller (preposition)
struct PollardRho
{
    ll n;
    map<ll, int> ans;
    PollardRho(ll n) : n(n) {}
    ll random(ll u)
    {
        return abs(rand()) % u;
    }
    ll mul(ll a, ll b, ll mod)
    {
        a %= mod;
        b %= mod;
        ll q = (ld)a * b / mod;
        ll r = a * b - q * mod;
        return (r % mod + mod) % mod;
    }

    ll pow(ll a, ll b, ll m)
    {
        ll ans = 1;
        a %= m;
        for (; b; b >>= 1)
        {
            if (b & 1)
                ans = mul(ans, a, m);
            a = mul(a, a, m);
        }
        return ans;
    }

    pair<ll, ll> factor(ll n)
    {
        ll s = 0;
        while ((n & 1) == 0)
        {
            s++;
            n >>= 1;
        }
        return {s, n};
    }
    // Rabin - Miller
    bool miller(ll n)
    {
        if (n < 2)
            return 0;
        if (n == 2)
            return 1;
        ll s = 0, m = n - 1;
        while (m % 2 == 0)
        {
            s++;
            m >>= 1;
        }
        // 1 - 0.9 ^ 40
        for (int it = 1; it <= 40; it++)
        {
            ll u = random(n - 2) + 2;
            ll f = pow(u, m, n);
            if (f == 1 || f == n - 1)
                continue;
            for (int i = 1; i < s; i++)
            {
                f = mul(f, f, n);
                if (f == 1)
                    return 0;
                if (f == n - 1)
                    break;
            }
            if (f != n - 1)
                return 0;
        }
        return 1;
    }

    ll f(ll x, ll n)
    {
        return (mul(x, x, n) + 1) % n;
    }
    // Find a factor
    ll findfactor(ll n)
    {
        ll x = random(n - 1) + 2;
        ll y = x;
        ll p = 1;
        while (p == 1)
        {
            x = f(x, n);
            y = f(f(y, n), n);
            p = __gcd(abs(x - y), n);
        }
        return p;
    }
    // prime factorization
    void pollard_rho(ll n)
    {
        if (n <= 1000000)
        {
            for (int i = 2; i * i <= n; i++)
            {
                while (n % i == 0)
                {
                    ans[i]++;
```

```
                n /= i;
            }
        }
        if (n > 1)
            ans[n]++;
        return;
    }

    if (miller(n))
    {
        ans[n]++;
        return;
    }
    ll p = 0;

    while (p == 0 || p == n)
        p = findfactor(n);

    pollard_rho(n / p);
    pollard_rho(p);
  }
};
```

5.5 FFT

```
using cd = complex<double>;
const double PI = acos(-1);
// invert == true means Interpolation
// invert == false means dft
void fft(vector<cd> &a, bool invert) {
    int n = a.size();
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1) {
            j ^= bit;
        }
        j ^= bit;
        if (i < j)
            swap(a[i], a[j]);
    }

    for (int len = 2; len <= n; len <<= 1) {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for (int i = 0; i < n; i += len) {
            cd w(1);
            for (int j = 0; j < len / 2; j++) {
                cd u = a[i + j],
                v = a[i + j + len / 2] * w;
                a[i + j] = u + v;
                a[i + j + len / 2] = u - v;
                w *= wlen;
            }
        }
    }

    if (invert) {
        for (cd &x : a)
        x /= n;
    }
}

vector<long long> multiply(vector<long long>& A, vector<long long
    >& B) {
    vector<cd> fa(A.begin(), A.end()), fb(B.begin(), B.end());

    int n1 = (int)A.size(), n2 = (int)B.size();
    int n = 1;
    while (n < n1 + n2 - 1) n <<= 1;

    fa.resize(n);
    fb.resize(n);

    fft(fa, false);
    fft(fb, false);
    for (int i = 0; i < n; i++) fa[i] *= fb[i];
    fft(fa, true);

    vector<long long> res(n1 + n2 - 1);
    for (int i = 0; i < (int)res.size(); i++) {
        res[i] = (long long) llround(fa[i].real()); // round to
            nearest integer
    }
    return res;
}
```

5.6 FFT (Mod 998244353)

```
// NTT (FFT mod 998244353) + convolution
static const int MOD = 998244353;
static const int G   = 3;

long long modpow(long long a, long long e) {
    long long r = 1 % MOD;
    a %= MOD;
    while (e > 0) {
        if (e & 1) r = r * a % MOD;
        a = a * a % MOD;
        e >>= 1;
    }
    return r;
}

// invert=false: forward NTT, invert=true: inverse NTT
void fft_mod(vector<int> &a, bool invert) {
    int n = (int)a.size();
    static vector<int> rev;
    static vector<int> roots{0, 1};

    // bit-reversal permutation
    if ((int)rev.size() != n) {
        int k = __builtin_ctz(n);
        rev.assign(n, 0);
        for (int i = 0; i < n; i++) {
            rev[i] = 0;
            for (int j = 0; j < k; j++)
                if (i & (1 << j)) rev[i] |= 1 << (k - 1 - j);
        }
    }

    // roots of unity
    if ((int)roots.size() < n) {
        int k = __builtin_ctz((int)roots.size());
        roots.resize(n);
        while ((1 << k) < n) {
            long long e = modpow(G, (MOD - 1) >> (k + 1));
            for (int i = 1 << (k - 1); i < (1 << k); i++) {
                roots[2 * i] = roots[i];
                roots[2 * i + 1] = (long long)roots[i] * e % MOD;
            }
            k++;
        }
    }

    for (int i = 0; i < n; i++)
        if (i < rev[i]) swap(a[i], a[rev[i]]);

    for (int len = 1; len < n; len <<= 1) {
        for (int i = 0; i < n; i += 2 * len) {
            for (int j = 0; j < len; j++) {
                int u = a[i + j];
                int v = (long long)a[i + j + len] * roots[len + j]
                    % MOD;
                int x = u + v;
                if (x >= MOD) x -= MOD;
                a[i + j] = x;
                x = u - v;
                if (x < 0) x += MOD;
                a[i + j + len] = x;
            }
        }
    }

    if (invert) {
        // inverse via reversing (valid for this root table
            construction)
        reverse(a.begin() + 1, a.end());
        long long inv_n = modpow(n, MOD - 2);
        for (int &x : a) x = (long long)x * inv_n % MOD;
    }
}

vector<long long> multiply(const vector<long long>& A, const
    vector<long long>& B) {
    if (A.empty() || B.empty()) return {};
    int n1 = (int)A.size(), n2 = (int)B.size();
    int n = 1;
    while (n < n1 + n2 - 1) n <<= 1;

    vector<int> fa(n, 0), fb(n, 0);
    for (int i = 0; i < n1; i++) fa[i] = (int)(A[i] % MOD);
    for (int i = 0; i < n2; i++) fb[i] = (int)(B[i] % MOD);

    fft_mod(fa, false);
    fft_mod(fb, false);
    for (int i = 0; i < n; i++) fa[i] = (long long)fa[i] * fb[i] %
        MOD;
    fft_mod(fa, true);

    vector<long long> res(n1 + n2 - 1);
    for (int i = 0; i < (int)res.size(); i++) res[i] = fa[i];
    return res;
}
```

5.7 FFT Mod (Template by Tran Khoi Nguyen)

```
struct FFTmod
{
    typedef complex<double> C;
    const ll M = mod;
    void fft(vector<C> &a)
    {
        int n = a.size(), L = 31 - __builtin_clz(n);
        static vector<complex<long double>> R(2, 1);
        static vector<C> rt(2, 1); // (^ 10% faster if double)
        for (static int k = 2; k < n; k *= 2)
        {
            R.resize(n);
            rt.resize(n);
            auto x = polar(1.0L, acos(-1.0L) / k);
            for (int i = k; i < 2 * k; i++)
                rt[i] = R[i] = i & 1 ? R[i / 2] * x : R[i / 2];
        }
        vector<int> rev(n);
        for (int i = 0; i < n; i++)
            rev[i] = (rev[i / 2] | (i & 1) << L) / 2;

        for (int i = 0; i < n; i++)
            if (i < rev[i])
                swap(a[i], a[rev[i]]);
        for (int k = 1; k < n; k *= 2)
            for (int i = 0; i < n; i += 2 * k)
                for (int j = 0; j < k; j++)
                {
                    // C z = rt[j+k] * a[i+j+k]; // (25% faster if
                        hand-rolled)  /// include-line
                    auto x = (double *)&rt[j + k], y = (double *)&
                        a[i + j + k]; /// exclude-line
                    C z(x[0] * y[0] - x[1] * y[1], x[0] * y[1] + x
                        [1] * y[0]);  /// exclude-line
                    a[i + j + k] = a[i + j] - z;
                    a[i + j] += z;
                }
    }

    typedef vector<ll> vl;
    vl convMod(const vl &a, const vl &b)
    {

        vl res((int)a.size() + b.size() - 1);
```

```
        int B = 32 - __builtin_clz(res.size()), n = 1 << B, cut =
             int(sqrt(M));

        vector<C> L(n), R(n), outs(n), outl(n);

        for (int i = 0; i < (int)a.size(); i++)
            L[i] = C((int)a[i] / cut, (int)a[i] % cut);

        for (int i = 0; i < (int)b.size(); i++)
            R[i] = C((int)b[i] / cut, (int)b[i] % cut);

        fft(L), fft(R);

        for (int i = 0; i < n; i++)
        {
            int j = -i & (n - 1);
            outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
            outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
        }

        fft(outl), fft(outs);

        for (int i = 0; i < (int)res.size(); i++)
        {
            ll av = (ll)(real(outl[i]) + .5);
            ll cv = (ll)(imag(outs[i]) + .5);
            ll bv = (ll)(imag(outl[i]) + .5) + (ll)(real(outs[i])
                 + .5);
            res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
        }
        return res;
    }
};
```

5.8 Fast Walsh-Hadamard Transform (FWHT)

```
void FST(vector<int> &a, bool inv) {
    for (int n = (int) a.size(), step = 1; step < n; step *= 2)
        for (int i = 0; i < n; i += 2 * step)
            for (int j = 0; j < step; ++j) {
                int u = a[i + j];
                int v = a[i + j + step];

                // tie(a[i + j], a[i + j + step]) = (inv ?
                     make_pair(v, u - v) : make_pair(u + v, v));
                     // AND
                // tie(a[i + j], a[i + j + step]) = (inv ?
                     make_pair(u - v, v) : make_pair(u, u + v));
                     // OR
                tie(a[i + j], a[i + j + step]) = make_pair(u + v,
                     u - v); // XOR
            }

    if (inv) {
        for (int &x : a) x /= (int) a.size(); // XOR only
    }
}

vector<int> conv(vector<int> &a, vector<int> &b) {
    int n = 1, need = (int)a.size() + (int)b.size() - 1;
    while (n < need) n <<= 1;
    a.resize(n, 0); b.resize(n, 0);

    FST(a, 0); FST(b, 0);
    for (int i = 0; i < (int) a.size(); ++i) a[i] *= b[i];
    FST(a, 1);

    return a;
}
```

5.9 Fast Walsh-Hadamard Transform (FWHT Base m)

```
// m | MOD - 1 is required
int primitive_mth_root(int m, int mod) {
    int g = PrimitiveRoot(mod);
    return Pow(g, (mod - 1) / m, mod);
}

void fwht_m(vector<ll>& a, int m, int omega, bool inverse) {
    const int SZ = (int)a.size();
    ll w = inverse ? Pow(omega, m-1, mod) : omega;

    vector<ll> wp(m, 1);
    for (int t = 1; t < m; ++t) wp[t] = wp[t-1] * w % mod;

    vector<ll> Mmt(m * m);
    for (int k = 0; k < m; ++k)
        for (int t = 0; t < m; ++t)
            Mmt[k * m + t] = wp[(k * t) % m];

    int stages = 0;
    for (int len=1; len<SZ; len *= m) {
        ++stages;
        for (int base = 0; base < SZ; base += m * len){
            for (int j = 0; j < len; ++j){
                static vector<ll> x, y;
                x.assign(m, 0); y.assign(m, 0);
                for (int t=0; t<m; ++t) x[t] = a[base + j + t *
                     len];

                for (int k = 0; k < m; ++k){
                    ll s = 0;
                    const ll* row = &Mmt[k*m];
                    for(int t = 0; t < m; ++t) {
                        s += x[t] * row[t];
                        s %= mod;
                    }
                    y[k] = s;
                }
                for (int k = 0; k < m; ++k) a[base + j + k * len]
                     = y[k];
            }
        }
    }

    if(inverse){
        ll invm = mod_inv(m); ll scale = 1;
        for (int s = 0; s < stages; ++s) scale = scale * invm %
             mod;
        for (ll &v : a) v = v * scale % mod;
    }
}
```

5.10 Count Primes

```
// To initialize, call init_count_primes() first.
// Function count_primes(n) will compute the number of
// prime numbers lower than or equal to n.
//
// Time complexity: Around O(n ^ 0.75)

constexpr int N = 1e5 + 5; // keep N larger than max(sqrt(n) + 2)
bool prime[N];
int prec[N];
vector<int> P;

ll rec(ll n, int k)
{
    if (n <= 1 || k < 0)
        return 0;
    if (n <= P[k])
        return n - 1;

    if (n < N && ll(P[k]) * P[k] > n)
        return n - 1 - prec[n] + prec[P[k]];

    const int LIM = 250;
    static int memo[LIM * LIM][LIM];
    bool ok = n < LIM * LIM;
    if (ok && memo[n][k])
        return memo[n][k];

    ll ret = n / P[k] - rec(n / P[k], k - 1) + rec(n, k - 1);
    if (ok)
        memo[n][k] = ret;
    return ret;
}
void init_count_primes()
{
    prime[2] = true;
    for (int i = 3; i < N; i += 2)
        prime[i] = true;
    for (int i = 3, j; i * i < N; i += 2)
        if (prime[i])
            for (j = i * i; j < N; j += i + i)
                prime[j] = false;

    for (int i = 1; i < N; ++i)
        if (prime[i])
            P.push_back(i);

    for (int i = 1; i < N; ++i)
        prec[i] = prec[i - 1] + prime[i];
}

ll count_primes(ll n)
{
    if (n < N)
        return prec[n];
    int k = prec[(int)sqrt(n) + 1];
    return n - 1 - rec(n, k) + prec[P[k]];
}
```

5.11 Interpolation (Mod a prime)

```
// You can change mod into other prime number
// update k to the degree of polynomial
// Just work when we know a[1] = P(1), a[2] = P(2),..., a[k] = P(k
     ) [The degree of P(x) is k-1]
// update() then build() then cal()

/*
 * Complexity: O(Nlog(mod), N)
 */

constexpr ll mod = 1e9 + 7; // Change mod here
constexpr ll N = 1e5 + 5;   // Change size here

struct Interpolation
{
    ll a[N], fac[N], ifac[N], prf[N], suf[N];
    int k;

    ll Pow(ll a, ll b)
    {
        ll ans(1);
        for (; b; b >>= 1)
        {
            if (b & 1)
                ans = ans * a % mod;
            a = a * a % mod;
        }

        return ans;
    }

    void upd(int u, ll v)
    {
        a[u] = v;
    }

    void build()
    {
        fac[0] = ifac[0] = 1;
        for (int i = 1; i < N; i++)
        {
            fac[i] = (long long)fac[i - 1] * i % mod;
            ifac[i] = Pow(fac[i], mod - 2);
        }
```

```
    }

    // Calculate P(x)
    ll calc(int x)
    {
        prf[0] = suf[k + 1] = 1;

        for (int i = 1; i <= k; i++)
            prf[i] = prf[i - 1] * (x - i + mod) % mod;

        for (int i = k; i >= 1; i--)
            suf[i] = suf[i + 1] * (x - i + mod) % mod;

        ll res = 0;

        for (int i = 1; i <= k; i++)
        {
            if (!((k - i) & 1))
                res = (res + prf[i - 1] * suf[i + 1] % mod * ifac[
                     i - 1] % mod * ifac[k - i] % mod * a[i]) %
                     mod;
            else
                res = (res - prf[i - 1] * suf[i + 1] % mod * ifac[
                     i - 1] % mod * ifac[k - i] % mod * a[i] % mod
                      + mod) % mod;
        }

        return res;
    }
};
```

5.12 Bignum

```
/// M is the number of digits in the answer
/// In case that we don't use multiplication, let BASE be 1e17 or
     1e18
/// a = Bignum("5")
/// The operator / is only for integer, the result is integer too

using cd = complex<long double>;
const long double PI = acos(-1);
const int M = 2000;
const ll BASE = 1e8;
const int gd = log10(BASE);
const int maxn = M / gd + 1;
struct Bignum
{
    int n;
    ll a[maxn];
    Bignum(ll x = 0)
    {
        memset(a, 0, sizeof a);
        n = 0;
        do
        {
            a[n++] = x % BASE;
            x /= BASE;
        } while (x);
    }
    Bignum(const string &s)
    {
        Convert(s);
    }
    ll stoll(const string &s)
    {
        ll ans(0);
        for (auto i : s)
            ans = ans * 10 + i - '0';
        return ans;
    }
    void Convert(const string &s)
    {
        memset(a, 0, sizeof a);
        n = 0;
        for (int i = s.size() - 1; ~i; --i)
        {
            int j = max(0, i - gd + 1);
            a[n++] = stoll(s.substr(j, i - j + 1));
            i = j;
        }
        fix();
    }
    void fix()
    {
        ++n;
        for (int i = 0; i < n - 1; ++i)
        {
            a[i + 1] += a[i] / BASE;
            a[i] %= BASE;
            if (a[i] < 0)
            {
                a[i] += BASE;
                --a[i + 1];
            }
        }
        while (n > 1 && a[n - 1] == 0)
            --n;
    }
    Bignum &operator+=(const Bignum &x)
    {
        n = max(n, x.n);
        for (int i = 0; i < n; ++i)
            a[i] += x.a[i];
        fix();
        return *this;
    }
    Bignum &operator-=(const Bignum &x)
    {
        for (int i = 0; i < x.n; ++i)
            a[i] -= x.a[i];
        fix();
        return *this;
    }
    Bignum &operator*=(const Bignum &x)
    {
        vector<ll> c(x.n + n, 0);
        for (int i = 0; i < n; ++i)
            for (int j = 0; j < x.n; ++j)
                c[i + j] += a[i] * x.a[j];
        n += x.n;
        for (int i = 0; i < n; ++i)
            a[i] = c[i];
        fix();
        return *this;
    }
    Bignum &operator/=(const ll &x)
    {
        ll r = 0ll;
        for (int i = n - 1; i > -1; --i)
        {
            r = r * BASE + a[i];
            a[i] = r / x;
            r %= x;
        }
        fix();
        return *this;
    }
    Bignum operator+(const Bignum &s)
    {
        Bignum c;
        copy(a, a + n, c.a);
        c.n = n;
        c += s;
        return c;
    }
    Bignum operator-(const Bignum &s)
    {
        Bignum c;
        copy(a, a + n, c.a);
        c.n = n;
        c -= s;
        return c;
    }
    Bignum operator*(const Bignum &s)
    {
        Bignum c;
        copy(a, a + n, c.a);
        c.n = n;
        c *= s;
        return c;
    }
    Bignum operator/(const ll &x)
    {
        Bignum c;
        copy(a, a + n, c.a);
        c.n = n;
        c /= x;
        return c;
    }
    ll operator%(const ll &x)
    {
        ll ans(0);
        for (int i = n - 1; ~i; --i)
            ans = (ans * BASE + a[i]) % x;
        return ans;
    }
    int com(const Bignum &s) const
    {
        if (n < s.n)
            return 1;
        if (n > s.n)
            return 2;
        for (int i = n - 1; i > -1; --i)
            if (a[i] > s.a[i])
                return 2;
            else if (a[i] < s.a[i])
                return 1;
        return 3;
    }
    bool operator<(const Bignum &s) const
    {
        return com(s) == 1;
    }
    bool operator>(const Bignum &s) const
    {
        return com(s) == 2;
    }
    bool operator==(const Bignum &s) const
    {
        return com(s) == 3;
    }
    bool operator<=(const Bignum &s) const
    {
        return com(s) != 2;
    }
    bool operator>=(const Bignum &s) const
    {
        return com(s) != 1;
    }
    void read()
    {
        string s;
        cin >> s;
        Convert(s);
    }
    void print()
    {
        int i = n;
        while (i > 0 && a[i] == 0)
            --i;
        cout << a[i];
        for (--i; ~i; --i)
            cout << setw(gd) << setfill('0')
                 << a[i];
    }
};
```

5.13 Bignum with FFT multiplication

```
// Replace function *= in Bignum implementation with below code:
void fft(vector<cd> &a, bool invert)
{
```

```
    int n = a.size();
    for (int i = 1, j = 0; i < n; i++)
    {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1)
            j ^= bit;
        j ^= bit;
        if (i < j)
            swap(a[i], a[j]);
    }
    for (int len = 2; len <= n; len <<= 1)
    {
        double ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for (int i = 0; i < n; i += len)
        {
            cd w(1);
            for (int j = 0; j < len / 2; j++)
            {
                cd u = a[i + j], v = a[i + j + len / 2] * w;
                a[i + j] = u + v;
                a[i + j + len / 2] = u - v;
                w *= wlen;
            }
        }
    }
    if (invert)
    {
        for (cd &x : a)
            x /= n;
    }
}
Bignum &operator*=(const Bignum &x)
{
    int m = 1;
    while (m < n + x.n)
        m <<= 1;
    vector<cd> fa(m), fb(m);
    for (int i = 0; i < m; ++i)
    {
        fa[i] = a[i];
        fb[i] = x.a[i];
    }
    fft(fa, false); /// dft
    fft(fb, false); /// dft
    for (int i = 0; i < m; i++)
        fa[i] *= fb[i];
    fft(fa, true); /// Interpolation
    n = m;
    for (int i = 0; i < n; ++i)
        a[i] = round(fa[i].real());
    fix();
    return *this;
}
```

5.14 Tonelli Shanks (Find square root modulo prime)

```
/*
Takes as input an odd prime p and n < p and returns r such that r
     * r = n [mod p].
There's exist r if and only if n ^ [(p-1) / 2] = 1 (mod p)
*/

using ll = int; // Change type of data here

ll Pow(ll a, ll b, ll mod)
{
    ll ans(1);

    for (; b; b >>= 1)
    {
        if (b & 1)
            ans = ans * a % mod;
        a = a * a % mod;
    }

    return ans;
}

ll tonelli_shanks(ll n, ll p)
{
    ll s = 0;
    ll q = p - 1;
    while ((q & 1) == 0)
    {
        q /= 2;
        ++s;
    }
    if (s == 1)
    {
        ll r = Pow(n, (p + 1) / 4, p);
        if ((r * r) % p == n)
            return r;
        return 0;
    }
    // Find the first quadratic non-residue z by brute-force
        search
    ll z = 1;
    while (Pow(++z, (p - 1) / 2, p) != p - 1)
        ;
    ll c = Pow(z, q, p);
    ll r = Pow(n, (q + 1) / 2, p);
    ll t = Pow(n, q, p);
    ll m = s;
    while (t != 1)
    {
        ll tt = t;
        ll i = 0;
        while (tt != 1)
        {
            tt = (tt * tt) % p;
            ++i;
            if (i == m)
                return 0;
        }
        ll b = Pow(c, Pow(2, m - i - 1, p - 1), p);
        ll b2 = (b * b) % p;
        r = (r * b) % p;
        t = (t * b2) % p;
        c = b2;
        m = i;
    }
    if ((r * r) % p == n)
        return r;
    return -1; // Can't find
}
```

5.15 Discrete Logarithm (Find x that $a^x \equiv b \ (mod \ m)$)

```
// Returns minimum x for which a ^ x % m = b % m.
// Returns -1 if x isn't exist

using ll = int;

ll DiscreteLogarithm(ll a, ll b, ll m)
{
    a %= m, b %= m;
    ll k = 1, add = 0, g;
    while ((g = __gcd(a, m)) > 1)
    {
        if (b == k)
            return add;
        if (b % g)
            return -1;
        b /= g, m /= g, ++add;
        k = (k * 1ll * a / g) % m;
    }

    ll n = sqrt((ld)m) + 1;
    ll an = 1;
    for (ll i = 0; i < n; ++i)
        an = (an * 1ll * a) % m;
    unordered_map<ll, ll> vals;
    for (ll q = 0, cur = b; q <= n; ++q)
    {
        vals[cur] = q;
        cur = (cur * 1ll * a) % m;
    }

    for (ll p = 1, cur = k; p <= n; ++p)
    {
        cur = (cur * 1ll * an) % m;
        if (vals.count(cur))
        {
            ll ans = n * p - vals[cur] + add;
            return ans;
        }
    }
    return -1;
}
```

5.16 Primitive Root (Exist k that $g^k \equiv a \ (mod \ n)$ for all a)

```
/*
g is a primitive root modulo n if and only if for any integer a
     such that gcd(a, n) = 1, there exists an integer k such that:
g^k = a (mod n).

Primitive root modulo n exists if and only if:
    - n is 1, 2, 4
    - n is power of an odd prime number (n = p ^ k)
    - n is twice power of an odd prime number (n = 2 * p ^ k)

This theorem was proved by Gauss in 1801.
*/

using ll = int; // Change type of data here

ll Pow(ll a, ll b, ll mod)
{
    ll ans(1);

    for (; b; b >>= 1)
    {
        if (b & 1)
            ans = ans * a % mod;
        a = a * a % mod;
    }

    return ans;
}

ll GetPhi(ll n)
{
    ll ans(1);

    for (ll i = 2; i * i <= n; ++i)
        if (n % i == 0)
        {
            while (n % i == 0)
            {
                n /= i;
                ans *= i;
            }

            ans = ans / i * (i - 1);
        }

    if (n != 1)
        ans *= n - 1;

    return ans;
}

ll PrimitiveRoot(ll p)
{
    vector<ll> fact;
    ll phi = GetPhi(p);
    ll n = phi;
```

```
    for (int i = 2; i * i <= n; ++i)
        if (n % i == 0)
        {
            fact.push_back(i);
            while (n % i == 0)
                n /= i;
        }

    if (n > 1)
        fact.push_back(n);

    for (ll res = 2; res <= p; ++res)
    {
        bool ok = true;

        for (int i = 0; i < fact.size() && ok; ++i)
            ok &= Pow(res, phi / fact[i], p) != 1;

        if (ok)
            return res;
    }

    return -1; // can't find
}
```

5.17 Discrete Root (Find x that $x^k \equiv a \pmod n$, n is a prime)

```
/*
Given a prime n and two integers a and k, find all x for which:\
    - x ^ k = a (mod n)

Notice:
    - In case k = 2, let's use Tonelli - Shanks
    - You must insert my implementation of Discrete Logarithm and
        Primitive Root to run algorithm
*/

ll Pow(ll a, ll b, ll mod)
{
    ll ans(1);

    for (; b; b >>= 1)
    {
        if (b & 1)
            ans = ans * a % mod;
        a = a * a % mod;
    }

    return ans;
}

ll DiscreteRoot(ll a, ll k, ll n)
{
    ll g = PrimitiveRoot(n);
    ll v = Pow(g, k, n);
    ll ans = DiscreteLogarithm(v, a, n);

    if (ans == -1)
        return -1; // Can't find

    return Pow(g, ans, n);
}
```

5.18 Super Sieve of Primes (Code by RR)

```
// Sieve up to 10^9 by RR
namespace Sieve
{
    const int MAX = 1000000000LL;
    const int WHEEL = 3 * 5 * 7 * 11 * 13;
    const int N_SMALL_PRIMES = 6536;    // cnt primes less than
        2^16
    const int SIEVE_SPAN = WHEEL * 64; // one iteration of
        segmented sieve
    const int SIEVE_SIZE = SIEVE_SPAN / 128 + 1;

    uint64_t ONES[64];                  // ONES[i] = 1<<i
    int small_primes[N_SMALL_PRIMES]; // primes less than 2^16

    // each element of sieve is a 64-bit bitmask.
    // Each bit (0/1) stores whether the corresponding element is
        a prime number.
    // We only need to store odd numbers
    // -> 1st bitmask stores 3, 5, 7, 9, ...
    uint64_t si[SIEVE_SIZE];
    // for each 'wheel', we store the sieve pattern (i.e. what
        numbers cannot be primes)
    uint64_t pattern[WHEEL];

    inline void mark(uint64_t *s, int o) { s[o >> 6] |= ONES[o &
        63]; }
    inline int test(uint64_t *s, int o) { return (s[o >> 6] & ONES
        [o & 63]) == 0; }

    // update_sieve {{{
    void update_sieve(int offset)
    {
        // copy each wheel pattern to sieve
        for (int i = 0, k; i < SIEVE_SIZE; i += k)
        {
            k = std::min(WHEEL, SIEVE_SIZE - i);
            memcpy(si + i, pattern, sizeof(*pattern) * k);
        }

        // Correctly mark 1, 3, 5, 7, 11, 13 as not prime / primes
        if (offset == 0)
        {
            si[0] |= ONES[0];
            si[0] &= ~(ONES[1] | ONES[2] | ONES[3] | ONES[5] |
                ONES[6]);
        }

        // sieve for primes >= 17 (stored in `small_primes`)
        for (int i = 0; i < N_SMALL_PRIMES; ++i)
        {
            int j = small_primes[i] * small_primes[i];
            if (j > offset + SIEVE_SPAN - 1)
                break;
            if (j > offset)
                j = (j - offset) >> 1;
            else
            {
                j = small_primes[i] - offset % small_primes[i];
                if ((j & 1) == 0)
                    j += small_primes[i];
                j >>= 1;
            }
            while (j < SIEVE_SPAN / 2)
            {
                mark(si, j);
                j += small_primes[i];
            }
        }
    }
    // }}}

    void sieve()
    {
        // init small primes {{{
        for (int i = 0; i < 64; ++i)
            ONES[i] = 1ULL << i;

        // sieve to find small primes
        for (int i = 3; i < 256; i += 2)
        {
            if (test(si, i >> 1))
            {
                for (int j = i * i / 2; j < 32768; j += i)
                    mark(si, j);
            }
        }
        // store primes >= 17 in `small_primes` (we will sieve
            differently
        // for primes 2, 3, 5, 7, 11, 13)
        {
            int m = 0;
            for (int i = 8; i < 32768; ++i)
            {
                if (test(si, i))
                    small_primes[m++] = i * 2 + 1;
            }
        }
        // }}}

        // For primes 3, 5, 7, 11, 13: we initialize wheel pattern
            ..
        for (int i = 1; i < WHEEL * 64; i += 3)
            mark(pattern, i);
        for (int i = 2; i < WHEEL * 64; i += 5)
            mark(pattern, i);
        for (int i = 3; i < WHEEL * 64; i += 7)
            mark(pattern, i);
        for (int i = 5; i < WHEEL * 64; i += 11)
            mark(pattern, i);
        for (int i = 6; i < WHEEL * 64; i += 13)
            mark(pattern, i);

        // Segmented sieve
        long long sum_primes = 2;

        for (int offset = 0; offset < MAX; offset += SIEVE_SPAN)
        {
            update_sieve(offset);

            for (uint32_t j = 0; j < SIEVE_SIZE; j++)
            {
                uint64_t x = ~si[j];
                while (x)
                {
                    uint32_t p = offset + (j << 7) + (
                        __builtin_ctzll(x) << 1) + 1;
                    if (p > offset + SIEVE_SPAN - 1)
                        break;
                    if (p <= MAX)
                    {
                        // p is a prime
                    }
                    x ^= (-x & x);
                }
            }
        }
    }
};
```

6 Graph algorithms

6.1 Twosat (2-SAT)

```
// start from 0
// pos(V) is the vertex that represent V in graph
// neg(V) is the vertex that represent !V
// pos(V) ^ neg(V) = 1, use two functions below
// (U v V) <=> (!U -> V) <=> (!V -> U)
// You need do addEge(represent(U), represent(V))
// solve() == false mean no answer
// Want to get the answer ?
// color[pos(U)] = 1 means we choose U
// otherwise, we don't
constexpr int N = 1e5 + 5; // Keep N double of n
inline int pos(int u) { return u << 1; }
inline int neg(int u) { return u << 1 | 1; }
struct TwoSAT
{
    int n, numComp, cntTarjan;
    vector<int> adj[N], stTarjan;
    int low[N], num[N], root[N], color[N];
    TwoSAT(int n) : n(n * 2)
    {
        memset(root, -1, sizeof root);
        memset(low, -1, sizeof low);
```

```
        memset(num, -1, sizeof num);
        memset(color, -1, sizeof color);
        cntTarjan = 0;
        stTarjan.clear();
    }
    void addEdge(int u, int v)
    {
        adj[u ^ 1].push_back(v);
        adj[v ^ 1].push_back(u);
    }
    void tarjan(int u)
    {
        stTarjan.push_back(u);
        num[u] = low[u] = cntTarjan++;
        for (int v : adj[u])
        {
            if (root[v] != -1)
                continue;
            if (low[v] == -1)
                tarjan(v);
            low[u] = min(low[u], low[v]);
        }
        if (low[u] == num[u])
        {
            while (1)
            {
                int v = stTarjan.back();
                stTarjan.pop_back();
                root[v] = numComp;
                if (u == v)
                    break;
            }
            numComp++;
        }
    }
    bool solve()
    {
        for (int i = 0; i < n; i++)
            if (root[i] == -1)
                tarjan(i);
        for (int i = 0; i < n; i += 2)
        {
            if (root[i] == root[i ^ 1])
                return 0;
            color[i] = (root[i] < root[i ^ 1]);
        }
        return 1;
    }
};
```

6.2 Eulerian Path

```
// Path that goes all edges
// Start from 1
struct EulerianGraph
{
    vector<vector<pair<int, int>>> a;
    int num_edges;

    EulerianGraph(int n)
    {
        a.resize(n + 1);
        num_edges = 0;
    }

    void add_edge(int u, int v, bool undirected = true)
    {
        a[u].push_back(make_pair(v, num_edges));
        if (undirected)
            a[v].push_back(make_pair(u, num_edges));
        num_edges++;
    }

    vector<int> get_eulerian_path()
    {
        vector<int> path, s;
        vector<bool> was(num_edges);

        s.push_back(1);
        // start of eulerian path
        // directed graph: deg_out - deg_in == 1
        // undirected graph: odd degree
        // for eulerian cycle: any vertex is OK

        while (!s.empty())
        {
            int u = s.back();
            bool found = false;
            while (!a[u].empty())
            {
                int v = a[u].back().first;
                int e = a[u].back().second;
                a[u].pop_back();
                if (was[e])
                    continue;
                was[e] = true;
                s.push_back(v);
                found = true;
                break;
            }
            if (!found)
            {
                path.push_back(u);
                s.pop_back();
            }
        }
        reverse(path.begin(), path.end());
        return path;
    }
};
```

6.3 Biconnected Component Tree

```
// Biconnected Component Tree
// 1 is the root of Tree
// n + i is the node that represent i-th bcc, its depth is even

const int N = 3e5 + 5; // Change size to n + number of bcc (For
     safety, set N >= 2 * n)
int n, nBicon, nTime;
int low[N], num[N];
vector<int> adj[N], nadj[N];
vector<int> s;

void dfs(int v, int p = -1)
{
    low[v] = num[v] = ++nTime;
    s.emplace_back(v);

    for (auto i : adj[v])
        if (i != p)
        {
            if (!num[i])
            {
                dfs(i, v);
                low[v] = min(low[v], low[i]);

                if (low[i] >= num[v])
                {
                    ++nBicon;
                    nadj[v].emplace_back(n + nBicon);

                    int vertex;
                    do
                    {
                        vertex = s.back();
                        s.pop_back();

                        nadj[n + nBicon].emplace_back(vertex);
                    } while (vertex != i);
                }
            }
            else
                low[v] = min(low[v], num[i]);
        }
}
```

7 String

7.1 Palindrome Tree

```
// base on idea odd palindrome, even palindrome
// 0-odd is the root of tree
struct node
{
    int len;
    node *child[26], *sufflink;
    node()
    {
        len = 0;
        for (int i = 0; i < 26; ++i)
            child[i] = NULL;
        sufflink = NULL;
    }
};
struct PalindromeTree
{
    node odd, even;
    PalindromeTree()
    {
        odd.len = -1;
        odd.sufflink = &odd;
        even.len = 0;
        even.sufflink = &odd;
    }
    void Assign(string &s)
    {
        node *last = &even;
        for (int i = 0; i < (int)s.size(); ++i)
        {
            node *tmp = last;
            while (s[i - tmp->len - 1] != s[i])
                tmp = tmp->sufflink;
            if (tmp->child[s[i] - 'a'])
            {
                last = tmp->child[s[i] - 'a'];
                continue;
            }
            tmp->child[s[i] - 'a'] = new node;
            last = tmp->child[s[i] - 'a'];
            last->len = tmp->len + 2;
            if (last->len == 1)
            {
                last->sufflink = &even;
                continue;
            }
            tmp = tmp->sufflink;
            while (s[i - tmp->len - 1] != s[i])
                tmp = tmp->sufflink;
            last->sufflink = tmp->child[s[i] - 'a'];
        }
    }
};
```

7.2 Suffix Array

```
// string and array pos start from 0
// but array sa and lcp start from 1

constexpr int N = 3e5 + 5; // change size to size of string;

struct SuffixArray
{
    string s;
    int n, c[N], p[N], rp[N], lcp[N];

    //p[] : suffix array
    // lcp[]: lcp array
```

```
    void Assign(const string &x)
    {
        s = x;
        s.push_back('$'); // Change character here due to range of
              charater in string
        n = s.size();
        Build();
        s.pop_back();
        n = s.size();
    }

    void Build()
    {
        vector<int> pn(N), cn(N), cnt(N);

        for (int i = 0; i < n; ++i)
            ++cnt[s[i]];
        for (int i = 1; i <= 256; ++i)
            cnt[i] += cnt[i - 1];
        for (int i = 0; i < n; ++i)
            p[--cnt[s[i]]] = i;

        for (int i = 1; i < n; ++i)
            c[p[i]] = c[p[i - 1]] + (s[p[i]] != s[p[i - 1]]);

        int maxn = c[p[n - 1]];

        for (int i = 0; (1 << i) < n; ++i)
        {
            for (int j = 0; j < n; ++j)
                p[j] = ((p[j] - (1 << i)) % n + n) % n;
            for (int j = 0; j <= maxn; ++j)
                cnt[j] = 0;

            for (int j = 0; j < n; ++j)
                ++cnt[c[p[j]]];

            for (int j = 1; j <= maxn; ++j)
                cnt[j] += cnt[j - 1];

            for (int j = n - 1; ~j; --j)
                pn[--cnt[c[p[j]]]] = p[j];

            for (int j = 1; j < n; ++j)
                cn[pn[j]] = cn[pn[j - 1]] + (c[pn[j]] != c[pn[j -
                      1]] || c[(pn[j] + (1 << i)) % n] != c[(pn[j -
                       1] + (1 << i)) % n]);

            maxn = cn[pn[n - 1]];

            for (int j = 0; j < n; ++j)
            {
                p[j] = pn[j];
                c[j] = cn[j];
            }
        }
    }

    void BuildLCP()
    {
        for (int i = 1; i <= n; ++i)
            rp[p[i]] = i;
        for (int i = 0; i < n; ++i)
        {
            if (i)
                lcp[i] = max(lcp[i - 1] - 1, 0);
            if (rp[i] == n)
                continue;

            while (lcp[i] < n - i && lcp[i] < n - p[rp[i] + 1] &&
                 s[i + lcp[i]] == s[p[rp[i] + 1] + lcp[i]])
                ++lcp[i];
        }
    }
} g;
```

7.3 Suffix Array (Template by Tran Khoi Nguyen)

```
struct suffix_array
{
    vector<int> sa_naive(const vector<int> &s)
    {
        int n = (int)s.size();
        vector<int> sa(n);
        iota(sa.begin(), sa.end(), 0);
        sort(sa.begin(), sa.end(), [&](int l, int r)
             {
            if(l == r) return false;
            for(; l < n && r < n; ++ l, ++ r) if(s[l] != s[r])
                 return s[l] < s[r];
            return l == n; });
        return sa;
    }
    vector<int> sa_doubling(const vector<int> &s)
    {
        int n = (int)s.size();
        vector<int> sa(n), rank = s, tmp(n);
        iota(sa.begin(), sa.end(), 0);
        for (auto k = 1; k < n; k <<= 1)
        {
            auto cmp = [&](int x, int y)
            {
                if (rank[x] != rank[y])
                    return rank[x] < rank[y];
                int rx = x + k < n ? rank[x + k] : -1;
                int ry = y + k < n ? rank[y + k] : -1;
                return rx < ry;
            };
            sort(sa.begin(), sa.end(), cmp);
            tmp[sa[0]] = 0;
            for (auto i = 1; i < n; ++i)
                tmp[sa[i]] = tmp[sa[i - 1]] + (cmp(sa[i - 1], sa[i
                      ]) ? 1 : 0);
            swap(tmp, rank);
        }
        return sa;
    }
    template <int THRESHOLD_NAIVE = 10, int THRESHOLD_DOUBLING =
          40>
    vector<int> sa_is(const vector<int> &s, int sigma)
    {
        int n = (int)s.size();
        if (n == 0)
            return {};
        if (n == 1)
            return {0};
        if (n == 2)
        {
            if (s[0] < s[1])
                return {0, 1};
            else
                return {1, 0};
        }
        if (n < THRESHOLD_NAIVE)
            return sa_naive(s);
        if (n < THRESHOLD_DOUBLING)
            return sa_doubling(s);
        vector<int> sa(n);
        vector<bool> ls(n);
        for (auto i = n - 2; i >= 0; --i)
            ls[i] = (s[i] == s[i + 1]) ? ls[i + 1] : (s[i] < s[i +
                  1]);
        vector<int> sum_l(sigma), sum_s(sigma);
        for (auto i = 0; i < n; ++i)
        {
            if (!ls[i])
                ++sum_s[s[i]];
            else
                ++sum_l[s[i] + 1];
        }
        for (auto i = 0; i < sigma; ++i)
        {
            sum_s[i] += sum_l[i];
            if (i + 1 < sigma)
                sum_l[i + 1] += sum_s[i];
        }

        auto induce = [&](const vector<int> &lms)
        {
            fill(sa.begin(), sa.end(), -1);
            vector<int> buf(sigma);
            copy(sum_s.begin(), sum_s.end(), buf.begin());
            for (auto d : lms)
            {
                if (d == n)
                    continue;
                sa[buf[s[d]]++] = d;
            }
            copy(sum_l.begin(), sum_l.end(), buf.begin());
            sa[buf[s[n - 1]]++] = n - 1;
            for (auto i = 0; i < n; ++i)
            {
                int v = sa[i];
                if (v >= 1 && !ls[v - 1])
                    sa[buf[s[v - 1]]++] = v - 1;
            }
            copy(sum_l.begin(), sum_l.end(), buf.begin());
            for (auto i = n - 1; i >= 0; --i)
            {
                int v = sa[i];
                if (v >= 1 && ls[v - 1])
                    sa[--buf[s[v - 1] + 1]] = v - 1;
            }
        };
        vector<int> lms_map(n + 1, -1);
        int m = 0;
        for (auto i = 1; i < n; ++i)
            if (!ls[i - 1] && ls[i])
                lms_map[i] = m++;
        vector<int> lms;
        lms.reserve(m);
        for (auto i = 1; i < n; ++i)
            if (!ls[i - 1] && ls[i])
                lms.push_back(i);
        induce(lms);
        if (m)
        {
            vector<int> sorted_lms;
            sorted_lms.reserve(m);
            for (auto v : sa)
                if (lms_map[v] != -1)
                    sorted_lms.push_back(v);
            vector<int> rec_s(m);
            int rec_sigma = 0;
            rec_s[lms_map[sorted_lms[0]]] = 0;
            for (auto i = 1; i < m; ++i)
            {
                int l = sorted_lms[i - 1], r = sorted_lms[i];
                int end_l = (lms_map[l] + 1 < m) ? lms[lms_map[l]
                      + 1] : n;
                int end_r = (lms_map[r] + 1 < m) ? lms[lms_map[r]
                      + 1] : n;
                bool same = true;
                if (end_l - l != end_r - r)
                    same = false;
                else
                {
                    for (; l < end_l; ++l, ++r)
                        if (s[l] != s[r])
                            break;
                    if (l == n || s[l] != s[r])
                        same = false;
                }
                if (!same)
                    ++rec_sigma;
                rec_s[lms_map[sorted_lms[i]]] = rec_sigma;
            }
            auto rec_sa = sa_is<THRESHOLD_NAIVE,
                 THRESHOLD_DOUBLING>(rec_s, rec_sigma + 1);
            for (auto i = 0; i < m; ++i)
                sorted_lms[i] = lms[rec_sa[i]];
            induce(sorted_lms);
        }
        return sa;
    }
```

```
    int n;
    // data: sorted sequence of suffices including the empty
         suffix
    // rank[i]: position of the suffix i in the suffix array
    // lcp[i]: longest common prefix of data[i] and data[i + 1]
    // index start from 1
    vector<int> data, rank, lcp;
    // O(n + sigma)
    suffix_array(const vector<int> &s, int sigma) : n((int)s.size
         ()), rank(n + 1), lcp(n)
    {
        assert(0 <= sigma);
        for (auto d : s)
            assert(0 <= d && d < sigma);
        data = sa_is(s, sigma);
        data.insert(data.begin(), n);
        for (auto i = 0; i <= n; ++i)
            rank[data[i]] = i;
        for (auto i = 0, h = 0; i <= n; ++i)
        {
            if (h > 0)
                --h;
            if (rank[i] == 0)
                continue;
            int j = data[rank[i] - 1];
            for (; j + h <= n && i + h <= n; ++h)
                if ((j + h == n) != (i + h == n) || j + h < n && s
                     [j + h] != s[i + h])
                    break;
            lcp[rank[i] - 1] = h;
        }
    }
    // O(n log n) time, O(n) space
    template <class T>
    suffix_array(const vector<T> &s, bool prepare_lcp) : n((int)s.
         size()), rank(n + 1), lcp(n)
    {
        vector<int> idx(n);
        iota(idx.begin(), idx.end(), 0);
        sort(idx.begin(), idx.end(), [&](int l, int r)
             { return s[l] < s[r]; });
        vector<int> s2(n);
        int now = 0;
        for (auto i = 0; i < n; ++i)
        {
            if (i && s[idx[i - 1]] != s[idx[i]])
                ++now;
            s2[idx[i]] = now;
        }
        data = sa_is(s2, now + 1);
        data.insert(data.begin(), n);
        for (auto i = 0; i <= n; ++i)
            rank[data[i]] = i;
        for (auto i = 0, h = 0; i <= n; ++i)
        {
            if (h > 0)
                --h;
            if (rank[i] == 0)
                continue;
            int j = data[rank[i] - 1];
            for (; j + h <= n && i + h <= n; ++h)
                if ((j + h == n) != (i + h == n) || j + h < n && s
                     [j + h] != s[i + h])
                    break;
            lcp[rank[i] - 1] = h;
        }
    }
    // RMQ must be built over lcp
    // O(1)
    template <class RMQ>
    int longest_common_prefix(int i, int j, const RMQ &rmq) const
    {
        assert(0 <= i && i <= n && 0 <= j && j <= n);
        return i == j ? n - i : rmq.query(min(rank[i], rank[j]),
             max(rank[i], rank[j]));
    }
};
```

7.4 Aho Corasick - Extended KMP

```
constexpr int ALPHABET_SIZE = 26;
constexpr int firstCharacter = 'a';

struct Node
{
    Node *to[ALPHABET_SIZE];
    Node *suflink;
    int ending_length; // 0 if is not ending

    Node()
    {
        for (int i = 0; i < ALPHABET_SIZE; ++i)
            to[i] = NULL;
        suflink = NULL;
        ending_length = false;
    }
};

struct AhoCorasick
{
    Node *root;

    AhoCorasick()
    {
        root = new Node();
    }

    void add(const string &s)
    {
        Node *cur_node = root;

        for (char c : s)
        {
            int v = c - firstCharacter;

            if (!cur_node->to[v])
                cur_node->to[v] = new Node();

            cur_node = cur_node->to[v];
        }

        cur_node->ending_length = s.size();
    }

    // if a->to[v] == NULL
    // for convinient a->to[v] = the node x->to[v] that a match x
         and x->to[v] != NULL
    // root -> suflink = root

    void build()
    {
        queue<Node *> Q;
        root->suflink = root;
        Q.push(root);

        while (!Q.empty())
        {
            Node *par = Q.front();
            Q.pop();
            for (int c = 0; c < ALPHABET_SIZE; ++c)
            {
                if (par->to[c])
                {
                    par->to[c]->suflink = par == root ? root : par
                         ->suflink->to[c];
                    Q.push(par->to[c]);
                }
                else
                {
                    par->to[c] = par == root ? root : par->suflink
                         ->to[c];
                }
            }
        }
    }
};
```

7.5 Aho Corasick (Template by Tran Khoi Nguyen)

```
struct aho_corasick
{
    struct tk
    {
        ll link;
        ll nxt[27];
        ll par;
        char ch;
        ll go[27];
        ll val;
        ll leaf;
        tk(ll par = -1, char ch = 'a') : par(par), ch(ch)
        {
            memset(nxt, -1, sizeof(nxt));
            memset(go, -1, sizeof(go));
            val = -1;
            link = -1;
            leaf = 0;
        }
    };
    vector<tk> vt;
    void init()
    {
        vt.clear();
        vt.pb({-1, 'a'});
    }
    ll add(string s, ll val)
    {
        ll nw = 0;
        for (auto to : s)
        {
            if (vt[nw].nxt[to - 'a' + 1] == -1)
            {
                vt[nw].nxt[to - 'a' + 1] = vt.size();
                vt.pb({nw, to});
            }
            nw = vt[nw].nxt[to - 'a' + 1];
        }
        vt[nw].leaf = val;
        return nw;
    }
    ll get_val(ll u)
    {
        if (u == 0)
            return 0;
        if (vt[u].val == -1)
        {
            vt[u].val = vt[u].leaf + get_val(get_link(u));
        }
        return vt[u].val;
    }
    ll go(ll v, ll t)
    {
        if (vt[v].go[t] == -1)
        {
            if (vt[v].nxt[t] != -1)
            {
                vt[v].go[t] = vt[v].nxt[t];
            }
            else
            {
                if (v == 0)
                    vt[v].go[t] = 0;
                else
                    vt[v].go[t] = go(get_link(v), t);
            }
        }
        return vt[v].go[t];
    }
    ll get_link(ll v)
    {
        if (vt[v].link == -1)
        {
```

```
            if (vt[v].par == 0 || v == 0)
                vt[v].link = 0;
            else
                vt[v].link = go(get_link(vt[v].par), vt[v].ch - 'a
                    ' + 1);
        }
        return vt[v].link;
    }
    ll get(string s)
    {
        ll nw = 0;
        ll ans = 0;
        for (auto to : s)
        {
            nw = go(nw, to - 'a' + 1);
            ans += get_val(nw);
        }
        return ans;
    }
};
```

7.6 Suffix Tree (Template by Tran Khoi Nguyen)

```
struct tk
{
    map<ll, ll> nxt;
    ll par, f, len;
    ll link;
    tk(ll par = -1, ll f = 0, ll len = 0) : par(par), f(f), len(
        len)
    {
        nxt.clear();
        link = -1;
    }
};

struct Suffix_Tree
{
    vector<tk> st;
    ll node;
    ll dis;
    s
        ll n;
    vector<ll> s;
    void init()
    {
        st.clear();
        node = 0;
        dis = 0;
        st.emplace_back(-1, 0, base);
        n = 0;
    }

    void go_edge()
    {
        while (dis > st[st[node].nxt[s[n - dis]]].len)
        {
            node = st[node].nxt[s[n - dis]];
            dis -= st[node].len;
        }
    }

    void add_char(ll c)
    {
        ll last = 0;
        s.pb(c);
        n = s.size();
        dis++;
        while (dis > 0)
        {
            go_edge();
            ll edge = s[n - dis];
            ll &v = st[node].nxt[edge];
            ll t = s[st[v].f + dis - 1];
            if (v == 0)
            {
                v = st.size();
                st.emplace_back(node, n - dis, base);
                st[last].link = node;
                last = 0;
            }
            else if (c == t)
            {
                st[last].link = node;
                return;
            }
            else
            {
                ll u = st.size();
                st.emplace_back(node, st[v].f, dis - 1);
                st[u].nxt[c] = st.size();
                st.emplace_back(u, n - 1, base);
                st[u].nxt[t] = v;
                st[v].f += (dis - 1);
                st[v].len -= (dis - 1);
                v = u;
                st[last].link = u;
                last = u;
            }
            if (node == 0)
                dis--;
            else
                node = st[node].link;
        }
    }
};
```

7.7 Z Function

```
// string start from 1
// f[i] = longest prefix match with s[i...i + f[i] - 1]

constexpr int N = 2e5 + 5;

void Build(string &s, int n, int f[N]) // n = size of string, f =
     z array
{
    int l(1), r(1);

    f[1] = n;

    for (int i = 2; i <= n; ++i)
        if (r < i)
        {
            l = r = i;
            while (r <= n && s[r - i + 1] == s[r])
                ++r;
            f[i] = r - i;
            --r;
        }
        else if (f[i - l + 1] < r - i + 1)
            f[i] = f[i - l + 1];
        else
        {
            l = i;
            while (r <= n && s[r - i + 1] == s[r])
                ++r;
            f[i] = r - i;
            --r;
        }
}
```

8 Data structures

8.1 Ordered Set

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

#define ordered_set tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update>

/*
order_of_key (k) : Number of items strictly smaller than k.
find_by_order(k) : K-th element in a set (counting from zero).
*/
```

8.2 Fenwick Tree (With Walk on tree)

```
// This is equivalent to calculating lower_bound on prefix sums
    array
// LOGN = log2(N)

struct FenwickTree
{
    int n, LOGN;
    ll a[N]; // BIT array

    FenwickTree()
    {
        memset(a, 0, sizeof a);
    }

    void Update(int p, ll v)
    {
        for (; p <= n; p += p & -p)
            a[p] += v;
    }

    ll Get(int p)
    {
        ll ans(0);

        for (; p; p -= p & -p)
            ans += a[p];

        return ans;
    }

    int search(ll v)
    {
        ll sum = 0;
        int pos = 0;
        for (int i = LOGN; i >= 0; i--)
        {
            if (pos + (1 << i) <= n && sum + a[pos + (1 << i)] < v
                )
            {
                sum += a[pos + (1 << i)];
                pos += (1 << i);
            }
        }
        return pos + 1;
        //+1 because pos will be position of largest value less
            than v
    }
};
```

8.3 Convex Hull Trick (Min)

```
// If you want to get maximum, sort coef (A) not decreasing and
    change B[line.back()] > B[i] into B[line.back()] < B[i]

struct ConvexHullTrick
{
    vector<ll> A, B;
    vector<int> line;
    vector<ld> point;
    ConvexHullTrick(int n = 0)
    {
        A.resize(n + 2, 0);
        B.resize(n + 2, 0);
        point.emplace_back(-Inf);
    }

    ld ff(int x, int y)
    {
        return (ld)1.0 * (B[y] - B[x]) / (A[x] - A[y]);
```

```
    }

    void Add(int i)
    {
        while ((int)line.size() > 1 || ((int)line.size() == 1 && A
             [line.back()] == A[i]))
        {
            if (A[line.back()] == A[i])
            {
                if (B[line.back()] > B[i])
                {
                    line.pop_back();
                    if (!line.empty())
                        point.pop_back();
                }
                else
                    break;
            }
            else
            {
                if (ff(i, line.back()) <= ff(i, line[line.size() -
                     2]))
                {
                    line.pop_back();
                    if (!line.empty())
                        point.pop_back();
                }
                else
                    break;
            }
        }

        if (line.empty() || A[line.back()] != A[i])
        {
            if (!line.empty())
                point.emplace_back(ff(line.back(), i));
            line.emplace_back(i);
        }
    }
    ll Get(int x)
    {
        int j = lower_bound(point.begin(), point.end(), x) - point
             .begin();
        return A[line[j - 1]] * x + B[line[j - 1]];
    }
};
```

8.4 Dynamic Convex Hull Trick (Min)

```
struct Line
{
    mutable ll k, m, p;
    bool operator<(const Line& o) const
    {
        if (k==o.k) return m>o.m;
        return k > o.k;
    }
    bool operator<(ll x) const
    {
        return p < x;
    }
};
struct LineContainer : multiset<Line, less<>>
{
    static const ll inf = LLONG_MAX;
    ll div(ll a, ll b)
    {
        return a / b - ((a ^ b) < 0 && a % b);
    }
    bool isect(iterator x, iterator y)
    {
        if (y == end())
            return x->p = inf, 0;
        if (x->k == y->k)
            x->p = x->m < y->m ? inf : -inf;
        else
            x->p = div(y->m - x->m, x->k - y->k);
        return x->p >= y->p;
    }
    void add(ll k, ll m)
    {
        auto z = insert({k, m, 0}), y = z++, x = y;
        while (isect(y, z))
            z = erase(z);
        if (x != begin() && isect(--x, y))
            isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p)
            isect(x, erase(y));
    }
    ll query(ll x)
    {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};
```

8.5 SPlay Tree

```
struct KNode
{
    int Value;
    int Size;
    KNode *P, *L, *R;
};
using QNode = KNode *;
KNode No_thing_here;
QNode nil = &No_thing_here, root;

void Link(QNode par, QNode child, bool Right)
{
    child->P = par;
    if (Right)
        par->R = child;
    else
        par->L = child;
}

void Update(QNode &a)
{
    a->Size = a->L->Size + a->R->Size + 1;
}

void Init()
{
    nil->Size = 0;
    nil->P = nil->L = nil->R = nil;
    root = nil;
    for (int i = 1; i <= n; ++i)
    {
        QNode cur = new KNode;
        cur->P = cur->L = cur->R = nil;
        cur->Value = i;
        Link(cur, root, false);
        root = cur;
        Update(root);
    }
}

void Rotate(QNode x)
{
    QNode y = x->P;
    QNode z = y->P;
    if (x == y->L)
    {
        Link(y, x->R, false);
        Link(x, y, true);
    }
    else
    {
        Link(y, x->L, true);
        Link(x, y, false);
    }
    Update(y);
    Update(x);
    x->P = nil;
    if (z != nil)
        Link(z, x, z->R == y);
}

void Up_to_Root(QNode x)
{
    while (1){
        QNode y = x->P;
        QNode z = y->P;
        if(y == nil)
            break;
        if(z != nil){
            if((x == y->L) == (y == z->L))
                Rotate(y);
            else
                Rotate(x);
        }
        Rotate(x);
    }
}

QNode The_kth(QNode x, int k)
{
    while (true)
    {
        if (x->L->Size == k - 1)
            return x;
        if (x->L->Size >= k)
            x = x->L;
        else
        {
            k -= x->L->Size + 1;
            x = x->R;
        }
    }
    return nil;
}

void Split(QNode x, int k, QNode &a, QNode &b)
{
    if (k == 0)
    {
        a = nil;
        b = x;
        return;
    }
    QNode cur = The_kth(x, k);
    Up_to_Root(cur);
    a = cur;
    b = a->R;
    a->R = nil;
    b->P = nil;
    Update(a);
}

QNode Join(QNode a, QNode b)
{
    if (a == nil)
        return b;
    while (a->R != nil)
        a = a->R;
    Up_to_Root(a);
    Link(a, b, true);
    Update(a);
    return a;
}

void Print(QNode &a)
{
    if (a->L != nil)
        Print(a->L);
    cout << (a->Value) << " ";
    if (a->R != nil)
        Print(a->R);
}
```

8.6 Hashing (Template by Tran Khoi Nguyen)

```
struct Hashing
{
    vector<vector<vector<ll>>> f;
    vector<ll> mod;
    vector<vector<ll>> mu;
    vector<ll> chr;
    ll num;
    ll base;
    void init()
    {
        num = 2;
        f.clear();
        mod.clear();
        mu.clear();
        chr.clear();
        vector<ll> vt = {999244369, 999254351, 999154309,
             989154311, 989254411, 997254397, 991294387,
             991814399, 994114351, 994914359, 994024333};
        random_shuffle(vt.begin(), vt.end());
        base = 317;
        for (int i = 1; i <= 26; i++)
            chr.pb(abs((ll)(rnd())));
        for (int i = 0; i < num; i++)
        {
            f.emplace_back();
            mod.pb(vt[i]);
            vector<ll> pt;
            pt.pb(1);
            for (int j = 1; j < maxn; j++)
            {
                pt.pb((pt.back() * base) % mod[i]);
            }
            mu.pb(pt);
        }
    }
    ll add(string s)
    {
        ll n = s.length();
        ll id = f[0].size();
        for (int j = 0; j < num; j++)
        {
            vector<ll> vt1;
            vt1.pb(0);
            for (int i = 1; i <= n; i++)
            {
                vt1.pb((vt1.back() * base + chr[s[i - 1] - 'a']) %
                      mod[j]);
            }
            f[j].pb(vt1);
        }
        return id;
    }
    pll get_hash(ll id, ll l, ll r)
    {
        return make_pair(((f[0][id][r] - f[0][id][l - 1] * mu[0][r
              - l + 1]) % mod[0] + mod[0]) % mod[0], ((f[1][id][r]
              - f[1][id][l - 1] * mu[1][r - l + 1]) % mod[1] + mod
             [1]) % mod[1]);
    }
};
```

8.7 BIT 2D (Template by Tran Khoi Nguyen)

```
struct BIT_2D
{
    vector<ll> vt;
    vector<vector<ll>> f;
    vector<vector<ll>> node;
    void init(vector<ll> vt1)
    {
        vt = vt1;
        sort(vt.begin(), vt.end());
        vt.resize(unique(vt.begin(), vt.end()) - vt.begin());
        f = vector<vector<ll>>(vt.size() + 2, vector<ll>(0));
        node = vector<vector<ll>>(vt.size() + 2, vector<ll>(0));
    }
    void rearrange()
    {
        for (int i = 1; i <= vt.size(); i++)
        {
            sort(node[i].begin(), node[i].end());
            node[i].resize(unique(node[i].begin(), node[i].end())
                  - node[i].begin());
            f[i] = vector<ll>(node[i].size() + 2, 0);
        }
    }
    void fake_update(ll x, ll y)
    {
        for (int i = lower_bound(vt.begin(), vt.end(), x) - vt.
             begin() + 1; i <= vt.size(); i += i & (-i))
        {
            node[i].pb(y);
        }
    }
    void fake_get(ll x, ll y)
    {
        for (int i = lower_bound(vt.begin(), vt.end(), x) - vt.
             begin() + 1; i; i -= i & (-i))
        {
            node[i].pb(y);
        }
    }
    void update(ll x, ll y, ll val)
    {
        for (int i = lower_bound(vt.begin(), vt.end(), x) - vt.
             begin() + 1; i <= vt.size(); i += i & (-i))
        {
            for (int j = lower_bound(node[i].begin(), node[i].end
                 (), y) - node[i].begin() + 1; j <= node[i].size()
                 ; j += j & (-j))
            {
                f[i][j] = f[i][j] + val;
            }
        }
    }
    ll get(ll x, ll y)
    {
        ll ans = 0;
        for (int i = lower_bound(vt.begin(), vt.end(), x) - vt.
             begin() + 1; i; i -= i & (-i))
        {
            for (int j = lower_bound(node[i].begin(), node[i].end
                 (), y) - node[i].begin() + 1; j; j -= j & (-j))
            {
                ans += f[i][j];
            }
        }
        return ans;
    }
};
```

8.8 Wavelet Tree

```
struct wavelet_tree{
        int lo, hi;
        wavelet_tree *l, *r;
        vector<int> b;

        //nos are in range [x,y]
        //array indices are [from, to)
        wavelet_tree(int *from, int *to, int x, int y){
                lo = x, hi = y;
                if(lo == hi or from >= to) return;
                int mid = (lo+hi)/2;
                auto f = [mid](int x){
                        return x <= mid;
                };
                b.reserve(to-from+1);
                b.push_back(0);
                for(auto it = from; it != to; it++)
                        b.push_back(b.back() + f(*it));
                //see how lambda function is used here
                auto pivot = stable_partition(from, to, f);
                l = new wavelet_tree(from, pivot, lo, mid);
                r = new wavelet_tree(pivot, to, mid+1, hi);
        }

        //kth smallest element in [l, r]
        int kth(int l, int r, int k){
                if(l > r) return 0;
                if(lo == hi) return lo;
                int inLeft = b[r] - b[l-1];
                int lb = b[l-1]; //amt of nos in first (l-1) nos
                     that go in left
                int rb = b[r]; //amt of nos in first (r) nos that
                     go in left
                if(k <= inLeft) return this->l->kth(lb+1, rb , k);
                return this->r->kth(l-lb, r-rb, k-inLeft);
        }

        //count of nos in [l, r] Less than or equal to k
        int LTE(int l, int r, int k) {
                if(l > r or k < lo) return 0;
                if(hi <= k) return r - l + 1;
                int lb = b[l-1], rb = b[r];
                return this->l->LTE(lb+1, rb, k) + this->r->LTE(l-
                     lb, r-rb, k);
        }

        //count of nos in [l, r] equal to k
        int count(int l, int r, int k) {
                if(l > r or k < lo or k > hi) return 0;
                if(lo == hi) return r - l + 1;
                int lb = b[l-1], rb = b[r], mid = (lo+hi)/2;
                if(k <= mid) return this->l->count(lb+1, rb, k);
                return this->r->count(l-lb, r-rb, k);
        }
};
/**
 * Example use:
 * int a[N];
 * wavelet_tree T(a+1, a+n+1, 1, MAX);
 */
```