

Nextflow cheatsheet: creating input channels

channel creation

Channel.of("A")

- Channel.of() or Channel.fromList() will not alter anything

Channel.fromPath("A")

Channel.fromPath("/path/A")

- If the full file path is absent, .fromPath() will prefix current folder as path
- So the resulting channels always carry a full path

channel content

A

/path/A

use the channel in the process

input: val(x) `""" echo $x """`

input: path(x) `""" cat $x """` • both work

input: path("x.txt") `""" cat x.txt """`

- input: path("x.txt") will create a **symlink** in the working directory with the name "x.txt" (can use any name) pointing to /path/A

• From text files

input text file

A

B

C

channel creation

**Channel.fromPath("file.txt")
.splitText { it.strip() }**

- .splitText will read in the file.txt
- it.strip() will remove the blank items

**Channel.fromPath("file.txt")
.splitText { it.strip() }
.map { it -> file(it) }**

- file() adds current folder as path unless there is already full path in the item.

channel content

A
B
C

use the channel in the process

input: val(x)

- 1 channel, 3 items

- 3 parallel executions of process

/path/A
/path/B
/path/C

input: file(x)

A	/path/A.bam	/path/A.bam.bai
B	/path/B.bam	/path/B.bam.bai
C	/path/C.bam	/path/C.bam.bai

**Channel.fromPath("file.tsv")
.splitCsv(sep: "\t")
.map { row -> [row[0], file(row[1]), file(row[2])] }**

- .map{ } doesn't output of this example, but it is very useful to select columns and specify channel structure.

[A, /path/A.bam, /path/A.bam.bai]
[B, /path/B.bam, /path/B.bam.bai]
[C, /path/C.bam, /path/C.bam.bai]

input: tuple val(x), file(bam), file(bai)

strain	bam
A	A.bam
B	B.bam
C	C.bam

**Channel.fromPath("file.tsv")
.splitCsv(header:true, sep: "\t")
.map { row ->
 if (params.bam_path != "") {
 row.bam = "\${params.bam_path}/\${row.bam}"
 }
 [row.strain, file("\${row.bam}"), file("\${row.bam}.bai")] }**

- If params.bam_path doesn't add a full path, file() will.

• Automatically from a list of files

file list

A_R1.fq
A_R2.fq
B_R1.fq
B_R2.fq

Channel.fromPath("*.fq")

/path/A_R1.fq
/path/A_R2.fq
/path/B_R1.fq
/path/B_R2.fq

input: path(fq)

- 1 channel, 4 items, 4 parallel executions of process

Channel.fromFilePairs("/path/*_R{1,2}.fq")

[A, [/path/A_R1.fq, /path/A_R2.fq]]
[B, [/path/B_R1.fq, /path/B_R2.fq]]

input: tuple val(x), path(R1R2))

Channel.fromFilePairs("/path/*_R{1,2}.fq", flat:true)

[A, /path/A_R1.fq, /path/A_R2.fq]
[B, /path/B_R1.fq, /path/B_R2.fq]

input: tuple val(x), path(R1), path(R2)

A.bam
A.bam.bai
B.bam
B.bam.bai

Channel.fromFilePairs("/path/*.{bam, bam.bai}", flat:true)

[A, /path/A.bam, /path/A.bam.bai]
[B, /path/B.bam, /path/B.bam.bai]

input: tuple val(x), path(bam), path(bai)

- First item "A" came from stripping the path and common pattern ".{bam, bam.bai}" as specified in Channel.fromFilePairs

Nextflow cheatsheet: combine inputs into 1 channel

examples of 1 channel:

```
Channel.of( "A.fa", "B.fa", "C.fa" )
```

A.fa →
B.fa →
C.fa →

- Each item (row) has 1 parallel execution of process
- 1 channel, 3 items
- 3 parallel executions of process

```
Channel.of( [ "A.fa", "B.fa", "C.fa" ] )
```

[A.fa, B.fa, C.fa] →


- 1 channel, 1 item, 1 execution

```
Channel.of( [ "I.vcf", "I.vcf.tbi" ],  
            [ "II.vcf", "II.vcf.tbi" ],  
            [ "III.vcf", "III.vcf.tbi" ] )
```


[I.vcf, I.vcf.tbi] →
[II.vcf, II.vcf.tbi] →
[III.vcf, III.vcf.tbi] →

- 1 channel, 3 items
- 3 parallel executions of process
- [] indicates a "set" "tuple" "ArrayList"

• With 1 input channel: change number of items and parallel execution of the process



• With multiple input channels: combine them and change number of items



• Other useful cases

