



1 Preconditii

1.1 Azure pentru studenti




1.2 Configurarea mediului de lucru



2 Infrastructura Cloud

2.1 Zone si regiuni

2.1.1 Identificarea zonelor disponibile pentru subscriptie



2.2 Grupuri de resurse

2.2.1 Crearea unui grup de resurse

```
dan [ ~ ]$ az group create --name CloudLabRG --location italnorth
{
  "id": "/subscriptions/b8a400bd-6466-4af0-a961-5858bd830924/resourceGroups/CloudLabRG",
  "location": "italynorth",
  "managedBy": null,
  "name": "CloudLabRG",
  "properties": {
    "provisioningState": "Succeeded"
  },
  "tags": null,
  "type": "Microsoft.Resources/resourceGroups"
}
dan [ ~ ]$
```

2.2.2 Stergerea unui grup de resurse

```
dan [ ~ ]$ az group delete --name CloudLabRG --yes --no-wait
dan [ ~ ]$ az group list
[]
dan [ ~ ]$
```

2.3 Masina virtuala (Virtual Machine- VM)

```
dan [ ~ ]$ az vm list-sizes --location italnorth --output table
This command has been deprecated and will be removed in a future release. Use 'az vm list-skus' instead.
```

MaxDataDiskCount	MemoryInMB	Name	NumberOfCores	OsDiskSizeInMB	ResourceDiskSizeInMB
16	1894400	Standard_ND96isr_H200_v5	96	1047552	1048576
8	4096	Standard_D2pls_v6	2	1047552	0
12	8192	Standard_D4pls_v6	4	1047552	0
24	16384	Standard_D8pls_v6	8	1047552	0
48	32768	Standard_D16pls_v6	16	1047552	0
64	65536	Standard_D32pls_v6	32	1047552	0
64	98304	Standard_D48pls_v6	48	1047552	0
64	131072	Standard_D64pls_v6	64	1047552	0
64	196608	Standard_D96pls_v6	96	1047552	0
8	8192	Standard_D2pds_v6	2	1047552	0
12	16384	Standard_D4pds_v6	4	1047552	0
24	32768	Standard_D8pds_v6	8	1047552	0
48	65536	Standard_D16pds_v6	16	1047552	0
64	131072	Standard_D32pds_v6	32	1047552	0
64	196608	Standard_D48pds_v6	48	1047552	0
64	262144	Standard_D64pds_v6	64	1047552	0
64	393216	Standard_D96pds_v6	96	1047552	0
8	4096	Standard_D2plds_v6	2	1047552	0
12	8192	Standard_D4plds_v6	4	1047552	0

2.3.2 Imagini ale sistemului de operare

```
dan [ ~ ]$ az vm image list
You are viewing an offline list of images, use --all to retrieve an up-to-date list
[
  {
    "architecture": "x64",
    "offer": "CentOS",
    "publisher": "OpenLogic",
    "sku": "8_5-gen2",
    "urn": "OpenLogic:CentOS:8_5-gen2:latest",
    "urnAlias": "CentOS85Gen2",
    "version": "latest"
  },
  {
    "architecture": "x64",
    "offer": "debian-11",
    "publisher": "Debian",
    "sku": "11-backports-gen2",
    "urn": "Debian:debian-11:11-backports-gen2:latest",
    "urnAlias": "Debian11",
    "version": "latest"
  }
]
```

2.3.3 Crearea unui VM

```
dan [ ~ ]$ az vm create --resource-group CloudLabRG --name MyFirstVM --size Standard_B2als_v2 --image Ubuntu2004 --admin-username azureuser --generate-ssh-keys --public-ip-sku Standard --location italnorth
The default value of '--size' will be changed to 'Standard_D2s_v5' from 'Standard_D51_v2' in a future release.
SSH key files '/home/dan/.ssh/id_rsa' and '/home/dan/.ssh/id_rsa.pub' have been generated under ~/.ssh to allow SSH access to the VM. If using machines without permanent storage, back up your keys to a safe location.
| Running ..
{
  "fqdns": "",
  "id": "/subscriptions/b8a400bd-6466-4af0-a961-5858bd838924/resourceGroups/CloudLabRG/providers/Microsoft.Compute/virtualMachines/MyFirstVM",
  "location": "italynorth",
  "macAddress": "7C-ED-8D-01-51-5E",
  "powerState": "VM running",
  "privateIpAddress": "10.0.0.4",
  "publicIpAddress": "172.213.221.253",
  "resourceGroup": "CloudLabRG"
}
dan [ ~ ]$
dan [ ~ ]$
```

2.3.4 Verificare si Conectare

```
dan [ ~ ]$ az vm list-ip-addresses --resource-group CloudLabRG --name MyFirstVM --output table
VirtualMachine      PublicIPAddresses      PrivateIPAddresses
-----
MyFirstVM           172.213.221.253        10.0.0.4
dan [ ~ ]$ ssh azuruser@172.213.221.253
Welcome to Ubuntu 24.04.3 LTS (GNU/Linux 6.14.0-1017-azure x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Mon Dec 22 14:26:11 UTC 2025

System load: 0.09          Processes:            122
Usage of /:   5.6% of 28.02GB Users logged in:           0
Memory usage: 7%          IPv4 address for eth0: 10.0.0.4
Swap usage:   0%

Expanded Security Maintenance for Applications is not enabled.

0 updates can be applied immediately.

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.
```

2.3.5 Stergerea unui VM

```
dan [ ~ ]$ az vm delete --resource-group CloudLabRG --name MyFirstVM --yes
dan [ ~ ]$
```

2.4 Scalabilitate si Load Balancing (VM Scale Sets)

2.4.1 Crearea unui cluster de VM-uri

```
dan [ ~ ]$ az vmss create --resource-group CloudLabRG --name LabScaleSet --image Ubuntu2404 --vm-sku Standard_D2sls_v2 --upgrade-policy-mode automatic --admin-username azuruser --generate-ssh-keys --instance-count 2 --backend-port 80
-location italenorth
The default value of "--vm-sku" will be changed to "Standard_D2sls_v5" from "Standard_D2sls_v2" in a future release.
{
  "vmss": {
    "constrainedMaximumCapacity": false,
    "highSpeedInterconnectPlacement": "None",
    "orchestrationMode": "Flexible",
    "platformFaultDomainCount": 1,
    "provisioningState": "Succeeded",
    "singlePlacementGroup": false,
    "timeCreated": "2025-12-22T14:37:41.6442138+00:00",
    "uniqueId": "cb792fc-018b-463e-883e-19215823bdc",
    "upgradePolicy": {
      "mode": "Automatic"
    },
    "virtualMachineProfile": {
      "networkProfile": {
        "networkApiVersion": "2020-11-01",
        "networkInterfaceConfigurations": [
          {
            "name": "labsc67f3nic",
            "properties": {
              "auxiliaryMode": "None",
              "auxiliarySku": "None",
              "deleteOption": "Delete",
              "disableIcmpStateTracking": false,
              "dnsSettings": {
                "dnsServers": []
              }
            }
          }
        ]
      }
    }
  }
}
```


2.5.5 Conectarea terminalului la cluster

```
dan [ ~ ]$ az aks get-credentials --resource-group CloudLabRG --name LabAKSCluster
Merged "LabAKSCluster" as current context in /home/dan/.kube/config
dan [ ~ ]$
```

2.5.6 Lansarea unei Aplicatii Web (AKS Hello World)

```
dan [ ~ ]$ nano aks-app.yaml
dan [ ~ ]$ cat aks-app.yaml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: aks-helloworld
spec:
  replicas: 1
  selector:
    matchLabels:
      app: aks-helloworld
  template:
    metadata:
      labels:
        app: aks-helloworld
    spec:
      nodeSelector:
        kubernetes.io/os: linux
      containers:
        - name: aks-helloworld
          # Imagine oficială Microsoft stabilă pentru testare
          image: mcr.microsoft.com/azuredocs/aks-helloworld:v1
          ports:
            - containerPort: 80
          env:
            - name: TITLE
              value: "Salutare din Laboratorul Azure!"
---
apiVersion: v1
kind: Service
metadata:
  name: aks-helloworld
spec:
  type: LoadBalancer
  ports:
```

```
dan [ ~ ]$ kubectl apply -f aks-app.yaml
deployment.apps/aks-helloworld created
service/aks-helloworld created
dan [ ~ ]$ kubectl get service azure-vote-front --watch
Error from server (NotFound): services "azure-vote-front" not found
dan [ ~ ]$ kubectl get service azure-vote-front --watch
Error from server (NotFound): services "azure-vote-front" not found
dan [ ~ ]$
```

2.5.7 Comenzi comune in Kubernetes

```
dan [ ~ ]$ kubectl get nodes
NAME                                STATUS    ROLES    AGE   VERSION
aks-nodepool1-71914792-vmss000000  Ready    <none>   11m   v1.33.5
dan [ ~ ]$ kubectl get pods
NAME                                READY    STATUS    RESTARTS   AGE
aks-helloworld-658684fd99-t7lz9     1/1      Running   0           2m7s
dan [ ~ ]$ kubectl get pods -o wide
error: the server doesn't have a resource type "pods-o"
dan [ ~ ]$ kubectl get pods -o wide
NAME                                READY    STATUS    RESTARTS   AGE   IP              NODE                                NOMINATED NODE   READINESS GATES
aks-helloworld-658684fd99-t7lz9     1/1      Running   0           2m36s  10.244.0.109    aks-nodepool1-71914792-vmss000000  <none>           <none>
dan [ ~ ]$ kubectl get services
NAME      TYPE          CLUSTER-IP    EXTERNAL-IP    PORT(S)          AGE
aks-helloworld  LoadBalancer  10.0.157.247   <pending>       80:32055/TCP     2m57s
kubernetes   ClusterIP      10.0.0.1       <none>          443/TCP          14m
dan [ ~ ]$ kubectl describe pod aks-helloworld-658684fd99-t7lz9
Name:          aks-helloworld-658684fd99-t7lz9
Namespace:     default
Priority:       0
Service Account: default
Node:          aks-nodepool1-71914792-vmss000000/10.224.0.4
Start Time:    Mon, 22 Dec 2025 15:18:10 +0000
Labels:        app=aks-helloworld
               pod-template-hash=658684fd99
Annotations:   <none>
Status:        Running
IP:            10.244.0.109
IPs:
  IP:          10.244.0.109
Controlled By: ReplicaSet/aks-helloworld-658684fd99
Containers:
  aks-helloworld:
    Container ID:  containerd://fc3dedc5366f347790e891c147797da6936ed3181131f2b8e4321d8cb3dc8012
```

```

dan [ ~ ]$ kubectl logs aks-helloworld-658684fd99-t7lz9
Checking for script in /app/prestart.sh
Running script /app/prestart.sh
Running inside /app/prestart.sh, you could add migrations to this file, e.g.:

#!/usr/bin/env bash

# Let the DB start
sleep 10;
# Run migrations
alembic upgrade head

/usr/lib/python2.7/dist-packages/supervisor/options.py:298: UserWarning: Supervisor is running as root and it is searching for its confi
specify a "-c" argument specifying an absolute path to a configuration file for improved security.
'Supervisord is running as root and it is searching '
2025-12-22 15:18:18,820 CRIT Supervisor running as root (no user in config file)
2025-12-22 15:18:18,820 INFO Included extra file "/etc/supervisor/conf.d/supervisord.conf" during parsing
2025-12-22 15:18:18,827 INFO RPC interface 'supervisor' initialized
2025-12-22 15:18:18,827 CRIT Server 'unix_http_server' running without any HTTP authentication checking
2025-12-22 15:18:18,827 INFO supervisord started with pid 7
2025-12-22 15:18:19,829 INFO spawned: 'nginx' with pid 10
2025-12-22 15:18:19,831 INFO spawned: 'uwsgi' with pid 11
[uwsgi] getting INI configuration from /app/uwsgi.ini
[uwsgi] getting INI configuration from /etc/uwsgi/uwsgi.ini
*** Starting uWSGI 2.0.15 (64bit) on [Mon Dec 22 15:18:19 2025] ***
compiled with version: 6.3.0 20170516 on 04 February 2018 16:22:48
os: Linux-5.15.0-1101-azure #110-Ubuntu SMP Wed Nov 19 02:16:35 UTC 2025
nodename: aks-helloworld-658684fd99-t7lz9
machine: x86_64
clock source: unix
pcpre jit disabled
detected number of CPU cores: 4
current working directory: /app
detected binary path: /usr/local/bin/uwsgi

```

2.5.8 Steregerea resurselor

```

dan [ ~ ]$ az group delete --name CloudLabRG --yes --no-wait
dan [ ~ ]$

```

3 Module optionale

3.1 Azure Functions (Serverless)

3.1.1 Exemplu practic: Serverless HTTP Endpoint

```

dan [ ~ ]$ RND=$RANDOM
GRP="ServerlessRG-$RND"
LOC="italynorth"
STO="funcstore-$RND"
APP="MyLabFuncApp-$RND"
echo "Se creeaza resursele in grupul: $GRP..."
Se creeaza resursele in grupul: ServerlessRG-27569...
dan [ ~ ]$ az group create --name $GRP --location $LOC
{
  "id": "/subscriptions/b8a400bd-6466-4af0-a961-5858bd830924/resourceGroups/ServerlessRG-27569",
  "location": "italynorth",
  "managedBy": null,
  "name": "ServerlessRG-27569",
  "properties": {
    "provisioningState": "Succeeded"
  },
  "tags": null,
  "type": "Microsoft.Resources/resourceGroups"
}

```



```

dan [ ~ ]$ az storage account create --name $STO --location $LOC --resource-group $GRP --sku Standard_LRS
{
  "accessTier": "Hot",
  "accountMigrationInProgress": null,
  "allowBlobPublicAccess": false,
  "allowCrossTenantReplication": null,
  "allowSharedKeyAccess": null,
  "allowedCopyScope": null,
  "azureFilesIdentityBasedAuthentication": null,
  "blobRestoreStatus": null,
  "creationTime": "2025-12-22T16:35:01.551928+00:00",
  "customDomain": null,
  "defaultToOAuthAuthentication": null,
  "dnsEndpointType": null,
  "dualStackEndpointPreference": null,
  "enableExtendedGroups": null,
  "enableHttpsTrafficOnly": true,
  "enableNfsV3": null,
  "encryption": {
    "encryptionIdentity": null,
    "keySource": "Microsoft.Storage",
    "keyVaultProperties": null,
    "requireInfrastructureEncryption": null,
  },
  "services": {
    "blob": {
      "enabled": true,
      "keyType": "Account",
      "lastEnabledTime": "2025-12-22T16:35:01.598802+00:00"
    },
    "file": {
      "enabled": true,
      "keyType": "Account",
      "lastEnabledTime": "2025-12-22T16:35:01.598802+00:00"
    }
  }
}

```

```

dan [ ~ ]$ az provider register --namespace Microsoft.Web
Registering is still on-going. You can monitor using 'az provider show -n Microsoft.Web'
dan [ ~ ]$ az provider show --namespace Microsoft.Web --query "registrationState"
"Registering"
dan [ ~ ]$ az provider show --namespace Microsoft.Web --query "registrationState"
"Registering"
dan [ ~ ]$ az provider show --namespace Microsoft.Web --query "registrationState"
"Registered"
dan [ ~ ]$

```

```

dan [ ~ ]$ az functionapp create --resource-group $GRP --consumption-plan-location $LOC --runtime node --runtime-version 24 --functions-version 4 --name $APP --storage-account $STO
Resource provider 'Microsoft.OperationalInsights' used by this operation is not registered. We are registering for you.

Registration succeeded.
Resource provider 'microsoft.insights' used by this operation is not registered. We are registering for you.
Registration succeeded.
Application Insights 'MyLabFuncApp-29198' was created for this Function App. You can visit https://portal.azure.com/#resource/subscriptions/b8a400bd-6466-4af0-a061-5858bd830924/resourceGroups/ServerlessRG-29198/providers/microsoft.insights/components/MyLabFuncApp-29198/overview to view your Application Insights component
https://portal.azure.com/#resource/subscriptions/b8a400bd-6466-4af0-a061-5858bd830924/resourceGroups/ServerlessRG-29198/providers/microsoft.insights/components/MyLabFuncApp-29198/overview
{
  "autoGeneratedDomainNameLabelScope": null,
  "availabilityState": "Normal",
  "clientAffinityEnabled": false,
  "clientAffinityPartitioningEnabled": null,
  "clientAffinityProxyEnabled": false,
  "clientCertEnabled": false,
  "clientCertExclusionPaths": null,
  "clientCertMode": "Required",
  "cloningInfo": null,
  "containerSize": 1536,
  "customDomainVerificationId": "73C9C20A8E9588CE6137B9D1678F676A30752532E403A338BFAF6666E1050FE2",
  "dailyMemoryTimeQuota": 0,
  "daprConfig": null,
  "defaultHostName": "mylabfuncapp-29198.azurewebsites.net",
  "dnsConfiguration": {
    "dnsAllServer": null,
    "dnsAgesSortOrder": null,
    "dnsMaxCacheTimeout": null,
    "dnsMaxRetryAttemptCount": null,
    "dnsRetryAttemptTimeout": null,
    "dnsServers": null
  }
}

```



```

dan [ ~ ]$ FUNC_URL="https://$APP.azurewebsites.net"
echo "Aplicatia este activa: $FUNC_URL"
Aplicatia este activa: https://MyLabFuncApp-29198.azurewebsites.net
dan [ ~ ]$ curl-I $FUNC_URL
bash: curl-I: command not found
dan [ ~ ]$ curl -I $FUNC_URL
HTTP/2 200
content-type: text/html
date: Mon, 22 Dec 2025 16:57:43 GMT
content-length: 150093

dan [ ~ ]$

```

3.1.2 Adaugarea si publicarea codului personalizat

```

dan [ ~ ]$ mkdir MyLocalFunc
dan [ ~ ]$ cd MyLocalFunc
dan [ ~/MyLocalFunc ]$ func init --worker-runtime node --language javascript

The new Node.js programming model is generally available. Learn more at https://aka.ms/AzFuncNodeV4
Writing package.json
Writing .funcignore
Writing .gitignore
Writing host.json
Writing local.settings.json
Writing /home/dan/MyLocalFunc/.vscode/extensions.json
Running 'npm install'...dan [ ~/MyLocalFunc ]$
dan [ ~/MyLocalFunc ]$ func new --name MyCustomTrigger --template "HTTPtrigger" --authlevel anonymous
'local.settings.json' found in root directory (/home/dan/MyLocalFunc).
Resolving worker runtime to 'node'.
Select a number for template:HTTPtrigger
Function name: [httpTrigger] Creating a new file /home/dan/MyLocalFunc/src/functions/MyCustomTrigger.js
The function "MyCustomTrigger" was created successfully from the "HTTPtrigger" template.
dan [ ~/MyLocalFunc ]$ func azure functionapp publish $APP
'local.settings.json' found in root directory (/home/dan/MyLocalFunc).
Resolving worker runtime to 'node'.
Setting Functions site property 'netFrameworkVersion' to 'v8.0'
Getting site publishing info...
[2025-12-22T17:01:15.138Z] Starting the function app deployment...
Creating archive for current directory...
Uploading 657.63 KB [#####]
Upload completed successfully.
Deployment completed successfully.
[2025-12-22T17:01:43.407Z] Syncing triggers...
Functions in MyLabFuncApp-29198:
  MyCustomTrigger - [httpTrigger]
    Invoke url: https://mylabfuncapp-29198.azurewebsites.net/api/mycustomtrigger

dan [ ~/MyLocalFunc ]$ curl "https://$APP.azurewebsites.net/api/MyCustomTrigger?name=CloudLabUser"
bash: curlhttps://MyLabFuncApp-29198.azurewebsites.net/api/MyCustomTrigger?name=CloudLabUser: No such file or directory
dan [ ~/MyLocalFunc ]$ curl "https://$APP.azurewebsites.net/api/MyCustomTrigger?name=CloudLabUser"
dan [ ~/MyLocalFunc ]$ curl "https://$APP.azurewebsites.net/api/MyCustomTrigger?name=CloudLabUser"
Hello, CloudLabUser!dan [ ~/MyLocalFunc ]$

```

3.1.3 Stergerea resurselor


```

dan [ ~/MyLocalFunc ]$ az group delete --name $GRP --yes --no-wait
dan [ ~/MyLocalFunc ]$


```

3.2 Terraform(IaC)

3.2.1 Task: Deploy Container "HelloWorld"



3.2.2 Apicare



3.3 Ansible (Configuration Management)

3.3.1 Provizionarea infrastructurii

```
dan [ ~/ansible ]$ az group create --name CloudLabRG --location italnorth
{
  "id": "/subscriptions/b8a400bd-6466-4af0-a961-5858bd830924/resourceGroups/CloudLabRG",
  "location": "ItalyNorth",
  "managedBy": null,
  "name": "CloudLabRG",
  "properties": {
    "provisioningState": "Succeeded"
  },
  "tags": null,
  "type": "Microsoft.Resources/resourceGroups"
}
dan [ ~/ansible ]$ az vm create --resource-group CloudLabRG --name AnsibleTargetVM --image Ubuntu2404 --size Standard_B2s_v2 --location italnorth --admin-username azureuser --generate-ssh-keys --public
The default value of '--size' will be changed to 'Standard_D2s_v5' from 'Standard_DS1_v2' in a future release.
{
  "fqdns": "",
  "id": "/subscriptions/b8a400bd-6466-4af0-a961-5858bd830924/resourceGroups/CloudLabRG/providers/Microsoft.Compute/virtualMachines/AnsibleTargetVM",
  "location": "ItalyNorth",
  "macAddress": "7C-ED-8D-01-7A-F1",
  "powerState": "VM running",
  "privateIpAddress": "10.0.0.4",
  "publicIpAddress": "172.213.247.28",
  "resourceGroup": "CloudLabRG"
}
dan [ ~/ansible ]$ az vm open-port --resource-group CloudLabRG --name AnsibleTargetVM --port 80 --priority 1010
{
  "defaultSecurityRules": [
    {
      "access": "Allow",
      "description": "Allow inbound traffic from all VMs in VNET",
      "destinationAddressPrefix": "VirtualNetwork",
      "destinationAddressPrefixes": [],
      "destinationPortRange": "*",
      "destinationPortRanges": [],
      "direction": "Inbound",
      "etag": "8b1f6ed0e9-4069-4170-a196-2a1cf6f2fd45",
      "id": "/subscriptions/b8a400bd-6466-4af0-a961-5858bd830924/resourceGroups/CloudLabRG/providers/Microsoft.Network/networkSecurityGroups/AnsibleTargetVMNSG/defaultSecurityRules/AllowVnetInBound",
      "name": "AllowVnetInBound",
      "priority": 45000,
      "protocol": "*",
      "provisioningState": "Succeeded",
      "resourceGroup": "CloudLabRG",
      "sourceAddressPrefix": "VirtualNetwork",
      "sourceAddressPrefixes": []
    }
  ]
}
```

3.3.2 Definirea inventarului

```
dan [ ~/ansible ]$ nano inventory.ini
dan [ ~/ansible ]$ cat inventory.ini
[webserver]
172.213.247.28 ansible_user=azureuser ansible_ssh_private_key_file=~/.ssh/id_rsa
dan [ ~/ansible ]$
```

3.3.3 Automatizare – Web Server & System Hardening

```
dan [ ~/ansible ]$ nano setup_server.yml
dan [ ~/ansible ]$ cat setup_server.yml
- name: Hardening & Web Server Setup
  hosts: webservers
  become: true  # Rulează comenzile cu sudo

  vars:
    app_user: "webapp_user"
    http_port: 80

  tasks:
    # --- 1. System Hardening ---
    - name: Create application user
      user:
        name: "{{ app_user }}"
        state: present
        shell: /bin/bash

    - name: Allow SSH traffic (CRITICAL before enabling UFW)
      ufw:
        rule: allow
        name: OpenSSH

    - name: Allow HTTP traffic
      ufw:
        rule: allow
        port: "{{ http_port }}"
        proto: tcp

    - name: Enable firewall (UFW)
      ufw:
        state: enabled
        policy: deny

    # --- 2. Application Configuration ---
    - name: Install Nginx
      apt:
        name: nginx
        state: present
        update_cache: yes

    - name: Start Nginx service
      service:
        name: nginx
        state: started
        enabled: yes
```

3.3.4 Executie si validare

```
dan [ ~/ansible ]$ ANSIBLE_HOST_KEY_CHECKING=False ansible-playbook -i inventory.ini setup_server.yml

PLAY [Hardening & Web Server Setup] *****

TASK [Gathering Facts] *****
[WARNING]: Host '172.213.247.28' is using the discovered Python interpreter at '/usr/bin/python3.12', but future installation of another Python interpreter could cause a different interpreter
See https://docs.ansible.com/ansible-core/2.19/reference_appendices/interpreter_discovery.html for more information.
ok: [172.213.247.28]

TASK [Create application user] *****
changed: [172.213.247.28]

TASK [Allow SSH traffic (CRITICAL before enabling UFW)] *****
changed: [172.213.247.28]

TASK [Allow HTTP traffic] *****
changed: [172.213.247.28]

TASK [Enable firewall (UFW)] *****
changed: [172.213.247.28]

TASK [Install Nginx] *****
changed: [172.213.247.28]

TASK [Start Nginx service] *****
ok: [172.213.247.28]

PLAY RECAP *****
172.213.247.28 : ok=7 changed=5 unreachable=0 failed=0 skipped=0 rescued=0 ignored=0

dan [ ~/ansible ]$ curl 172.213.247.28
<!DOCTYPE html>
<html>
<head>
<title>Welcome to nginx!</title>
<style>
html { color:scheme: light dark; }
body { width: 35em; margin: 0 auto;
font-family: Tahoma, Verdana, Arial, sans-serif; }
</style>
</head>
<body>
<h1>Welcome to nginx!</h1>
<p>If you see this page, the nginx web server is successfully installed and
working. Further configuration is required.</p>
```

3.3.5 Stergerea resurselor

```
dan [ ~/ansible ]$ az group delete --name CloudLabRG --yes --no-wait
dan [ ~/ansible ]$
```

3.4 Jenkins (CI/CD Clasic)


3.4.1 Jenkins in ecosistemul Azure


3.4.2 Lansarea Jenkins in Cloud (Azure Container Instances)

```
dan [ ~/jenkins ]$ az group create --name CloudLabRG --location italynorth
{
  "id": "/subscriptions/8a400bd-6466-4af0-a961-5858bd30924/resourceGroups/CloudLabRG",
  "location": "italynorth",
  "managedBy": null,
  "name": "CloudLabRG",
  "properties": {
    "provisioningState": "Succeeded"
  },
  "tags": null,
  "type": "Microsoft.Resources/resourceGroups"
}
dan [ ~/jenkins ]$ az container create --resource-group CloudLabRG --name lab-jenkins --image jenkins/jenkins:its --ports 8080 --dns-name-label jenkins-lab-${RANDOM} --cpu 1 --memory 1.5 --os-type Linux
{
  "confidentialComputeProperties": null,
  "containerGroupProfile": null,
  "containers": [
    {
      "command": null,
      "configMap": {
        "keyValuePair": {}
      },
      "environmentVariables": {},
      "image": "jenkins/jenkins:its",
      "instanceView": {
        "currentState": {
          "detailStatus": "",
          "exitCode": null,
          "finishTime": null,
          "startTime": "2025-12-22T18:01:45.599000+00:00",
          "state": "Running"
        },
        "events": [
          {
            "count": 1,
            "firstTimestamp": "2025-12-22T18:01:16+00:00",
            "lastTimestamp": "2025-12-22T18:01:16+00:00",
            "message": "pulling image \"jenkins/jenkins@sha256:b768bbb69b5f1b6579e23e7253ae1157a339a20a2e9befdf8e03923e893b800\"",
            "name": "Pulling",
            "type": "Normal"
          }
        ]
      },
      "ports": [
        {
          "count": 1,
          "firstTimestamp": "2025-12-22T18:01:16+00:00",
          "lastTimestamp": "2025-12-22T18:01:16+00:00",
          "message": "pulling image \"jenkins/jenkins@sha256:b768bbb69b5f1b6579e23e7253ae1157a339a20a2e9befdf8e03923e893b800\"",
          "name": "Pulling",
          "type": "Normal"
        }
      ]
    }
  ]
}
```


3.4.3 Accesare si configurare initiala

```
dan [ ~/jenkins ]$ az container show --resource-group CloudLabRG --name lab-jenkins --query ipAddress.fqdn --output tsv
jenkins-lab-31025.italnorth.azurecontainer.io
dan [ ~/jenkins ]$ az container logs --resource-group CloudLabRG --name lab-jenkins
[WARN tini (19)] Tini is not running as PID 1 and isn't registered as a child subreaper.
Zombie processes will not be re-parented to Tini, so zombie reaping won't work.
To fix the problem, use the -s option or set the environment variable TINI_SUBREAPER to register Tini as a child subreaper, or run Tini as PID 1.
Running from: /usr/share/jenkins/jenkins.war
webroot: /var/jenkins_home/war
2025-12-22 18:01:47.262+0000 [id=1] INFO winstone.Logger$logInternal: Beginning extraction from war file
2025-12-22 18:01:49.083+0000 [id=1] WARNING o.e.j.ee9.nested.ContextHandler$setContextPath: Empty contextPath
2025-12-22 18:01:49.203+0000 [id=1] INFO org.eclipse.jetty.server.Server$doStart: jetty-12.0.25; built: 2025-08-11T23:52:37.219Z; git: a862b76d8372e2420576
2025-12-22 18:01:50.358+0000 [id=1] INFO o.e.j.e.w.StandardDescriptorProcessor$visitServlet: NO JSP Support for /, did not find org.eclipse.jetty.ee9.jsp.
2025-12-22 18:01:50.509+0000 [id=1] INFO o.e.j.s.DefaultSessionIdManager$doStart: Session workerName=node0
2025-12-22 18:01:51.523+0000 [id=1] INFO hudson.WebAppMain$contextInitialized: Jenkins home directory: /var/jenkins_home found at: EnvVars.masterEnvVars.ge
2025-12-22 18:01:51.801+0000 [id=1] INFO o.e.j.s.handler.ContextHandler$doStart: Started oeje9n.ContextHandler$CoreContextHandler$3c782d8e(Jenkins v2.528.3
=oeje9n.ContextHandler$CoreContextHandler$CoreToNestedHandler$572e6fd9(STARTED))
2025-12-22 18:01:51.848+0000 [id=1] INFO o.e.j.server.AbstractConnector$doStart: Started ServerConnector$7bca6fac(HTTP/1.1, (http/1.1)){(0.0.0.0:8080)}
2025-12-22 18:01:51.889+0000 [id=1] INFO org.eclipse.jetty.server.Server$doStart: Started oejs.Server$3668d4(STARTING)[12.0.25,sto=0] @6201ms
2025-12-22 18:01:51.892+0000 [id=25] INFO winstone.Logger$logInternal: Winstone Servlet Engine running: controlPort=disabled
2025-12-22 18:01:52.152+0000 [id=24] INFO jenkins.model.Jenkins$<init>: Starting version 2.528.3
2025-12-22 18:01:52.407+0000 [id=31] INFO jenkins.InitReactorRunner$1$onAttained: Started initialization
2025-12-22 18:01:52.448+0000 [id=31] INFO jenkins.InitReactorRunner$1$onAttained: Listed all plugins
2025-12-22 18:01:54.635+0000 [id=32] INFO jenkins.InitReactorRunner$1$onAttained: Prepared all plugins
2025-12-22 18:01:54.641+0000 [id=32] INFO jenkins.InitReactorRunner$1$onAttained: Started all plugins
2025-12-22 18:01:54.642+0000 [id=31] INFO jenkins.InitReactorRunner$1$onAttained: Augmented all extensions
2025-12-22 18:01:55.125+0000 [id=32] INFO jenkins.InitReactorRunner$1$onAttained: System config loaded
2025-12-22 18:01:55.126+0000 [id=32] INFO jenkins.InitReactorRunner$1$onAttained: System config adapted
2025-12-22 18:01:55.126+0000 [id=32] INFO jenkins.InitReactorRunner$1$onAttained: Loaded all jobs
2025-12-22 18:01:55.130+0000 [id=32] INFO jenkins.InitReactorRunner$1$onAttained: Configuration for all jobs updated
2025-12-22 18:01:56.113+0000 [id=46] INFO hudson.util.Retrier$start: Attempt #1 to do the action check updates server
2025-12-22 18:01:56.622+0000 [id=31] INFO jenkins.install.SetupWizard$init:
[LF]>
[LF]> *****
[LF]> *****
[LF]> *****
[LF]>
[LF]> Jenkins initial setup is required. An admin user has been created and a password generated.
[LF]> Please use the following password to proceed to installation:
[LF]>
[LF]> 7504e53e90ea49ebbcf0b17b149b51f
[LF]>
[LF]> This may also be found at: /var/jenkins_home/secrets/initialAdminPassword
[LF]>
[LF]> *****
[LF]> *****
```





3.4.4 Simulare Pipeline Azure(Groovy)



3.4.5 Executia si monitorizarea pipeline-ului

Jenkins Pipeline Overview for Pipeline #1. The pipeline is currently at the '4. Manual Approval' stage, which is highlighted in blue. The previous stages (1. Code Checkout, 2. Build Container, 3. Deploy to Dev) are completed with green checkmarks. The '4. Manual Approval' stage has a duration of 2m 48s and started 2m 50s ago. The graph shows the flow from Start to End, with the current stage being '4. Manual Approval'. Below the graph, there is a search bar and a list of stages. The '4. Manual Approval' stage is selected, showing a message: 'Testele automate au trecut. Lansam in productie?' with buttons 'DA, lansam!' and 'Abort'.

Jenkins Pipeline Overview for Pipeline #1. The pipeline is now completed, indicated by a green checkmark and the '4. Manual Approval' stage being highlighted in green. The final stage is '5. Deploy to Production' with a duration of 0.23s. The graph shows the flow from Start to End, with all stages completed. Below the graph, there is a search bar and a list of stages. The '4. Manual Approval' stage is selected, showing a message: 'Wait for interactive input'.

Jenkins Console Output for Pipeline #1. The output shows the execution details of the pipeline, including the stages and the commands executed. The output is as follows:

```
Started by user admin
[Pipeline] Start of Pipeline
[Pipeline] node
Running on Jenkins in /var/jenkins_home/workspace/Pipeline
[Pipeline] {
[Pipeline] withEnv
[Pipeline] {
[Pipeline] stage
[Pipeline] { (1. Code Checkout)
[Pipeline] echo
Se descarca codul sursa pentru aplicatia aks-helloworld...
[Pipeline] echo
Repository clonat cu succes.
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
[Pipeline] { (2. Build Container)
[Pipeline] echo
Se construieste imaginea Docker...
[Pipeline] echo
Building image: mcr.microsoft.com/azuredocs/aks-helloworld:v1
[Pipeline] echo
Pushing image to Azure Container Registry...
[Pipeline] }
[Pipeline] // stage
[Pipeline] stage
[Pipeline] { (3. Deploy to Dev)
[Pipeline] echo
Se aplica manifestul in clusterul de dezvoltare...
[Pipeline] echo
Executing: kubectl apply -f aks-app.yaml
```

3.4.6 Stergerea resurselor

```
dan [ ~ ]$ az container delete --resource-group CloudLabRG --name lab-jenkins --yes
{
  "confidentialComputeProperties": null,
  "containerGroupProfile": null,
  "containers": [
    {
      "command": null,
      "configMap": {
        "keyValuePairs": {}
      },
      "environmentVariables": [],
      "image": "jenkins/jenkins:lts",
      "instanceView": {
        "currentState": {
          "detailStatus": "",
          "exitCode": null,
          "finishTime": null,
          "startTime": "2025-12-22T18:01:45.599000+00:00",
          "state": "Running"
        },
        "events": [
          {
            "count": 1,
            "firstTimestamp": "2025-12-22T18:01:16+00:00",
            "lastTimestamp": "2025-12-22T18:01:16+00:00",
            "message": "pulling image \"jenkins/jenkins@sha256:b768bbb699b5f1b6579e23e7253ae1157a339a20a2e9befdf8e03923e893b800\"",
            "name": "Pulling",
            "type": "Normal"
          },
          {
            "count": 1,
            "firstTimestamp": "2025-12-22T18:01:36+00:00",
            "lastTimestamp": "2025-12-22T18:01:36+00:00",

```

```
dan [ ~ ]$ az group delete --name CloudLabRG --yes --no-wait
dan [ ~ ]$
```

3.5 GitHub Actions

3.6 Stiva ELK & Grafana

3.6.1 Configurare

```
logstash.conf
1 input {
2   http {
3     port => 5000
4     codec => json
5   }
6 }
7
8 filter {
9   # Dacă nu există un timestamp, adăugăm unul bazat pe timpul curent
10  if ![timestamp] {
11    mutate {
12      add_field => {
13        "timestamp" => "%{@timestamp}"
14      }
15    }
16  }
17 }
18
19 output {
20   elasticsearch {
21     hosts => ["elasticsearch:9200"]
22     index => "ecommerce-logs-%{+YYYY.MM.dd}"
23   }
24
25   # Afișează logurile și în consolă pentru debugging
26   stdout {
27     codec => rubydebug
28   }
29 }
```



Welcome logstash.conf docker-compose.yml X


docker-compose.yml

```
1  version: "3.8"
2
3  Run All Services
4  services:
5    Run Service
6    elasticsearch:
7      image: docker.elastic.co/elasticsearch/elasticsearch:7.9.2
8      environment:
9        - discovery.type=single-node
10     ports:
11       - "9200:9200"
12
13    Run Service
14    logstash:
15      image: docker.elastic.co/logstash/logstash:7.9.2
16      volumes:
17        - ./logstash.conf:/usr/share/logstash/pipeline/logstash.conf
18     ports:
19       - "5000:5000"
20     depends_on:
21       - elasticsearch
22
23    Run Service
24    grafana:
25      image: grafana/grafana:latest
26     ports:
27       - "3000:3000"
28     depends_on:
29       - elasticsearch
30
31    Run Service
32    traffic-generator:
33      image: alpine
34     depends_on:
35       - logstash
36     command: >
37       sh -c '
38         apk add --no-cache curl &&
39         while true; do
40           AMOUNT=$((RANDOM % 500));
41           USER_ID=$((RANDOM % 100));
42           curl -X POST -H "Content-Type: application/json" \
43             -d "{\"user\":\"user_${USER_ID}\",\"amount\": ${AMOUNT}}" \
44             http://logstash:5000;
45           sleep 1;
46         done
47       '
```

3.6.2 Rulare si vizualizare

```
PS D:\VirtualBox Shared\aso_share\Operating-Systems-Administration\Laboratory13\lab> docker-compose up -d
time="2025-12-22T22:03:42+02:00" level=warning msg="D:\\VirtualBox Shared\\aso_share\\Operating-Systems-Administration\\Laboratory1
move it to avoid potential confusion"
[+] Running 4/4
  ✓ Container lab-elasticsearch-1    Started      0.5s
  ✓ Container lab-grafana-1          Started      0.5s
  ✓ Container lab-logstash-1         Started      0.5s
  ✓ Container lab-traffic-generator-1 Started      0.4s
PS D:\VirtualBox Shared\aso_share\Operating-Systems-Administration\Laboratory13\lab>
```





3.6.3 Oprire resurse

```
PS D:\VirtualBox Shared\aso_share\Operating-Systems-Administration\Laboratory13\lab> docker-compose down
time="2025-12-22T22:14:08+02:00" level=warning msg="D:\VirtualBox Shared\aso_share\Operating-Systems-Administration\Laboratory13\lab\docker-compose.yml: move it to avoid potential confusion"
[+] Running 5/5
  ✓ Container lab-traffic-generator-1 Removed
  ✓ Container lab-grafana-1           Removed
  ✓ Container lab-logstash-1          Removed
  ✓ Container lab-elasticsearch-1     Removed
  ✓ Network lab_default               Removed
PS D:\VirtualBox Shared\aso_share\Operating-Systems-Administration\Laboratory13\lab>
```