

Extension samples

The Command Palette provides a full extension model, allowing developers to create their own experiences for the palette.

For the most up-to-date samples, check out [the samples project on GitHub](#) . This contains up-to-date samples of everything that's possible with Command Palette.

Create a command to do something

Create a class that implements `IInvokableCommand` and implement the `Invoke` method. This method will be called when the user selects the command in the Command Palette.

C#

```
class MyCommand : Microsoft.CommandPalette.Extensions.Toolkit.InvokableCommand {
    public class MyCommand()
    {
        Name = "Do it"; // A short name for the command
        Icon = new("\uE945"); // Segoe UI LightningBolt
    }

    // Open GitHub in the user's default web browser
    public ICommandResult Invoke() {
        Process.Start(new ProcessStartInfo("https://github.com") { UseShellExecute =
true });

        // Hides the Command Palette window, without changing the page that's open
        return CommandResult.Hide();
    }
}
```

Create a page of commands

The following example shows how to create a page of commands. This page will be shown when the user selects the "Open" command in the Command Palette:

C#

```

using Microsoft.CommandPalette.Extensions.Toolkit;

class MyPage : ListPage {
    public MyPage()
    {
        Icon = IconHelpers.FromRelativePath("Assets\\StoreLogo.png");
        Title = "My sample extension";
        Name = "Open";
    }

    public override IListItem[] GetItems()
    {
        return [
            new ListItem(new OpenUrlCommand("https://github.com"))
            {
                Title = "Open GitHub",
            },
            new ListItem(new OpenUrlCommand("https://learn.microsoft.com"))
            {
                Title = "Open Microsoft Learn",
            },
            new ListItem(new OpenUrlCommand("https://github.com/microsoft/PowerToys"))
            {
                Title = "Open PowerToys on GitHub",
            },
            new ListItem(new CopyTextCommand("Foo bar"))
            {
                Title = "Copy 'Foo bar' to the clipboard",
            },
        ];
    }
}

```

Icons

Icons using the [IconInfo](#) class can be specified in a number of ways. Here are some examples:

C#

```

using Microsoft.CommandPalette.Extensions.Toolkit;

namespace ExtensionName;

internal sealed class Icons
{
    // Icons can be specified as a Segoe Fluent icon, ...
    internal static IconInfo OpenFile { get; } = new("\uE8E5"); // OpenFile
}

```

```
// ... or as an emoji, ...
internal static IconInfo OpenFileDialogEmoji { get; } = new("📁");

// ... Or as a path to an image file, ...
internal static IconInfo FileExplorer { get; } =
IconHelpers.FromRelativePath("Assets\\FileExplorer.png");

// ... which can be on a remote server, or svg's, or ...
internal static IconInfo FileExplorerSvg { get; } =
new("https://raw.githubusercontent.com/microsoft/PowerToys/refs/heads/main/src/modules/cmdpal/Exts/Microsoft.CmdPal.Ext.Indexer/Assets/FileExplorer.svg");

// Or they can be embedded in a exe / dll:
internal static IconInfo FolderIcon { get; } =
new("%systemroot%\system32\shell32.dll,3");
}
```

Related content

- [PowerToys Command Palette utility](#)
- [Extensibility overview](#)

Last updated on 04/07/2025