

Wind Power Notes 2024 Shriya and Gaby


Exam Overview

- **Physics of Wind Energy:**
 - **Aerodynamics:** Understand lift, drag, and how airfoil shapes influence wind turbine efficiency.
 - **Energy Conversion:** How wind kinetic energy is converted to mechanical energy and then to electricity (generators, turbines).
 - **Power Calculations:** Learn formulas for wind power ($P = 0.5 * \rho * A * v^3$) and how to calculate power output.
- **Wind Turbine Components:**
 - **Blade:** Types of blades (traditional, twisted, adaptive blades) and how they affect performance
 - **Rotor:** Blades, hub, pitch control systems.
 - **Tower:** Types of towers (lattice, guyed, tubular), height considerations.
 - **Nacelle:** Housing for the gearbox, generator, and other components.
 - **Gearbox:** Transmits power from the low-speed rotor to the high-speed generator.
 - **Generator:** Converts mechanical energy into electrical energy.
- **Wind Farm Considerations:**
 - **Site Selection:** Factors like wind speed, turbulence, and land availability.
 - **Environmental Impact:** Bird and bat mortality, visual impact, noise pollution.
 - **Grid Integration:** Connecting wind farms to the electrical grid.
 - **Energy Storage:** Solutions for intermittency (batteries, pumped hydro, etc.).
- **Alternative Energy Sources:**
 - **Solar Power:** Photovoltaic cells, solar thermal.
 - **Hydropower:** Dams, tidal power.
 - **Geothermal Energy**
 - **Bioenergy:** Biomass, biogas.
 - **Nuclear Power:** Fission, fusion.

Aerodynamics

1. Lift and Drag

- Lift:
 - force that acts perpendicular to airflow, generated by the pressure difference between the upper and lower surfaces of the airfoil
 - primary role in wind turbine blades is to propel the blades forward and cause them to rotate, generating mechanical energy that can be converted to electrical energy
 - maximized when the angle of attack (the angle between the wind direction and the chord line of the airfoil) is optimized, typically between 5° and 15°, depending on wind conditions.
 - wind turbine blades are designed with an airfoil shape that maximizes lift at various wind speeds.
- Drag:
 - force that acts parallel and opposite to the airflow, resisting motion.
 - The SI units for resistance are Ohm (Ω)
 - there are two types of drag:
 - parasite drag: caused by friction between the air and the blade surface.
 - induced drag: caused by the generation of lift.
 - high drag reduces efficiency as it resists the turbine's rotation, so minimizing drag is crucial for optimal performance.
 - The goal is to design blades with as little drag as possible while maintaining sufficient lift to ensure the blades can turn effectively.



2. Airfoil Shapes and Their Influence on Efficiency

- Airfoil Design:
 - directly affects the amount of lift and drag produced. Wind turbine blades often use airfoils with curved upper surfaces and flatter lower surfaces to optimize pressure differences.
 - airfoils are usually designed to have a thicker profile at the root (near the hub) and a thinner profile at the tip to reduce drag and minimize the effects of turbulence.
- Types of Airfoils:
 - Symmetrical airfoils: These have the same shape on both the top and bottom surfaces. They are used in conditions where lift and drag must be controlled for various angles of attack.
 - Asymmetrical airfoils: These are commonly used for wind turbines because their curved upper surface creates a larger pressure difference between the top and bottom, generating more lift.
- Key Factors in Airfoil Design:
 - Angle of Attack: The angle between the relative wind and the chord line of the airfoil. Increasing the angle of attack increases lift up to a point, but too much angle leads to stall, which significantly reduces efficiency.
 - Thickness: Thicker airfoils produce more lift but also more drag. For wind turbines, a balance between lift and drag is key to maintaining efficiency.

- Camber (Curvature): The degree of curvature of the airfoil's upper surface. More camber increases the lift-to-drag ratio, but too much camber can cause turbulent flow and increase drag.
- Twist of the Blade: Wind turbine blades often have a twist from the root to the tip to maintain an optimal angle of attack along the length of the blade. This helps maximize the lift-to-drag ratio.

3. Effects of Airfoil Shape on Wind Turbine Efficiency

- The shape of the blade has a direct effect on the lift-to-drag ratio, which determines how efficiently the turbine converts wind energy into mechanical energy.
 - High lift-to-drag ratio: This is ideal for wind turbines, as it allows the blades to generate more power for the same wind speed.
 - Tip Effects: The tip of the blade experiences reduced lift due to turbulence, which can cause inefficiencies. Airfoils with tip designs that reduce vortex drag (e.g., winglets or tapered tips) help mitigate this.
 - Blade Shape and Performance: Blades with larger chord lengths near the root and smaller chord lengths near the tip are designed to capture more energy from the wind at lower speeds and reduce drag at higher speeds.

4. Impact of Airfoil Design on Real-World Performance

- Optimizing for Local Wind Conditions: In practice, the efficiency of wind turbine blades can be increased by designing airfoils that are tailored to specific wind conditions (e.g., coastal regions, mountainous areas, or urban environments).
 - Coastal regions might benefit from airfoils optimized for higher wind speeds and greater lift.
 - Urban environments or regions with turbulent winds might require airfoils designed to handle wind gusts and reduce drag while maintaining stable operation.

5. Wake Effect

- The wake effect happens in wind farms when the wind slows down and becomes more turbulent after passing through a wind turbine. This can reduce the wind speed and create disturbances for other turbines located behind it.

- How it works
 - When a turbine generates electricity, it takes energy from the wind.
 - This leaves the air behind it with less energy and more turbulence (rough, unstable wind).
 - The turbines in the back get weaker, less efficient wind, reducing their power output.
- Key Points
 - The wake effect can reduce the power production of turbines behind others by up to 40%.
 - Spacing turbines further apart and using smarter layouts can help reduce the wake effect.
 - Some turbines are equipped with technology to adjust their angle and redirect the wake, making the wind farm more efficient.

6. Conclusion

- lift and drag are the two most important aerodynamic forces influencing wind turbine performance. The balance between these forces determines how effectively a turbine can convert wind energy into mechanical power.
- the airfoil shape plays a crucial role in optimizing these forces and maximizing turbine efficiency.
- understanding and designing efficient airfoils is central to improving wind turbine technology, making them more productive and sustainable as a source of renewable energy.
- the wake effect causes turbulence and reduced wind speed behind a turbine, impacting the efficiency of downstream turbines in wind farms and influencing optimal turbine spacing.

Limits

1. Key Factors Limiting Wind Turbine Height:

1. Structural Integrity: Taller towers face greater stress from wind and their own weight, requiring stronger materials and design.
2. Material and Construction Costs: Height increases material use, transportation challenges, and installation complexity.
3. Logistics and Transport: Transporting large tower sections is difficult, especially through roads and ports.
4. Wind Dynamics: Higher altitudes have stronger, steadier winds, but excessive height can expose turbines to extreme gusts.
5. Regulations and Permits: Aviation regulations, zoning laws, and environmental concerns may limit height.
6. Maintenance Accessibility: Taller towers complicate inspections, repairs, and maintenance.

2. Impact of Tower Height on Power Generation

- Increased Energy Capture: Taller towers access stronger, more consistent winds, boosting energy output.
- Higher Capacity Factor: Improved wind conditions lead to more consistent turbine operation, increasing annual electricity production.
- Diminishing Returns: Beyond a certain height, cost increases may outweigh energy gains.

In essence, greater height enhances wind capture and power generation, but structural, economic, and regulatory factors limit practical tower height.

3. Pitch control:

- The pitch system regulates the power output of the wind turbine by adjusting the rotor blades; at the same time, it functions as the main brake. This is absolutely crucial for ensuring the greatest possible efficiency of the wind turbine and the highest possible energy yield.
- Pitch control in wind turbines adjusts the blade angle to optimize performance and protect the system. In high winds, it reduces the blade angle (feathering) to prevent the turbine from spinning too fast and overloading. While this lowers efficiency during strong winds, it ensures the turbine operates safely, preventing damage and extending its lifespan

Energy

1. Wind Kinetic Energy

- Wind Kinetic Energy: Wind possesses kinetic energy due to the motion of air molecules. The amount of energy depends on the wind speed and the density of the air.
- SI unit for energy: Joule
 - One joule is the kinetic energy of an object with a mass of 2 kilograms moving with a velocity of one meter per second. $1 \text{ J} = 1 \text{ kg m}^2 \text{ s}^{-2}$.
- Betz Limit:
 - The theoretical limit for the energy of a wind turbine in ideal conditions
 - Established by German physicist, Albert Betz, it states that a wind turbine can only convert a maximum of approximately of 59.3% of kinetic energy into usable power
 - Calculated based on principles of momentum transfer in fluid dynamics
 - While no real-world turbine can reach the full Betz Limit due to factors like design limitations and wind variations, it serves as a benchmark for evaluating wind turbine performance
 - No, the Betz limit does not apply to steam turbines. The Betz limit is specific to wind turbines and describes the maximum theoretical efficiency for extracting kinetic energy from a moving fluid, like air, which is about 59.3%.

2. Conversion to Mechanical Energy

- Wind Turbines:
 - The wind turbine captures the kinetic energy of the wind with its blades.
 - The blades are designed to rotate when wind passes through them due to their aerodynamic shape.
 - The rotation of the blades turns a shaft connected to the rotor.
 - The rotor's movement is the mechanical energy generated from the wind's kinetic energy.

3. Conversion to Electrical Energy

- Generators:
 - The rotor shaft is connected to a generator, often through a gearbox that increases the rotation speed to the optimal level needed for the generator.
 - Inside the generator, the mechanical energy is converted into electrical energy.
 - This process is based on electromagnetic induction, where the rotating shaft spins a coil of wire within a magnetic field, inducing an electrical current.
- Measured in kilowatt hours

4. Power Transmission

- The generated electricity is transmitted from the wind turbine to the power grid.
- It is often transformed to a higher voltage for efficient long-distance transmission.

This process of converting wind energy to electrical energy involves two main stages: converting kinetic energy into mechanical energy using the turbine, and then converting that mechanical energy into electrical energy using a generator.

5. Hydroelectric power

- Hydroelectric power plants convert gravitational potential energy and kinetic energy into electromagnetic energy
- Gravitational potential energy
 - Water stored at a height in a reservoir has potential energy due to gravity
 - This energy is the result of the water's position relative to the Earth's surface.
- Kinetic energy
 - When the water is released from the reservoir, its potential energy is converted into kinetic energy as it flows downhill toward the turbines.
- Electromagnetic energy
 - The moving water (kinetic energy) spins the turbine blades, which are connected to a generator. The generator then converts the mechanical energy from the spinning turbine into electrical energy through electromagnetic induction.
- In essence, gravitational potential energy is the primary source, and kinetic energy is the intermediate form, ultimately resulting in electromagnetic energy (electricity).
- *Steam* is the most common form of power generator today
- *Induction generator* is the most commonly used for wind turbines

Energy Sources

1. Fossil Fuels

- What they are
 - Fossil fuels—coal, oil, and natural gas—are derived from ancient organic materials that have been compressed and heated over millions of years, creating carbon-rich energy sources.
- How they work
 - When burned, these fuels release energy in the form of heat, which is used to generate steam. The steam drives turbines connected to electricity generators. Oil and natural gas are also refined into fuels like gasoline and diesel for transportation.
- Global Use
 - Fossil fuels are the dominant energy source worldwide, accounting for about 80-85% of global energy production. They are used in power plants, vehicles, industrial processes, and residential heating.
- Challenges
 - Pollution: Burning fossil fuels releases CO₂, contributing to global warming. Other pollutants like sulfur dioxide (SO₂), nitrogen oxides (NO_x), and particulate matter can cause acid rain, smog, and respiratory issues.
 - Climate Change: Fossil fuel use is the largest driver of climate change, with CO₂ emissions causing the Earth's temperature to rise.
 - Finite Resources: Fossil fuels are non-renewable, and as extraction becomes more difficult and costly, prices can increase, leading to energy security concerns.

2. Coal

- Non-renewable
- 19% of U.S. electricity
- Pros:
 - High energy output

- low cost
- Cons
 - High CO2 emissions
 - Pollution
 - Mining impact

3. Natural Gas

- What it is
 - A cleaner-burning fossil fuel primarily composed of methane (CH₄). It's used for heating, electricity generation, and as a transportation fuel (compressed natural gas, CNG).
- How it works
 - Natural gas is burned in turbines, engines, or boilers to produce heat or electricity. It's also used in homes for heating and cooking.
- Global Use
 - Natural gas is a major energy source in countries like the United States, Russia, and Qatar, often used in power plants and as a transportation fuel.
- Advantages:
 - Cleaner than Coal and Oil: Natural gas produces less CO₂ and fewer pollutants when burned.
 - Versatile: It can be used in many sectors: residential heating, electricity generation, and industrial uses.
- Challenges:
 - Methane Leaks: Methane, though less harmful than CO₂, is a potent greenhouse gas. Leaks during extraction, transportation, and storage can have a significant environmental impact.
 - Non-Renewable: Like all fossil fuels, natural gas is finite and will eventually be depleted.
- Non-renewable
- 39% of U.S. electricity
- Pros
 - Lower CO₂ than coal

- efficient
- Cons
 - Methane leakage
 - non-renewable

4. Oil

- What it is
 - A liquid fossil fuel formed from ancient marine organisms. It's refined into fuels like gasoline, diesel, and jet fuel, and is used in a wide variety of industrial products.
- How it works
 - Oil is refined and processed into usable products that power vehicles, planes, and ships. It's also used in power plants to generate electricity.
- Global Use
 - Oil is the dominant energy source for transportation, with nearly 90% of global oil consumption dedicated to fuel for cars, trucks, ships, and planes.
- Advantages
 - High Energy Density: Oil contains a large amount of energy per unit volume, making it very efficient for transportation and industrial applications.
 - Widely Used: Oil products are integral to global economies, with many industries relying on it.
- Challenges
 - Pollution: Oil combustion releases significant CO2 emissions and other pollutants, contributing to climate change and air quality issues.
 - Oil Spills: Extraction and transportation can result in oil spills, which can devastate marine ecosystems.
 - Resource Depletion: Oil is finite, and extraction can become more difficult and environmentally harmful over time.
- Non-renewable
- ~1% of U.S. electricity
- Pros
 - High energy density

- Cons
 - Expensive for power generation
 - volatile prices

5. Nuclear

- What it is
 - Energy produced by splitting the nucleus of atoms in a process called nuclear fission. The most common fuel is uranium-235, although other isotopes can be used.
- How it works
 - In a nuclear power plant, uranium atoms are split to release a large amount of heat. This heat is used to generate steam, which spins turbines and produces electricity.
- Global Use
 - Nuclear power provides around 10% of global electricity, with countries like the U.S., France, and China being major users.
- Advantages
 - Low Carbon Emissions: Nuclear power produces little to no greenhouse gas emissions during operation.
 - High Energy Output: A small amount of nuclear fuel produces a vast amount of energy.
 - Reliable: Unlike wind and solar, nuclear power can produce electricity continuously, making it a reliable source of baseload power.
- Challenges:
 - Nuclear Waste: Nuclear power creates radioactive waste that remains hazardous for thousands of years. Safe disposal and long-term storage are significant challenges.
 - Accidents: While rare, accidents like the Chernobyl and Fukushima disasters have demonstrated the potential dangers of nuclear power.
 - High Costs: Nuclear power plants are expensive to build and decommission, and the regulatory environment is stringent.
- Non-renewable
- 19% of U.S. electricity
- Pros

- Low emissions
- high energy density
- Cons
 - Waste disposal
 - high cost

Renewables

- What they are: Renewable energy comes from sources that are naturally replenished, such as sunlight, wind, water, geothermal heat, and biomass. These sources are key to reducing greenhouse gas emissions and combating climate change.
- Global Trends: There is a growing push towards increasing renewable energy usage worldwide as a response to climate change and the need for energy security. Renewables are seen as a key solution to transitioning away from fossil fuels.

6. Solar

- What It Is
 - Solar energy is energy harnessed from the Sun's radiation.
 - It's a clean, renewable source of energy
 - can be used in a variety of ways, such as for generating electricity, heating water, and even for cooling purposes.
 - The most common methods of harnessing solar energy are through photovoltaic (PV) cells and solar thermal systems.
- How It Works:
 - Photovoltaic (PV) Systems:
 - PV cells convert sunlight directly into electricity. When sunlight strikes the surface of a PV cell, it excites electrons in the material (typically silicon), causing them to move and generate electricity.
 - Solar Panels: Multiple PV cells are combined into solar panels, which are installed on rooftops or in large-scale solar farms. The electricity generated is typically direct current (DC), but an inverter is used to

convert it to alternating current (AC), which is used in homes and businesses.

- Solar Thermal Systems:
 - These systems use mirrors or lenses to concentrate sunlight onto a small area, generating heat. This heat is then used to produce steam, which drives a turbine to generate electricity. Solar thermal systems can also be used for direct heating of water or air in residential or commercial buildings.
 - There are two main types of solar thermal systems: concentrated solar power (CSP) and solar water heating.
- Global Use:
 - Solar energy is rapidly growing around the world, with major installations found in countries like China, the U.S., India, and Germany. It's used for both small-scale residential installations (such as rooftop panels) and large-scale solar farms.
- Advantages:
 - Renewable and Abundant
 - Solar energy is virtually limitless and can be harnessed anywhere in the world where sunlight is available.
 - Clean Energy
 - Solar power doesn't produce air pollution or greenhouse gases during operation, making it an environmentally friendly alternative to fossil fuels.
 - Low Operating Costs
 - Once installed, solar panels require very little maintenance, and the cost of operating solar systems is minimal. Solar systems have long lifespans, often lasting 20–30 years.
 - Energy Independence
 - Solar energy allows individuals, businesses, and countries to reduce dependence on imported fossil fuels and enhance energy security.
 - Scalable
 - Solar energy can be used at various scales—from small rooftop panels to large utility-scale solar farms.
 - Energy Access

- Solar power can provide electricity in remote areas without access to a centralized grid, improving energy access and helping to power off-grid locations.
- Challenges:
 - Intermittency
 - Solar energy is intermittent because it depends on sunlight, which is not available at night and can be blocked by clouds or bad weather. This requires energy storage solutions (like batteries) or backup power systems to ensure a continuous supply.
 - Energy Storage
 - To make solar power reliable 24/7, excess energy produced during the day needs to be stored for nighttime use. Energy storage systems like lithium-ion batteries are improving but can still be costly.
 - Space Requirement
 - Large-scale solar farms require large areas of land, and rooftop installations may not be viable for all buildings, especially in dense urban areas.
 - Initial Cost
 - The upfront cost of purchasing and installing solar panels, as well as the inverter and other components, can be high. However, the cost of solar installations has dropped dramatically in recent years and continues to decrease, making it more affordable.
 - Efficiency
 - Solar panels typically have an efficiency of around 15-20%, meaning only a fraction of the sunlight hitting the panel is converted into electricity. Researchers are working on improving the efficiency of solar cells.
- Types of Solar Technologies:
 - Photovoltaic (PV) Solar Panels
 - These are the most common and familiar form of solar technology, used to directly convert sunlight into electricity.
 - Concentrated Solar Power (CSP)
 - These systems use mirrors or lenses to concentrate sunlight onto a small area, generating heat that can be used to produce electricity.

CSP is usually used in large-scale power plants rather than residential applications.

- Solar Water Heating
 - Solar thermal collectors are used to heat water for residential or commercial use, reducing the need for electricity or gas to heat water.
- Building-Integrated Photovoltaics (BIPV)
 - This technology integrates solar cells into building materials, such as windows, roofs, and walls, making them part of the building structure itself.
- Global Trends
 - Solar energy has experienced rapid growth over the past decade due to falling costs and increasing environmental concerns.
 - It's one of the fastest-growing energy sectors, driven by technological advancements, government incentives, and a push for cleaner energy.
 - Solar is expected to play a major role in the global transition to a low-carbon economy, and many countries have set ambitious goals for solar power generation in the coming years.
- Summary
 - Pros: Renewable, clean, abundant, low operational cost, and increasingly affordable.
 - Cons: Intermittency (requires storage or backup), space requirements, and high initial cost (though this is decreasing).
 - Role in the Future: Solar energy is expected to continue growing and play a major role in reducing global dependence on fossil fuels and mitigating climate change.
 - Renewable
 - 6% of U.S. electricity
 - Pros: Clean, low maintenance
 - Cons: Intermittent, land use
 - Harnessed in 3 main ways: The most commonly used solar technologies for homes and businesses are solar photovoltaics for electricity, passive solar design for space heating and cooling, and solar water heating.

- Advantages of photovoltaic solar energy: Renewable & Sustainable: It's an endless, eco-friendly energy source.
- Solar thermal vs photovoltaic: Both generate electricity but one uses solar panels and one uses solar thermal
- Low Operating Costs: Minimal maintenance and long lifespan (25+ years).
- Cost Savings: Reduces electricity bills and allows for selling excess power.
- Energy Independence: Reduces reliance on imported energy.
- Scalability: Suitable for both small and large systems.
- Job Creation: Boosts employment in manufacturing and installation.
- Low Maintenance: Simple upkeep with periodic cleaning.
- Technological Advancements: Continual improvements in efficiency and storage.

7. Wind

- What it is
 - Wind energy harnesses the kinetic energy of the wind to generate electricity.
- How it works
 - Wind turbines with large blades are placed in windy areas. As the wind blows, it spins the blades, which turn a rotor connected to a generator that produces electricity.
- Global Use
 - Wind energy is one of the fastest-growing renewable energy sources worldwide, with countries like China, the U.S., and Germany leading in installed wind capacity.
 - Advantages:
 - Clean and Renewable: Wind energy generates no emissions, making it environmentally friendly.
 - Cost-Effective: Wind power is becoming increasingly cost-competitive with fossil fuels, especially in regions with strong winds.

Challenges:

- **Intermittent:** Wind doesn't blow constantly, so wind energy generation is intermittent and requires energy storage or backup systems.
- **Space and Noise:** Wind farms require large areas of land, and turbines can produce noise, which can be a concern in populated areas.
 - Renewable
 - 10% of U.S. electricity
 - Pros: Clean, scalable
 - Cons: Intermittent, wildlife impact
- Hydropower

What it is: Hydropower uses the energy of flowing water to generate electricity.

How it works: Water flows through dams or other water systems, turning turbines that generate electricity.

Global Use: Hydropower is the largest source of renewable electricity globally, providing around 16% of global power.

Advantages:

- **Reliable and Flexible:** Hydropower is a stable, baseload energy source and can be ramped up or down depending on demand.
- **No Emissions:** It's a clean source of energy with little environmental impact once the infrastructure is built.

Challenges:

- **Environmental Impact:** Dams can disrupt local ecosystems, fish migration, and water quality. Large-scale hydropower projects may displace communities.
- **Geographically Limited:** Hydropower requires suitable river systems, making it location-dependent.

- Renewable
- 5% of U.S. electricity
- Pros: Reliable, efficient
- Cons: Ecosystem disruption, land use
- Geothermal

What it is: Geothermal energy comes from heat stored beneath the Earth's surface, typically near tectonic plate boundaries or volcanic regions.

How it works: Geothermal power plants use steam or hot water from underground reservoirs to drive turbines and generate electricity.

Global Use: Geothermal energy provides around 0.3% of global electricity, with the majority of plants located in countries like Iceland, the U.S., and New Zealand.

Advantages:

- **Constant and Reliable:** Geothermal energy is available 24/7, unlike solar or wind, which are intermittent.
- **Low Emissions:** It produces very little pollution compared to fossil fuels.

Challenges:

- **Location-Specific:** Geothermal plants are most effective in geologically active areas, limiting their widespread use.
- **High Initial Costs:** Drilling wells and building infrastructure can be expensive.
 - Renewable
 - ~1% of U.S. electricity
 - Pros: Reliable, low emissions
 - Cons: High initial cost, site-specific
- Biomass

What it is: Biomass is organic material that can be used as a fuel, such as wood, agricultural waste, and even municipal waste.

How it works: Biomass can be burned directly for heat, converted into biofuels like ethanol or biodiesel, or used to generate electricity.

Global Use: Biomass provides about 5% of global energy, especially in developing countries where wood is a major fuel for cooking and heating.

Advantages:

- **Waste Reduction:** Biomass can help reduce waste and convert it into useful energy.
- **Renewable:** As long as biomass sources are sustainably managed, they can be replenished.

Challenges:

- **CO2 Emissions:** Although biomass is renewable, it still produces CO2 when burned. However, it's argued that the CO2 released is offset by the CO2 absorbed by plants during their growth.
- **Land Use:** Growing biomass crops can compete with food production and lead to deforestation if not managed sustainably.
 - Renewable
 - ~1% of U.S. electricity
 - Pros: Reduces waste, carbon-neutral (if sourced sustainably)
 - Cons: Air pollution, land use
- Tidal
 - **What it is:** Tidal energy uses the rise and fall of ocean tides to generate electricity.
 - **How it works:** Tidal turbines, similar to underwater wind turbines, are placed in areas with strong tidal flows. The moving water turns the turbines to generate power.
 - **Global Use:** Tidal energy is still in the early stages of development, with only a few pilot projects worldwide, such as in the UK and South Korea.

- **Advantages:**
 - **Predictable:** Tides are highly predictable, making tidal energy more reliable than wind or solar.
 - **No Emissions:** Tidal energy is a clean source of power.
- **Challenges:**
 - **High Costs:** Tidal energy infrastructure is expensive to install.
 - **Environmental Impact:** The construction of tidal power plants could impact marine ecosystems and local fishing industries.
- Renewable

5. U.S. Electricity Generation Mix (2024)

1. Natural Gas: 39%
2. Renewables: 22%
 - Wind: 10%
 - Solar: 6%
 - Hydropower: 5%
 - Biomass & Geothermal: ~1%
3. Coal: 19%
4. Nuclear: 19%
5. Oil: ~1%

Batteries

1. Nickel-Cadmium (NiCd) Batteries

- Chemistry: Nickel (Ni) and Cadmium (Cd)
- Voltage: Typically 1.2V per cell
- Advantages:
 - Robust and durable.
 - Perform well in extreme temperatures.
 - Can deliver high discharge currents.
- Disadvantages:
 - Memory effect: If not fully discharged before recharging, capacity can decrease over time.
 - Environmental concern: Cadmium is toxic and harmful to the environment.
- Common Uses: Power tools, cameras, and emergency lighting.
- Rechargeable: Yes
 - Common Recharge Cycles: Typically can be recharged 500–1,000 times, depending on usage and care.
 - Rechargeable Features: Can be recharged using a compatible charger, though they are prone to the memory effect, which can reduce their effective capacity over time if they are not fully discharged before recharging.

2. Nickel-Metal Hydride (NiMH) Batteries

- Chemistry: Nickel (Ni) and a metal hydride (instead of cadmium)
- Voltage: Typically 1.2V per cell
- Advantages:
 - Higher capacity than NiCd, making them last longer on a charge.
 - No memory effect (or much less of one).
 - More environmentally friendly than NiCd, though still not entirely eco-friendly.
- Disadvantages:
 - Higher self-discharge rate than other chemistries (they lose charge faster when not in use).

- Can be more expensive than other types.
- Common Uses: Hybrid cars (e.g., Toyota Prius), digital cameras, portable electronics.
- Rechargeable: Yes
 - Common Recharge Cycles: Typically can be recharged 500–1,000 times, with some newer models lasting even longer.
 - Rechargeable Features: A better choice than NiCd in many applications due to a higher capacity and less memory effect.

3. Zinc-Carbon Batteries

- Chemistry: Zinc (Zn) and Carbon (C), typically with a manganese dioxide cathode
- Voltage: Typically 1.5V per cell
- Advantages:
 - Low cost.
 - Readily available.
- Disadvantages:
 - Lower energy density and shorter lifespan than other types (e.g., alkaline batteries).
 - Can leak and corrode over time.
 - Not suitable for high-drain devices.
- Common Uses: Flashlights, remote controls, clocks, and other low-drain devices.
- Rechargeable: Yes
 - Common Recharge Cycles: Can usually be recharged around 300–500 times, though this can vary depending on the quality of the battery and charging conditions. Li-ion batteries generally last longer with proper care.
 - Rechargeable Features: No memory effect, high energy density, and longer lifespan compared to NiCd and NiMH.

4. Lithium-Ion (Li-ion) Batteries

- Chemistry: Lithium-based (various types, but often lithium cobalt oxide or lithium iron phosphate)
- Voltage: Typically 3.7V per cell
- Advantages:

- High energy density (more power in a smaller, lighter package).
- Long lifespan (can last for several hundred charge cycles).
- Low self-discharge rate.
- No memory effect.
- Disadvantages:
 - Can be expensive.
 - Sensitive to overcharging and overheating, requiring protection circuits.
 - Degrades over time if stored at high temperatures or with a full charge.
 - Highly flammability
- Common Uses: Smartphones, laptops, electric vehicles, power tools, and other portable electronics.
- Rechargeable: Yes
 - Common Recharge Cycles: Typically 300–500 charge cycles, depending on the depth of discharge.
 - Rechargeable Features: Lead-acid batteries are widely used in automotive and backup power systems. They are rugged but have lower energy density and can be heavy compared to newer technologies.

5. Lead-Acid Batteries

- Chemistry: Lead (Pb) and Lead Oxide (PbO), with sulfuric acid (H₂SO₄) as the electrolyte
- Voltage: Typically 2V per cell (usually grouped in 6-cell or 12V configurations for practical uses)
- Advantages:
 - Very inexpensive and widely available.
 - Reliable for high current applications.
 - Well-established technology with a long history.
- Disadvantages:
 - Low energy density (bulky and heavy for the amount of power they deliver).
 - Shorter lifespan compared to newer battery technologies (especially when deeply discharged regularly).
 - Environmental concerns due to the lead and sulfuric acid.

- Common Uses: Car batteries, uninterruptible power supplies (UPS), solar energy storage, and large-scale backup power.
- Rechargeable: No
 - Common Recharge Cycles: Zinc-carbon batteries are single-use and cannot be recharged. Once depleted, they need to be disposed of or recycled.

6. Summary Table

Battery Type	Voltage	Energy Density	Cost	Lifespan	Common Uses
Nickel-Cadmium (NiCd)	1.2V	Low	Moderate	Moderate	Power tools, emergency lights, cameras
Nickel-Metal Hydride (NiMH)	1.2V	Moderate	Moderate	Moderate	Hybrid cars, portable electronics, cameras
Zinc-Carbon	1.5V	Low	Very Low	Short	Low-drain devices (e.g., remotes, clocks)
Lithium-Ion (Li-ion)	3.7V	High	High	Long	Smartphones, laptops, EVs, power tools
Lead-Acid	2V per cell	Low	Very Low	Short	Car batteries, backup power, solar storage

Each battery type has its strengths and weaknesses, and their suitability depends on the application, cost constraints, and environmental considerations.

Energy Densities of the Listed Substances

1. Silicon:

- Specific energy density: ~1.0 MJ/kg
- Explanation: Silicon is often used in energy storage applications (like in batteries), but by itself, it doesn't release much energy compared to fuels or biological molecules. Silicon-based energy storage primarily works in a different way (e.g., in batteries or photovoltaic cells) rather than releasing energy directly as a fuel.

2. Hydrazine (N_2H_4):

- Specific energy density: ~19.6 MJ/kg
- Explanation: Hydrazine is a highly energetic compound, often used as a rocket propellant due to its high specific energy.

3. Glucose ($\text{C}_6\text{H}_{12}\text{O}_6$):

- Specific energy density: ~15.6 MJ/kg
- Explanation: Glucose is a form of sugar that provides energy in biological systems (e.g., cellular respiration), but its specific energy density is lower than many chemical fuels.

4. Methanol (CH_3OH):

- Specific energy density: ~22.7 MJ/kg
- Explanation: Methanol is a simple alcohol and is often used as a fuel or in fuel cells. It has a relatively high specific energy density compared to many organic compounds.

5. Butanol ($\text{C}_4\text{H}_9\text{OH}$):

- Specific energy density: ~30.0 MJ/kg

- Explanation: Butanol is another alcohol, and it has a higher specific energy density than both glucose and methanol, making it a good candidate for biofuels.

6. Conclusion:

The substance with the lowest specific energy density among the options you listed is silicon, which has only about 1.0 MJ/kg. The other substances—hydrazine, glucose, methanol, and butanol—are all much more energy-dense.

The largest capacity form of grid energy storage worldwide is pumped hydro storage.

Storage

Energy storage types

1. **Compressed gas** - Compressed air energy storage (CAES) is a method of storing energy by compressing air and storing it in underground caverns.
 - a. Compression: Surplus electricity powers compressors that store high-pressure air underground or in tanks.
 - b. Storage: Compressed air is held until electricity is needed.
 - c. Expansion: Air is released, heated, and expanded through a turbine to generate electricity.
2. **Flywheels** - Flywheel energy storage systems store energy in the rotational motion of a flywheel.
 - a. Have fast response times
3. **Hydrogen** - Hydrogen can be used for energy storage in fuel cells or through chemical conversion processes.
4. **Superconducting magnets** - Superconducting magnetic energy storage (SMES) uses magnetic fields to store energy.
5. **Zinc/air batteries** - Zinc-air batteries are a type of battery that stores energy electrochemically.

1. Pumped Hydro Storage (PHS)

- Capacity: Pumped hydro storage accounts for the vast majority of global grid energy storage capacity. It represents approximately 95% of the world's total energy storage capacity, with tens of gigawatts (GW) installed globally.
- How It Works:
 - Pumping phase: During periods of low demand, excess electricity (often from renewable sources like wind or solar) is used to pump water from a lower reservoir to a higher reservoir.
 - Generation phase: When energy demand is high, the stored water is released from the upper reservoir, flowing downhill to generate electricity through turbines connected to generators.
- Advantages

- Large-scale storage: PHS can store massive amounts of energy (up to several gigawatt-hours) and deliver it quickly when needed.
- Proven and reliable: It's a well-established technology with over 100 years of use.
- Long-duration storage: PHS can typically store energy for many hours, making it ideal for balancing daily fluctuations in grid demand.
- Disadvantages
 - Turbine inefficiency – Energy is lost during the conversion between electrical and mechanical forms, reducing overall efficiency.
 - Geographic limitations – Requires specific terrain with elevation differences and large water reservoirs.
 - High initial cost – Construction of dams, reservoirs, and tunnels involves significant capital investment.
- Examples: Some of the largest pumped hydro storage facilities are in countries like China, the United States, and Japan. For instance, the Three Gorges Dam in China, which has a huge capacity of 22,500 MW in pumped storage.

2. Other Forms of Grid Storage (Smaller Scale):

While pumped hydro dominates, there are other forms of grid energy storage that are growing but are still far smaller in scale:

1. Lithium-ion batteries:
 - Growing quickly for grid storage due to their flexibility and fast response time. However, their capacity is still much smaller compared to pumped hydro.
2. Compressed Air Energy Storage (CAES):
 - This is another form of large-scale energy storage, though it is still much less common than pumped hydro.
3. Flow batteries:
 - A promising technology for longer-duration storage but still in the early stages compared to pumped hydro.

3. Conclusion:

Pumped hydro storage is still by far the largest capacity form of grid energy storage in use today worldwide. It is unmatched in scale, reliability, and the ability to store large amounts of energy for extended periods.

Washington's largest wind farm, Windy Point Wind Farm, is located in the Columbia Basin region of Central Washington, near the town of Goldendale in Klickitat County.

The number of wind-powered mills peaked around 1830. This was a period when windmills were widely used before the advent of steam engines and other industrial technologies that started to replace them.

Environment



- How do offshore wind turbines address challenges such as saltwater corrosion and the extreme conditions of the marine environment?
 - Corrosion Resistance: Stainless steel, galvanized steel, TSA coatings, and epoxy paints.
 - Cathodic Protection: Sacrificial anodes (zinc/aluminum) and ICCP systems.
 - Sealed Components: Climate-controlled enclosures, gaskets, and moisture barriers.
 - Structural Durability: Aerodynamic blades, reinforced towers, and weatherproofing.
 - Monitoring & Maintenance: Sensors, remote tracking, and predictive AI diagnostics.
 - Sturdy Foundations: Floating mooring systems and reinforced fixed-bottom structures.

These measures ensure long-term efficiency and durability in harsh marine environments.

The term for the practice of ensuring minimal environmental impact during the installation of wind turbines: environmental mitigations

Potential negative impact of wind farms: habitat destruction

Wind power graphs and data



As of October 2024, the top U.S. states generating electricity from wind power are:

1. Texas: 10,552 MWh (26.4% of total U.S. wind energy generation)
2. Iowa: 4,543 MWh (11.4%)
3. Oklahoma: 3,355 MWh (8.4%)
4. Kansas: 2,867 MWh (7.2%)

5. Illinois: 2,220 MWh (5.5%)
6. Colorado: 1,582 MWh (4.0%)
7. Minnesota: 1,401 MWh (3.5%)
8. North Dakota: 1,354 MWh (3.4%)
9. New Mexico: 1,290 MWh (3.2%)
10. Nebraska: 1,201 MWh (3.0%)

These ten states collectively account for a significant portion of the nation's wind energy production.

Formulas

1. Wind power

- $P = \frac{1}{2} \cdot \rho \cdot A \cdot v^3$
- in which
 - P is the power in watts (W)
 - ρ is the air density (kg/m³)
 - A is the swept area of the turbine (m²)
 - v is the wind speed (m/s)
- What is the wind power passing through a wind turbine with the following conditions? Turbine radius = 0.2m, wind speed = 3m/s, air density = 1.23 kg/m³
 - calculate A (the swept area of the turbine) with $A = \pi r^2$, $A = 0.1256 \text{ m}^2$
 - plug into equation $P = 1/2 \cdot 1.23 \text{ kg/m}^3 \cdot 0.1256 \text{ m}^2 \cdot (3 \text{ m/s})^3$
 - $P = 0.5 \cdot 1.23 \cdot 0.1256 \cdot 27 = 2.089 \text{ W}$

2. Power Output of a Wind Power

- $P_{\text{turbine}} = \frac{1}{2} \cdot \rho \cdot A \cdot v^3 \cdot C_p$
- in which
 - P_{turbine} is the actual power output in watts
 - C_p is the power coefficient
 - cannot exceed the Betz limit of approximately 0.593
 - ρ is the air density (kg/m³)
 - v is the wind speed (m/s)
 - A is the swept area of the turbine (m²)

***Cp:

The power coefficient (C_p) in wind turbine technology measures a turbine's efficiency in converting wind energy into electrical power. It's defined as:

$$C_p = P_{\text{actual}} / P_{\text{wind}}$$

where:

- P_{actual} :
 P_{actual} is the turbine's generated power.
- P_{wind} :
 P_{wind} is the total available wind power in the swept area.

The Betz Limit states that no turbine can capture more than 59.3% of the wind's kinetic energy, as extracting too much energy would stop airflow through the rotor.

Modern Wind Turbines and the Betz Limit:

- Advanced turbines achieve C_p values between 0.45 and 0.50, reaching about 75–85% of the Betz Limit.
- Improvements like optimized blade designs, pitch control systems, and reduced aerodynamic losses help push efficiency closer to this theoretical maximum.

While turbines can't surpass the Betz Limit, continued advancements are narrowing the gap, maximizing energy capture from available wind.

3. Wind Energy

- $E_{\text{wind}} = P_{\text{turbine}} \cdot t$
- in which
 - E_{wind} is the total energy produced (in joules or watt-hours),
 - P_{turbine} is the power output of the turbine (in watts),
 - t is the time over which energy is produced (in seconds)

4. Power Loss/ Power in an Electrical Circuit

- $P = I^2 \cdot R$ or $P = IV$
- in which
 - P = power in watts
 - I = current in amperes
 - R = resistance in Ohms

- V = voltage in volts

5. Area of a Circle

- $A = \pi r^2$
- Use to find the swept area of turbine
- in which
 - A is the area
 - r is the radius
 - and π is 3.1415926

6. Circumference of a Circle

- $C = 2\pi r$
- in which
 - C is the area
 - r is the radius
 - and π is 3.1415926

7. Sector Area of a Circle

- $A_{\text{sector}} = \frac{\theta}{360^\circ} \cdot \pi r^2$
- in which
 - A_{sector} is the area of the sector
 - θ is the central angle (in degrees)
 - r is the radius
 - and π is 3.1415926

8. Sector Area of a Circle

- $L_{\text{arc}} = \frac{\theta}{360^\circ} \cdot 2\pi r$
- in which
 - L_{arc} is the length of the arc
 - θ is the central angle (in degrees)
 - r is the radius

- and π is 3.1415926

9. Efficiency of the Turbine

- Efficiency = total power generated/ total power available x 100

History of the Wind Turbine

1. Ancient Beginnings (2000 BCE – 500 CE)

- Early Windmills: The first known use of wind for mechanical power dates back to ancient civilizations.
 - Persia (500–900 CE): Early windmills, known as Persian Windmills, were vertical-axis windmills (VAWT) used to grind grain and pump water. These mills were typically built in areas with consistent winds like Persia (modern-day Iran).
 - Egypt & Mesopotamia: Wind-powered boats and basic sails were used for transportation.

2. Medieval Period (1100 – 1600)

- Horizontal-Axis Windmills: The European windmill emerged around the 12th century, especially in the Netherlands, with the introduction of horizontal-axis windmills (HAWT). These mills were used for draining land, grinding grain, and pumping water.
- Windmill Development in Europe: Windmills in the Netherlands, England, and France evolved into more efficient machines with rotating blades mounted on a horizontal axis. These mills spread across Europe as technology improved.

3. Early Modern Period (1600s – 1800s)

- Industrial Revolution: During this period, windmills were used mainly for grinding grain, pumping water, and propelling boats, especially in agricultural areas. However, the development of steam engines and other industrial technologies began to reduce reliance on wind power.
- First Mechanical Wind Turbines: In the 1800s, wind energy experimentation moved beyond grinding grain. People like Charles F. Brush in the U.S. and James Blythe in Scotland started building small wind turbines to generate electricity.
 - Charles F. Brush (1887): Built the first large-scale wind turbine in Cleveland, Ohio, generating electricity to power his home. It was a 12-meter-tall wind turbine with a 17-meter rotor.

- James Blythe (1887): A Scottish inventor, Blythe built the first wind turbine to generate electricity, powering his home in Marykirk, Scotland.
- Scotland was first country to use windmills to generate electricity

4. Early 20th Century Developments (1900 – 1930s)

- Wind Turbine for Power Generation: In the early 20th century, wind turbines began being used for rural electrification in remote areas where grid connections were not available.
 - 1930s: The American Wind Power Company and other manufacturers began building wind turbines for farms, providing off-grid electricity to rural communities.

5. Mid 20th Century – Post-War Era (1940s – 1970s)

- The Oil Crisis: The energy crises of the 1970s led to a renewed interest in renewable energy, including wind power. In this period, the technology began shifting from small-scale, local use to larger-scale turbines.
 - 1973 Oil Embargo: The U.S. faced a petroleum shortage that reignited interest in alternative energy sources, including wind.
 - Development of Modern Turbines: Larger and more efficient turbines were developed in Denmark, the U.S., and other countries. The first commercial wind farms began to emerge, particularly in Denmark and the U.S.
- 1979: The U.S. government funded large-scale wind power projects under the Wind Energy Program to develop and promote renewable energy technology.

6. Modern Wind Energy Era (1980s – Present)

- Wind Farms and Commercialization: By the late 1980s and 1990s, wind turbines began to be used more widely as part of commercial wind farms. Major advancements in turbine efficiency, size, and design occurred.
 - 1990s: Denmark became a leader in wind energy production, with companies like Vestas dominating the global market.
 - Global Expansion: Countries like Germany, Spain, the U.S., and China expanded their wind energy industries, leading to larger, more cost-effective wind turbines and farm-scale projects.

- Technological Innovations: Turbines became significantly more efficient, with larger rotors and better materials like carbon fiber used in blades. Offshore wind farms started to become a viable option due to improvements in technology.
 - Offshore Wind Turbines: By the 2000s, offshore wind farms were built, taking advantage of strong winds at sea to generate electricity more reliably.

7. Present and Future of Wind Energy

- Wind Power Today: Wind turbines are a major part of global renewable energy, with countries like China, Germany, and the U.S. having large-scale operations. Wind power is now one of the fastest-growing sources of energy worldwide.
 - Global Capacity: As of 2020, global wind energy capacity reached over 700 GW, and wind is expected to continue growing in the coming decades.
 - Technological Advances: Innovations such as floating turbines (for deeper waters), larger blades, and more efficient materials are improving the cost-effectiveness of wind power.
 - Environmental Impact: Wind power is considered one of the cleanest renewable energy sources, emitting little to no greenhouse gases
 - China leads the world in installed wind power capacity as of 2025 since 2010

“Father of modern wind power” due to pioneering work on large scale wind turbines in 1970s-Dr. Ulrich Hutter

Laws

1. Laws of Motion (Newton's Laws) in Wind Power

- First Law (Inertia)
 - An object in motion stays in motion unless acted upon by an external force
 - For wind turbines, the blades are set in motion by the wind, and once spinning, they want to keep turning until resistance (like friction, air resistance, or mechanical resistance) slows them down.
- Second Law (Force = Mass × Acceleration)
 - The force exerted by the wind on the turbine blades (which causes them to move) is proportional to the wind speed and the size of the blades.
 - The larger the blades or the stronger the wind, the greater the force applied to the turbine.
- Third Law (Action and Reaction): For every action, there's an equal and opposite reaction.
 - As the wind hits the blades of a turbine, the blades push back on the wind, causing a change in the direction of the airflow.
 - This action leads to energy extraction from the wind and is critical in how turbines convert kinetic energy into mechanical energy.

2. Ohm's Law in Wind Power

- Ohm's Law
 - Ohm's Law is directly related to electrical circuits, it plays a crucial role in the transmission and management of the electrical power generated by wind turbines.
 - $P = I^2 \cdot R$
 - V is the voltage (in volts, V)
 - I is the current (in amperes, A)
 - R is the resistance (in ohms, Ω)
- Wind turbines generate alternating current (AC) power, and the electricity is often transported through wires to a grid or storage system.

- The resistance in these wires impacts how much energy is lost during transmission. High resistance leads to energy loss (heat), which can reduce the efficiency of power delivery.
- Managing resistance in electrical components (such as transformers, capacitors, and inverters) is crucial to ensure minimal energy loss.

3. Watt's Law in Wind Power

- Watt's Law is used to relate power, current, and voltage in an electrical system, and it can be written as:
 - $P = I \times V$ (where P is power, I is current, and V is voltage)
 - Or, if you know resistance, you can use the formula: $P = I^2 \times R$ or $P = V^2 / R$.

In wind power:

- This formula helps you calculate the electrical power generated by a wind turbine after the mechanical energy is converted into electrical energy.
- $P = I \times V$ can be used to determine how much electrical power is generated based on the output voltage and current after the turbine's generator converts mechanical energy into electrical form.
- In a more practical sense, once you have the voltage (V) and the current (I) from the turbine, you can use Watt's Law to determine the power output, which is usually measured in watts (W) or kilowatts (kW).

4. Conservation of Energy

Wind power also heavily relies on the principle of conservation of energy. The energy in the wind (kinetic energy) is converted into mechanical energy (rotation of the turbine blades), and then that mechanical energy is converted into electrical energy.

- Kinetic Energy of Wind:
 - The wind has kinetic energy given by the formula $E = \frac{1}{2}mv^2$ where m is the mass of the air moved by the wind, and v is the velocity of the wind.
- Conversion to Mechanical Energy:

- As wind passes through the turbine blades, the turbine extracts some of this kinetic energy, causing the blades to rotate.
- Mechanical to Electrical Energy:
 - The mechanical energy is then converted into electrical energy using a generator connected to the turbine. This process follows the laws of electromagnetic induction (Faraday's Law), which states that a change in magnetic flux induces an electromotive force (EMF), generating current.

Principles

1. Pascal's principle

- Pascal's Principle states that any change in pressure applied to an enclosed fluid is transmitted undiminished to all portions of the fluid and to the walls of its container. This principle applies to liquids and gases in a confined space.
- Formula:
 $P = \frac{F}{A}$ where:
 - P is the pressure,
 - F is the force applied,
 - A is the area over which the force is applied.
- Example:
 - If you apply a force to a piston in a hydraulic system, the pressure is transmitted equally throughout the fluid and acts on another piston. This allows a small force applied to one piston to generate a large force on another piston. This principle is used in hydraulic lifts, brakes, and presses.

2. Archimedes' Principle

Archimedes' Principle states that an object submerged in a fluid experiences an upward buoyant force equal to the weight of the fluid that the object displaces. This explains why objects seem lighter when placed in water or another fluid.

- Formula:
The buoyant F_b can be expressed as:
 $F_b = \rho \cdot V \cdot g$
where:
 - ρ is the density of the fluid,
 - V is the volume of the displaced fluid,
 - g is the acceleration due to gravity.
- Example:
If you place a block of wood in water, the block will float because the buoyant force

from the displaced water is greater than or equal to the weight of the block. If the weight of the object is greater than the buoyant force, it will sink.

3. Bernoulli's principle

- Created by Swedish Daniel Bernoulli in 1738
- Bernoulli's principle states that as the speed of a fluid increases, the pressure within the fluid decreases.
- In wind power: wind speed will increase increases in a mountain pass due to relationship between speed and pressure

Transformers

Transformers

- Role: Transforms the voltage generated by wind turbines to a higher level for grid integration or lowers it for local distribution.
- Function: Wind turbines usually produce low voltage, which is stepped up by transformers for efficient long-distance transmission.


Core Losses in Transformers:

- Definition: Core losses (or iron losses) are energy losses in the transformer's core due to the alternating magnetic field.
- Causes:
 - Hysteresis Loss: Due to the continuous magnetization and demagnetization of the core material (typically iron) with each cycle of the AC current.
 - Eddy Current Loss: Circulating currents induced in the core material by the alternating magnetic field, which causes heating.

Important Conditions Before Connecting Transformers in Parallel:

- Voltage Matching: The primary voltage ratings should be the same to avoid circulating currents.
- Phase Sequence: Ensure both transformers have the same phase sequence; otherwise, short circuits can occur.
- Impedance Matching: The percentage impedance of transformers must be nearly the same to ensure proper load sharing.
- Polarity Matching: Ensure correct polarity, as reverse polarity can lead to short circuits.
- Load Sharing: Transformers should have similar load capacity and characteristics for balanced load sharing.
- Magnetic Flux: Same flux density in the core to avoid unbalanced conditions.

Types of Turbines



1. Blade Configurations

- Single-Bladed:
 - Uses one blade to minimize material costs and reduce weight.
 - Efficient at high speeds but often unstable.

- Double-Bladed:
 - More balanced than single-bladed turbines.
 - Easier to install and maintain but can cause more vibration.
- Three-Bladed:
 - The most common design for modern wind turbines.
 - Provides a good balance of efficiency, stability, and noise reduction.
- U.S. Farm Windmill (Multi-Bladed):
 - Typically used for pumping water rather than generating electricity.
 - Designed to operate at low wind speeds.
- Bicycle Multi-Bladed:
 - A lightweight, low-cost design.
 - Suitable for small-scale applications.


2. Orientation and Placement

- Up-Wind:
 - Faces directly into the wind.
 - Prevents blade interference with the tower but requires a yaw mechanism.
- Down-Wind:
 - Positioned with the wind blowing from behind.
 - Simplifies the design but may experience turbulence.
- Sail Wing:
 - Inspired by sail technology, using a lightweight wing for power generation.
 - Efficient in low wind conditions.
- Multi-Rotor:
 - Uses multiple small rotors instead of one large rotor.
 - Increases energy capture while reducing mechanical stress.
- Enfield - Andreau:
 - Features a ducted or augmented flow system to increase efficiency.
 - Less common but offers increased power output.
- Counter-Rotating Blades:

- Uses two rotors rotating in opposite directions to maximize energy extraction.
- Compensates for torque and increases efficiency.

3. Special Designs

- **Cross-Wind Savonius:**
 - A type of vertical-axis wind turbine (VAWT) with an S-shaped rotor.
 - Ideal for low-wind and urban environments.
- **Cross-Wind Paddles:**
 - Similar to Savonius but with flat paddle-like blades.
 - Simple design and used for small-scale applications.
- **Diffuser:**
 - Features a shroud or duct around the turbine to concentrate airflow.
 - Enhances efficiency and increases power generation.
- **Concentrator:**
 - Similar to the diffuser but focuses wind to a specific point.
 - Suitable for areas with inconsistent wind patterns.
- **Unconfined Vortex:**
 - Utilizes wind-induced vortices to generate energy without blades.
 - Innovative and noise-free but still in experimental stages.




4. Vertical Axis

- Darrieus Wind Turbine (Vertical Axis)
 - This is a vertical-axis wind turbine (VAWT) with a shape resembling a "H" or an "eggbeater." It was designed by French engineer Georges Darrieus in the 1920s.
 - Function: The blades of this turbine are curved, and it generates electricity as wind passes across them. The primary advantage is that it can capture wind from any direction, making it versatile in areas with variable wind direction.
 - Challenges: It's harder to start at low wind speeds and typically requires a mechanical drive system to work efficiently.
- Savonius Wind Turbine (Vertical Axis) - optimal for low-speed, high-torque use and fuller
 - This is another type of VAWT, named after Finnish engineer Sigurd Savonius. The turbine has a distinctive "S" shape, often using half-cylinders as blades.
 - Function: It works by capturing wind with the concave side of the blades, creating a drag force that turns the turbine. It's often used for smaller, low-power applications.
 - Advantages: It's simple to construct and works well in areas with turbulent or low winds.
 - Challenges: It's less efficient than other designs, particularly for large-scale energy production
- Solar Wind Turbine
 - This term is typically a reference to devices that combine both solar energy and wind energy generation. They might be hybrid systems that utilize solar panels alongside wind turbines to capture both forms of renewable energy.
 - Function: The solar panels generate electricity during the day when the sun is shining, while the wind turbine produces energy when the wind blows.
 - Advantages: The combined system can provide energy in different weather conditions, making it more reliable than relying on just one source.
- Helical Wind Turbine (Vertical Axis)
 - This type of VAWT has a spiral or helical shape, making it look like a twisted ribbon.

- Function: It captures wind from all directions with its curved blades, similar to the Darrieus turbine, but its shape helps reduce mechanical stresses and vibrations.
- Advantages: It's quieter and can operate in turbulent wind conditions. The design makes it more structurally sound, which is ideal for urban or residential areas.
- **Noguchi Wind Turbine**
 - This is a more recent design inspired by the Darrieus turbine but with an additional variation. Developed by the Japanese engineer Noguchi, the turbine uses blades shaped like an S or a double-helix design.
 - Function: This design aims to improve efficiency and reduce mechanical complexity while capturing wind from any direction.
 - Advantages: It's more stable in gusty conditions and reduces vibration.
- **Maglev Wind Turbine**
 - Description: A maglev wind turbine uses magnetic levitation (maglev) technology to eliminate friction and reduce wear. Instead of traditional mechanical bearings, the turbine's components are suspended by magnets.
 - Function: The levitation reduces friction and mechanical losses, allowing the turbine to operate more efficiently, especially in low wind conditions.
 - Advantages: Less maintenance, quieter operation, and increased lifespan due to the lack of friction.

5. Horizontal Axis

- **Cochrane Wind Turbine**
 - The Cochrane wind turbine is a horizontal-axis wind turbine (HAWT) design that emphasizes ease of maintenance and robustness. It was created by British engineer Sir George Cochrane.
 - Function: Like other horizontal-axis turbines, it has blades that rotate around a horizontal axis, and it typically faces directly into the wind using a yaw mechanism.
 - Advantages: Known for efficiency at larger scales and ease of manufacturing, it's one of the most commonly used designs for modern wind farms.



6. Helicoidal Wind Turbine vs H-Rotor Wind Turbine

- Helicoidal Wind Turbine
 - A vertical-axis wind turbine with blades that twist in a spiral shape.
 - The twisted blades capture wind from any direction, turning the rotor.
 - Pros
 - Works well in windy areas with gusts or changing wind directions.
 - Quieter and more stable, with less vibration.
 - Cons
 - The blades are harder to make, so it can be more expensive.
 - Not as efficient as other designs, especially for large-scale power generation.

- H- Rotor Wind Turbine
 - A vertical-axis wind turbine with straight blades forming an "H" shape.
 - The blades rotate around a vertical axis and can capture wind from any direction.
 - Pros
 - Simple to build and maintain.
 - Good for areas with unpredictable or gusty winds.
 - Cons
 - Not as efficient at generating large amounts of power.
 - Can be harder to start spinning at low wind speeds.
- These turbines are both designed to work in areas with changing or turbulent winds, with the **Helicoidal** turbine being more stable and quieter, and the **H-Rotor** being simpler and more robust.

Turbines on Different Energy Sources

1. Wind Turbine

- How it Works: Wind spins the blades of the turbine, which are connected to a rotor. The rotor turns a shaft connected to a generator that produces electricity.
- Key Component: Gearbox (increases rotational speed for the generator) or Direct Drive (without a gearbox).
- Application: Onshore and offshore wind farms.

2. Hydropower (Water) Turbine

- How it Works: Flowing or falling water (from dams, rivers, or streams) passes through the turbine blades, causing them to spin. The rotating shaft drives a generator.
- Types:
 - Pelton Turbine: Uses water jets for high-head (tall drop) applications.
 - Francis Turbine: Used in medium-head applications with curved blades.
 - Kaplan Turbine: Adjustable blades used for low-head applications.
- Application: Hydropower plants.

3. Steam Turbine

- How it Works: High-pressure steam produced by heating water (often in coal, gas, nuclear, or solar thermal plants) is directed at turbine blades. The steam spins the blades, driving a generator.
- Application: Thermal and nuclear power plants.

4. Gas Turbine

- How it Works: Compressed air is mixed with fuel and ignited, creating high-temperature exhaust gases. These gases spin the turbine blades, turning a generator.
- Application: Power plants and jet engines.

5. Tidal and Wave Turbine

- How it Works:
 - Tidal Turbines: Installed underwater, where ocean currents drive the blades.
 - Wave Turbines: Capture the motion of surface waves to spin the turbine.
- Application: Coastal energy generation.

In summary, while all turbines follow the principle of converting motion into electricity, the energy source (wind, water, steam, or gas) determines the type of turbine used

VAWT and HAWT

HAWTs are the most commonly used wind turbines in large scale wind farms

False – VAWTs are generally less efficient than HAWTs.

True – VAWTs are typically smaller and more compact.

False – HAWTs are primarily lift-based; drag-based designs are rare and less efficient.

False – HAWTs are more common, especially in large-scale wind farms.

True – In VAWTs, the generator and drivetrain are closer to the ground, making maintenance easier.

VAWT (Vertical-Axis Wind Turbine) and **HAWT** (Horizontal-Axis Wind Turbine) are two main types of wind turbines, differing in design, efficiency, and applications.

1. Vertical-Axis Wind Turbine (VAWT)

- Axis Orientation: Rotor shaft is vertical, perpendicular to the ground.
- Design: Blades rotate around the central axis (e.g., Darrieus, Savonius models).
- Most commonly used turbine on large-scale wind farms
- Advantages:
 - Operates in any wind direction (no yaw mechanism needed).
 - Generator and drivetrain are near the ground, easing maintenance.
 - Compact design, suitable for urban areas and low-wind environments.
- Disadvantages
 - Lower efficiency due to drag and limited wind capture.
 - Structural stress and fatigue issues reduce lifespan.
 - Typically used in small-scale or residential setups.

2. Horizontal-Axis Wind Turbine (HAWT)

- Axis Orientation: Rotor shaft is horizontal, parallel to the ground.
- Design: Blades face the wind and rotate perpendicular to the tower (e.g., three-bladed design is most common).

- Advantages:
 - Higher efficiency and energy capture, especially in strong, steady winds.
 - Proven technology, widely used in large-scale wind farms.
 - Lift-based design reduces drag, improving performance.
- Disadvantages:
 - Requires yaw mechanism to face the wind.
 - Generator and drivetrain are elevated, making maintenance more complex.
 - Larger size and noise may limit urban use.

Key Differences:

Feature	VAWT	HAWT
Orientation	Vertical	Horizontal
Wind Direction Sensitivity	Omni-directional (no yaw needed)	Must face wind (yaw mechanism required)
Efficiency	Lower (due to drag and limited wind capture)	Higher (lift-based, efficient in steady winds)
Maintenance	Easier (generator near ground)	Harder (generator at tower top)
Size and Application	Smaller, ideal for urban and residential use	Larger, common in utility-scale wind farms
Popularity	Less common	More common globally

Summary

HAWTs dominate the wind energy industry due to their higher efficiency and scalability, making them ideal for large-scale electricity generation.

VAWTs are favored in niche applications where space is limited, aesthetics matter, or wind direction is variable.

Onshore vs Offshore

Offshore and onshore energy generators refer to where energy is produced, particularly in the context of wind energy and sometimes other renewable sources like solar or wave energy.

Most critical factor when selecting a site for a wind farm: Proximity to a power grid

1. Onshore Energy Generators

- Location
 - Built on land
 - often in open fields, hills, or rural areas
- Examples
 - Onshore wind turbines
 - solar farms
 - hydropower plants
- Advantages
 - Easier and cheaper to install and maintain
 - Faster construction time
 - Easier access for repairs and monitoring
- Disadvantages
 - Can produce noise and visual impact
 - Less consistent wind compared to offshore
 - Land use competition with agriculture or residential areas

2. Offshore Energy Generators

- Growth of offshore wind power
 - Higher and consistent wind speeds
 - Less land use and visual impact
- Location
 - Installed in bodies of water like oceans or seas
 - usually far from the coast.
- Examples


- Offshore wind farms
- wave energy converters
- tidal energy systems
- Advantages
 - Stronger and more consistent wind than onshore, resulting in more energy generation
 - No noise or visual disruption for people
 - Can cover large areas without competing for land use
- Disadvantages
 - Expensive to build and maintain due to harsh sea conditions
 - Difficult to access for repairs
 - Environmental impact on marine ecosystems

3. Comparison Summary

<u>Aspect</u>	<u>Onshore Generators</u>	<u>Offshore Generators</u>
Location	On land	In water (sea or ocean)
Cost	Lower installation and maintenance	Higher due to water-based setup
Energy Output	Moderate, depending on wind quality	Higher due to stronger winds
Environmental Impact	Land use impact, noise, and visuals	Impact on marine life, but no noise pollution

Maintenance	Easier and cheaper	Difficult and expensive
Reliability	Lower wind speeds, more variable	Consistent, strong winds

Both offshore and onshore generators play a significant role in renewable energy production. Onshore is more common, but offshore is growing rapidly, especially in areas with strong coastal winds.



Synchronous vs. Asynchronous Power Generators

Rectifiers convert the generator's AC output into DC, enabling use in applications that require direct current, such as battery charging or DC power systems.

1. Synchronous Generators

- Synchronous generators (also called alternators) are machines that produce alternating current (AC) electricity.
- They operate at a constant speed called synchronous speed, which is directly proportional to the frequency of the electrical system and the number of poles in the generator.
- Use electromagnets to create a magnetic field on the rotor, which spins inside the stator to induce alternating current (AC) in the stator windings.
- Working Principle
 - The rotor (magnetic field) of a synchronous generator rotates at the same speed as the rotating magnetic field of the stator.
 - It uses a direct current (DC) supply to create a magnetic field in the rotor.
 - The stator is where the electricity is generated as the magnetic field passes through its windings.
- Key Features
 - Operates at a fixed speed (synchronous speed).
 - Provides stable and constant frequency output.
 - Typically used in large power plants for grid generation.
- Applications
 - Power plants (hydropower, nuclear, thermal)
 - Industrial power stations
 - Grid synchronization
- Disadvantages
 - Expensive maintenance
 - Requires synchronization
 - Needs external excitation

Aspect	Advantages
Speed Stability	Operates at constant (synchronous) speed → maintains system frequency
Power Factor Control	Adjustable excitation allows for power factor correction (leading, lagging)
Voltage Regulation	Good voltage regulation even under varying load conditions
High Efficiency	More efficient at high power levels compared to induction generators
Grid Compatibility	Ideal for large-scale grid-connected applications

Aspect	Disadvantages
Complex Control	Requires external excitation system and voltage regulation
Synchronization Needed	Must be synchronized with grid before connection
Maintenance Needs	Brush and slip ring systems (unless brushless) need upkeep
Startup Requirements	Needs external motor or prime mover to reach synchronous speed before generating
Less Flexibility	Not suitable for variable-speed applications without additional systems

2. Asynchronous Generators

- Asynchronous generators (also known as induction generators) are often used in wind turbines or small hydroelectric plants.
- Unlike synchronous generators, they operate at a speed slightly above synchronous speed to generate electricity.
- Working Principle
 - The rotor rotates at a speed higher than the synchronous speed, inducing a current in the rotor through electromagnetic induction.
 - No external excitation system is needed; instead, it relies on the magnetic field from the stator.
- Key Features
 - Simpler and more robust compared to synchronous generators.
 - Lower maintenance and operational cost.
 - Frequency and voltage may fluctuate without external regulation.
- Applications
 - Wind turbines
 - Small hydroelectric generators
 - Backup power in industrial systems

Aspect	Advantages
Simple Design	Rugged and simple construction → fewer components to fail
Low Cost	Generally cheaper than synchronous generators
Self-Starting	Can start easily when driven above synchronous speed
Low Maintenance	No brushes or slip rings → less maintenance

Automatic Synchronization	Automatically synchronizes with the grid without complex controls
----------------------------------	---

Aspect	Disadvantages
Needs Reactive Power	Cannot generate reactive power → requires external source (grid or capacitors)
Poor Voltage Regulation	Voltage drops significantly under load
Fixed Power Factor	Always operates at lagging power factor → not ideal for grid stability
Limited Standalone Use	Not ideal for standalone/off-grid systems unless capacitors are added
Lower Efficiency	Slightly lower efficiency due to rotor losses

3. Key Differences Between Synchronous and Asynchronous Generators

<u>Aspect</u>	<u>Synchronous Generator</u>	<u>Asynchronous Generator</u>
----------------------	-------------------------------------	--------------------------------------

Speed	Runs at synchronous speed	Runs above synchronous speed
Excitation System	Requires external DC supply for excitation	No external excitation required
Grid Synchronization	Can be directly connected to the grid	Requires reactive power for magnetizing
Efficiency	Higher efficiency at steady load	Lower efficiency at variable loads
Maintenance	More complex, requires regular maintenance	Simple and low maintenance
Cost	Higher initial and maintenance cost	Lower initial cost
Application	Large power plants	Wind turbines, small-scale hydro plants

High Voltage Power Transmissions

High Voltage Power Transmission – Structured Notes

- Purpose
 - Transmits electricity over long distances from power plants to substations with minimal loss.
- Material
 - Typically made of Aluminum Conductor Steel Reinforced (ACSR)
 - aluminum for conductivity
 - steel for strength.
- Voltage Levels
 - Operates at tens to hundreds of kilovolts (kV) to reduce current and minimize energy loss.
- Power Losses
 - Mainly due to resistance in the wires (I^2R losses)
 - higher current = higher losses.
- Efficiency Factors
 - Affected by conductor resistance
 - Wire material
 - Length of wires
 - transmission distance
 - line voltage
 - ambient temperature
- Why High Voltage
 - Higher voltage = lower current for the same power → reduces losses and allows thinner, lighter cables.
- Support Structures
 - Carried by large transmission towers or pylons across vast areas.
- Insulation
 - Requires strong insulators to prevent arcing and withstand high voltages.

Corona Discharge

1. What is Corona Discharge?

- Corona discharge is an electrical phenomenon where ionization occurs in a fluid (like air) surrounding a conductor carrying a high voltage.
- It happens when the electric field strength exceeds the breakdown voltage of air (~3 kV/mm), but not enough to cause a full electrical breakdown (arc).
- Leads to the emission of a faint glow and sometimes a hissing sound.
- Commonly seen around high-voltage power lines, sharp conductors, or during thunderstorms (St. Elmo's fire).

2. Connection to Wind Power & Energy

- Wind Turbines & Power Transmission: High-voltage power lines from wind farms can experience corona discharge, leading to energy losses and electromagnetic interference.
- Impact on Efficiency: Unwanted corona discharge dissipates energy as heat, light, and sound, reducing overall efficiency in electrical transmission.
- Ionization Effects on Wind Turbines: Some research suggests that corona discharge could be used to manipulate airflow, possibly enhancing wind turbine performance by reducing drag.

3. Connection to Energy Conservation

- Minimizing Power Loss: Utilities try to reduce corona discharge in transmission lines by using smooth conductors, corona rings, or insulating materials to conserve energy.
- High-Voltage DC (HVDC) Transmission: HVDC systems experience less corona loss compared to AC systems, improving energy efficiency.

4. Connection to Radiation

- Electromagnetic Radiation: Corona discharge emits radio frequency (RF) noise, which can interfere with communication systems.

- **X-Ray Production:** In extreme cases, corona discharge can generate soft X-rays, especially in vacuum or low-pressure environments.
- **Ozone Formation:** Corona discharge ionizes air, leading to ozone (O₃) production, which has both environmental and industrial applications but can also be harmful in high concentrations.

Permanent Magnet Generator

- a type of electrical generator
- uses permanent magnets to produce electricity rather than relying on external excitation (like in traditional generators)
- commonly used in applications like wind turbines, hydropower plants, and portable generators

1. How they work

- Rotor with Magnets: The rotor contains permanent magnets that create a magnetic field.
- Stator with Coils: The stator consists of coils of wire. As the rotor spins, the magnetic field passes over these coils.
- Electricity Generation: The movement of the magnetic field induces an electric current in the coils using Faraday's Law of Electromagnetic Induction.

In short, when the rotor (magnets) turns, it produces electricity in the stator coils.

2. Advantages of Permanent Magnet Generators

- No External Power Required: Unlike traditional generators, PMGs don't need an external electrical source for magnetism since they use permanent magnets.
- High Efficiency: They have lower energy losses and operate more efficiently.
- Compact and Lightweight: PMGs are often smaller and lighter compared to other generators of the same capacity.
- Reliable and Low Maintenance: Fewer parts and no need for brushes or slip rings reduce maintenance.

3. Disadvantages of Permanent Magnet Generators

- Magnet Cost: High-quality permanent magnets (e.g., neodymium magnets) are expensive.
- Demagnetization Risk: Magnets can lose strength over time, especially if exposed to high temperatures or physical damage.

- Limited Control: Unlike traditional generators, PMGs have limited control over voltage output without additional electronic components.

4, Applications of Permanent Magnet Generators

- Wind Turbines: PMGs are commonly used in both onshore and offshore wind turbines because they are efficient at varying wind speeds.
- Hydropower Plants: They are also used in small hydroelectric projects.
- Electric Vehicles (EVs): PMGs provide efficient power generation for regenerative braking systems.
- Portable Generators: Many small, portable generators use PMGs for reliable power output.

In summary, Permanent Magnet Generators are efficient, reliable, and well-suited for renewable energy applications, making them a key player in modern sustainable power generation.

Miscellaneous

Rectifier generators are a type of generator that produces **DC power** by converting AC to DC using **rectifiers** (typically diodes or thyristors). These are often used in applications where **DC output is required**, such as electroplating, battery charging, welding, or DC motor drives.

Copper was the preferred material for overhead conductors in earlier days, but aluminum has replaced copper because of the much lower cost and lighter weight of the aluminum conductor compared with a copper conductor of the same resistance.

Converter stations needed to connect to AC power grids are very expensive. Converter substations are more complex than HVAC substations, not only in additional converting equipment, but also in more complicated control and regulating systems.

1. AC (Alternating Current):

- In most wind power systems, the electricity generated by the turbine's generator is in **AC** form.
- **AC** power alternates direction periodically and is the most common form of electricity used in homes and businesses.
- Wind turbines often generate low-voltage AC, which is then converted to the grid's standard AC voltage through power electronics and inverters.

2. DC (Direct Current):

- **DC** power flows in one direction and is typically used in some specialized types of wind energy systems, such as small-scale or off-grid applications.
- In certain turbines, the generator produces **DC** power, which must then be converted to AC for grid compatibility.

- DC is more common in battery storage systems, where energy is stored for later use.
- Inverters convert DC to AC
- 3. **HVDC (High Voltage Direct Current):**
 - **HVDC** is used for long-distance transmission of electricity. When wind farms are located far from the areas where the power is needed, **HVDC** technology is often employed.
 - **HVDC** allows for efficient transmission of electricity over long distances with less energy loss compared to AC transmission.
 - Wind farms, especially offshore farms, might convert their generated power to **HVDC** for transmission to the mainland grid, where it can be converted back to AC.

In short:

- **AC** is the most common form of power generated by wind turbines.
- **DC** might be used in small-scale or storage applications.
- **HVDC** is used for long-distance, efficient transmission of electricity, especially in large offshore wind farms.

U.S. Electricity Grids

Major Grid Regions:

1. **Eastern Interconnection (EI)**
 - Covers most of the eastern U.S.
 - Largest grid in the U.S.
 - Connects 39 states, 2 Canadian provinces.
2. **Western Interconnection (WI)**
 - Covers the western U.S., parts of Canada, and Mexico.
 - Includes major areas like California, Texas, and the Pacific Northwest.
3. **Texas Interconnection (ERCOT)**
 - Independent grid, mostly within Texas.
 - Separate from EI and WI for reliability and regulatory reasons.
4. **Alaska and Hawaii**

- Separate, smaller grids.
- Not connected to the continental U.S. grid.

Windmills appeared in Europe around the **12th century**. They were first used in areas like the Netherlands and England for tasks such as grinding grain and draining water from low-lying land.