

Timeshift on Ubuntu 24.04 @ subvolume not present

 askubuntu.com/questions/1513250/timeshift-on-ubuntu-24-04-subvolume-not-present

mchid

May 8, 2024

2

I just did a fresh install of **Ubuntu 24.04** LTS on **BTRFS**. Installed Timeshift and it did not work because the 24.04 system was installed on / without creating BTRFS subvolumes @ and @home. (Ubuntu 22.04 installs the system inside @, not /.)

How can we make Timeshift work with the Ubuntu 24.04 install?

asked May 8, 2024 at 2:22

[Majal](#)

8,25944 gold badges3535 silver badges5151 bronze badges

1 Answer

Sorted by:

3

Thanks to the [comments](#), for it gave me the general idea on how to proceed, as well as [this Ubuntu article](#) on reinstalling GRUB 2. The steps below worked on my system, a clean install of Ubuntu 24.04. Edit based on your custom setup. If you have files you can't lose, **backup first**.

1. Prepare **another system** to boot from (e.g. a Live USB). Or attach your system storage to another computer.
2. Once your system storage is attached, get its **device paths**, both the system **disk** and **partition**.

Example HDD paths: disk: /dev/sdb, partition: /dev/sdb2

Example NVME paths: disk: /dev/nvme0n1, partition: /dev/nvme0n1p3

These paths may be known by running `lsblk` or `fdisk -l` if using the CLI, or by launching GNOME Disks if you prefer a GUI.

3. On the Terminal, run these commands (lines after # are comments):

```
sudo su
```

```
mount /dev/${partition} /mnt
cd /mnt
```

If you haven't yet, edit fstab, i.e. `nano /mnt/etc/fstab`. The updated fstab must point

```

# from @ or @home subvolumes, so change the options from "defaults" to include
"subvol="
# Example root: UUID=ABC... /      btrfs subvol=@      0 0
# Example home: UUID=ABC... /home btrfs subvol=@home 0 0

btrfs subvolume create @
btrfs subvolume create @home

mv home/* @home
mv !(@|@home) @

sync

# Mount /boot and /boot/efi if those came from other partitions.
# In 24.04 by default, /boot/efi is in another partition, while /boot is not.
# To confirm, check fstab, or run `ls @/boot/` and it will list several files

# If /boot is from another partition, run: mount /dev/${boot_partition} @/boot

mount /dev/${boot-efi_partition} @/boot/efi

# https://help.ubuntu.com/community/Grub2/Installing#via\_the\_LiveCD\_terminal
# Note: Insert path for system disk, not system partition. See step 2.

grub-install --boot-directory=/mnt/@/boot --efi-directory=/mnt/@/boot/efi
/dev/${disk}

# Before exiting, double-check that all in @/etc/fstab are in place

```

4. Exit Live USB and boot in your system.

answered May 9, 2024 at 14:41