

Install Docker Engine on Ubuntu

 docs.docker.com/engine/install/ubuntu

Docker Inc

August 10, 2026



To get started with Docker Engine on Ubuntu, make sure you [meet the prerequisites](#), and then follow the [installation steps](#).

[Prerequisites](#)

[Firewall limitations](#)



Warning

Before you install Docker, make sure you consider the following security implications and firewall incompatibilities.

- If you use `ufw` or `firewalld` to manage firewall settings, be aware that when you expose container ports using Docker, these ports bypass your firewall rules. For more information, refer to [Docker and ufw](#).
- Docker is only compatible with `iptables-nft` and `iptables-legacy`. Firewall rules created with `nft` are not supported on a system with Docker installed. Make sure that any firewall rulesets you use are created with `iptables` or `ip6tables`, and that you add them to the `DOCKER-USER` chain, see [Packet filtering and firewalls](#).

[OS requirements](#)

To install Docker Engine, you need the 64-bit version of one of these Ubuntu versions:

- Ubuntu Resolute 26.04 (LTS)
- Ubuntu Noble 24.04 (LTS)
- Ubuntu Jammy 22.04 (LTS)

Docker Engine for Ubuntu is compatible with x86_64 (or amd64), armhf, arm64, s390x, and ppc64le (ppc64el) architectures.



Note

Installation on Ubuntu derivative distributions, such as Linux Mint, is not officially supported (though it may work).

Uninstall old versions

Before you can install Docker Engine, you need to uninstall any conflicting packages.

Your Linux distribution may provide unofficial Docker packages, which may conflict with the official packages provided by Docker. You must uninstall these packages before you install the official version of Docker Engine.

The unofficial packages to uninstall are:

- `docker.io`
- `docker-compose`
- `docker-compose-v2`
- `docker-doc`
- `docker-buildx`
- `podman-docker`

Moreover, Docker Engine depends on `containerd` and `runc`. Docker Engine bundles these dependencies as one bundle: `containerd.io`. If you have installed the `containerd` or `runc` previously, uninstall them to avoid conflicts with the versions bundled with Docker Engine.

Run the following command to uninstall all conflicting packages:

`apt` might report that you have none of these packages installed.

Images, containers, volumes, and networks stored in `/var/lib/docker/` aren't automatically removed when you uninstall Docker. If you want to start with a clean installation, and prefer to clean up any existing data, read the [uninstall Docker Engine](#) section.

Installation methods

You can install Docker Engine in different ways, depending on your needs:

- Docker Engine comes bundled with [Docker Desktop for Linux](#). This is the easiest and quickest way to get started.
- Set up and install Docker Engine from [Docker's apt repository](#).
- [Install it manually](#) and manage upgrades manually.
- Use a [convenience script](#). Only recommended for testing and development environments.

Apache License, Version 2.0. See [LICENSE](#) for the full license.

[Install using the apt repository](#)

Before you install Docker Engine for the first time on a new host machine, you need to set up the Docker apt repository. Afterward, you can install and update Docker from the repository.

1. Set up Docker's apt repository.
2. Install the Docker packages.

To install the latest version, run:

Note

After installation, verify that Docker is running:

```
$ sudo systemctl status docker
```

If Docker is not running, start it manually:

```
$ sudo systemctl start docker
```

3. Verify that the installation is successful by running the hello-world image:

This command downloads a test image and runs it in a container. When the container runs, it prints a confirmation message and exits.

You have now successfully installed and started Docker Engine.

Tip

Receiving errors when trying to run without root?

The docker user group exists but contains no users, which is why you're required to use sudo to run Docker commands. Continue to [Linux postinstall](#) to allow non-privileged users to run Docker commands and for other optional configuration steps.

Upgrade Docker Engine

To upgrade Docker Engine, follow step 2 of the [installation instructions](#), choosing the new version you want to install.

Install from a package

If you can't use Docker's apt repository to install Docker Engine, you can download the deb file for your release and install it manually. You need to download a new file each time you want to upgrade Docker Engine.

1. Go to <https://download.docker.com/linux/ubuntu/dists/>.
2. Select your Ubuntu version in the list.
3. Go to pool/stable/ and select the applicable architecture (amd64, armhf, arm64, or s390x).
4. Download the following deb files for the Docker Engine, CLI, containerd, and Docker Compose packages:
 - containerd.io_<version>_<arch>.deb
 - docker-ce_<version>_<arch>.deb
 - docker-ce-cli_<version>_<arch>.deb
 - docker-buildx-plugin_<version>_<arch>.deb
 - docker-compose-plugin_<version>_<arch>.deb
5. Install the .deb packages. Update the paths in the following example to where you downloaded the Docker packages.

Note

After installation, verify that Docker is running:

```
$ sudo systemctl status docker
```

If Docker is not running, start it manually:

```
$ sudo systemctl start docker
```

6. Verify that the installation is successful by running the hello-world image:

This command downloads a test image and runs it in a container. When the container runs, it prints a confirmation message and exits.

You have now successfully installed and started Docker Engine.

Tip

Receiving errors when trying to run without root?

The docker user group exists but contains no users, which is why you're required to use sudo to run Docker commands. Continue to [Linux postinstall](#) to allow non-privileged users to run Docker commands and for other optional configuration steps.

[Upgrade Docker Engine](#)

To upgrade Docker Engine, download the newer package files and repeat the [installation procedure](#), pointing to the new files.

[Install using the convenience script](#)

Docker provides a convenience script at <https://get.docker.com/> to install Docker into development environments non-interactively. The convenience script isn't recommended for production environments, but it's useful for creating a provisioning script tailored to your needs. Also refer to the [install using the repository](#) steps to learn about installation steps to install using the package repository. The source code for the script is open source, and you can find it in the [docker-install repository on GitHub](#).

Always examine scripts downloaded from the internet before running them locally. Before installing, make yourself familiar with potential risks and limitations of the convenience script:

- The script requires root or sudo privileges to run.
- The script attempts to detect your Linux distribution and version and configure your package management system for you.
- The script doesn't allow you to customize most installation parameters.
- The script installs dependencies and recommendations without asking for confirmation. This may install a large number of packages, depending on the current configuration of your host machine.
- By default, the script installs the latest stable release of Docker, containerd, and runc. When using this script to provision a machine, this may result in unexpected major version upgrades of Docker. Always test upgrades in a test environment before deploying to your production systems.
- The script isn't designed to upgrade an existing Docker installation. When using the script to update an existing installation, dependencies may not be updated to the expected version, resulting in outdated versions.



Tip

Preview script steps before running. You can run the script with the `--dry-run` option to learn what steps the script will run when invoked:

```
$ curl -fsSL https://get.docker.com -o get-docker.sh
$ sudo sh ./get-docker.sh --dry-run
```

This example downloads the script from <https://get.docker.com/> and runs it to install the latest stable release of Docker on Linux:

You have now successfully installed and started Docker Engine. The docker service starts automatically on Debian based distributions. On RPM based distributions, such as CentOS, Fedora or RHEL, you need to start it manually using the appropriate `systemctl` or `service` command. As the message indicates, non-root users can't run Docker commands by default.

Use Docker as a non-privileged user, or install in rootless mode?

The installation script requires root or sudo privileges to install and use Docker. If you want to grant non-root users access to Docker, refer to the [post-installation steps for Linux](#). You can also install Docker without root privileges, or configured to run in rootless mode. For instructions on running Docker in rootless mode, refer to [run the Docker daemon as a non-root user \(rootless mode\)](#).

Install pre-releases

Docker also provides a convenience script at <https://test.docker.com/> to install pre-releases of Docker on Linux. This script is equal to the script at `get.docker.com`, but configures your package manager to use the test channel of the Docker package repository. The test channel includes both stable and pre-releases (beta versions, release-candidates) of Docker. Use this script to get early access to new releases, and to evaluate them in a testing environment before they're released as stable.

To install the latest version of Docker on Linux from the test channel, run:

Upgrade Docker after using the convenience script

If you installed Docker using the convenience script, you should upgrade Docker using your package manager directly. There's no advantage to re-running the convenience script. Re-running it can cause issues if it attempts to re-install repositories which already exist on the host machine.

Uninstall Docker Engine

1. Uninstall the Docker Engine, CLI, containerd, and Docker Compose packages:
2. Images, containers, volumes, or custom configuration files on your host aren't automatically removed. To delete all images, containers, and volumes:
3. Remove source list and keyrings

You have to delete any edited configuration files manually.

Next steps

Continue to [Post-installation steps for Linux](#).