

CodeForge - B01 - Interface Cơ Bản

Độ khó: ★ Easy

Đề bài

Tạo interface đầu tiên:

- **Interface** `Drawable` với:
 - Abstract method `void draw();` (implicit public abstract)
- Class `Circle` **implements** `Drawable` với:
 - `double radius`
 - Constructor nhận radius
 - **Implement** `draw()` in "Drawing circle with radius [r]"

Trong `main()`:

1. **KHÔNG THỂ** tạo `new Drawable()` (interface)
2. Tạo `Circle` object
3. Gọi `draw()`
4. Polymorphic reference: `Drawable d = new Circle(5);`

◇ Input

- Một số thực radius

◇ Output

- "Drawing circle with radius [r]"

◇ Constraints

- $0 < radius \leq 100$

Ví dụ

Test case 1

Input:

5.0

Output:

Drawing circle with radius 5.00

Test case 2

Input:

```
3.5
```

Output:

```
Drawing circle with radius 3.50
```

Tags: `interface`, `basic`, `implements`, `cannot-instantiate`

CodeForge - B02 - Implements Keyword

Độ khó: ★ Easy

Đề bài

Class implements interface:

- Interface **Flyable** với:
 - `void fly();`
- Classes **Bird**, **Airplane**, **Superman** implements **Flyable** với:
 - Different implementations của `fly()`

Lưu ý: Interface method mặc định là `public abstract`

◇ Input

- Một dòng: Type ("B", "A", hoặc "S")

◇ Output

- Flying message tương ứng

◇ Constraints

- Input chỉ là B, A, hoặc S

Ví dụ

Test case 1

Input:

B

Output:

Bird is flying with wings

Test case 2

Input:

A

Output:

```
Airplane is flying with engines
```

Test case 3**Input:**

```
S
```

Output:

```
Superman is flying with superpowers
```

Tags: `interface`, `implements`, `polymorphism`

CodeForge - B03 - Multiple Methods Trong Interface

Độ khó: ★ Easy

Đề bài

Interface với nhiều methods:

- Interface **Movable** với:
 - `void moveUp();`
 - `void moveDown();`
 - `void moveLeft();`
 - `void moveRight();`
- Class **Player** implements Movable với:
 - `int x, y` (position)
 - Implement tất cả 4 methods

◇ Input

- Dòng 1: Initial x, y
- Dòng 2: N (số moves)
- N dòng: Direction (U/D/L/R)

◇ Output

- Final position

◇ Constraints

- $1 \leq N \leq 100$
- $-1000 \leq x, y \leq 1000$

Ví dụ

Test case 1

Input:

```
0 0
4
U
R
D
L
```

Output:

```
0 0
```

Test case 2

Input:

```
5 5
3
U
U
R
```

Output:

```
6 7
```

Tags: `interface`, `multiple-methods`, `implementation`

CodeForge - B04 - Interface Methods Implicit Public Abstract

Độ khó: ★ Easy

Đề bài

Interface methods mặc định public abstract:

- Interface `Printable` với:
 - `void print();` (không cần public abstract - implicit)
- Class `Document` implements `Printable` với:
 - **PHẢI** implement với `public void print()` (cannot reduce visibility)

Demo compile error nếu dùng private/protected.

◇ Input

- Một dòng: Document content

◇ Output

- "Printing: [content]"

◇ Constraints

- Độ dài ≤ 200

Ví dụ

Test case 1

Input:

```
Hello World
```

Output:

```
Printing: Hello World
```

Tags: `interface`, `public-abstract`, `implicit`, `visibility`

CodeForge - B05 - Polymorphism Với Interface

Độ khó: ★ ★ Medium

Đề bài

Interface làm polymorphic reference:

- Interface `Shape` với:
 - `double getArea();`
 - `double getPerimeter();`
- Classes `Circle`, `Rectangle`, `Triangle` implements `Shape`

Trong `main()`:

- Tạo `Shape[] shapes` với mixed types
- Calculate total area polymorphically

◇ Input

- Dòng 1: `N`
- `N` dòng: Shape data

◇ Output

- Total area (2 chữ số)

◇ Constraints

- $1 \leq N \leq 20$

Ví dụ

Test case 1

Input:

```
3
C 5.0
R 4.0 6.0
T 3.0 4.0 5.0
```

Output:

```
109.54
```

Tags: interface, polymorphism, array, shapes

CodeForge - B06 - Interface Không Có Fields (Chỉ Constants)

Độ khó: ★ Easy

Đề bài

Interface chỉ có constants (public static final):

- Interface `MathConstants` với:
 - `double PI = 3.14159;` (implicit public static final)
 - `int MAX_VALUE = 1000;`
- Class `Calculator` implements `MathConstants`

Lưu ý: Không thể thay đổi giá trị constants

◇ Input

- Một số thực radius

◇ Output

- Area using PI constant

◇ Constraints

- $0 < \text{radius} \leq 100$

Ví dụ

Test case 1

Input:

5.0

Output:

78.54

Tags: `interface`, `constants`, `public-static-final`, `implicit`

CodeForge - B07 - Multiple Interface Implementation

Độ khó: ★ ★ Medium

Đề bài

Class có thể implements nhiều interfaces:

- Interface `Swimmable` với `void swim();`
- Interface `Flyable` với `void fly();`
- Interface `Runnable` với `void run();`
- Class `Duck` implements `Swimmable`, `Flyable` với:
 - Implement cả 2 methods
- Class `Penguin` implements `Swimmable`, `Runnable` với:
 - Implement cả 2 methods

Multiple inheritance via interfaces!

◇ Input

- Một dòng: Animal type ("D" hoặc "P")

◇ Output

- Abilities của animal

◇ Constraints

- N/A

Ví dụ

Test case 1

Input:

```
D
```

Output:

```
Duck swimming
Duck flying
```

Test case 2

Input:

```
P
```

Output:

```
Penguin swimming  
Penguin running
```

Tags: `interface`, `multiple-implementation`, `multiple-inheritance`

CodeForge - B08 - Interface Extending Interface

Độ khó: ★ ★ Medium

Đề bài

Interface có thể extend interface khác:

- Interface `Vehicle` với `void start();`
- Interface `ElectricVehicle` extends `Vehicle` với:
 - Inherit `start()`
 - Add `void charge();`
- Class `Tesla` implements `ElectricVehicle` với:
 - **PHẢI** implement cả 2 methods (`start` + `charge`)

◇ Input

- Không có input

◇ Output

- 2 dòng: `start`, `charge`

◇ Constraints

- N/A

Ví dụ

Test case 1

Output:

```
Tesla starting
Tesla charging
```

Tags: `interface`, `extending`, `inheritance`, `chain`

CodeForge - B09 - Interface Extending Multiple Interfaces

Độ khó: ★ ★ Medium

Đề bài

Interface có thể extend NHIỀU interfaces:

- Interface `Readable` với `void read();`
- Interface `Writable` với `void write();`
- Interface `ReadWrite` extends `Readable`, `Writable` với:
 - Inherit cả 2 methods
 - Add `void close();`
- Class `File` implements `ReadWrite` với:
 - Implement tất cả 3 methods

◇ Input

- Không có input

◇ Output

- 3 dòng: read, write, close

◇ Constraints

- N/A

Ví dụ

Test case 1

Output:

```
Reading file
Writing file
Closing file
```

Tags: `interface`, `multiple-extending`, `diamond`, `inheritance`

CodeForge - B10 - Constants Trong Interface

Độ khó: ★ ★ Medium

Đề bài

Interface constants (public static final implicit):

- Interface `GameConstants` với:
 - `int MAX_PLAYERS = 4;`
 - `int BOARD_SIZE = 10;`
 - `String GAME_NAME = "MyGame";`
- Class `Game` implements `GameConstants`
- Access constants qua interface name: `GameConstants.MAX_PLAYERS`

◇ Input

- Không có input

◇ Output

- All constants

◇ Constraints

- N/A

Ví dụ

Test case 1

Output:

```
Max Players: 4
Board Size: 10
Game Name: MyGame
```

Tags: `interface`, `constants`, `static-final`, `access`

CodeForge - B11 - Marker Interface

Độ khó: ★ ★ Medium

Đề bài

Marker interface (empty interface):

- Interface `Serializable` (empty - no methods)
- Classes implement để "mark" special capability
- Class `User` implements `Serializable`
- Class `Product` implements `Serializable`

Check `instanceof Serializable` để verify capability.

◇ Input

- Dòng 1: N objects
- N dòng: Type ("U" hoặc "P")

◇ Output

- Count serializable objects

◇ Constraints

- $1 \leq N \leq 100$

Ví dụ

Test case 1

Input:

```
4
U
P
U
P
```

Output:

```
4
```


Tags: interface, marker, empty, capability

CodeForge - B12 - Interface Constants Best Practices

Độ khó: ★ ★ Medium

Đề bài

Use interface cho constants (anti-pattern warning):

- Interface `Colors` với:
 - `String RED = "#FF0000";`
 - `String GREEN = "#00FF00";`
 - `String BLUE = "#0000FF";`

Lưu ý: Đây là anti-pattern! Better: enum (Module sau)

Nhưng vẫn widely used trong legacy code.

◇ Input

- Một dòng: Color name (RED/GREEN/BLUE)

◇ Output

- Hex code

◇ Constraints

- N/A

Ví dụ

Test case 1

Input:

RED

Output:

#FF0000

Tags: `interface`, `constants`, `anti-pattern`, `legacy`

CodeForge - B13 - Default Methods (Java 8)

Độ khó: ★ ★ Medium

Đề bài

Interface có thể có default methods (Java 8+):

- Interface **Logger** với:
 - Abstract `void log(String message);`
 - **Default** `default void logError(String message)` có body:
 - `log("[ERROR] " + message)`
- Class **ConsoleLogger** implements **Logger** với:
 - Implement `log()` only
 - Inherit `logError()` (no need to implement)

◇ Input

- Dòng 1: Normal message
- Dòng 2: Error message

◇ Output

- 2 log messages

◇ Constraints

- Độ dài ≤ 200

Ví dụ

Test case 1

Input:

```
Application started
Connection failed
```

Output:

```
Application started
[ERROR] Connection failed
```

Tags: `interface`, `default-method`, `java8`, `backward-compatible`

CodeForge - B14 - Overriding Default Methods

Độ khó: ★ ★ Medium

Đề bài

Class có thể override default methods:

- Interface **Formatter** với:
 - **Default** `default String format(String s)` return `s.toUpperCase()`
- Class **CustomFormatter** implements **Formatter** với:
 - **Override** `format()` return `s.toLowerCase()`
- Class **BasicFormatter** implements **Formatter** với:
 - Use inherited default (no override)

◇ Input

- Dòng 1: Formatter type ("C" hoặc "B")
- Dòng 2: String

◇ Output

- Formatted string

◇ Constraints

- Độ dài ≤ 100

Ví dụ

Test case 1

Input:

```
C
Hello World
```

Output:

```
hello world
```

Test case 2

Input:

```
B  
Hello World
```

Output:

```
HELLO WORLD
```

Tags: `interface`, `default`, `override`, `optional`

CodeForge - B15 - Static Methods Trong Interface (Java 8)

Độ khó: ★ ★ Medium

Đề bài

Interface có thể có static methods (Java 8+):

- Interface `MathUtils` với:
 - Static** `static int add(int a, int b)` return `a + b`
 - Static** `static int multiply(int a, int b)` return `a * b`
- Call qua interface name: `MathUtils.add(5, 3)`
- KHÔNG** inherit vào implementing class

◇ Input

- Dòng 1: `a, b`

◇ Output

- Dòng 1: Sum
- Dòng 2: Product

◇ Constraints

- $-1000 \leq a, b \leq 1000$

Ví dụ

Test case 1

Input:

```
5 3
```

Output:

```
8
15
```

Tags: `interface`, `static-method`, `java8`, `utility`

CodeForge - B16 - Private Methods Trong Interface (Java 9)

Độ khó: ★ ★ ★ Hard

Đề bài

Interface có thể có private methods (Java 9+):

- Interface `Validator` với:
 - **Private** `private boolean isEmpty(String s)` return `s != null && !s.isEmpty()`
 - **Default** `default boolean validateName(String name)` use `isEmpty()`
 - **Default** `default boolean validateEmail(String email)` use `isEmpty()` + check @

Private methods = helper methods cho default methods.

◇ Input

- Dòng 1: Name
- Dòng 2: Email

◇ Output

- Validation results

◇ Constraints

- Độ dài ≤ 100

Ví dụ

Test case 1

Input:

```
Alice
alice@example.com
```

Output:

```
Name valid: true
Email valid: true
```

Test case 2

Input:

```
invalid-email
```

Output:

```
Name valid: false  
Email valid: false
```

Tags: `interface`, `private-method`, `java9`, `helper`

CodeForge - B17 - Abstract Class Vs Interface - Comparison

Độ khó: ★ ★ ★ Hard

Đề bài

So sánh Abstract Class vs Interface:

Abstract Class:

- Can have constructor ✓
- Can have instance fields ✓
- Can have concrete methods ✓
- Single inheritance only X

Interface:

- Cannot have constructor X
- Only constants (public static final) ✓
- Can have default/static methods (Java 8+) ✓
- Multiple implementation ✓

Tạo 2 examples minh họa differences.

◇ Input

- Type ("ABSTRACT" hoặc "INTERFACE")

◇ Output

- Demo characteristics

◇ Constraints

- N/A

Ví dụ

Test case 1

Input:

ABSTRACT

Output:

```
Abstract: Has constructor  
Abstract: Has fields  
Abstract: Single parent only
```

Test case 2

Input:

```
INTERFACE
```

Output:

```
Interface: No constructor  
Interface: Constants only  
Interface: Multiple implementation
```

Tags: [interface](#), [abstract](#), [comparison](#), [differences](#)

CodeForge - B18 - When To Use Interface

Độ khó: ★ ★ ★ Hard

Đề bài

Khi nào dùng Interface:

- ☒ Định nghĩa contract (behavior)
- ☒ Multiple inheritance cần thiết
- ☒ Không có shared implementation
- ☒ Unrelated classes với common behavior

Example:

- Interface `Comparable` cho sorting
- Interface `Cloneable` cho copying
- Different classes implement same behavior

◇ Input

- Dòng 1: N objects
- N dòng: Type và data

◇ Output

- Sorted objects (using Comparable interface)

◇ Constraints

- $1 \leq N \leq 50$

Ví dụ

Test case 1

Input:

```
3
STUDENT Alice 85
STUDENT Bob 92
STUDENT Charlie 78
```

Output:

```
Charlie 78  
Alice 85  
Bob 92
```

Tags: `interface`, `when-to-use`, `design`, `decision`

CodeForge - B19 - When To Use Abstract Class

Độ khó: ★ ★ ★ Hard

Đề bài

Khi nào dùng Abstract Class:

- ☒ Có shared code (concrete methods)
- ☒ Có common fields
- ☒ Related classes (IS-A relationship)
- ☒ Template Method pattern

Example:

- Abstract class `Animal` với `eat()`, `sleep()` concrete
- Abstract method `makeSound()` varies

So sánh với Interface (no shared code).

◇ Input

- Design problem description

◇ Output

- Recommendation: Abstract class or Interface

◇ Constraints

- N/A

Ví dụ

Test case 1

Input:

```
Need shared fields and methods
Related classes
```

Output:

```
Use Abstract Class
```

Test case 2

Input:

Unrelated classes
Just define contract

Output:

Use Interface

Tags: `abstract`, `when-to-use`, `design`, `comparison`

CodeForge - B20A - Plugin System Với Interfaces

Độ khó: ★ ★ ★ Hard (Advanced)

Đề bài

Tạo plugin architecture:

- Interface `Plugin` với:
 - `String getName();`
 - `String getVersion();`
 - `void initialize();`
 - `void execute();`
 - `void shutdown();`
- Classes `SecurityPlugin`, `LoggingPlugin`, `CachePlugin` implements `Plugin`
- Class `PluginManager` với:
 - `ArrayList<Plugin> plugins`
 - `void loadPlugin(Plugin p)`
 - `void initializeAll()`
 - `void executeAll()`
 - `void shutdownAll()`

Trong `main()`:

1. Create plugin manager
2. Load N plugins
3. Initialize all
4. Execute all
5. Shutdown all

◇ Input

- Dòng 1: N (plugins)
- N dòng: Plugin type

◇ Output

- Lifecycle log cho tất cả plugins

◇ Constraints

- $1 \leq N \leq 10$

Ví dụ

Test case 1

Input:

```
3
SECURITY
LOGGING
CACHE
```

Output:

```
Loading: SecurityPlugin v1.0
Loading: LoggingPlugin v1.0
Loading: CachePlugin v1.0

Initializing all plugins...
SecurityPlugin initialized
LoggingPlugin initialized
CachePlugin initialized

Executing all plugins...
SecurityPlugin running
LoggingPlugin running
CachePlugin running

Shutting down all plugins...
SecurityPlugin stopped
LoggingPlugin stopped
CachePlugin stopped
```

Tags: [interface](#), [plugin](#), [architecture](#), [lifecycle](#), [advanced](#)

CodeForge - B21A - Event Listener System

Độ khó: ★ ★ ★ Hard (Advanced)

Đề bài

Tạo event system với interfaces:

- Interface `EventListener` với:
 - `void onEvent(String eventType, String data);`
- Interface `EventSource` với:
 - `void addEventListener(EventListener listener);`
 - `void removeEventListener(EventListener listener);`
 - `void fireEvent(String eventType, String data);`
- Class `Button` implements `EventSource`
- Classes `ClickLogger`, `ClickCounter`, `ClickNotifier` implements `EventListener`

Observer pattern với interfaces!

◇ Input

- Dòng 1: N (listeners)
- N dòng: Listener types
- Dòng N+2: M (clicks)
- M dòng: Click data

◇ Output

- Event notifications tới tất cả listeners

◇ Constraints

- $1 \leq N \leq 10$
- $1 \leq M \leq 50$

Ví dụ

Test case 1

Input:

```
3
LOGGER
COUNTER
NOTIFIER
3
x=10 y=20
```

```
x=30 y=40  
x=50 y=60
```

Output:

```
Logger: Click at x=10 y=20  
Counter: Total clicks = 1  
Notifier: Alert! Button clicked  
  
Logger: Click at x=30 y=40  
Counter: Total clicks = 2  
Notifier: Alert! Button clicked  
  
Logger: Click at x=50 y=60  
Counter: Total clicks = 3  
Notifier: Alert! Button clicked
```

Tags: [interface](#), [event](#), [listener](#), [observer](#), [pattern](#), [advanced](#)

CodeForge - B22A - Strategy Pattern Với Interfaces

Độ khó: ★ ★ ★ Hard (Advanced)

Đề bài

Tạo strategy pattern:

- Interface `PaymentStrategy` với:
 - `boolean pay(double amount);`
 - `String getPaymentType();`
- Classes `CreditCardStrategy`, `PayPalStrategy`, `CryptoStrategy` implements `PaymentStrategy`
- Class `ShoppingCart` với:
 - `ArrayList<Item> items`
 - `PaymentStrategy paymentStrategy`
 - `void setPaymentStrategy(PaymentStrategy strategy)`
 - `void checkout()`

Trong main():

1. Add items to cart
2. Try different payment strategies
3. Process checkout

◇ Input

- Dòng 1: N (items)
- N dòng: Item name, price
- Dòng N+2: Payment type

◇ Output

- Cart summary
- Payment processing

◇ Constraints

- $1 \leq N \leq 20$

Ví dụ

Test case 1

Input:

```
3
Laptop 1000.00
```

```
Mouse 25.00  
Keyboard 75.00  
CREDITCARD
```

Output:

```
Shopping Cart:  
- Laptop: $1000.00  
- Mouse: $25.00  
- Keyboard: $75.00  
Total: $1100.00  
  
Processing with Credit Card...  
Payment successful!
```

Tags: `interface`, `strategy`, `pattern`, `payment`, `advanced`

CodeForge - B23A - Sorting Algorithm Interface

Độ khó: ★ ★ ★ Hard (Advanced)

Đề bài

Tạo sorting framework với interfaces:

- Interface `Sorter` với:
 - `void sort(int[] arr);`
 - `String getAlgorithmName();`
 - `default void printArray(int[] arr) print array`
- Classes `BubbleSort`, `QuickSort`, `MergeSort`, `InsertionSort` implements `Sorter`
- Class `SortingBenchmark` với:
 - `void benchmark(Sorter sorter, int[] data)`
 - Measure performance

◇ Input

- Dòng 1: N
- Dòng 2: N numbers
- Dòng 3: M (algorithms to test)
- M dòng: Algorithm names

◇ Output

- Sorted arrays
- Performance comparison

◇ Constraints

- $1 \leq N \leq 100$

Ví dụ

Test case 1

Input:

```
10
9 5 2 8 1 7 3 6 4 0
3
BUBBLE
QUICK
MERGE
```

Output:

```
Bubble Sort:  
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]  
Time: 0.05ms
```

```
Quick Sort:  
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]  
Time: 0.02ms
```

```
Merge Sort:  
[0, 1, 2, 3, 4, 5, 6, 7, 8, 9]  
Time: 0.03ms
```

```
Fastest: Quick Sort
```

Tags: [interface](#), [sorting](#), [algorithm](#), [benchmark](#), [advanced](#)

CodeForge - B24A - Data Persistence Interface

Độ khó: ★ ★ ★ Hard (Advanced)

Đề bài

Tạo persistence layer với interfaces:

- Interface `Repository<T>` với:
 - `void save(T entity);`
 - `T findById(String id);`
 - `List<T> findAll();`
 - `void delete(String id);`
- Classes `FileRepository`, `DatabaseRepository`, `MemoryRepository` implements `Repository`
 - Different storage mechanisms
- Class `User` với id, name, email

Trong main():

- Create repositories
- Save entities
- Find và delete
- Compare different implementations

◇ Input

- Dòng 1: Repository type
- Dòng 2: N (operations)
- N dòng: Operation (SAVE/FIND/DELETE) và data

◇ Output

- Operation results

◇ Constraints

- $1 \leq N \leq 50$

Ví dụ

Test case 1

Input:

```
MEMORY
5
SAVE U001 Alice alice@email.com
```

```
SAVE U002 Bob bob@email.com
FIND U001
DELETE U002
FINDALL
```

Output:

```
[Memory] Saved: U001 - Alice
[Memory] Saved: U002 - Bob
[Memory] Found: U001 - Alice (alice@email.com)
[Memory] Deleted: U002
[Memory] All users:
- U001: Alice (alice@email.com)
```

Tags: [interface](#), [repository](#), [persistence](#), [crud](#), [advanced](#)

CodeForge - B25A - Complete Interface System - Notification Framework

Độ khó: ★ ★ ★ Hard (Advanced)

Đề bài

Tạo complete notification framework:

- Interface `NotificationChannel` với:
 - `boolean send(String recipient, String message);`
 - `String getChannelName();`
 - default boolean `isAvailable()` return true (hook)
- Interface `NotificationFormatter` với:
 - `String format(String message, String priority);`
- Classes `EmailChannel`, `SMSChannel`, `PushChannel`, `SlackChannel` implements `NotificationChannel`
- Classes `PlainFormatter`, `HTMLFormatter`, `MarkdownFormatter` implements `NotificationFormatter`
- Class `Notification` với:
 - `String message, priority, recipient`
- Class `NotificationService` với:
 - `List<NotificationChannel> channels`
 - `NotificationFormatter formatter`
 - Strategy pattern: set formatter dynamically
 - `void broadcast(Notification notification)` send via all channels
 - `void sendVia(NotificationChannel channel, Notification notification)`

Trong main():

1. Configure notification service
2. Add multiple channels
3. Set formatter
4. Send notifications
5. Handle failures gracefully
6. Generate delivery report

◇ Input

- Dòng 1: N (channels)
- N dòng: Channel types
- Dòng N+2: Formatter type
- Dòng N+3: M (notifications)
- M dòng: Priority, recipient, message

◇ Output

- Delivery log

- Summary report

◇ Constraints

- $1 \leq N \leq 5$
- $1 \leq M \leq 20$

Ví dụ

Test case 1

Input:

```
4
EMAIL
SMS
PUSH
SLACK
HTML
3
HIGH admin@company.com Server down
MEDIUM user@company.com Update available
LOW team@company.com Daily report
```

Output:

```
=== Notification Service Started ===
Channels: Email, SMS, Push, Slack
Formatter: HTML

Broadcasting: HIGH priority to admin@company.com
[Email] ✓ Sent: <b>HIGH</b> Server down
[SMS] ✓ Sent: <b>HIGH</b> Server down
[Push] ✓ Sent: <b>HIGH</b> Server down
[Slack] ✓ Sent: <b>HIGH</b> Server down

Broadcasting: MEDIUM priority to user@company.com
[Email] ✓ Sent: <b>MEDIUM</b> Update available
[SMS] ✓ Sent: <b>MEDIUM</b> Update available
[Push] ✓ Sent: <b>MEDIUM</b> Update available
[Slack] ✓ Sent: <b>MEDIUM</b> Update available

Broadcasting: LOW priority to team@company.com
[Email] ✓ Sent: <b>LOW</b> Daily report
[SMS] ✓ Sent: <b>LOW</b> Daily report
[Push] ✓ Sent: <b>LOW</b> Daily report
[Slack] ✓ Sent: <b>LOW</b> Daily report

=== Delivery Report ===
Total Notifications: 3
```

Total Deliveries: 12
Success Rate: 100%
Channels Used: 4

Tags: `interface`, `notification`, `complete-system`, `strategy`, `observer`, `capstone`, `advanced`