



The PanPipe Workflow Manager

Daniel Ortiz Martínez

Mathematics and Computer Science Department
University of Barcelona

Table of Contents

1. Introduction
2. Package Overview
3. Main Tools and File Formats
4. Toy Pipeline Example

Introduction

- Pipeline execution is a complex task
 - Pipeline composed of very heterogeneous tasks/processes
 - Processes may present dependencies with other ones
 - Often necessary to add or remove pipeline processes
 - Need to allocate computational resources
 - Independent processes should be executed concurrently
 - Hard to maintain and reuse code
 - ...
- PanPipe has been created as a highly portable, configurable and extensible solution

Package Overview

Package Dependencies

- Shell Bash
- Python
- Slurm Workload Manager (optional)

Package Installation

- Obtain the package using git:

```
git clone https://github.com/daormar/panpipe.git
```

- Change to the directory with the package's source code and type:

```
./reconf  
./configure  
make  
make install
```

NOTE: use `--prefix` option of `configure` to install the package in a custom directory

- PanPipe is an engine to execute general pipelines
- Executes only those pipeline processes that are pending
- Handles computational resources for each process
- Executes process arrays

Execution Model

- PanPipe follows the *flow-based programming* paradigm
 - Network of *black box* processes
 - Relations between processes are defined by the data they exchange
 - Component oriented
- PanPipe follows a simple execution model based on a file enumerating a list of pipeline processes to be executed
- Processes are executed simultaneously unless dependencies are specified
- Process implementation is given in module files

Main Tools and File Formats

Main Tools

- `panpipe_exec`
- `panpipe_exec_batch`
- `panpipe_check`
- `panpipe_status`

- Automates execution of general pipelines
- Main input parameters:
 - `--pfile <string>`: file with pipeline processes to be performed
 - `--outdir <string>`: output directory
 - `--sched <string>`: scheduler used for pipeline execution
 - `--showopts`: show pipeline options
 - `--checkopts`: check pipeline options
 - `--debug`: do everything except launching pipeline processes

- Content of output directory:
 - `scripts`: directory containing the scripts used for each pipeline process
 - `<pipeline_process_name>`: directory containing the results of the pipeline process of the same name
- Additional directories may be created depending on the pipeline

- **Built-in Scheduler**

- Allows to execute pipelines locally
- Incorporates a basic resource allocation mechanism

- **Slurm Scheduler**

- Allows to exploit large computational resources
- Usage transparent to the user
- Slurm behavior influenced by pipeline description

- Automates execution of pipeline batches
- Main input parameters:
 - -f <string>: file with a set of panpipe_exec commands
 - -m <string>: Maximum number of concurrently executed pipelines
 - -o <string>: Output directory to move output of each pipeline

- Checks correctness of pipelines and converts them to other formats
- Main input parameters:
 - -p <string>: pipeline file
 - -g: print pipeline in graphviz format

- Checks execution status of a given pipeline
- Main input parameters:
 - -d <string>: directory where the pipeline processes are stored
 - -s <string>: process name whose status should be determined (optional)

The `panpipe_lib.sh` Library

- Shell library with functions used by the previously described tools
- Functions can be classified as follows:
 - Implementation of the package execution model
 - Automated creation of scripts executing pipeline processes
 - Helper functions to implement pipeline processes

- **Pipeline file:** file enumerating all of the pipeline processes to be carried out when processing a normal-tumor sample
- **Module file:** file defining the code of the pipeline processes
- **Pipeline automation script:** file with a sequence of `panpipe_exec` commands automating the analysis of a dataset

Pipeline File

- **Module import** (module names separated by commas)
- **Entry format** (one entry per line)

Process name, Slurm account, Slurm partition, CPUs, Memory limit, Time limit, Dependencies, ...

- **Dependency types:** none, after, afterok, afternotok, afterany

```
#import panpipe_software_test
#
process_a  cpus=1 mem=32 time=00:01:00 processdeps=none
process_b  cpus=1 mem=32 time=00:01:00 processdeps=afterok:process_a
process_c  cpus=1 mem=32 time=00:01:00 throttle=2 processdeps=afterok:process_a
```

- Contains the definition of the different processes
- Written in bash
- Three bash functions should be defined for each process:
 - `processname_explain_cmdline_opts()`
 - `processname_define_opts()`
 - `processname()`

Module File: `processname_explain_cmdline_opts()`

- This function documents the command line options that the process needs to work
- The aggregated documentation for the different processes is shown when executing `panpipe_exec --showopts`
- Whenever two processes share the same option, it is important to give it the same name

Module File: processname_explain_cmdline_opts()

```
process_a_explain_cmdline_opts()
{
    # -a option
    description="Sleep time in seconds for process_a (required)"
    explain_cmdline_opt "-a" "<int>" "$description"
}
```

Module File: `processname_define_opts()`

- This function should create a string containing the options that are specific to the process
- The main idea is to map command line options to process options
- The package provides multiple built-in functions to make the implementation of this function easier

Module File: processname_define_opts()

```
processname_define_opts()
{
    # Initialize variables
    local cmdline=$1
    local process_spec=$2
    local optlist=""

    # Use built-in functions to add options to optlist variable
    ...

    # Save option list
    save_opt_list optlist
}
```

Module File: processname_define_opts()

```
process_a_define_opts()
{
    # Initialize variables
    local cmdline=$1
    local process_spec=$2
    local optlist=""

    # -a option
    define_cmdline_opt "$cmdline" "-a" optlist || exit 1

    # Save option list
    save_opt_list optlist
}
```

- Implements the process
- The function should incorporate code at the beginning to read the options defined by `processname_define_opts()`

Module File: processname()

```
process_a()
{
    # Initialize variables
    local sleep_time=`read_opt_value_from_line "$*" "-a"`

    # Sleep some time
    sleep ${sleep_time}
}
```

Pipeline Automation Script

- Automates the analysis of a whole dataset
- At each entry (one per line), `panpipe_exec` tool is used to execute a whole pipeline
- Can be used as input for `panpipe_exec_batch`
- Entry example:

```
panpipe_exec --pfile example.ppl --outdir outdir1 --sched SLURM -opt1 <opt1_val> -opt2 <opt2_val> ...
panpipe_exec --pfile example.ppl --outdir outdir2 --sched SLURM -opt1 <opt1_val> -opt2 <opt2_val> ...
panpipe_exec --pfile example.ppl --outdir outdir3 --sched SLURM -opt1 <opt1_val> -opt2 <opt2_val> ...
...
panpipe_exec --pfile example.ppl --outdir outdirn --sched SLURM -opt1 <opt1_val> -opt2 <opt2_val> ...
```

- Since multiple imports are permitted, a new module may contain process definitions missing in another one
- The order in which modules are imported is relevant
 - if two modules define the same function, the definition in the module imported last will prevail
 - the previous property can be used to modify a specific process without repeating the code of the whole module

Toy Pipeline Example

Pipeline File

```
#import panpipe_software_test
#
process_a cpus=1 mem=32 time=00:01:00 processdeps=none
process_b cpus=1 mem=32 time=00:01:00 processdeps=afterok:process_a
process_c cpus=1 mem=32 time=00:01:00 throttle=2 processdeps=afterok:process_a
process_d cpus=1 mem=32 time=00:01:00 processdeps=none
process_e cpus=1 mem=32 time=00:01:00 processdeps=after:process_d
process_f cpus=1 mem=32 time=00:01:00 processdeps=none
```


Pipeline Representation

