

Vulnerability in XiXunTianTian (喜讯天天) for Android

Daoyuan Wu*, Xiapu Luo* and Rocky K. C. Chang
The Hong Kong Polytechnic University
{csdwu, csxluo, csrchang}@comp.polyu.edu.hk
Mar 1, 2012 at 7:45 PM HKT

Abstract

We found that XiXunTianTian 0.6.2 beta has a vulnerability that allows a crafted application to read and modify user's sensitive calendar information without permission, including user's calendar accounts (username and password in plaintext!), user's calendar (contents, events, alerts and friends' birthday).

1 Application Information

Please see the following link in our AppSec website:

<http://www4.comp.polyu.edu.hk/~appsec/bugs/CVE-2012-1388-vulnerability-in-XiXunTianTian.html>

2 Description

Please see the exposed content providers in the AndroidManifest.xml file, which are not properly protected, as shown in follows:

- ```
<provider android:name="com.xixun.providers.CalendarProvider"
 android:authorities="com.xixun.calendar" />
```
- ```
<provider android:name="com.xixun.providers.WidgetProvider"
  android:authorities="com.xixun.widgets" />
```

3 Impact

Please see the following snapshots generated by our arrack demo:

AttackDemo	AttackDemo	AttackDemo
content://com.xixun.calendar/accounts	content://com.xixun.calendar/accounts	content://com.xixun.calendar/accounts
InsertAttack! Inserted Count: 1 Inserted Uri: content://com.xixun.calendar/accounts/1	queryAttack! Column Count: 7 Rows Count: 1 1[_id]: 1 1[name]: name 1[passwd]: passwd 1[user_id]: user_id 1[last_sync_range_begin]: last_sync_range_begin 1[last_sync_range_end]: last_sync_range_end 1[selected]: selected	deleteAttack! Deleted Count: 1

AttackDemo	AttackDemo	AttackDemo
content://com.xixun.calendar/calendar_alerts	content://com.xixun.calendar/calendar_alerts	content://com.xixun.calendar/calendar_alerts
InsertAttack! Inserted Count: 1 Inserted Uri: content://com.xixun.calendar/calendar_alerts/1	queryAttack! Column Count: 15 Rows Count: 1 1[_id]: 1 1[title]: title 1[event_id]: event_id 1[instance_id]: instance_id 1[begin]: begin 1[end]: end 1[alarm_time]: alarm_time 1[creation_time]: creation_time 1[received_time]: received_time 1[notify_time]: notify_time 1[state]: state 1[minutes]: minutes 1[selected]: selected 1[color]: color 1[all_day]: all_day	deleteAttack! Deleted Count: 1

AttackDemo	AttackDemo	AttackDemo
content://com.xixun.calendar/calendars	content://com.xixun.calendar/calendars	content://com.xixun.calendar/calendars
InsertAttack! Inserted Count: 1 Inserted Uri: content://com.xixun.calendar/calendars/1	queryAttack! Column Count: 18 Rows Count: 1 1[_id]: 1 1[uuid]: uuid 1[_sync_id]: _sync_id 1[_sync_version]: _sync_version 1[_sync_time]: _sync_time 1[user_id]: user_id 1[name]: name 1[display_name]: display_name 1[location]: location 1[description]: description 1[selected]: selected 1[timezone]: timezone 1[deleted]: deleted 1[url]: url 1[color]: color 1[sync_events]: sync_events 1[access_level]: access_level 1[created_at]: 1330596674672	deleteAttack! Deleted Count: 1

AttackDemo	AttackDemo	AttackDemo
content://com.xixun.calendar/reminders	content://com.xixun.calendar/reminders	content://com.xixun.calendar/reminders
InsertAttack! Inserted Count: 1 Inserted Uri: content://com.xixun.calendar/reminders/1	queryAttack! Column Count: 9 Rows Count: 1 1[_id]: 1 1[_sync_id]: _sync_id 1[_sync_version]: _sync_version 1[_sync_time]: _sync_time 1[event_id]: event_id 1[minutes]: minutes 1[uuid]: uuid 1[deleted]: deleted 1[method]: method	deleteAttack! Deleted Count: 1

AttackDemo	AttackDemo	AttackDemo
content://com.xixun.calendar/events	content://com.xixun.calendar/city_weather	content://com.xixun.calendar/history_weather
columnAttack! Column Count: 29 0: location 1: rrule 2: has_attendees 3: original_all_day 4: rdate 5: exrule 6: timezone 7: dtstart 8: title 9: _sync_time 10: _id 11: _sync_id 12: description 13: created_at 14: all_day 15: _sync_version 16: last_date 17: calendar_id 18: dtend 19: original_event 20: status	columnAttack! Column Count: 8 0: _id 1: display_name 2: search_critical 3: forecast_infos 4: priority 5: selected 6: auto_get 7: query_date	columnAttack! Column Count: 4 0: _id 1: city 2: current_forecast_info 3: dt_query

AttackDemo	AttackDemo	AttackDemo
content://com.xixun.widgets/bodhisattva_birthdays	content://com.xixun.widgets/bodhisattva_birthdays	content://com.xixun.widgets/bodhisattva_birthdays
InsertAttack! Inserted Count: 1 Inserted Uri: content://com.xixun.widgets/bodhisattva_birthdays/1	queryAttack! Column Count: 3 Rows Count: 1 1[_id]: 1 1[time]: time 1[names]: names	deleteAttack! Deleted Count: 1

4 Solution

Our advice is to set the permission of these application's content providers properly, or avoid exporting these content providers in the AndroidManifest.xml file. Currently, a user could disable the application temporarily and wait for an official update.

5 Technical Description

Please see the following exposed content providers and tables:

Content Provider Authority	Table Name
com.xixun.calendar	accounts
com.xixun.calendar	calendar_alerts
com.xixun.calendar	calendars
com.xixun.calendar	city_weather
com.xixun.calendar	events
com.xixun.calendar	history_weather
com.xixun.calendar	reminders
com.xixun.calendar	trackings
com.xixun.widgets	bodhisattva_birthdays
com.xixun.widgets	festivals
com.xixun.widgets	vehicle_limits
com.xixun.widgets	widget_config
com.xixun.widgets	widgets