

Master's thesis: Numerical comparison of MCMC methods for Quantum tomography

Danila Mokeev

Supervisors: Estelle Massart, Andrew Thompson and Tameem Adel

21st of June 2024

Ecole Polytechnique de Louvain

Scope of this thesis

Topic: Markov chain Monte Carlo (MCMC) methods in Quantum tomography

Research questions:

1. How do these methods perform in different experimental setups?
2. Why do some methods perform better than others?

Purpose:

- Enable new directions of research
- Help researchers make an informed choice for their use case

1. Numerically compare 2 MCMC algorithms, the prob-estimator and the Projected Langevin algorithm
2. Propose 2 new algorithms to understand the impact of the prior and the algorithm on the accuracy

Table of Contents

Brief introduction to Quantum tomography

Markov chain Monte Carlo methods

Main algorithms

Experiments and results

Table of Contents

Brief introduction to Quantum tomography

Markov chain Monte Carlo methods

Main algorithms

Experiments and results

Motivation behind Quantum tomography


Quantum tomography is a process to reconstruct the quantum state of a system.

There are some challenges to consider:

- Quantum systems are inherently probabilistic
- A measurement can only be made once
- We can only measure the position or momentum, but not both

Quantum tomography: a diagram

Quantum tomography allows to address the existing challenges



Quantum tomography: mathematical description (1)

The Born rule states that

$$p(m) = \text{tr}(\rho P_m) \quad (1)$$

with

- $p(m)$ the probability of occurrence of m
- P_m the projector matrix associated to the eigenvalue m of an *observable* O
- ρ the *density matrix* representing the quantum state

The size of ρ is $2^n \times 2^n$ with n the number of qubits.

Quantum tomography: mathematical description (2)

If we flatten the matrices

$$A = \begin{bmatrix} P_{11} & P_{12} & P_{13} \cdots \\ P_{21} & P_{22} & P_{23} \cdots \\ \vdots & \vdots & \vdots \\ P_{m1} & P_{m2} & P_{m3} \cdots \end{bmatrix} \quad \vec{\rho} = \begin{bmatrix} \rho_{11} \\ \rho_{12} \\ \rho_{13} \\ \vdots \end{bmatrix} \quad (2)$$

then we can estimate ρ by solving the resulting system of equations

$$A\vec{\rho} = \hat{p} \quad (3)$$

Most common methods

- Direct methods:

$$\hat{\rho} = (A^T A)^{-1} A^T \hat{p} \quad (4)$$

- Optimization-based methods:

$$\hat{\rho} = \operatorname{argmin}_{\vec{\rho}} \|A\vec{\rho} - \hat{p}\| \quad (5)$$

- Pauli basis expansion:

$$\hat{\rho} = \sum_{b \in \{I, x, y, z\}^n} \rho_b \sigma_b \quad (6)$$

- Bayesian methods, and in particular MCMC methods

$$\hat{\rho} = \frac{1}{N} \sum_{i=1}^N \rho_i \quad \text{with } \rho_i \sim \pi(\rho | \mathbf{D}) \quad (7)$$

Existing methods: our focus in this thesis

- Direct methods:

$$\hat{\rho} = (A^T A)^{-1} A^T \hat{p} \quad (8)$$

- Optimization-based methods:

$$\hat{\rho} = \operatorname{argmin}_{\vec{\rho}} \|A\vec{\rho} - \hat{p}\| \quad (9)$$

- Pauli basis expansion:

$$\hat{\rho} = \sum_{b \in \{I, x, y, z\}^n} \rho_b \sigma_b \quad (10)$$

- Bayesian methods, and in particular MCMC methods

$$\hat{\rho} = \frac{1}{N} \sum_{i=1}^N \rho_i \quad \text{with } \rho_i \sim \pi(\rho | \mathbf{D}) \quad (11)$$

Table of Contents

Brief introduction to Quantum tomography

Markov chain Monte Carlo methods

Main algorithms

Experiments and results

In the Bayesian framework:

$$\underbrace{\pi(\rho|\mathbf{D})}_{\text{Posterior}} \propto \underbrace{\pi(\mathbf{D}|\rho)}_{\text{Likelihood}} \underbrace{\pi(\rho)}_{\text{Prior}} \quad (12)$$

Recall that each term is a distribution!

In the context of Quantum tomography:

- Likelihood $\pi(\mathbf{D}|\rho) = \exp(-||A\vec{\rho} - \hat{p}||)$
- Prior $\pi(\rho)$ is method specific

Markov chain Monte Carlo methods

- Markov chain Monte Carlo (MCMC) methods *sample* from $\pi(\rho|\mathbf{D})$.
- They build a Markov chain of samples ρ_1, ρ_2, \dots such that

$$f(x) = \pi(\rho|\mathbf{D}) \quad (13)$$

with the equilibrium distribution $f(x)$ of the chain

- The density matrix is then calculated as

$$\tilde{\rho} = \mathbb{E}[\rho] = \int \rho \pi(\rho|\mathbf{D}) d\rho \quad (14)$$

$$\Leftrightarrow \hat{\rho} = \frac{1}{N} \sum_{i=1}^N \rho_i \quad \text{with } \rho_i \sim \pi(\rho|\mathbf{D}) \quad (15)$$

An example: Metropolis-Hastings algorithm

mcmc.gif

Advantages of MCMC algorithms

Why are we interested in MCMC methods?

- Prior $\pi(\rho)$: additional information about the density matrix - low-rank for example
- Uncertainty quantification: working with distributions instead of point estimates

Table of Contents

Brief introduction to Quantum tomography

Markov chain Monte Carlo methods

Main algorithms

Experiments and results

Prob-estimator: prior

- Sum of rank-1 matrices:

$$\rho = \sum_{i=1}^d \gamma_i V_i V_i^\dagger$$

- The prior $\pi_1(\gamma_1 \dots \gamma_d)$ is a Dirichlet distribution. A typical draw leads to a sparse vector.

$$\gamma = \begin{bmatrix} 0 & \dots & 1 & \dots & 0 \end{bmatrix}$$

- The prior $\pi_2(V_i)$ is a unit sphere distribution

$$\|V_i\| = 1$$

Prob-estimator: algorithm

Algorithm: Prob-estimator algorithm

```
for  $t \leftarrow 1 : T$  do  
    // Iterate over each dimension  $i$   
    for  $i \leftarrow 1 : d$  do  
        1. Sample  $\gamma_i^*$  from  $\pi_1(\gamma_i)$   
        2. Update  $\gamma^{(t)}$  with accept/reject step  
    end  
    for  $i \leftarrow 1 : d$  do  
        1. Sample  $V_i^*$  from  $\pi_2(V_i)$   
        2. Update  $V^{(t)}$  with an accept/reject step  
    end  
end
```

Prob-estimator: algorithm

Algorithm: Prob-estimator algorithm

```
for  $t \leftarrow 1 : T$  do  
    // Iterate over each dimension  $i$   
    for  $i \leftarrow 1 : d$  do  
        1. Sample  $\gamma_i^*$  from  $\pi_1(\gamma_i)$   
        2. Update  $\gamma^{(t)}$  with accept/reject step  
    end  
    for  $i \leftarrow 1 : d$  do  
        1. Sample  $V_i^*$  from  $\pi_2(V_i)$   
        2. Update  $V^{(t)}$  with an accept/reject step  
    end  
end
```

Prob-estimator: algorithm

Algorithm: Prob-estimator algorithm

```
for  $t \leftarrow 1 : T$  do  
  // Iterate over each dimension  $i$   
  for  $i \leftarrow 1 : d$  do  
    1. Sample  $\gamma_i^*$  from  $\pi_1(\gamma_i)$   
    2. Update  $\gamma^{(t)}$  with accept/reject step  
  end  
  for  $i \leftarrow 1 : d$  do  
    1. Sample  $V_i^*$  from  $\pi_2(V_i)$   
    2. Update  $V^{(t)}$  with an accept/reject step  
  end  
end
```

Prob-estimator: algorithm

Algorithm: Prob-estimator algorithm

```
for  $t \leftarrow 1 : T$  do  
    // Iterate over each dimension  $i$   
    for  $i \leftarrow 1 : d$  do  
        1. Sample  $\gamma_i^*$  from  $\pi_1(\gamma_i)$   
        2. Update  $\gamma^{(t)}$  with accept/reject step  
    end  
    for  $i \leftarrow 1 : d$  do  
        1. Sample  $V_i^*$  from  $\pi_2(V_i)$   
        2. Update  $V^{(t)}$  with an accept/reject step  
    end  
end
```

Prob-estimator: algorithm

Algorithm: Prob-estimator algorithm

```
for  $t \leftarrow 1 : T$  do  
    // Iterate over each dimension  $i$   
    for  $i \leftarrow 1 : d$  do  
        1. Sample  $\gamma_i^*$  from  $\pi_1(\gamma_i)$   
        2. Update  $\gamma^{(t)}$  with accept/reject step  
    end  
    for  $i \leftarrow 1 : d$  do  
        1. Sample  $V_i^*$  from  $\pi_2(V_i)$   
        2. Update  $V^{(t)}$  with an accept/reject step  
    end  
end
```

Projected Langevin: prior

- Burer-Monteiro factorization: $\rho = YY^\dagger$, with $\text{rank}(Y) = r$
- Low-rank prior: spectral scaled Student-t distribution

$$\pi(Y) = \prod_{j=1}^r (\theta^2 + \underbrace{s_j(Y)^2}_{j\text{th eigenvalue of } Y})^{-(2d+r+2)/2} \quad (16)$$

- Promotes sparsity among the eigenvalues leading to a low rank
- Very similar to the Student-t distribution

Projected Langevin: algorithm

Algorithm: Projected Langevin algorithm

for $t \leftarrow 1 : T$ **do**

1. Sample $\tilde{w}^{(t)} \sim N(\mathbf{0}, \mathbf{I})$

$$2. \tilde{Y}^{(t)} \leftarrow \tilde{Y}^{(t-1)} - \eta^{(t)} \underbrace{\nabla \pi(\tilde{Y}^{(t-1)} | \mathbf{D})}_{\text{gradient}} + \frac{\sqrt{2\eta^{(t)}}}{\beta} \tilde{w}^{(t)}$$

end

The gradient allows us to explore the regions of high density faster.

Projected Langevin: algorithm

Algorithm: Projected Langevin algorithm

for $t \leftarrow 1 : T$ **do**

1. Sample $\tilde{w}^{(t)} \sim N(\mathbf{0}, \mathbf{I})$

2. $\tilde{Y}^{(t)} \leftarrow \tilde{Y}^{(t-1)} - \eta^{(t)} \underbrace{\nabla \pi(\tilde{Y}^{(t-1)} | \mathbf{D})}_{\text{gradient}} + \frac{\sqrt{2\eta^{(t)}}}{\beta} \tilde{w}^{(t)}$

end

The gradient allows us to explore the regions of high density faster.

Projected Langevin: algorithm

Algorithm: Projected Langevin algorithm

for $t \leftarrow 1 : T$ **do**

1. Sample $\tilde{w}^{(t)} \sim N(\mathbf{0}, \mathbf{I})$

2. $\tilde{Y}^{(t)} \leftarrow \tilde{Y}^{(t-1)} - \eta^{(t)} \underbrace{\nabla \pi(\tilde{Y}^{(t-1)} | \mathbf{D})}_{\text{gradient}} + \frac{\sqrt{2\eta^{(t)}}}{\beta} \tilde{w}^{(t)}$

end

The gradient allows us to explore the regions of high density faster.

Table of Contents


Brief introduction to Quantum tomography

Markov chain Monte Carlo methods

Main algorithms

Experiments and results


Convergence plot




\Rightarrow Projected Langevin converges faster for $n = 3$ qubits

Convergence speed for $n = 4, 5$

Reminder: a larger n means a larger density matrix




(a) $n = 4$



(b) $n = 5$


\Rightarrow Projected Langevin converges slower than previously

Computation time for $n = 3$




\implies For $n = 3$, Projected Langevin takes much less time

Computation time for $n = 4, 5$



(a) $n = 4$



(b) $n = 5$

\implies When n increases, Projected Langevin becomes as slow as the prob-estimator due to the gradient cost.

Introducing 2 new methods

What makes Projected Langevin perform better ?


To answer this question, we introduce 2 new algorithms:

1. Metropolis-Hastings with Student-t prior (MHS)
2. Metropolis-Hastings with Gibbs with Student-t prior (MHGS)

They combine:

- The algorithm from the prob-estimator
- The prior from the Projected Langevin algorithm


Convergence comparison



⇒ The prior itself is not a solution, and must be paired with the right algorithm to be fast and accurate

Impact of the number of shots


Shot: measurement we perform on a clone of the state




⇒ The prob-estimator does not scale!

Impact of knowing the rank of ρ

Reminder: for Projected Langevin, $\rho = YY^\dagger$, with $\text{rank}(Y) = r$



(a) Rank of ρ known



(b) Rank of ρ not known

\implies The information about the rank only marginally affects the accuracy

- Quantum tomography is not yet a solved problem, especially for large systems
- MCMC methods are a promising direction of research, thanks to uncertainty quantification and prior information
- The choice of the algorithm might have more impact on the convergence speed and accuracy than the prior

- Extend tests to larger n to check for robustness of conclusions
- Try other gradient-based algorithms to see the impact on convergence speed (for example HMC)
- Try other priors to see the impact on computation time (the gradient may be faster to compute) and accuracy

Prob-estimator: full

It can be seen as eigendecomposition, without the orthogonality property:

$$\rho = U\Lambda U^\dagger \quad (17)$$

Prior:

$$\pi(\rho) = \pi_1(\gamma_1, \dots, \gamma_d) \prod_{i=1}^d \pi_{2,i}(V_i) \quad (18)$$

Likelihood:

$$\pi(\mathbf{D}|\rho) = \pi(\rho, \mathbf{D}) = \exp(-\lambda\ell(\rho, \mathbf{D})) \quad (19)$$

with:

$$\ell(\rho, \mathbf{D}) = \sum_{\mathbf{a} \in \mathcal{E}^n} \sum_{\mathbf{s} \in \mathcal{R}^n} [\text{tr}(\rho P_{\mathbf{s}}^{\mathbf{a}}) - \hat{p}_{\mathbf{a},\mathbf{s}}]^2 \quad (20)$$

Posterior:

$$\pi(\nu|\mathbf{D}) \propto \exp(-\lambda\ell(\nu, \mathbf{D}))\pi(\nu) \quad (21)$$

Projected Langevin: full

Prior:

$$\nu_{\theta}(Y) = C_{\theta} \det(\theta^2 I_d + YY^{\dagger})^{-(2d+r+2)/2} \quad (22)$$

Likelihood:

$$L(Y, \mathbf{D}) = \sum_{i=1}^M (\hat{p}_m - \text{tr}(A_m YY^{\dagger}))^2 \quad (23)$$

Posterior:

$$\hat{\nu}_{\lambda, \theta}(Y, \mathbf{D}) = \exp(-f_{\lambda, \theta}(Y, \mathbf{D})) \quad (24)$$

with

$$f_{\lambda, \theta}(Y, \mathbf{D}) = \lambda \sum_{i=1}^M (\hat{p}_m - \text{tr}(A_m YY^{\dagger}))^2 + \frac{2d + r + 2}{2} \log \det(\theta^2 I_d + YY^{\dagger}) \quad (25)$$

Potential future experiments

- Try experiments with more qubits to draw more robust conclusions
- Test with other algorithms and priors to see if it's a property of this prior in particular, or it generalizes (The calculation of the gradient is going to be more costly in all cases)
- Try to use HMC to see if it still converges as fast for higher dimensions