

Git Advanced 2

[SWE2021]

JinYeong Bak

jy.bak@skku.edu

Human Language Intelligence Lab, SKKU

Slide credit: HyunJin Kim / khyunjin1993@g.skku.edu

Objective

By the end of this class, you will understand...

- Basic branching and merging
- Managing branch
- Basic merge conflict
- Branching workflow

Basic branching and merging

Imagine a workflow that looks like the following ...

- Do some work on a repository “**main**” or “**master**”
- Create a branch “**even_list**” for developing a new function
- Do some work in the “**even_list**” branch

At this stage, you have encountered an issue that need to be fixed at “**main**” branch

Basic branching and merging

Since the issue should be fixed, you need a hotfix (i.e., small patch)

- Switch your branch to “**main**”
- Create a branch “**hotfix**” to add the hotfix
- Fix codes in the “**hotfix**” branch and commit
- Merge branch “**main**” with “**hotfix**”
- Merge branch “**main**” with “**even_list**” branch

Basic branching and merging

Do some work on a repository “main” or “master”


- Create a new repository “git_advanced_2” and create a “main.py” with skeleton code in [HERE](#)
- Add and commit in the “main” branch

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git add .
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git commit -m "skeleton code"
[main (root-commit) 37b1326] skeleton code
 1 file changed, 41 insertions(+)
 create mode 100644 main.py
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git status
On branch main
nothing to commit, working tree clean
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git log
commit 256413245026303cbb187118e46cafa8e5a0328a (HEAD -> main)
Author: agwaBom <khyunjin1993@gmail.com>
Date: Mon Apr 3 16:46:49 2023 +0900

    main initialized
```

Basic branching and merging


Do some work on a repository “**main**” or “**master**”



Basic branching and merging

Create a branch “**even_list**” for a new function you’re working on

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch even_list
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git checkout even_list
Switched to branch 'even_list'
```



Basic branching and merging

- Do some work in the “**even_list**” branch
- Click [HERE](#) to refer changes

```
3  # Skeleton code
4  def even_list(int_list):
5      """
6      Determines the sum of squares of even integers in a list.
7
8      Args:
9      |   int_list: A list of integers.
10
11     Returns:
12     |   A list of even integers.
13     """
14     even_list = [num for num in int_list if num % 2 == 0]
15     return even_list

31  # Main function
32  def main():
33      # Example list
34      int_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
35
36      # Modified to call the new function even_list
37      output = sum_of_squares_of_even(even_list(int_list))
38      print(output)
39
```


Basic branching and merging

- Do some work in the “**even_list**” branch
- Check “**main.py**” has been modified and commit


```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git status
On branch even_list
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   main.py

no changes added to commit (use "git add" and/or "git commit -a")
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git add main.py
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git commit -m "even_list implemented"
[even_list f7e33c1] even_list implemented
1 file changed, 2 insertions(+), 2 deletions(-)
```

Basic branching and merging

Do some work in the “**even_list**” branch

Assume, we’ve encountered an issue at this stage



Basic branching and merging

- Switch to your production branch “**main**” or “**master**”


```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git checkout main  
Switched to branch 'main'
```

- Create a branch “**hotfix**” to add the hotfix
“-b” flag enables to automatically make and change into a newly made branch

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git checkout -b hotfix  
Switched to a new branch 'hotfix'  
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch  
  even_list  
* hotfix  
  main
```

Basic branching and merging

- Switch to your production branch “**main**” or “**master**”
- Create a branch “**hotfix**” to add the hotfix



Basic branching and merging

- Fix codes in the “**hotfix**” branch, and commit
- Details on changes can be found [HERE](#)

```
31     # Main function
32     def main():
33         # Example list
34         int_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
35
36         # Fixed wrongly written code
37         output = even_list(int_list)
38         output = sum_of_squares_of_even(output)
39         print(output)
40
```

Basic branching and merging


- Fix codes in the “**hotfix**” branch, and commit
- Details on changes can be found [HERE](#)

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git status
On branch hotfix
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   main.py

no changes added to commit (use "git add" and/or "git commit -a")
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git add main.py
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git commit -m "hotfix on main.py"
[hotfix 32f7f38] hotfix on main.py
 1 file changed, 3 insertions(+), 2 deletions(-)
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git log --oneline --graph --all
* 32f7f38 (HEAD -> hotfix) hotfix on main.py
| * f7e33c1 (even_list) even_list implemented
|/
* 2564132 (main) main initialized
```

Basic branching and merging

- Fix codes in the “**hotfix**” branch, and commit
- Details on changes can be found [HERE](#)



Basic branching and merging


Merge branch “main” with “hotfix” (using “git merge <branch_name>”)

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git checkout main
Switched to branch 'main'
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git log --oneline --graph --all
* 32f7f38 (hotfix) hotfix on main.py
| * f7e33c1 (even_list) even_list implemented
|/
* 2564132 (HEAD -> main) main initialized
```

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git merge hotfix
Updating 2564132..32f7f38
Fast-forward
 main.py | 5 +++--
 1 file changed, 3 insertions(+), 2 deletions(-)
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git log --oneline --graph --all
* 32f7f38 (HEAD -> main, hotfix) hotfix on main.py
| * f7e33c1 (even_list) even_list implemented
|/
* 2564132 main initialized
```


Basic branching and merging

- Merge branch “**main**” with “**hotfix**” (using “**git merge <branch_name>**”)
- “**fast-forward**”: simply move the pointer forward that is directly ahead of current branch (i.e., position of HEAD)



Branch management

- We know that there are a total of three branches using the “**git branch**” command

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch
  even_list
  hotfix
* main
```

- We can see the latest commit on each branch by using “**git branch -v**”

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch -v
  even_list f7e33c1 even_list implemented
  hotfix    32f7f38 hotfix on main.py
* main      32f7f38 hotfix on main.py
```

Branch management

- The “**--merged**” and “**--no-merged**” option can filter the list of branches whether merged or not


```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch --merged
hotfix
* main
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch --no-merged
even_list
```

- We can delete merged branches by “**git branch -d <branch_name>**”

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch --merged
hotfix
* main
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch -d hotfix
Deleted branch hotfix (was 32f7f38).
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch
even_list
* main
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch --merged
* main
```

Branch management

- We can delete merged branches by “**git branch -d <branch_name>**”
- Resulting in following commit graph



Branch management

- Deleting not merged branch will cause the error

```
⊗ (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch -d even_list  
error: The branch 'even_list' is not fully merged.  
If you are sure you want to delete it, run 'git branch -D even_list'.
```

- If you want to really delete the branch, run
 “git branch -D <branch_name>” (Do not run in class today)

Branch management

We can also change the branch name by using

- “git branch --move <old_branch_name> <new_branch_name>”
- “git branch -m <old_branch_name> <new_branch_name>”


```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch
  even_list
* main
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch -m even_list changed_even_list
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git branch
  changed_even_list
* main
```

...or push an existing repository from the command line

```
git remote add origin https://github.com/agwaBom/temp.git
git branch -M main
git push -u origin main
```

Basic merging

Suppose you've decided that your work ("**even_list**") is complete and ready to merge the "**even_list**" branch into your "**main**" branch



Basic merging

If you try to merge “**main**” with “**changed_even_list**” branch, merge conflict will occur

```
⊗ (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git merge changed_even_list
Auto-merging main.py
CONFLICT (content): Merge conflict in main.py
Automatic merge failed; fix conflicts and then commit the result.
```


Basic merging

- If you try to merge “main” with “changed_even_list” branch, a merge conflict will occur
- Because **you changed the same part of the file differently in the two branches** you’re merging, git won’t be able to merge them

“main” branch

```
31 # Main function
32 def main():
33     # Example list
34     int_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
35
36     # Fixed wrongly written code
37     output = even_list(int_list)
38     output = sum_of_squares_of_even(output)
39     print(output)
40
```

“changed_even_list” branch

```
31 # Main function
32 def main():
33     # Example list
34     int_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
35
36     # Modified to call the new function even_list
37     output = sum_of_squares_of_even(even_list(int_list))
38     print(output)
39
```

Basic merging

After “git status” you will see that “main.py” is both modified

```
● (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git status
On branch main
You have unmerged paths.
  (fix conflicts and run "git commit")
  (use "git merge --abort" to abort the merge)

Unmerged paths:
  (use "git add <file>..." to mark resolution)
    both modified:   main.py

no changes added to commit (use "git add" and/or "git commit -a")
```

Basic merging

- You can open them manually with your favorite editor “**main.py**” and resolve those conflicts
- Your file contains a section that looks something like this:

```
# Main function
def main():
    # Example list
    int_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

<<<<<<< HEAD
    # Fixed wrongly written code
    output = even_list(int_list)
    output = sum_of_squares_of_even(output)
    =====
    # Modified to call the new function even_list
    output = sum_of_squares_of_even(even_list(int_list))
>>>>>>> changed_even_list
    print(output)

# Boilerplate code
if __name__ == "__main__":
    main()
```

Basic merging

HEAD is in the “**main**” branch, Upper Redbox will be the main branch’s modification and the bottom Redbox will be the “**changed_even_list**” branch

We can either choose a code between

- <<<<<< and =====
- ===== and >>>>>>

```
# Main function
def main():
    # Example list
    int_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

<<<<<< HEAD
    # Fixed wrongly written code
    output = even_list(int_list)
    output = sum_of_squares_of_even(output)
=====
    # Modified to call the new function even_list
    output = sum_of_squares_of_even(even_list(int_list))
>>>>>> changed_even_list
    print(output)

# Boilerplate code
if __name__ == "__main__":
    main()
```


Basic merging

In my case, I choose the HEAD section (i.e., “**main**” branch)

```
# Main function
def main():
    # Example list
    int_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

<<<<<<< HEAD
    # Fixed wrongly written code
    output = even_list(int_list)
    output = sum_of_squares_of_even(output)
=====
    # Modified to call the new function even_list
    output = sum_of_squares_of_even(even_list(int_list))
>>>>>>> changed_even_list
    print(output)

# Boilerplate code
if __name__ == "__main__":
    main()
```



```
# Main function
def main():
    # Example list
    int_list = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]

    # Fixed wrongly written code
    output = even_list(int_list)
    output = sum_of_squares_of_even(output)
    print(output)
```


Basic merging

After modification, commit, and merge

```
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git add main.py
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git log --graph --all --oneline
* a897a8c (changed_even_list) even_list implemented
| * 32f7f38 (HEAD -> main) hotfix on main.py
|/
* 2564132 main initialized
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git commit -m "merge with changed_even_list"
[main da4eb3f] merge with changed even list
• (base) khyunjin1993@amazon:~/dev/homework/open_source_software/git_advanced_2$ git log --graph --all --oneline
* da4eb3f (HEAD -> main) merge with changed_even_list
| \
| * a897a8c (changed_even_list) even_list implemented
* | 32f7f38 hotfix on main.py
|/
* 2564132 main initialized
```

You can see that it is now successfully merged :)

Branching workflow

Two approaches in the workflow

- Long-Running Branches
- Topic Branches


Branching workflow (Long-running branches)

Many git developers have a workflow that embraces this approach


- Code that is entirely stable in their “**main**” branch (only code that has been or will be released)
- They have another parallel branch named “**develop**” that they work from or use to **test stability**
- “**topic**” branches for a new feature

Branching workflow (Long-running branches)

A linear view of long-running branching (progressive-stability branching)




Generally easier to think about them as work “**silos**” (i.e., work individually)



Branching workflow (Topic branches)

- A topic branch is a **short-lived branch that you create and use for a single particular feature**
- This technique allows you to context-switch quickly and completely



Fork

Assignment_9 Private

Unwatch 1 Fork 0 Star 0

main 4 Branches 0 Tags

Go to file Add file Code

agwaBom train_file_list_to_json implemented? 0b1de63 · last year 5 Commits

english.txt	initialized repository with skeleton code	last year
german.txt	initialized repository with skeleton code	last year
main.py	train_file_list_to_json implemented?	last year

About

No description, website, or topics provided.

Activity

0 stars

1 watching

0 forks

Fork

Create a new fork

A *fork* is a copy of a repository. Forking a repository allows you to freely experiment with changes without affecting the original project.

Required fields are marked with an asterisk ().*

Owner *



Human-Language-Intelligence ▾

Repository name *

Assignment_9

✔ Assignment_9 is available.

By default, forks are named the same as their upstream repository. You can customize the name to distinguish it further.

Description (optional)

☐ Copy the `main` branch only

Contribute back to agwaBom/Assignment_9 by adding your own branch. [Learn more.](#)

You are creating a fork in the Human-Language-Intelligence organization.

Create fork

Uncheck!

Fork

Branches

New branch

OverviewYoursActiveStaleAll

Q Search branches...

Default

Branch	Updated	Check status	Behind	Ahead	Pull request
main	6 months ago			Default	

Your branches

Branch	Updated	Check status	Behind	Ahead	Pull request
write_file_list	last year		2	0	
path_to_file_list	last year		2	1	
train_file_list_to_json	last year		1	1	