

**THEORETICAL EVALUATION****NAME OF COURSE: Basic Training for Oil and Chemical Tanker Cargo Operations****STANDARD:** Regulation V/1-1, Paragraph 2.2, Section A-V/1-1, Paragraph 1 and Table A-V/1-1-1) of the Convention STCW'78, as amended and the STCW Code.

Name of Participant: <i>Nombre del Participante</i>		National ID or Passport: <i>Cédula o Pasaporte</i>	
Place of Course <i>Lugar del Curso</i>		Date of Exam: <i>Fecha del Examen</i>	
Instructor's Name <i>Nombre del Instructor</i>		Final Evaluation <i>Evaluación Final</i>	

Competence:

- Contribute to the safe cargo operation of oil and chemical tankers.
- Take precautions to prevent hazards.
- Apply occupational health and safety precautions and measures.
- Carry out fire-fighting operations.
- Respond to emergency.
- Take precautions to prevent pollution of the environment from the release of oil or chemicals.

PART A. CHOOSES THE BEST ANSWER.

1-The process used to separate the substances composing a mixture.

- a- Distillation.
- b- Condensation.
- c- Evaporation.
- d- None

2- It has been pressurized and cooled so as to liquefy it for convenience in shipping and storage,

- a- Petrolatum.
- b- Natural Gas.
- c- Naphtha.
- d- None

3- The atmosphere in the crude oil tanks itself is inserted with,

- a- Fresh Air
- b- Halon Gas
- c- Carbon Dioxide Gas
- d- None

4- One of the procedures to minimize the free surface effect is,

- a- To fill the tanks nearly 33% full.



- b- To fill the tanks nearly 50% full.
- c- To fill the tanks nearly 90% full.
- d- None.

5- LNG Vessel is:

- a- Special cargo vessels.
- b- Vessels whose cargos are petroleum and its derivatives.
- c- Vessels whose cargo is liquefied natural gas.
- d- Ships known as mammoth vessels.

6- OBO Vessel is:

- a- Vessel whose cargo is Petroleum or mineral in bulk.
- b- Vessel whose cargos are dangerous goods.
- c- Vessel whose cargos are refined petroleum.
- d- Vessel whose cargos are minerals.

7- V.L.C.C. Vessel is,

- a- Are vessels in a range between 35000 and 160000 tons.
- b- Are vessels over 300000 tons.
- c- Are vessels in a range between 160000 and 300000 tons.
- d- Are vessels in a range between 6000 and 35000 tons.

8- After the completion of loading arm connection, preparations for loading should be started in the following manner,

- a- Keep gate valves at the manifold open until the start of cargo loading.
- b- Keep gate valves at the manifold closed until the start of cargo loading
- c- Never use the gate valves for cargo loading.
- d- None

9- MARPOL means,

- a- The International Convention for Maritime Policy for Tanker Ships 76/84.
- b- The International Convention of Life at Sea 74/88
- c- The International Convention for the Prevention of Pollution from ships 73/78
- d- None

10- It use in order to prevent drops in tank pressure as a result of cargo discharge and also in order to make the tank atmosphere inert,

- a- IGS
- b- EEBD
- c- IMDG
- d- None.



11- After the oxygen content drops to below 5% after the start of cargo discharge by starting cargo pumps, start supplying inert gas to cargo tanks. The tank pressure is set within a range of

- a- 0 to 100 mmAq.
- b- 100 to 200 mmAq.
- c- 300 to 900 mmAq
- d- None.

12- Crude oil washing is a system to remove deposits of crude oil such as sludge adhering to the inside of tanks by utilizing the solvency of crude oil which is jetted by tank cleaning machines at a high pressure of,

- a- 1.5 kg/cm² or more.
- b- 5 kg/cm² or more.
- c- 10 kg/cm² or more.
- d- None.

13- Dirty ballast is,

- a- Ballast loaded in cargo tanks after cargo discharge.
- b- Ballast loaded in ballast tanks from the sea during cargo discharge.
- c- Ballast unloaded in ballast tanks from the sea after cargo discharge.
- d- None.

14- The risk of spontaneous combustion is biggest with,

- a- Vegetable oils.
- b- Heavy Petroleum oils.
- c- Diesel fuel oils.
- d- None.

15- The instrument for measuring the composition of hydrocarbon gas/air mixtures, usually giving the result as a percentage of the lower flammable limit is,

- a- Interface detector.
- b- Flame arrester.
- c- Combustible gas indicator.
- d- None.

16- The Flashpoint is,

- a- The lowest temperature at which a liquid gives off sufficient gas to form a flammable gas mixture near the surface of the liquid.
- b- The highest temperature at which a liquid gives off sufficient gas to form a flammable gas mixture near the surface of the liquid.
- c- The point of concentrate to hydrocarbon gas in air below which there is insufficient hydrocarbon to support and propagate combustion
- d- None

17- The petroleum having a flash point of,

- a- 20° C.



- b- 40° C.
- c- 60° C.
- d- None

18- The total quantity of oil which a tanker may discharge in any ballast voyage whilst under way must not exceed of,

- a- 1/20,000 of the total cargo carrying capacity of the vessel.
- b- 1/25,000 of the total cargo carrying capacity of the vessel.
- c- 1/30,000 of the total cargo carrying capacity of the vessel.
- d- None.

19- When the suction pressure drops suddenly to a negative pressure,

- a- The slop tank has become dry.
- b- Stop the pump.
- c- Reduce the pump revolutions to the minimum.
- d- None.

20- The areas which are considered to be so vulnerable to pollution by oil that oil discharges within them have been completely prohibited, with minor and well-defined exceptions are called (as MARPOL),

- a- Special Area.
- b- Restricted Area.
- c- MARPOL does not say anything about areas.
- d- None.

WEIGHTING OF EVALUATION		
APPROVAL CRITERIA	MINIMUM PERCENTAGE	PERCENTAGE OBTAINED
THEORETICAL EVALUATION	70% *	
FINAL EVALUATION		
Results	APPROVED:	NOT APPROVED:

* Values for the answers:

Correct answers	Percentage
1 - 10	3% – 35%.
11 - 21	37% - 67%.
21 - 30	70% - 100%.

Instructor's Name:	
Signature:	