

Google Talk for Developers

Overview

Open Communications

libjingle

- Developer Guide
 - Changelist
 - Important Concepts
 - How libjingle
 - Applications Work
 - Creating a libjingle Application
 - Signing In to a Server
 - Sending and Querying Presence
 - Set Up the Session Management Pathway
 - Making and Receiving Connections
 - Scenarios

Sample Applications

- File Share Application
- Voice Chat Application

Reference

- BasicPortAllocator Class
- Call Class
- Codec Struct
- ChannelManager

P2PChannelTransport Class

Wraps communication between the local and remote computer, handled by one or more **Connection** objects. It monitors these connections and acts as the intermediary for peer to peer data between **Transport** and the **Connection** object. Call **SendPacket** to send data, and connect to **SignalReadPacket** to read incoming data. **P2PTransport** creates this channel at the request of the **Session** object. See [Transports, Channels, and Connections](#) for more information.

These methods are not thread-safe. Any method that does not have a calling thread specified can be called from any thread.

Syntax

```
class P2PTransportChannel : public TransportChannelImp
    public talk_base::MessageHandler
```

Methods

The following table lists the public methods of **P2PTransportChannel**.

Name	Description
~P2PTransportChannel	Destructor. Deletes references to all PortAllocatorSession objects that it holds.
bool writable()	Indicates whether the channel is currently writable. This method must be called from the worker thread.
Connection* best_connection()	Retrieves the best connection for this channel, as determined by preference and writability.
const std::vector<Connection*> connections()	Retrieves a list of Connection objects managed by this object.
int GetError()	Retrieves the last error that the channel had.
int SendPacket (const char *data, size_t len)	Sends <i>data</i> of size <i>len</i> bytes to the connected computer over the best connection.
int SetOption (Socket::Option opt, int value)	Sets various sending options!. Currently, the only values are as follows: <ul style="list-style-type: none">OPT_DONTFRAGMENT 1 or 0 (true or false) Specifies whether data blocks sent to Send can be

Class		split up and sent in multiple packets. True means they cannot.
Connection Class		
FileStream Class		
HttpPortAllocator Class	P2PTransportChannel (const std::string & <i>name</i> ,	Constructor. This object must be created in the worker thread.
MediaChannel Class	const std::string & <i>session_type</i> ,	<ul style="list-style-type: none"> <i>name</i> An arbitrary value used to identify the channel. This value is passed down and reused for the port objects that it creates. The file share sample creates this name in <code>FileShareSession::RequestConnectedStream</code> and <code>FileShareSession::OnProxyAccept</code>; the voice chat example in the <code>VoiceChannel</code> constructor.
MediaEngine Class	P2PTransport* <i>transport</i> ,	<ul style="list-style-type: none"> <i>session_type</i> A unique session type associated with the session that created this object. See Session:session_type for more information.
MemoryStream Class	PortAllocator* <i>allocator</i>);	<ul style="list-style-type: none"> <i>transport</i> The Transport object creating this object. <i>allocator</i> The PortAllocator subclass created by the client.
P2PTransportCha...		
Port Class		
PresenceOutTask Class		
PresencePushTask Class		
Session Class	std::string& name ()	A unique name associated with this channel, created inside the code. This name is used to differentiate between multiple channels in the same Transport .
SessionClient Class		
SessionManager Class	Transport* GetTransport ()	Returns the Transport object that manages this channel.
SessionSendTask Class	void Connect ()	Begins the process of attempting to make a connection to the other client.
StreamEvent Enumeration	void OnChannelMessage (const buzz::XmlElement* <i>msg</i>)	Received an incoming message. Typically the incoming message is a candidate message describing the remote candidate, which triggers P2PTransportChannel to create connections to the remote candidate.
StreamInterface Class		
StreamResult Enumeration	void OnMessage (Message* <i>pmsg</i>)	The listener for multithreaded requests.
StreamState Enumeration	void OnSignalingReady ()	Called by SocketManager to indicate that the signaling thread is ready.
Task Class		
VoiceChannel Class	void Reset ()	Resets the object to the same state it had after the constructor was called. This method must be called from the worker thread.
XmppClient Class		
XmppEngine Class		
XmppPump		
XmppTask Class		
License	<h2>Signals</h2> <p>SignalChannelMessage<TransportChannelImpl*, buzz::XmlElement*> Sends an outgoing message through the Session object.</p> <p>SignalRequestSignaling Sent to indicate that the signaling thread is live.</p> <p>SignalReadPacket< TransportChannel *, const char *, size_t > Sent when the socket has a packet of data from the other computer.</p> <p>SignalConnectionMonitor<P2PTransportChannel*></p>	
Google Talk XMPP Extensions		
User Settings		

2014年7月18日	P2PChannelTransport Class - Google Talk for Developers — Google Developers
Off the Record Chats	Sent with a pointer to itself when the connection state changes.
Jingle Server	SignalReadableState<TransportChannel* > Sent when the channel is readable.
Discovery	SignalWritableState<TransportChannel*> Sent when the channel is writable.
Gmail Notifications	SignalConnectionMonitor< P2PTransportChannel * > Sent when the list of available connections is being evaluated. You should not need to listen for this signal.
Shared Status	SignalRouteChange <TransportChannel*, const talk_base::SocketAddress&> Sent when there is a change in the way that packets are being routed. The address indicates the address of the first hop in the new route, if this is known. If this cannot be determined or is not well-defined, then the channel may give an address of 0.
Attributes	
JID Domain Discovery	
Voicemail	
OAuth 2.0	
Authorization	Attributes: public
Additional Resources	
Other IM Clients	Declaration file: talk/p2p/base/p2ptransportchannel.h
Accessories	
Google Talk Blog	

All rights reserved.

Last updated March 23, 2012.



Explore

Products

Showcase

Events

Communities

Jobs

Connect

Blog

Google+ Community Groups

YouTube Channel

Report an Issue

Programs

Experts

Startups

Women Techmakers

Top Products

Ads

Analytics

Android

Apps

Cast

Chrome

Cloud

Glass

Google+

Maps

Wallet

YouTube

Terms of Use

Privacy Policy

English

▼