

## Exercise 1 – Basic network stuff

- Easy Use the arp command and paste the output from the arp table on your system:

arp - stands for Address resolution protocol is used to resolve ip address to to MAC addresses. MAC address is physical address of a device. Whenever a device needs to communicate with another device on a local area network it needs MAC address for that device. arp stores MAC addresses in his local cache ARP cache. ARP Table is used to keep the record of the IP address and MAC address of the devices source and destination device for the communication between two devices

ds@ds-HP-ProBook-440-G6:~\$ arp -a

```
? (192.168.100.236) at 00:21:b7:2f:bf:4f [ether] on enp2s0
? (192.168.100.149) at 00:21:b7:7e:d1:11 [ether] on enp2s0
? (192.168.100.137) at 00:21:b7:d5:f2:e1 [ether] on enp2s0
? (192.168.100.141) at 00:21:b7:d5:f2:b1 [ether] on enp2s0
70-100-168-192.ds11-erie.roc.ny.frontiernet.net (192.168.100.70) at 58:20:b1:4e:bc:23 [ether] on enp2s0
? (192.168.100.231) at e0:70:ea:f9:2c:10 [ether] on enp2s0
node-81s.pool-1-1.dynamic.totinternet.net (192.168.1.1) at 00:1f:33:28:81:80 [ether] on wlp0s20f3
? (192.168.100.147) at 00:21:b7:e5:37:ce [ether] on enp2s0
? (192.168.100.1) at 04:76:b0:26:5a:74 [ether] on enp2s0
nothing.attdns.com (192.168.100.135) at e0:70:ea:f9:2c:5a [ether] on enp2s0
? (192.168.100.44) at e0:70:ea:f9:2c:b4 [ether] on enp2s0
ETH-240-ML3471ND.kultur.uni-hamburg.de (192.168.100.134) at 00:21:b7:d5:f6:c6 [ether] on enp2s0
```

- Use the route command and paste the output from the routing table on your system:

```
**ip route**
```

```
default via 192.168.100.1 dev enp2s0 proto static metric 100
default via 192.168.1.1 dev wlp0s20f3 proto dhcp metric 600
169.254.0.0/16 dev wlp0s20f3 scope link metric 1000
192.168.1.0/24 dev wlp0s20f3 proto kernel scope link src 192.168.1.2 metric 600
192.168.100.0/24 dev enp2s0 proto kernel scope link src 192.168.100.33 metric 100
```

- Use the traceroute command on your system and observe the hops to Google's DNS, 8.8.8.8. Paste the full output from the command bellow showing all the hops from your system to 8.8.8.8.

- o traceroute is command line

### traceroute 8.8.8.8

```
traceroute to 8.8.8.8 (8.8.8.8), 30 hops max, 60 byte packets
 1 192.168.100.1 (192.168.100.1)  1.097 ms  1.012 ms  0.960 ms
 2 192.168.22.137 (192.168.22.137)  4.066 ms  4.105 ms  4.790 ms
 3 62.162.85.14 (62.162.85.14)  3.421 ms  3.759 ms  3.746 ms
 4 62.162.85.13 (62.162.85.13)  6.402 ms  6.323 ms  2.673 ms
 5 host-41.152.158.95.etisalat.com.eg (95.158.152.41)  4.961 ms  4.911 ms  *
 6 95.158.188.213 (95.158.188.213)  7.625 ms  9.867 ms  10.643 ms
 7 ecs-1-92-251-142.compute.hwclouds-dns.com (142.251.92.1)  5.136 ms bras-base-mtrlpq427b
 8 209.85.243.245 (209.85.243.245)  4.727 ms 142.250.60.187 (142.250.60.187)  8.121 ms 108
 9 dns.google (8.8.8.8)  8.011 ms  7.957 ms  7.904 ms
```


- Why would you need to use the ping command?

Answer:

ping command is used to check connectivity between two hosts.

```
ds@ds-HP-ProBook-440-G6:~$ ping 8.8.8.8
PING 8.8.8.8 (8.8.8.8) 56(84) bytes of data:
 64 bytes from 8.8.8.8: icmp_seq=1 ttl=116 time=7.82 ms
 64 bytes from 8.8.8.8: icmp_seq=2 ttl=116 time=8.13 ms
 64 bytes from 8.8.8.8: icmp_seq=3 ttl=116 time=7.75 ms
 64 bytes from 8.8.8.8: icmp_seq=4 ttl=116 time=7.76 ms
 64 bytes from 8.8.8.8: icmp_seq=5 ttl=116 time=7.72 ms
 64 bytes from 8.8.8.8: icmp_seq=6 ttl=116 time=7.79 ms
 64 bytes from 8.8.8.8: icmp_seq=7 ttl=116 time=7.49 ms
```

## Exercise 2 – TCP/IP Basics

Refer to the exhibit and answer the questions below. The letter symbol , represents the IP packet as it travels across the network. In the example shown, the laptop attempts to communicate with the web server in question. During its travel the packet will be forwarded across the network nodes and will eventually end up across six network interfaces before it reaches the web server. Each packet as part of the TCP/IP Stack contains fields for the source and destination MAC Address, IP Address and the TCP/UDP Port.

1. The laptop initiates communication with the web server and prepares a packet. What

SRC IP        100.20.30.10  
DST IP        80.70.60.100  
SRC MAC       AA:AA:AA:33:33:33  
DST MAC BB:BB:BB:11:11:01

2. RTR1 receives the packet on its IF-LAN interface, prepares it accordingly and forwards it out its IF- WAN. What would the packet look like at this stage?

SRC IP 100.20.30.10    DST IP 80.70.60.100    SRC MAC BB:BB:BB:11:11:02    DST MAC CC:CC:CC:22:22:02

3. RTR2 receives the packet on its IF-WAN interface, prepares it accordingly and forwards it out via IF- LAN. What would the packet look like at this stage?

SRC IP 100.20.30.10    DST IP 80.70.60.100    SRC MAC CC:CC:CC:22:22:01    DST MAC DD:DD:DD:77:77:77

4. The web server receives the packet and prepares a response packet back. What would the packet look like at this stage?

SRC IP 80.70.60.100    DST IP 100.20.30.10    SRC MAC DD:DD:DD:77:77:77    DST MAC CC:CC:CC:22:22:01

Since we are talking about web traffic (www) in the example, which transport layer protocol will most probably be used?

TCP

If we do a traffic analysis with a network packet monitoring tool like WireShark, what can we expect to see for the source and destination ports when the laptop sends the packet?

- SRC PORT: • DST PORT: 80 / 443

Similarly, and vice versa, what can we expect to see as destination ports when the Web server sends a response packet back?

- SRC PORT: 80 / 443 • DST PORT:

=====

- Write down the TCP/UDP ports of the most commonly used services bellow in the form of TCP[PORT] or UDP[PORT]. As an example, the first two answers have been filled in:

- HTTP - TCP80
- SNMP - UDP161
- HTTPS 443 port
- DNS client - DNS uses port 53
- DNS zone transfer - use TCP port 53
- SMTP
- SSH -os using 22
- FTP - os using 21
- Telnet - 23 or 2323
- MSSQL - 1433
- MySQL - 3306
- PostgreSQL - 5432
- RDP (Remote Desktop Protocol) - 3389
- NTP port 123 is used for NTP server communication and NTP clients use port 1023
- NFS - 2049

- **Exercise 3 – Traffic analysis and identifying the OSI layers of the network packets**

Prerequisite: Search online and get familiar with the TCP's three-way handshake. Learn how to capture the three way handshake using Wireshark. Install Wireshark on your computer and use it to capture traffic against a website or a server or your choice. It is recommended that you capture traffic against a simple website. Name and the IP address of the website you plan to capture traffic:

Analyze the TCP's three-way handshake and using screenshots from the Wireshark window answer the questions bellow:

\*enp2s0

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

not arp and not udp and not ssdp and not quic

No.	Time	Source	Destination	Protocol	Length	Info
22	0.75099243	192.168.100.33	20.199.120.182	TCP	74	55580 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM=1 TSval=2387088436 TSecr=0 WS=128
23	0.799357575	20.199.120.182	192.168.100.33	TCP	66	443 → 55580 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1440 WS=1 SACK_PERM=1
24	0.799493178	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=1 Ack=1 Win=64256 Len=0
25	0.800240297	192.168.100.33	20.199.120.182	TLsv1.2	571	Client Hello
28	0.847512375	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
29	0.847619146	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=1461 Win=64128 Len=0
30	0.847645862	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1461 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
31	0.847676051	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=2921 Win=63488 Len=0
32	0.847736339	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=2921 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
33	0.847753289	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=4381 Win=62592 Len=0
34	0.847869391	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=4381 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
35	0.847877135	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5841 Win=64128 Len=0
36	0.866823435	fe80::9084:c1b2:81a...ff02::1:fff6f:5387	ff02::1:fff6f:5387	ICMPv6	86	Neighbor Solicitation for fe80::3664:a9ff:fe6f:5387 from b8:ac:6f:30:18:bb
38	0.887812908	20.199.120.182	192.168.100.33	TLsv1.2	141	Server Hello, Certificate, Certificate Status, Server Key Exchange, Server Hello Done
39	0.887873877	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5928 Win=64128 Len=0
40	0.893678577	192.168.100.33	20.199.120.182	TLsv1.2	212	Client Key Exchange, Change Cipher Spec, Encrypted Handshake Message
42	0.93595463	20.199.120.182	192.168.100.33	TLsv1.2	105	Change Cipher Spec, Encrypted Handshake Message
43	0.938136641	192.168.100.33	20.199.120.182	TLsv1.2	329	Application Data

Frame 22: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface enp2s0, id 0  
 Ethernet II, Src: HewlettP\_62:77:0d (b0:0c:d1:62:77:0d), Dst: Cisco\_26:5a:74 (04:76:b0:26:5a:74)  
 Internet Protocol Version 4, Src: 192.168.100.33, Dst: 20.199.120.182  
 Transmission Control Protocol, Src Port: 55580, Dst Port: 443, Seq: 0, Len: 0

\*enp2s0

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

not arp and not udp and not ssdp and not quic

No.	Time	Source	Destination	Protocol	Length	Info
22	0.75099243	192.168.100.33	20.199.120.182	TCP	74	55580 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM=1 TSval=2387088436 TSecr=0 WS=128
23	0.799357575	20.199.120.182	192.168.100.33	TCP	66	443 → 55580 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1440 WS=1 SACK_PERM=1
24	0.799493178	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=1 Ack=1 Win=64256 Len=0
25	0.800240297	192.168.100.33	20.199.120.182	TLsv1.2	571	Client Hello
28	0.847512375	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
29	0.847619146	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=1461 Win=64128 Len=0
30	0.847645862	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1461 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
31	0.847676051	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=2921 Win=63488 Len=0
32	0.847736339	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=2921 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
33	0.847753289	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=4381 Win=62592 Len=0
34	0.847869391	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=4381 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
35	0.847877135	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5841 Win=64128 Len=0
36	0.866823435	fe80::9084:c1b2:81a...ff02::1:fff6f:5387	ff02::1:fff6f:5387	ICMPv6	86	Neighbor Solicitation for fe80::3664:a9ff:fe6f:5387 from b8:ac:6f:30:18:bb
38	0.887812908	20.199.120.182	192.168.100.33	TLsv1.2	141	Server Hello, Certificate, Certificate Status, Server Key Exchange, Server Hello Done
39	0.887873877	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5928 Win=64128 Len=0
40	0.893678577	192.168.100.33	20.199.120.182	TLsv1.2	212	Client Key Exchange, Change Cipher Spec, Encrypted Handshake Message
42	0.93595463	20.199.120.182	192.168.100.33	TLsv1.2	105	Change Cipher Spec, Encrypted Handshake Message
43	0.938136641	192.168.100.33	20.199.120.182	TLsv1.2	329	Application Data

Frame 23: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface enp2s0, id 0  
 Ethernet II, Src: Cisco\_26:5a:74 (04:76:b0:26:5a:74), Dst: HewlettP\_62:77:0d (b0:0c:d1:62:77:0d)  
 Internet Protocol Version 4, Src: 20.199.120.182, Dst: 192.168.100.33  
 Transmission Control Protocol, Src Port: 55580, Seq: 0, Ack: 1, Len: 0

\*enp2s0

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

not arp and not udp and not ssdp and not quic

No.	Time	Source	Destination	Protocol	Length	Info
22	0.75099243	192.168.100.33	20.199.120.182	TCP	74	55580 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM=1 TSval=2387088436 TSecr=0 WS=128
23	0.799357575	20.199.120.182	192.168.100.33	TCP	66	443 → 55580 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1440 WS=1 SACK_PERM=1
24	0.799493178	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=1 Ack=1 Win=64256 Len=0
25	0.800240297	192.168.100.33	20.199.120.182	TLsv1.2	571	Client Hello
28	0.847512375	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
29	0.847619146	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=1461 Win=64128 Len=0
30	0.847645862	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1461 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
31	0.847676051	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=2921 Win=63488 Len=0
32	0.847736339	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=2921 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
33	0.847753289	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=4381 Win=62592 Len=0
34	0.847869391	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=4381 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
35	0.847877135	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5841 Win=64128 Len=0
36	0.866823435	fe80::9084:c1b2:81a...ff02::1:fff6f:5387	ff02::1:fff6f:5387	ICMPv6	86	Neighbor Solicitation for fe80::3664:a9ff:fe6f:5387 from b8:ac:6f:30:18:bb
38	0.887812908	20.199.120.182	192.168.100.33	TLsv1.2	141	Server Hello, Certificate, Certificate Status, Server Key Exchange, Server Hello Done
39	0.887873877	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5928 Win=64128 Len=0
40	0.893678577	192.168.100.33	20.199.120.182	TLsv1.2	212	Client Key Exchange, Change Cipher Spec, Encrypted Handshake Message
42	0.93595463	20.199.120.182	192.168.100.33	TLsv1.2	105	Change Cipher Spec, Encrypted Handshake Message
43	0.938136641	192.168.100.33	20.199.120.182	TLsv1.2	329	Application Data

Frame 24: 54 bytes on wire (432 bits), 54 bytes captured (432 bits) on interface enp2s0, id 0  
 Ethernet II, Src: HewlettP\_62:77:0d (b0:0c:d1:62:77:0d), Dst: Cisco\_26:5a:74 (04:76:b0:26:5a:74)  
 Internet Protocol Version 4, Src: 192.168.100.33, Dst: 20.199.120.182  
 Transmission Control Protocol, Src Port: 55580, Dst Port: 443, Seq: 1, Ack: 1, Len: 0

1. What is the source IP (of the initiating host): 192.168.100.33
2. What is the destination IP? (target website): 20.199.120.182

Identify the Network Interface (Layer 1 & 2) section of the SYN packet and paste a screenshot from it:

FileEditViewGoCaptureAnalyzeStatisticsTelephonyWirelessToolsHelp

not arp and not udp and not ssl and not quic

No.	Time	Source	Destination	Protocol	Length	Info
0	0.267283960	Cisco6_21:45:3d	LDLP Multicast	LDLP	80	MA:ac1a:0b:12:45:3c In/E1 120
22	0.756099243	192.168.100.33	20.199.120.182	TCP	74	55580 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM=1 TSval=2387088436 TSecr=0 WS=128
23	0.756391378	192.168.100.33	192.168.100.33	TCP	60	443 → 55580 [SYN, ACK] Seq=0 Ack=1 Win=0 Len=0 MSS=1440 WS=1 SACK_PERM=1
24	0.799493178	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=1 Ack=1 Win=64256 Len=0
25	0.800240297	192.168.100.33	20.199.120.182	TLV51.2	571	Client Hello
28	0.847512375	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
29	0.847619146	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=1461 Win=64128 Len=0
30	0.847645862	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1461 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
31	0.847676951	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=2921 Win=63488 Len=0
32	0.847736339	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=2921 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
33	0.847753289	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=4381 Win=62592 Len=0
34	0.847866391	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=4381 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
35	0.847877135	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5841 Win=64128 Len=0
36	0.866823435	fe80::9084:c1b2:81a...ff02::1:ffef:5387	ICMPv6	86	Neighbor Solicitation for fe80::3664:a9ff:feef:5387 from b8:ac:6f:30:18:bb	
38	0.887812908	20.199.120.182	192.168.100.33	TLV51.2	141	Server Hello, Certificate, Certificate Status, Server Key Exchange, Server Hello Done
39	0.887873877	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5928 Win=64128 Len=0
40	0.893678577	192.168.100.33	20.199.120.182	TLV51.2	212	Client Key Exchange, Change Cipher Sec, Encrypted Handshake Message
42	0.935895463	20.199.120.182	192.168.100.33	TLV51.2	185	Change Cipher Sec, Encrypted Handshake Message
43	0.938136641	192.168.100.33	20.199.120.182	TLV51.2	329	Application Data

\* Frame 22: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface enp2s0, id 0

\* Ethernet II, Src: HewlettP\_62:77:0d (b8:0c:d1:62:77:0d), Dst: Cisco\_26:5a:74 (04:76:b0:26:5a:74)

\* Destination: Cisco\_26:5a:74 (04:76:b0:26:5a:74)

\* Source: HewlettP\_62:77:0d (b8:0c:d1:62:77:0d)

Address: HewlettP\_62:77:0d (b8:0c:d1:62:77:0d)

.....0. .... = LG bit: Globally unique address (factory default)

.....0. .... = IG bit: Individual address (unicast)

Type: IPv4 (0x0800)

\* Internet Protocol Version 4, Src: 192.168.100.33, Dst: 20.199.120.182

\* Transmission Control Protocol, Src Port: 55580, Dst Port: 443, Seq: 0, Len: 0

0000 04 76 b0 26 5a 74 b8 0c d1 62 77 0d 08 00 45 00 -v-Zt- -bw- E-

0010 00 3c f0 a2 40 00 40 06 97 d2 c0 a8 64 21 14 c7 -K- 0-0- ...d-

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

not arp and not udp and not sctp and not quic

No.	Time	Source	Destination	Protocol	Length	Info
0	0.267283860	192.168.100.34	192.168.100.34	LLDP	66	66 00:0c:29:16:21:45:3e IN/161.120
22	0.750829243	192.168.100.33	192.168.100.182	TCP	74	55580 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM=1 TSval=2387088436 TSecr=0 WS=128
23	0.799357575	20.199.120.182	192.168.100.33	TCP	66	443 → 55580 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1440 WS=1 SACK_PERM=1
24	0.799493178	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=1 Ack=1 Win=64256 Len=0
25	0.806240297	192.168.100.33	20.199.120.182	TLsv1.2	571	Client Hello
26	0.847512375	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
29	0.847619140	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=1461 Win=64128 Len=0
29	0.847645862	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1461 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
31	0.847676051	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=2921 Win=63488 Len=0
32	0.847736339	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=2921 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
33	0.847753289	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=4381 Win=62592 Len=0
34	0.847860391	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=4381 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
35	0.847871135	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5641 Win=64128 Len=0
35	0.847883435	fe80::9804:c1b2::81a:f02::1::ffff:5387	fe80::9804:c1b2::81a:f02::1::ffff:5387	ICMPv6	86	Neighbor Solicitation for fe80::3064:aaff:fe0f:5387 from b8:ac:6f:30:18:bb
36	0.887812908	20.199.120.182	192.168.100.33	TLsv1.2	141	Server Hello, Certificate, Certificate Status, Server Key Exchange, Server Hello Done
39	0.887873877	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5928 Win=64128 Len=0
40	0.893678577	192.168.100.33	20.199.120.182	TLsv1.2	212	Client Key Exchange, Change Cipher Spec, Encrypted Handshake Message
42	0.935095463	20.199.120.182	192.168.100.33	TLsv1.2	105	Change Cipher Spec, Encrypted Handshake Message
43	0.938136641	192.168.100.33	20.199.120.182	TLsv1.2	329	Application Data
46	0.980723535	20.199.120.182	192.168.100.33	TLsv1.2	333	Application Data
47	0.982214728	192.168.100.33	20.199.120.182	TLsv1.2	298	Application Data
50	1.022717170	20.199.120.182	192.168.100.33	TLsv1.2	157	Application Data
51	1.023882534	192.168.100.33	20.199.120.182	TLsv1.2	538	Application Data
54	1.104912134	Cisco 20:5a:08	CDP/VTP/DTP/PagP/UDLD..DTP		60	Dynamic Trunk Protocol
55	1.126510673	20.199.120.182	192.168.100.33	TCP	60	443 → 55580 [ACK] Seq=6361 Ack=1589 Win=8192 Len=0
61	1.428847535	20.199.120.182	192.168.100.33	TLsv1.2	407	Application Data
62	1.430472922	192.168.100.33	20.199.120.182	TLsv1.2	277	Application Data

Source: HewlettP\_62:77:0d (b0:0c:d1:62:77:0d)  
 Address: HewlettP\_62:77:0d (b0:0c:d1:62:77:0d)  
 ....0. .... = LG bit: Globally unique address (factory default)  
 ....0. .... = IG bit: Individual address (unicast)  
 Type: IPv4 (0x000)

Internet Protocol Version 4, Src: 192.168.100.33, Dst: 20.199.120.182

Transmission Control Protocol, Src Port: 55580, Dst Port: 443, Seq: 0, Len: 0

Source Port: 55580  
 Destination Port: 443  
 [Stream index: 0]  
 [Conversation completeness: Incomplete, DATA (15)]  
 [TCP Segment Len: 0]  
 Sequence Number: 0 (relative sequence number)  
 Sequence Number (raw): 1208980315  
 [Next Sequence Number: 1 (relative sequence number)]  
 Acknowledgment Number: 0  
 Acknowledgment Number (raw): 0

0020 75 b6 d9 1c 01 bb 48 0f 93 5b 00 00 00 a0 02 x-----H [-----  
 0030 fa f0 b2 75 00 00 02 04 05 b4 04 02 08 0a 8e 48 -u-----H [-----  
 0040 14 34 00 00 00 00 01 03 03 07 .-----4-----

Identify the Network Layer 3 section of the SYN/ACK packet and paste a screenshot from it:



**File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help**

**[ ] not arp and not udp and not sddp and not quick**

No.	Time	Source	Destination	Protocol	Length	Info
22	0.750699243	192.168.100.33	20.199.120.182	TCP	74	55580 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM=1 TSval=2387088436 TSecr=0 WS=128
23	0.799357575	20.199.120.182	192.168.100.33	TCP	66	443 → 55580 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1440 WS=1 SACK_PERM=1
24	0.799493178	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=1 Ack=1 Win=64256 Len=0
25	0.806240297	192.168.100.33	20.199.120.182	TLsv1.2	571	Client Hello
26	0.847512375	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
27	0.847619146	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=1461 Win=64128 Len=0
28	0.847645862	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1461 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
29	0.847676651	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=2921 Win=63488 Len=0
30	0.847736339	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=2921 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
31	0.847753289	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=4381 Win=62592 Len=0
32	0.847806991	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=4381 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
33	0.847877135	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5841 Win=64128 Len=0
36	0.866823435	fe80::9084:c1b2:81a...f2::1:f6ff:5387	fc::1:f6ff:5387	ICMPv6	86	Neighbor Solicitation for fe80::3664:aaff:fe6f:5387 from b8:ac:6f:30:18:b0
38	0.887812986	20.199.120.182	192.168.100.33	TLsv1.2	141	Server Hello, Certificate, Certificate Status, Server Key Exchange, Server Hello Done
39	0.887873877	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5928 Win=64128 Len=0
40	0.893678577	192.168.100.33	20.199.120.182	TLsv1.2	212	Client Key Exchange, Change Cipher Spec, Encrypted Handshake Message
42	0.935095463	20.199.120.182	192.168.100.33	TLsv1.2	105	Change Cipher Spec, Encrypted Handshake Message
43	0.938186641	192.168.100.33	20.199.120.182	TLsv1.2	329	Application Data
46	0.980723535	20.199.120.182	192.168.100.33	TLsv1.2	333	Application Data
47	0.982214728	192.168.100.33	20.199.120.182	TLsv1.2	208	Application Data
50	1.022717170	20.199.120.182	192.168.100.33	TLsv1.2	157	Application Data
51	1.023882354	192.168.100.33	20.199.120.182	TLsv1.2	538	Application Data
54	1.046221434	cisco_26:5a:74	cisco_26:5a:74	CDPvRTP/PagP/UDP	60	Dynamic Configuration Protocol
55	1.126516073	20.199.120.182	192.168.100.33	TCP	60	443 → 55580 [ACK] Seq=6361 Ack=1589 Win=8192 Len=0
61	1.428847535	20.199.120.182	192.168.100.33	TLsv1.2	407	Application Data
62	1.430472922	192.168.100.33	20.199.120.182	TLsv1.2	277	Application Data

---

```

Frame 23: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface enp2s0, id 0
Ethernet II, Src: Cisco_26:5a:74 (04:76:b0:26:5a:74), Dst: HewlettP_62:77:0d (b0:0c:d1:62:77:0d)
  Destination: HewlettP_62:77:0d (b0:0c:d1:62:77:0d)
    Address: HewlettP_62:77:0d (b0:0c:d1:62:77:0d)
      ... .. = LG bit: Globally unique address (factory default)
      ... .. = IG bit: Individual address (unicast)
  Source: Cisco_26:5a:74 (04:76:b0:26:5a:74)
    Address: Cisco_26:5a:74 (04:76:b0:26:5a:74)
      ... .. = LG bit: Globally unique address (factory default)
      ... .. = IG bit: Individual address (unicast)
Type: IPv4 (0x0800)

Internet Protocol Version 4, Src: 20.199.120.182, Dst: 192.168.100.33
Transmission Control Protocol, Src Port: 443, Dst Port: 55580, Seq: 0, Ack: 1, Len: 0
  
```

---

```

0000 b0 0c d1 62 77 0d 04 76 b0 26 5a 74 08 00 45 00 ...bw.v..&TzE-
0010 09 34 f2 8f 48 00 0f 06 6e ed 14 c7 78 b6 c0 a8 .4...@.f...x...
0020 21 11 01 00 00 00 00 00 e9 40 48 0f 93 5c 00 12 d1 :?...|...|...
0030 20 00 ac 29 00 00 00 00 00 00 01 81 83 00 01 01 20...Q...|...|...
  
```

Identify the Transport Layer 4 section of the ACK packet and paste a screenshot from it bellow:

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

not arp and not udp and not sntp and not quick

No.	Time	Source	Destination	Protocol	Length	Info
9	0.267283668	Cisco_21:45:3d	LDLP Multicast	LDLP	60	MA/ac:a0:10:b0:21:45:3c IN/e1 120
22	0.756099243	192.168.100.33	20.199.120.182	TCP	74	55580 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 SACK_PERM=1 TSval=2387088436 TSecr=0 WS=128
23	0.759357575	20.199.120.182	192.168.100.33	TCP	60	443 → 55580 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1448 WS=1 SACK_PERM=1
24	0.76493176	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=1 Ack=1 Win=64256 Len=0
25	0.808240297	192.168.100.33	20.199.120.182	TLV1.2	571	Client Hello
28	0.847512375	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
29	0.847619146	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=1461 Win=64128 Len=0
30	0.847645862	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=1461 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
31	0.847676051	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=2921 Win=63488 Len=0
32	0.847736339	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=2921 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
33	0.847753289	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=4381 Win=62592 Len=0
34	0.79089391	20.199.120.182	192.168.100.33	TCP	1514	443 → 55580 [PSH, ACK] Seq=4381 Ack=518 Win=7675 Len=1460 [TCP segment of a reassembled PDU]
35	0.847877135	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5841 Win=64128 Len=0
36	0.866823435	fe80::9084:c1b2:81a...ff02::1:ff6f:5387	ICMPv6	86	Neighbor Solicitation for fe80::3664:a9ff:fe0f:5387 from b8:ac:6f:30:18:bb	
38	0.887812908	20.199.120.182	192.168.100.33	TLV1.2	141	Server Hello, Certificate, Certificate Status, Server Key Exchange, Server Hello Done
39	0.887873877	192.168.100.33	20.199.120.182	TCP	54	55580 → 443 [ACK] Seq=518 Ack=5928 Win=64128 Len=0
40	0.893678577	192.168.100.33	20.199.120.182	TLV1.2	212	Client Key Exchange, Change Cipher Spec, Encrypted Handshake Message
42	0.935095463	20.199.120.182	192.168.100.33	TLV1.2	108	Change Cipher Spec, Encrypted Handshake Message
43	0.938136641	192.168.100.33	20.199.120.182	TLV1.2	329	Application Data

▶ Frame 22: 74 bytes on wire (592 bits), 74 bytes captured (592 bits) on interface enp2s0, id 0

▶ Ethernet II, Src: Hewlett\_P\_62:77:0d (b0:0c:d1:62:77:0d), Dst: Cisco\_26:5a:74 (04:76:b0:26:5a:74)

▶ Destination: Cisco\_26:5a:74 (04:76:b0:26:5a:74)

▶ Source: Hewlett\_P\_62:77:0d (b0:0c:d1:62:77:0d)

▶ Address: Hewlett\_P\_62:77:0d (b0:0c:d1:62:77:0d)

.....0. .... = LG bit: Globally unique address (factory default)

.....0. .... = IG bit: Individual address (unicast)

Type: IPv4 (0x0800)

▶ Internet Protocol Version 4, Src: 192.168.100.33, Dst: 20.199.120.182

▶ Transmission Control Protocol, Src Port: 55580, Dst Port: 443, Seq: 0, Len: 0

0000 04 76 b0 26 5a 74 b0 0c d1 62 77 0d 08 00 00 00    v Zt...bw...E..

0010 80 3c fe a2 40 00 40 06 97 d2 c0 a8 64 21 14 c 7    <...@...d!...

Look closely at the L2 section of the three-way handshake packet details. Each of them shows the source and destination MAC address of the packets. Who is the owner of the destination MAC address of the SYN packet?

### Exercise 4 – Hacking mockup (for Bonus points)

Use Wireshark to capture the packet's application layer data and discover the implications of using unencrypted communication over a network. It is recommended that you use your own Linux Virtual Machine on your system on which you need to configure a telnet server. From your own system try to login with a Telnet on the target VM all while capturing the traffic with a Wireshark. As a proof of competition for this exercise paste in below a screenshot of the application layer data containing visible username and password.

Wireshark - Follow TCP Stream (tcp.stream eq 11) - Adapter for loopback traffic capture

No.	Time	Source	Destination	Protocol
130	14.539145	:::1	:::1	TCP
131	14.539173	:::1	:::1	TCP
132	14.539191	:::1	:::1	TCP
136	14.541641	:::1	:::1	HTTP
137	14.541671	:::1	:::1	TCP
140	14.988878	:::1	:::1	TCP
141	14.988107	:::1	:::1	TCP
142	14.988510	:::1	:::1	HTTP
143	14.988525	:::1	:::1	TCP
144	14.992346	:::1	:::1	HTTP
145	14.992373	:::1	:::1	TCP
146	14.992938	:::1	:::1	HTTP
147	14.992950	:::1	:::1	TCP
148	14.996803	:::1	:::1	TCP
149	14.996831	:::1	:::1	TCP
154	15.228330	:::1	:::1	TCP
155	15.228359	:::1	:::1	TCP
156	15.228897	:::1	:::1	HTTP
157	15.228914	:::1	:::1	TCP
158	15.363886	:::1	:::1	TCP
159	15.363114	:::1	:::1	TCP
164	15.364729	:::1	:::1	HTTP
165	15.364753	:::1	:::1	TCP
166	15.371698	:::1	:::1	TCP
167	15.371727	:::1	:::1	TCP
190	15.586464	:::1	:::1	HTTP
191	15.586426	:::1	:::1	TCP
192	15.588862	:::1	:::1	HTTP
193	15.588886	:::1	:::1	TCP
219	15.836411	:::1	:::1	HTTP
220	15.836464	:::1	:::1	TCP
227	15.870394	:::1	:::1	HTTP
228	15.870409	:::1	:::1	TCP
229	16.097103	:::1	:::1	HTTP
230	16.097151	:::1	:::1	TCP
237	16.336255	:::1	:::1	HTTP
238	16.336268	:::1	:::1	TCP
239	16.586856	:::1	:::1	HTTP
240	16.586870	:::1	:::1	TCP
247	16.842077	:::1	:::1	HTTP
248	16.842138	:::1	:::1	TCP
249	17.052717	:::1	:::1	HTTP
250	17.052742	:::1	:::1	TCP

POST /mkoglasnik.dev/login/ HTTP/1.1  
Host: localhost  
Connection: keep-alive  
Content-Length: 40  
Cache-Control: max-age=0  
sec-ch-ua: "Google Chrome";v="111", "Not(A;Brand";v="8", "Chromium";v="111"  
sec-ch-ua-mobile: ?0  
sec-ch-ua-platform: "Windows"  
Upgrade-Insecure-Requests: 1  
Origin: http://localhost  
Content-Type: application/x-www-form-urlencoded  
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/111.0.0.0 Safari/537.36  
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/png,\*/\*;q=0.8,application/signed-exchange;v=b3;q=0.7  
Sec-Fetch-Site: same-origin  
Sec-Fetch-Mode: navigate  
Sec-Fetch-User: ?1  
Sec-Fetch-Dest: document  
Referer: http://localhost/mkoglasnik.dev/login/  
Accept-Encoding: gzip, deflate, br  
Accept-Language: en-GB,en;q=0.9,mk-MK;q=0.8,mk;q=0.7,en-US;q=0.6  
Cookie: PHPSESSID=iaid0bvgufpodd16jh8n8c8fmr

mail@darkoavramovski.com:password=1234567890 Found

Date: Wed, 15-Mar-2023 09:17:51 GMT  
Server: Apache/2.4.54 (Ubuntu) OpenSSL/1.1.1f PHP/8.2.0  
X-Powered-By: PHP/8.2.0  
Expires: Thu, 19 Nov 1981 08:52:00 GMT  
Cache-Control: no-store, no-cache, must-revalidate  
Pragma: no-cache  
Location: ../profile  
Keep-Alive: timeout=5, max=100  
Connection: Keep-Alive  
Transfer-Encoding: chunked  
Content-Type: text/html; charset=UTF-8

308  
<!DOCTYPE html>  
<html lang="en">

<head>  
meta charset="utf-8"  
meta name="viewport" content="width=device-width, initial-scale=1"  
<title>mkoglasnik.mk | .....</title>  
<link rel="stylesheet" href="assets/css/bulma.css">  
<link rel="stylesheet" href="assets/css/main.css">  
<link rel="stylesheet" href="assets/css/custom.css">  
<link rel="stylesheet" href="assets/css/swiper-bundle.css">

Enter conversation (47 KB) Show data as ASCII Stream 11 Find Next

Frame 140: 15168 bytes on wire (121344 bits), 15168 bytes captured  
> Null/Loopback  
> Internet Protocol Version 6, Src: ::1, Dst: ::1  
> Transmission Control Protocol, Src Port: 80, Dst Port: 54969, Seq: 3052837656, Win: 65535, Len: 0

Wireshark\_NPF\_Loopback62X11.pcapng

Packets: 262 · Displayed: 43 (16.4%) · Dropped: 0 (0.0%) Profile: Default

10:19 AM 3/15/2023