



Ennobin

The objective of this RFB is to invite prospective Bidders to submit Bids for the supply, delivery and warranty of the Deliverables in the following six (6) categories, as described in this RFB:

- Category 1: 14-15' Aluminum Boat, Motor and Trailer
- Category 2: 16-16.5' Aluminum Boat, Motor and Trailer
- Category 3: 19-20.5' Aluminum Boat, Motor and Trailer
- Category 4: 21'8" to 22'8" Aluminum Skiff, Motor and Trailer
- Category 5: 24' to 26' Aluminum Skiff, Motor and Trailer
- Category 6: 21'8" to 22'8" Aluminum Skiff Dive Vessel, Motor and Trailer

The Ontario Provincial Police (OPP) marine unit enforces applicable statutes on Ontario waterways and provides educational opportunities for area boating organizations.

The vessels that the Ministry is seeking will be operated on lakes and rivers and will be used to perform search and rescue missions, law enforcement, and waterways security.

1.3.1 Specifications and Standards

(a) The Vendor(s) shall provide new vessels (2024 model or a newer model) as ordered by the Ministry that are constructed to the specifications for each category as outlined in Part 5 – Specifications and Requirements.

(b) The vessel(s) supplied by the Vendor(s) to the Ministry must be a proven design. The design of the hull for the proposed vessel(s) must be based on previously constructed hull design produced by the manufacturer.

(c) The trailer(s) supplied by the Vendor to the Ministry must comply with Transport Canada Standards and Canada Motor Vehicle Safety Standards ("CMVSS"). The trailer(s) supplied by the Vendor to the Ministry must be rated gross vehicle weight rating (GVWR) to accommodate the specified vessel(s). The trailer(s) supplied by the Vendor to the Ministry must be delivered completely assembled and serviced.

(d) During the production of the vessel(s) by the Vendor or the Vendor's manufacturer, if the Vendor is a distributor only, the Vendor (and if applicable, the Vendor's



Ennobin

manufacturer, if the Vendor is a distributor only) shall participate in regular teleconferences with the Ministry as required by the Ministry, and will permit the Ministry to attend the Vendor's production facility (or if applicable, the manufacturer's production facility as arranged by the Vendor) to ensure that the vessel(s) are being manufactured according to the specifications and standards outlined in this RFB as well as the drawings or blueprints provided by the Preferred Bidder, and approved by the Ministry. Where the Vendor is a distributor, it will be the responsibility of the Vendor to arrange the visits for the Ministry and the Vendor to attend the manufacturer's production facility, if requested by the Ministry.

(e) The Vendor shall ensure that the Deliverables meet the specifications in Part 5 – Specifications and Requirements and the requirements in this Part 3 - The Deliverables.

1.4 Warranty

(a) The Vendor shall provide a minimum twelve (12) month warranty for commercial use for all Deliverables at no additional cost to the Ministry. This warranty shall be all inclusive of all repairs, parts, technical support, shipping expenses, and labour expenses.

(b) The Vendor shall also provide a minimum ten (10) year limited structural hull warranty for the supplied vessel(s) to cover costs associated with addressing any hull workmanship or structural defects in the Deliverables.

(c) The above warranties will take effect upon the Ministry's written acceptance of the Deliverables after they have been delivered to OPP Headquarters at the location in section 1.10 of this Part 3 – The Deliverables and inspected and accepted by the Ministry as set out in the Contract

(d) The Vendor shall have available to the Ministry, designated service representative(s) who have technical knowledge and expertise and who are capable of handling warranty services for the Deliverables.

(e) The Vendor must be able to facilitate the handling of warranty returns, recalls, and repairs within the province of Ontario either through its own facility or through

arrangements with an authorized and approved Subcontractor. The Vendor must have this facility or these arrangements in place prior to delivery of any Deliverables to the Ministry.

(f) Shipping charges for the return and replacement of the Deliverables under warranty will be the responsibility of the Vendor.

(g) The Vendor shall ensure that it has the necessary mechanisms and procedures in place to deal and resolve all warranty issues in a timely manner eliminating any unnecessary extended down time. Once a warranty incident has been identified, the Vendor must communicate with the Ministry within one (1) Business Day of initial contact by the Ministry to begin resolution of the incident. The turnaround time for the Vendor to resolve any warranty issues is ten (10) days from time of notification by the Ministry of the issue or within a time frame agreed to by the Ministry.

(h) Following all work pertaining to warranty repairs, the Vendor shall submit a report listing all services rendered and provide the Ministry with a documented update on the performance and current conditions of the equipment.

(i) This section 1.4 shall survive termination or expiry of the Contract for the term of any warranty.

1.5 Technical Support and Preventative Maintenance

The Ministry will be responsible for the maintenance of the vessel(s).

During the minimum twelve (12) month commercial warranty period for the Deliverables as described in Section 1.4, the Vendor shall provide technical support to the Ministry at no additional cost to the Ministry to ensure the Deliverables are functional as required during this warranty period.

The Vendor shall provide technical support via various methods, including and not limited to phone and email.

The Vendor shall provide the Ministry with a preventive maintenance schedule so that the Ministry can follow the manufacturer's recommendations for servicing.

This section shall survive termination or expiry of the Contract for the term of any warranty



Ennobin

period.

Sea Trial Evaluation – Category 3, 4, 5 and 6 Only

The Vendor(s) for category 3, 4, 5 and 6 only will be required to provide one (1) vessel (with trailer and motor) to complete a sea trial. The Deliverables, with all required equipment must be constructed and ready for a sea trial within sixteen (16) weeks of the order being placed by the Ministry.

Prior to delivery of the Deliverables to the Ministry, the Vendor shall notify the Ministry that construction of the Deliverables is complete. The Ministry will schedule a sea trial evaluation, which will be conducted by the Ministry. The location of the sea trial evaluation is expected to be Lake Couchiching in Ontario, but the location may change to another location within Ontario depending on weather and ice conditions. The Ministry will advise the Vendor as to the specific location and date and time for sea trial evaluation.

The Vendor shall arrange, at its expense, for the Deliverables to be delivered to the location where the sea trial will be conducted. A representative of the Vendor shall be present to provide on-site and on-board to provide technical assistance and to respond to any questions that the Ministry may have during the sea trial evaluation of the Deliverables, including the testing of all hardware components to ensure they are functioning as required, and to the manufacturer's specifications.

At the sea trial evaluation location, the Ministry will conduct an on-site and on the water inspection of the Deliverables. The purpose of the inspection will be to ensure the Deliverables meet all requirements and specifications as per Part 5 – Specifications and Requirements, that it can meet the minimum cruising speed specified in Part 5 and that it meets the additional requirements below. The inspection will also ensure that the Deliverables are free of any defects and were not damaged in the course of delivery to the sea trial evaluation. The results of this inspection will be recorded in writing on Part 7 - Acceptance Checklist.

The sea trial evaluation will also consist of evaluating the vessel's ability, with four (4)



Ennobin

occupants in the vessel with a full capacity of fuel, to meet the following (all of which will also be included on Part 7 - Acceptance Checklist):

- Ability to handle enforcement type manoeuvres such as high-speed turns and tight manoeuvring
- High speed stability
- Controlled performance at high speed

After the sea trial evaluation, the Ministry will conduct an inspection, to record the condition of the vessel to ensure that there was no structural or mechanical damage to any part of the vessel.

In the event that the Ministry determines as a result of the sea trial evaluation that the Vendor's vessel does not comply with one or more of the specification requirements in Part 7 – Acceptance Checklist, or otherwise does not meet the requirements in this RFB, the Vendor will have seven (7) Business Days from the Ministry's notice, or as agreed upon by the Ministry, to address the issue(s) at no additional cost to the Ministry and the Vendor will be required to present the Deliverables for a second sea trial evaluation at a location and time arranged with the Ministry in accordance with the above process and evaluation. If the Ministry determines as a result of the second sea trial evaluation that the Vendor's vessel does not meet the RFB requirements, including but not limited to all requirements set out in this section, the Ministry may reject the vessel and terminate the Agreement without any liability on the part of the Ministry to the Vendor.

interim Acceptance

If the Deliverables provided by the Vendor in the sea trial (first or if necessary, a second sea trial) meets the RFB requirements, the Ministry will provide the Vendor with interim acceptance by signing Part 7 - Acceptance Checklist used for the evaluation. If the Ministry provides this interim acceptance of the Deliverables after the sea trial evaluation, the Vendor shall deliver the Deliverables to the Ministry as outlined in section 1.10, within five (5) Business Days, or as otherwise instructed by the Ministry.

Delivery Location



Ennobin

For categories 1 and 2 and in the case of categories 3, 4, 5 and 6, if the Ministry provides interim acceptance of the Vendor's Deliverables after the sea trial, the Vendor shall arrange, as its expense, for delivery of the Deliverables FOB Destination to the designated loading dock at OPP General Headquarters, 777 Memorial Avenue, Orillia, Ontario on a date and time approved in advance by the Ministry.

All applicable surcharges, freight and delivery charges must be included in all prices quoted in the Commercial Envelope.

Delivery charges shall not be accepted or paid if indicated as a surcharge on the invoice.

The Vendor is required to ensure all Deliverables are delivered in accordance with the specifications and to the designated receiving area.

1.11 Inspection upon Delivery and Final Acceptance

Once the Ministry is satisfied that the Deliverables are free of any defects and were not damaged in the course of delivery, the Ministry will give final acceptance by receiving the vessel(s) and the documents for each vessel listed in 1.13.

Damaged or Defective Shipments

If, upon delivery, the Ministry finds any of the Deliverables in a damaged or defective condition, or not in conformity with that Ministry's order, including, but not limited to, manufacturing defects, imperfections or design deficiencies, the Ministry shall have the right, exercisable in the Ministry's absolute discretion, not to accept the Deliverables.

Documents to be provided Upon Delivery

The following documents are to be provided upon delivery of the vessel(s) (with the motor(s) and trailer(s)) to OPP General Headquarters by a representative of the Vendor:

- Bill of Sale (bill of sale to be in a form acceptable to the Ministry that includes, at a minimum, the Ministry's purchase order number, the vessel V.I.N., make and model, the price of the Deliverables and HST, if applicable, listed separately)
- Manufacturer's Certificate of Origin
- New Vehicle Information Sheet (NVIS)
- Results of small craft stability test



Ennobin

- Warranty documentation for all supplied or vendor installed equipment
- Preventive Maintenance Schedule.

Training and Operational Instruction

The Vendor(s) will be required to provide at a minimum a one (1) day on-site training session to a maximum of ten (10) of the Ministry's personnel at OPP General Headquarters, 777 Memorial Avenue, Orillia, Ontario at no additional cost to the Ministry.

The Vendor must obtain confirmation of date and time from the Ministry Representative after delivery of the Deliverables to OPP Headquarters.

Training must include, at a minimum, training on:

- a. Transporting vessel
- b. Launching and inspection activities
- c. Use and maintenance of on-board equipment, instruments and tools
- d. Use and maintenance of safety equipment

The Vendor shall also provide English language manual(s) for the vessel(s) in a digital format to the Ministry at no additional cost to the Ministry.



Ennobin

1.0 Category 1: 14-15' Aluminum Boat, Motor and Trailer

The vessel, motor and trailer must meet the following specifications:

Hull	Minimum length of 14.0 feet up to a maximum of 15.0 feet in length
	Beam minimum of 68 inches
	No floor
	Riveted Hull, minimum thickness of 0.060 inch
	Bow eye
	Hull Type – V bottom
	Marine grade aluminum
	Transom drain plug
	All hardware to be stainless steel, chromed bronze or anodized aluminum.
	Transom height 15 inches
	Composite seat tops
	Modified split seat in the stern
	Black in colour. NO decals installed at time of delivery
	Trailering cover
	Splash rail
Trailer	Galvanized steel frame (heavy duty)
	Tongue mounted parking jack
	Heavy duty winch and steel cable or strap
	Supported fenders
	Completely wired with automotive style plug-in wiring
	Waterproof LED lights
	Suitable wheels and tires to match or exceed Gross Vehicle Weight (GVW) capacity
	Bearing buddies fitted to axle hubs
	Safety hooks on chains, MTO approved.
	Heavy duty 2 inch coupler
	Trailer is to be bunk type with wooden substructure.
	Track width to be suitable with overall trailer width.
Motor	
	Manufacturer make and model: Yamaha or equivalent – 25 Hp, short shaft clamps to transom, manual start
	Salt water rated
	Fuel Injection



Ennobin

	Shaft Length to match transom height
	Pull start.
	Four-stroke
	Portable marine gas can with primer hose assembly

2.0 Category 2: 16-16.5' Aluminum Boat, Motor and Trailer

The vessel, motor and trailer must meet the following specifications:

Hull	Minimum length of 16 feet up to a maximum of 16 ½ feet in length
	Beam minimum of 70 inches
	No floor
	Riveted hull, minimum bottom thickness of 0.060 inches
	Bow eye
	Hull Type – V bottom
	Marine grade aluminum
	Transom drain plug
	All hardware to be stainless steel, chromed bronze or anodized aluminum
	Transom height 20 inches
	Composite seat tops
	Modified split seats in the stern and midship
	Black in colour. NO decals installed at time of delivery
	Trailer cover
	Navigation lights
Trailer	Splash rail
	Galvanized steel frame (heavy duty)
	Tongue mounted parking jack
	Heavy duty winch and steel cable or strap
	Supported fenders
	Completely wired with automotive style plug-in wiring
	Waterproof LED lights
	Suitable wheels and tires to match or exceed GVW capacity
	Bearing buddies fitted to axle hubs
	Safety hooks on chains, MTO approved
	Heavy duty 2-inch coupler
	Trailer is to be bunk type with wooden substructure
	Track width to be suitable with overall trailer width
Motor	
	Spare tire mounted to trailer
	Torsion axle suspension
	Manufacturer make and model; Yamaha or equivalent – 40 Hp with electric start
	Battery
	Salt water rated
	Fuel injection
Motor	Shaft length to match transom height
	Pull start
	Four-stroke



Ennobin

	Portable marine gas can with primer hose assembly
--	---

3.0 Category 3: 19-20.5' Aluminum Boat, Motor and Trailer

The vessel, motor and trailer must meet the following specifications:

Hull	19-20.5 foot length
	Beam minimum of 84 inches
	Welded Hull, minimum bottom thickness of 0.160 inches, side thickness 0.125 inches
	Bow eye
	Hull Type – Deep "V" bottom or Modified Deep "V"
	Marine grade aluminum
	Self-draining foredeck (drop bow) to outside of vessel
	Bow rails
	Transom drain plug
	Two (2) transom motor well drains, self draining to outside of vessel
	Mooring cleats to be stainless steel, chromed bronze or aluminum
	All hardware to be stainless steel, chromed bronze or anodized aluminum
	Bucket style seat for operator and companion seating mounted on box with enclosed under storage. Grey in colour.
	Glove box (lockable)
	Dual console/walkthrough to drop bow
	Dash mounted steering
	Hydraulic steering, max turns of 3.5 from lock to lock
	Installed, dash mounted electric multi-function gauge, to monitor the following: fuel, tachometer, speedo, voltmeter, trim gauge and oil pressure, water pressure and temperature, overheat warning device compatible to motor specified
	Walk-thru safety glass windshield, capable of mounting two (2) heavy duty windshield wipers, one (1) on port and one (1) on starboard
	Two (2) transom lifting eyes
	Height of motor well or bailing well is to be full height or close to the height of the gunwale
	Boat deadrise – minimum of 16 degrees up to a maximum of 18 degrees
	Electric bilge pump and automatic switch and float, pump capacity suitable for this size of boat based on commercial standards
	Black exterior hull. Light colour topside
	No decals installed on the hull exterior
	Navigation lights
	Built-in fuel tank (25 imperial gallons capacity minimum)
	Rub rails- black rubber or equivalent trim
	Flooring – marine grade non-skid or aluminium checker plate
	One (1) section type swim platform mounted on the transom starboard side with swim ladder
Trailer	Single axle boat trailer to suitably carry a 19'0" – 20'6" deep "v" or modified deep "v" aluminum outboard hull boat, motor, full fuel tanks and 500 lbs. of additional equipment.
	Galvanized frame with torsion suspension and folding tongue
	Tongue mounted parking jack – 1200lb capacity



Ennobin

	Adjustable winch stand
	Heavy duty winch and steel cable or strap
	Fully supported fenders and step pads
	Completely wired with automotive style plug-in wiring
	Waterproof LED lights
	Suitable wheels and tires to match or exceed Gross Vehicle Weight (GVW) capacity
	Spare tire, wheel rim and carrier assembly mounted to trailer
	Bearing buddies fitted to axle hubs
	Surge drum brakes
	Heavy duty 2 inch coupler
	Heavy duty safety chains at hitch coupler with locking
	Safety hooks on chains, MTO approved
	Non marking rollers to adjust to any boat hull bottom design
	Tilting roller assemblies
	Keel rollers
	Track width to be suitable with overall trailer width
Motor	Trailer to be completely assembled and serviced
	Manufacturer make: Yamaha or equivalent
	Maximum rated (Transport Canada/Canadian Coast Guard) horsepower outboard that is compatible with hull
	Aluminum propeller
	Salt water rated
	Fuel injection
	Electric start

3.1 Additional Specifications and Requirements - Category 3

- (a) The vessel(s) supplied by the Vendor to the Ministry must meet or exceed all applicable National Marine Manufacturers Association (NMMA) standards for 2020.
- (b) The vessel(s) supplied by the Vendor to the Ministry must also comply with Transport Canada TP 1332 Standards and the Transport Canada - Small Vessel Compliance Program (SVCP).
- (c) The vessel(s) supplied by the Vendor to the Ministry must pass a small craft stability test in accordance with applicable Transport Canada standards. Testing of the vessel shall be done at the Vendor's expense. The Vendor shall provide these test results indicating that the vessel has passed the small craft stability test to the Ministry Representative at the time of delivery of the vessel to OPP Headquarters.
- (d) The hull of the vessel(s) supplied by the Vendor must be protected against corrosion and electrolysis.
- (e) During the seal trials the vessel (*full of fuel*) with 4 crew and with 600 Lbs of cargo must obtain a cruising speed of 50 MPH to pass for Category 3.

4.0 Category 4: 21'8" – 22'8" Aluminum Skiff, Motor and Trailer



Ennobin

The vessel, motor and trailer must meet the following specifications:

Hull	Minimum length of 21'8" up to a maximum of 22'8" foot length (not including swim platform or engines)
	Beam minimum of 100 inches
	Aluminium Thickness: Side 0.125 inch minimum Bottom 0.250 inch minimum
	Walk around deck
	Bow eye – reinforced with backing plate
	Hull Type – Deep "V" or modified Deep "V"
	Marine grade welded aluminum
	Partially or fully enclosed wheelhouse
	Deadrise is a minimum of 16 degrees
	Black exterior hull. Light colour topside
	No decals installed on the hull exterior
	Side height is a minimum of 32 inches
	Fuel Capacity: Minimum of 50 imperial gallons
Wheelhouse	If the wheelhouse is fully enclosed, the wheelhouse must have a weather-tight locking door
	Wheelhouse to have a minimum headroom of 6 ft. 3 inches
	Wheelhouse to be a minimum length of 72 inches
	Wheelhouse ceiling is to be lined/carpeted to prevent condensation
	Wheelhouse walls and ceiling to be insulated for cold weather use. If the wheelhouse is partially enclosed, insulation is not required.
	If the wheelhouse is fully enclosed, all cabin doors shall be hinged, aluminum, weather tight and lockable. Cabin doors both fore and aft will be capable of locking in the open position. Aft door will be a single door design
	Lockable, weather tight bow storage compartment(s) capable of supporting the weight of an officer (350 lbs. with full kit), as well as a bow anchor hatch in a separate compartment. The wheelhouse will have a lockable floor storage compartment. The lockable, weather tight bow storage compartment(s) is to be accessible from the bow deck.
Engine Instrumentation	11lb stainless steel Bruce anchor. 100ft of anchor line and 5ft of galvanized chain.
	Hour meter
	Oil pressure gauge
	Temperature gauge
	Battery voltmeter gauge
	Fuel gauge
	Tilt/Trim gauge
	Speedometer
	Tachometer
Mechanical	Water pressure gauge
	Power assisted hydraulic steering.
	Fly by wire controls.



Ennobin

	Two (2) heavy-duty windshield wipers (one (1) on Portside, one (1) on Starboard side)
	Minimum of two (2) interior lights for wheelhouse (red/white switchable)
	Minimum of two (2) bilge pumps – 1100 G.P.H. each min
	Hydraulic trim tabs
	Twin batteries with isolation switch
	2 USB charging ports on dash
	Two (2) 12-Volt weather sealed cig adapter style charge ports one (1) on port side and one (1) on starboard side
	Rigging to engine with power assisted hydraulic steering, controls, gauges, etc
	Three (3) roof mounted Rigid Industries flood lights or equivalent – one (1) port, one (1) starboard & one (1) rear. (Note: the location of the flood lights shall be as directed by the Ministry to the Vendor)
	Rigid Industries E-Series Pro 20" spot / flood combination light bar or equivalent– Mounted on front of wheelhouse roof. (Note: the location of the spot/flood combination light bar shall be as directed by the Ministry to the Vendor)
	Ability to mount a radar, antennas and other equipment to the roof
	Safety glass windshield with a rigid, sturdy frame
	Sliding windows (port side and Starboard side) Slide open to rear.
	Rear view mirror
	AM/FM stereo complete with 2 speakers (Bluetooth)
	GPS control heads for both sides of the vessel.
	18" high-definition dome radar
	Ships heading sensor.
	Marine compass
	Remote controlled LED search light
	Loud hailer system
	All install locations are to be directed by the Ministry to the Vendor.
Deck	FLIR
	Bow rail and fittings - with rail base backing plates
	Roof mount handrail on cabin
	Two (2) heavy duty stern eyes
	Reboarding platform (port side with stainless steel ladder extensions)
	Three (3) fender cleats per side on deck
	Minimum of three (3) mooring cleats per side
	Exterior hardtop handrail
	LED navigational lights (port side and starboard side)
	LED docking light
Upholstery & Seating (Interior and Exterior)	Non-marking rub rail (from bow to stern on the port side and starboard side).
	Non-slip, self-bailing aluminium deck. Foredeck to be a workable area.
	Two (2) heavy duty fully adjustable suspension-type operator and companion seats with armrests and horizontal and vertical seat position adjustments – armrests must fold up or be removable



Ennobin

Trailer	Galvanized tandem axle
	Hydraulic surge drum brakes on both axles
	Manual winch
	Folding tongue
	Transport tie down straps
	Roller type trailer
	Cross member protectors, roller design
	Tongue jack sized for trailer capacity
	Spare tire and wheel mounted to trailer
	Gross Vehicle Weight Rating (GVWR) to accommodate the vessel
Motor	Manufacturer make: Mercury /Yamaha or equivalent
	Single maximum rated (Transport Canada/Canadian Coast Guard) horsepower outboard that is compatible with hull complete with rigging
	Salt water rated
	Four-stroke outboard engine complete with rigging
	Aluminum propeller

4.1 Additional Specifications and Requirements – Category 4

- (a) The vessel(s) supplied by the Vendor to the Ministry must meet or exceed all applicable National Marine Manufacturers Association (NMMA) standards for 2020.
- (b) The vessel(s) supplied by the Vendor to the Ministry must also comply with Transport Canada TP 1332 Standards and the Transport Canada - Small Vessel Compliance Program (SVCP).
- (c) The vessel(s) supplied by the Vendor to the Ministry must pass a small craft stability test in accordance with applicable Transport Canada standards. Testing of the vessel shall be done at the Vendor's expense. The Vendor shall provide these test results indicating that the vessel has passed the small craft stability test to the Ministry Representative at the time of delivery of the vessel to OPP Headquarters.
- (d) The hull of the vessel(s) supplied by the Vendor must be protected against corrosion and electrolysis.
- (e) During the sea trials the vessel (*full of fuel*) with 4 crew and with 600 Lbs of cargo must obtain a cruising speed of 50 MPH to pass for Category 4.

5.0 Category 5: 24-26' Aluminum Skiff, Motor and Trailer

The vessel, motor and trailer must meet the following specifications:

Hull	Minimum length of 24' up to a maximum of 26' foot length (not including swim platform or engines)		
	Beam minimum of 101 inches		
	Aluminium Thickness:	Side	0.125 inch minimum
		Bottom	0.250 inch minimum
	Additional reinforcement to be installed to Keel.		
	Walk around deck		



Ennobin

	Bow eye – reinforced with backing plate
	Hull Type – Deep "V" or modified Deep "V"
	Fully enclosed wheelhouse
	Forward sloping windshield
	Deadrise is a minimum of 18 degrees
	Black exterior hull. Light colour topside
	No decals installed on the hull exterior
	Side height is a minimum of 30 inches
	Fuel Capacity: Minimum of 80 imperial gallons
Wheelhouse	Wheelhouse must have a weather-tight locking door. Minimum 30 inch
	Wheelhouse to have a minimum headroom of 6 ft. 3 inches
	Wheelhouse to be a minimum length of 90 inches
	Wheelhouse must include the ability to accommodate a stokes basket/backboard (90"x30") between the front seats with the wheelhouse door closed
	Wheelhouse ceiling is to be lined/carpeted to prevent condensation.
	Wheelhouse walls and ceiling to be insulated for cold weather use.
	Design must incorporate soundproofing – maximum decibel reading not to exceed 85 db
	All cabin doors shall be hinged, aluminum, weather tight and lockable. Cabin doors both fore and aft will be capable of locking in the open position. Aft door will be a single door design.
	Lockable, weather tight bow storage compartment(s) capable of supporting the weight of an officer (350 lbs. with full kit) , as well as a bow anchor hatch in a separate compartment. The wheelhouse will have a lockable floor storage compartment. The lockable, weather tight bow storage compartment(s) is to be accessible from the bow deck.
	Vessel not to have a cuddy
	Instrument lights must be controlled by an ON/OFF switch and rheostat
	Non-electric cabin heater (diesel)
	Minimum of two (2) fans to keep the front windows defogged / defrosted or electric "in glass" defroster.
Engine Instrumentation	Eleven pound (11lb) stainless steel Bruce anchor with 100ft of anchor line and 5ft of galvanized chain
	Hour meter
	Oil pressure gauge
	Temperature gauge
	Battery voltmeter gauge
	Fuel gauge
	Tilt/trim gauge
	Speedometer
	Tachometer
Mechanical	Water pressure gauge
	Power assisted hydraulic steering with 3.5 turns from lock to lock.
	One (1) heavy-duty windshield wiper per pane of glass in the windshield
	Minimum of two (2) interior lights for wheelhouse
	Minimum of two (2) bilge pumps – 1100 G.P.H. each
	Hydraulic trim tabs
	Twin batteries with isolation switch



Ennobin

	Two (2) USB charging ports per side in dash
	Two (2) 12-volt weather sealed cig adapter style charge ports one (1) on ports side and one (1) on starboard side
	Rigging to engine with power assisted hydraulic steering, controls, gauges, etc
	Three (3) roof mounted waterproof flood lights – one (1) port facing forward, one (1) starboard facing forward and one (1) rear facing aft. (Note: the location of the roof mounted waterproof flood lights shall be as directed by the Ministry to the Vendor)
	Two (2) flood lights at midship on port and starboard to illuminate side of vessel
	Remote controlled spotlight mounted on front of wheelhouse roof as not to cause glare when in operation
	Ability to mount a radar, antennas and other equipment to the roof.
	Safety glass windshield with a rigid, sturdy frame.
	Sliding windows (port side and starboard side) slide open to rear
	AM/FM stereo complete with four (4) Bluetooth speakers
	12 inch chart plotter (port side)
	10 inch chart plotter (starboard side)
	18 inch high-definition dome radar
	Ships heading sensor
	Marine IP camera (facing rear deck)
	Marine compass
	Remote controlled LED search light
	Loud hailer system
	front side glass to have the ability to be defrosted
	VHF & Police Radio antennas supplied by OPP and installed by Vendor
	Forward Looking Infrared (FLIR)
Deck	Bow rail and fittings with rail base backing plates
	Roof mount handrail on cabin
	Reboarding platform (port side with stainless steel ladder extensions)
	Minimum of three (3) mooring cleats per side
	Two (2) towing cleats on stern
	Four (4) tie down cleats on deck
	LED navigational lights (port side and starboard side)
	LED docking lights
	Six (6) LED deck lights
Upholstery & Seating (Interior and Exterior)	Non-marking rub rail (from Bow to stern on the port side and starboard side).
	Two (2) dive doors – one (1) port side, one (1) starboard side
	Non-slip aluminium deck. Cockpit deck to be self-bailing overboard.
	Two (2) heavy duty fully adjustable suspension-type operator and companion seats with bolster option, armrests, horizontal and vertical seat position adjustments – armrests must fold up or be removable
	Bench seating down both sides of wheelhouse
	Storage within/underneath the bench seats
	Chart table mounted in wheelhouse on port side



Ennobin

Trailer	Galvanized or aluminum tandem axle
	Hydraulic surge drum brakes on both axles
	Manual winch
	Folding tongue to fold to the right side
	Transport tie down straps
	Roller type trailer
	Cross member protectors, roller design
	Tongue jack sized for trailer capacity
	Spare tire and wheel mounted to trailer
	Gross Vehicle Weight Rating (GVWR) to accommodate the vessel
Motor	Manufacturer make: Mercury or Yamaha or equivalent
	Salt water rated
	Two (2) four-stroke outboard engines complete with rigging with one engine being a counter rotating engine
	Maximum rated (Transport Canada/Canadian Coast Guard) horsepower outboard that is compatible with hull complete with rigging

5.1 Additional Specifications and Requirements – Category 5

- (a) The vessel(s) supplied by the Vendor to the Ministry must meet or exceed all applicable National Marine Manufacturers Association (NMMA) standards for 2020.
- (b) The vessel(s) supplied by the Vendor to the Ministry must also comply with Transport Canada TP 1332 Standards and the Transport Canada - Small Vessel Compliance Program (SVCP).
- (c) The vessel(s) supplied by the Vendor to the Ministry must pass a small craft stability test in accordance with applicable Transport Canada standards. Testing of the vessel shall be done at the Vendor's expense. The Vendor shall provide these test results indicating that the vessel has passed the small craft stability test to the Ministry Representative at the time of delivery of the vessel to OPP Headquarters.
- (d) The hull of the vessel(s) supplied by the Vendor must be protected against corrosion and electrolysis.
- (e) During the seal trials the vessel (*full of fuel*) with 4 crew and with 600 Lbs of cargo must obtain a cruising speed of 50 MPH to pass for Category 5.

6.0 Category 6: 21'8" – 22'8" Aluminum Skiff - Dive Vessel, Motor and Trailer

The vessel, motor and trailer must meet the following specifications:

Hull	Minimum length of 21'8" up to a maximum of 22'8" length (not including swim platform or engines)		
	Beam minimum of 96 inches		
	Aluminium Thickness:	Side	0.125 inches minimum
		Bottom	0.250 inches minimum
	Keel guard to be installed on bottom of hull for added strength in severe conditions		



Ennobin

	Vessel with engines, a full fuel tank and weight of trailer will not exceed 2359KG (5200lb) combined
	Maximum amount of storage in the cabin and cockpit
	Welded bow eye with backing plate
	Hull Type – Deep "V" or modified Deep "V" or delta keel
	Marine grade welded aluminum
	Fully enclosed wheelhouse and rear sloping windshield
	Deadrise is a minimum of 16 degrees
	Black exterior hull, light colour topside
	No decals installed on the hull exterior
	Side height is a minimum of 36 inches
	Lifting strakes
	Self-draining bow
	Extended transom
	High pressure wash down system, to draw from lake
	Fuel capacity: minimum of 70 imperial gallons
Wheelhouse	Welded aluminum hard top wheelhouse
	Wheelhouse with weather-tight locking door (minimum 21" in width opening)
	Wheelhouse to have a minimum headroom of 6 ft. 1 inches
	Wheelhouse to be a minimum length of 7 feet
	Wheelhouse ceiling is to be lined/carpeted to prevent condensation
	Standard aft sloping windshield with tempered glass
	Sliding side windows on both port and starboard sides
	Stern area sloping cover
	All cabin doors shall be hinged, aluminum, weather tight and lockable. Cabin doors both fore and aft will be capable of locking in the open position.
	Bow anchor rope locker with anchor roller
	Eleven pound (11lb) stainless steel Bruce anchor. 100ft of anchor line and 5ft of galvanized chain
	Two (2) stainless steel roof mounted flagpole holders – ¾" diameter
	Vessel not to have a cuddy
	Instrument lights must be controlled by an ON/OFF switch and rheostat
	Diesel heater for wheelhouse. Wheelhouse heating ducts will be able to defrost windshield on both port and starboard sides.
Engine Instrumentation	Integrated with the multi-function display
	Hour meter
	Oil pressure gauge
	Temperature gauge
	Battery voltmeter gauge
	Fuel gauge
	Tilt/Trim gauge
	Speedometer
	Tachometer
	Water temperature gauge
Mechanical	Pressure gauge
	Rig to engine manufacturer with power assisted hydraulic steering – 3.5 turns from lock to lock



Ennobin

	Two (2) pantographic windshield wipers (One (1) port side and one (1) starboard side)
	Minimum of two (2) interior lights for wheelhouse
	Minimum of two (2) bilge pumps – 1100 G.P.H. each
	Adaptive trim tabs, Dometic or equivalent
	Twin batteries with isolation switch
	1500-watt pure sine inverter – 120 volts. Victron Energy Phoenix 800VA 12-Volt 120V AC Pure Sine Wave inverter or equivalent
	Two (2) USB charging ports for pilot and two (2) USB charging ports for navigator
	Two (2) 12-volt weather sealed cig adapter style charge ports one (1) on port side and one (1) on starboard side
	Rigging to engine with power assisted hydraulic steering, controls, gauges, etc
	Four (4) roof mounted waterproof flood lights, 202113 RIGID D-SRS PRO FLD SM/2 or equivalent – one (1) port facing forward, one (1) starboard facing forward, one (1) port facing aft deck and one (1) starboard facing aft deck.
	Two (2) flood lights at midship on port and starboard to illuminate side of vessel
	Sliding windows opening aft (port side and starboard side) with window tint
	AM/FM stereo complete with two (2) Bluetooth speakers
	12 inch chart plotter (starboard side) flush mounted to the dashboard
	9 inch chart plotter (port side) mounted to top of dashboard
	9 inch chart plotter mounted to rear helm station
	18 inch minimum dome radar with mount
	Ships heading sensor. Garmin 9-axis or equivalent
	Marine compass
	GlobalFix V5 AIS EPIRB with Category 1 Float Free Bracket (Programmed for Canada) or equivalent
	Remote controlled spotlight. – mounted on front of wheelhouse roof. One (1) hard wired dash mount remote on starboard side
	Loud hailer system. Shakespeare HS-40 or equivalent, to be approved by the Ministry
	Note: All install locations are to be directed by the Ministry to the Vendor.
	Vessel to be equipped with an auxiliary steering column on the stern deck. It will have throttle and steering controls for both the main and kicker motors
	Depth finder gauge on rear auxiliary steering column
Deck	Rear deck to be minimum length of 6 feet
	Bow area to not exceed 6 feet in length
	Roof mount handrail on cabin
	Reboarding platform (port side with stainless steel ladder extensions)
	Two (2) towing cleats on stern
	Exterior hardtop handrail
	Navigation lights
	Non-slip aluminium deck. Cockpit to be self-bailing.



Ennobin

Upholstery & Seating (Interior and Exterior)	Two (2) heavy duty fully adjustable suspension-type operator and companion seats with armrests and horizontal and vertical seat position adjustments – armrests must fold up or be removable. Smooth Moves or equivalent.
	Bench seating down both sides of wheelhouse
	Storage within/underneath the bench seats
	Seating in wheelhouse for six (6) adults
	Porta-Pottie that can be stored under a bench, with privacy screen
Trailer	Galvanized tandem axle
	Hydraulic surge drum brakes on both axles
	Manual winch
	Folding tongue
	Transport tie down straps
	Bunk type trailer
	Slick bunks
	Boat trailer skid pad cross member protectors
	Tongue jack sized for trailer capacity
	Spare tire and wheel mounted to trailer
	Gross Vehicle Weight Rating (GVWR) to accommodate the vessel
Motor	Load guides
	Manufacturer make: Mercury or Yamaha or equivalent
	Single maximum rated horsepower outboard that is compatible with hull complete with rigging
	Salt water rated
	Four-stroke outboard engine complete with rigging
	Main motor to be equipped with Level 4 - Helm Master EX with Setpoint positioning modes. Controls are to be at main helm in cabin
	Outboard engines to be mounted to swim platform
	Aluminum propeller plus one (1) spare aluminum propeller
	One 20 hp (20") shaft outboard with dedicated throttle controls at the aft deck only. Must have manual pull start if available. Steering to be tied to main engine. Equipped with aluminum propeller and one (1) spare aluminum propeller

6.1 Additional Specifications and Requirements - Category 6

- (a) The vessel(s) supplied by the Vendor to the Ministry must meet or exceed all applicable National Marine Manufacturers Association (NMMA) standards for 2020.
- (b) The vessel(s) supplied by the Vendor to the Ministry must also comply with Transport Canada TP 1332 Standards and the Transport Canada - Small Vessel Compliance Program (SVCP).
- (c) The vessel(s) supplied by the Vendor to the Ministry must pass a small craft stability test in accordance with applicable Transport Canada standards. Testing of the vessel shall be done at the Vendor's expense. The Vendor shall provide these test results indicating that the vessel has passed the small craft stability test to the Ministry Representative at the time of delivery of the vessel to OPP Headquarters.
- (d) The hull of the vessel(s) supplied by the Vendor must be protected against corrosion and electrolysis.
- (e) During the seal trials the vessel (full of fuel) with 4 crew and with 600 lbs of cargo must obtain a cruising speed of 40 MPH to pass.



Table 1 below, lists jurisdictions that are parties to trade agreements including government procurement obligations with Canada.

Table 1: List of Jurisdictions

Armenia	Iceland	New Zealand
Australia	Ireland	Norway
Austria	Israel	Peru
Belgium	Italy	Poland
Bulgaria	Japan	Portugal
Chinese Taipei	Korea (Republic of)	Romania
Croatia	Latvia	Singapore
Cyprus	Liechtenstein	Slovakia
Czech Republic	Lithuania	Slovenia
Denmark	Luxembourg	Spain
Estonia	Malaysia	Sweden
Finland	Malta	Switzerland
France	Mexico	Ukraine
Germany	Moldova, Republic of	United Kingdom
Greece	Montenegro	United States
Hong Kong, China	Netherlands	Vietnam
Hungary	Netherlands with respect to Aruba	