

PROJECT DEFINITION

A playable world. A precise build scope.

River Club is a React-based social casino game concept. The next development stage should turn its local demo into an immersive, coherent and testable multiplayer alpha, with a premium 3D-style presentation.



Future visual direction only. This artwork is conceptual and does not represent delivered functionality.

Hiring objective

Engage a senior game UI / full-stack developer, or a small team, to redesign the experience, implement the agreed online systems and deliver a maintainable Vite project with documented contract code.

Target experience

A cinematic social poker club: human characters, visible player actions, responsive table controls, global matchmaking, scheduled events and optional wallet interaction.

Document status

Proposed functional and design specification for contractor estimation. Scope, quantities and performance targets below are a recommended baseline, not previously approved commitments.

Revision 2.0 · 18 September 2026 · Upwork project attachment

Primary delivery: browser-based, play-money alpha. Real-value settlement is a separately priced phase.

Build on the demo. Define the next release.

The current project is a prototype foundation. Bidders must distinguish reuse, redesign and new backend development in their estimates.

Area	Current baseline	Proposed next stage
Client	React, TypeScript and Vite; local game/demo state.	Scene-led UI, shared design system, persistent accounts and recoverable sessions.
Characters	Atlas, Mika and Nova; cutout poses and CSS movement.	Clean layered assets, selection sequence and event-driven animation states.
Games	Simplified four-seat poker against bots; local blackjack.	Preserve rules for visual release; add authoritative four-player poker in online alpha.
Community	Simulated queue, seeded friends, local chat and private codes.	Real presence, invitations, rooms, moderation and cross-browser messaging.
Events	Local registration and a three-round demo circuit.	Server-managed schedules, capacity, results and reliable reward claims.
Web3	Injected wallet connection; attendance-only Solidity contract. Escrow and fairness lab are demos.	Verified testnet attendance flow. Any money-handling contracts require separate scope.

Phase boundaries

P0 - Visual foundation: redesign and animate the existing game without changing its mechanics. **P1 - Play-money online alpha:** add server authority, accounts, matchmaking, live social functions and events. **P2 - Optional expansion:** full poker rules, richer characters, testnet escrow and advanced tournaments.

Excluded from the base bid: mainnet wagering, real-money withdrawals, NFT marketplace, mobile native apps, voice/video chat, full 3D world, complex character rigging and independent security audit. Quote any requested option separately.

Source baseline: supplied River Club Vite prototype and its demo documentation. This specification is not a security audit or a claim that proposed features already exist.

A game interface, not an admin dashboard.

Use the poker scene as the primary canvas. Navigation, social activity and events should support the world rather than compete with it.

Scene composition

DS-01: Build one polished casino room with a clear table focal point, controlled perspective, grounded characters, soft contact shadows and restrained atmospheric lighting. Deliver background, table, characters, effects and HUD as separate layers. Avoid opaque foreground panels behind each character and remove matte edges from cutouts.

DS-02: Keep each player's face, cards, chip count, turn indicator and action readable. Decorative objects must never cover the active player's controls or another player's action. Establish safe areas at desktop, tablet and mobile layouts before producing final assets.

Interface vocabulary

Use a compact top navigation, a persistent identity/wallet area, a contextual action dock and an optional social drawer. Replace generic metric tiles with a featured event stage, playable game entries and animated character previews. Materials should combine deep navy surfaces, warm metallic accents and selective cyan lighting.

Token / behavior	Proposed direction
Color	Midnight #101827; ivory #F4F1EA; muted gold #B89B63; cyan #62D8D0. Validate contrast in the actual UI.
Typography	Display headings with game personality; readable sans-serif for rules, chat and balances. Tabular numerals for chips and timers.
Depth	Consistent light direction, subtle bevels, soft shadows and limited translucent surfaces.
States	Default, hover, focus, pressed, disabled, pending, success and error for every interactive control.
Motion	Short UI feedback; longer intentional scene transitions. Reduced-motion mode removes camera drift and particles.

Deliverables and acceptance

Provide editable design source, design tokens, component states, responsive layouts and export-ready assets. Approve lobby, character selection and table scene before implementing secondary screens. At 390 px and 1440 px widths, no essential control is clipped and no character obscures another player's status.

Every screen needs a clear next action.

Screen	Required content and interaction
Lobby	Quick Play, featured event, game selection, party presence, profile and clearly labeled demo/testnet balances.
Character selection	Three character previews, names, selected state, preview animation, confirm and back actions.
Queue / ready room	Region, mode, waiting status, cancel, party readiness and connection state.
Game table	Players, cards, pot, legal actions, action timer, last action, history, connection status and leave confirmation.
Events	Upcoming/live/completed filters, detail page, rules, registration, capacity, start time and results.
Social drawer	Friends, invitations, party members, room chat, mute/block/report and unread counts.
Clubhouse / profile	Character, display name, rewards, mission progress, recent results and settings.
Wallet / activity	Connection, chain, supported contract action, transaction history and pending/error recovery.

Primary journey: quick match

Open lobby → choose character → confirm mode and region → enter queue → accept ready check → receive a seat → play → view result → rematch or return to lobby. Preserve character and party across the journey. Canceling a queue must release the reservation.

Event journey

Open event → inspect rules and schedule → register → receive confirmation → check in → join assigned room → complete rounds → view final ranking and reward receipt. A missed check-in produces an explicit outcome; it must not silently consume an entry.

Recovery and empty states

Each screen needs loading, empty, unavailable and recoverable failure states. Distinguish no events from a failed event request. Preserve unsent chat text after a transient error. If a room closes or a session expires, explain the cause and provide a safe return to the lobby.

Acceptance: a new tester can enter a local demo without a wallet. An authenticated tester can complete the online quick-match journey in two separate browser sessions without manually copying internal identifiers.

Make every player visibly present.

The goal is convincing 3D-style presentation with lightweight assets. Fully modeled avatars and expensive real-time rigging are optional.

Character selection - CH-01

Launch with the existing three identities: Atlas, Mika and Nova. Show a full or half-body preview, short character description and a clear confirmation control. Selection uses a silhouette light, accent outline and name treatment; it must not rely on color alone. Persist the confirmed choice to the account in P1 and locally in P0. Character choice has no gameplay advantage.

Animation state contract - CH-02

State	Visible behavior	Trigger / exit
Idle	Subtle breathing, blink and occasional head shift; randomized phase per seat.	Default; interrupted by meaningful actions.
Enter / sit	Short approach or seated transition with grounded shadow.	Seat confirmed; finish in idle.
Thinking	Eye/head attention toward table; restrained hand gesture.	Player turn starts; exit when action resolves.
Check / call / raise	Distinct gesture plus chip movement where appropriate.	Accepted game action, never an unconfirmed click.
Fold	Cards pushed away; quieter seated pose.	Fold accepted; remain folded until next hand.
Win / loss	Brief reaction, then neutral reset; no constant celebration loop.	Authoritative result received.
Interaction / away	Emote response or muted connection indicator.	Rate-limited emote or disconnect event.

Asset and implementation requirements

Deliver transparent exports, consistent camera angle, scale and light direction, animation manifest, source files and license inventory. A sprite sequence, layered 2D rig or equivalent lightweight approach is acceptable. Do not stretch a static rectangle to imply a human body.

Acceptance

All four seats display remote actions. No colored boxes, opaque cutout backgrounds or floating feet appear. Repeated action messages cannot replay a gesture twice. Reconnection restores current poses without replaying an entire hand. Reduced-motion mode uses clear static poses and action labels. Animation never delays game-state updates or changes turn timing.

Preserve the mechanics. Make state unambiguous.

P0: preserve the existing rule set - GM-01

Keep the four-seat simplified poker loop: ante, private cards, community-card streets, check, fixed raise and fold, followed by best-five-of-seven evaluation and split-pot handling. Preserve local blackjack with hit/stand, dealer standing on all 17s and natural blackjack payout. Do not silently add blinds, side pots, all-ins, split hands or insurance during the visual redesign.

P1: authoritative poker - GM-02

The server owns deck generation, dealing, turn order, legal actions, pot accounting and results. Clients submit intentions with match, hand and action identifiers. Reject actions from the wrong seat, wrong turn, stale hand or insufficient balance. Send each player only their private cards and the public state. Bots must be labeled and used only in a clearly identified practice mode.

Implement explicit states: waiting, preparing hand, preflop, flop, turn, river, showdown, result and closed. Advance only after the active state is resolved. Hand history records accepted actions and revealed results without exposing unrevealed opponent cards.

Timers, disconnects and settlement

Proposed action clock: 20 seconds, controlled by server time. On timeout, check if legal; otherwise fold. A disconnected player follows the same timeout policy. Leaving during an active hand must not cancel a loss or duplicate a refund. Commit the hand outcome and chip ledger exactly once before displaying a final reward.

Optional full poker rules - GM-03 / P2

Price blinds, variable raises, minimum-raise rules, all-ins, side pots, heads-up behavior, odd-chip allocation and tournament blind levels as a separate rules package. Provide a written rulebook and deterministic evaluator tests before connecting these rules to events.

Acceptance scenario	Expected result
Duplicate raise request	One debit, one action and one animation.
Two winning hands tie	Pot allocation follows the approved split and rounding rule; total chips conserved.
Reload during a hand	Seat, private cards and current turn recover from server state.
Invalid / late action	Rejected with reason; pot and turn stay unchanged.

Connect real players with recoverable sessions.

Identity and session ownership - MP-01

P1 requires persistent user IDs and authenticated sessions. A wallet address may be linked after proving ownership, but is not itself a trusted login. Guest practice remains available. Store profile, confirmed character and settings on the server. Restrict simultaneous ownership of an active seat; a second tab must reconnect or receive a clear conflict message.

Queue behavior - MP-02

Filter the initial queue by game mode, selected region and agreed chip tier. Matchmaking for the alpha does not require skill-rating optimization. Show waiting time and permit cancellation. If insufficient players are available, offer explicit choices to keep waiting, change region or enter labeled practice. Never present bots as real global opponents.

Proposed ready check: 15 seconds. On a decline or timeout, release that player's reservation and return eligible players to the queue without a double entry charge. A party may enter only a supported group mode; ranked individual play must not imply an unsupported party advantage.

Room lifecycle and reliability - MP-03

Create rooms with unique IDs, seat reservations and server-issued access rights. State changes carry monotonically increasing sequence numbers. Clients detect missing updates and request a snapshot. Rejoining within a proposed 60-second connection grace period restores the same seat, subject to normal action timeouts. Expired reservations cannot block a room indefinitely.

Private rooms - MP-04

Allow host creation, invite code/link, join validation, ready status and host start when the room meets the configured minimum. Codes need expiry and attempt limits. A private code is an access convenience, not permission to impersonate another player. Define host migration or orderly closure if the host leaves before the game starts.

Acceptance: four independent browser sessions join one room, observe the same public state and complete a hand. One client disconnects and reconnects without losing its seat or receiving extra chips. Queue cancellation, simultaneous joins and repeated ready responses are tested.

Global means selectable regional matchmaking in this scope. Multi-region hosting, latency-based routing and worldwide capacity guarantees require a separately agreed infrastructure plan.

Turn schedules into playable events.

Event catalog and registration - EV-01

Each event has an ID, title, description, region, eligibility, game/rule version, capacity, registration window, start time, entry amount and reward configuration. Display times in the viewer's locale with a timezone label. Provide upcoming, live and completed filters. Event details must explain format, check-in, cancellation and tie rules before registration.

Registration is idempotent and capacity-controlled on the server. Reserve or charge play-money entry once according to the approved policy. Offer withdrawal before the published cutoff. Event cancellation releases reserved entries or creates one refund receipt per charged registration. A full event offers a clear unavailable state; waitlists are optional.

Proposed alpha competition format - EV-02

Use a four-player, three-round scored circuit for the first live event implementation, preserving the demo's concept while formalizing scoring. Proposed placement points: 10 / 6 / 3 / 1. Define tied-hand point allocation before development; recommended baseline is the average of occupied place points. Tied final totals share rank and split the combined rewards for occupied places. Round results and reward calculations must be replayable from the event log.

This alpha format does not include multi-table elimination, late registration, rebuys or expanding blind levels. Those features depend on the optional full poker rule set and should be estimated separately.

Event state machine - EV-03

Draft → published → registration open → registration closed → check-in → running → finalizing → completed. Cancellation is permitted before running; an interrupted live event enters a paused or failed state with an operator-visible resolution path. Publishing freezes critical rules for registered players, or requires explicit re-consent if changed.

Results and notifications - EV-04

Show round progression, provisional standings, final rank and reward receipt. Notify registered users of start/check-in and cancellation. Prevent duplicate claims across devices. A failed reward operation stays pending for retry, with no false success message.

Acceptance: test simultaneous registration for the final seat, duplicate payment attempts, missed check-in, event cancellation, a tied final ranking and a repeated reward request. Capacity and total reward allocation must remain correct.

Give the club a reason to return.

Friends, parties and chat - SO-01

Support friend request, accept, decline and remove. Presence distinguishes online, in lobby, in game and offline without exposing private table details. Parties support a host and up to three members, invite/accept/leave, ready status and queue cancellation. Invites expire and cannot silently pull a player out of an active hand.

Provide room and party text chat with sender, timestamp, message status and capped message length. Include mute, block and report. Apply server-side rate limits and authorization on every channel. A blocked user cannot continue sending invitations or direct interaction requests. Public global chat, voice and video are optional.

Profile, rewards and missions - SO-02

Persist display name, chosen character, motion/sound preferences, result history, XP and mission progress. Daily rewards use server UTC dates and are granted once per account per day. Mission rewards reference unique completion records. Do not trust a client-supplied win count or balance. Show locked, progressing, claimable and claimed states.

Separate spendable play chips from XP, event points and any testnet asset. Explain what each amount can be used for. Duplicate refreshes or concurrent device claims must not create extra rewards. Economy values in the prototype remain configurable and are not a final commercial economy.

Complete demo coverage - DM-01

Retain a self-contained demonstration mode for buyer review and onboarding. Provide preset scenarios for a normal hand, remote-player actions, a fold, showdown, queue, registration, circuit result, party invitation, chat, reward claim, wallet rejection and pending transaction. Each scenario is visibly labeled simulated and can be reset without affecting an online account.

Scenario	Acceptance evidence
Chat across two sessions	Authorized users receive one message in the correct room; unrelated users receive none.
Concurrent daily claims	Exactly one reward and one ledger entry.
Blocked player invitation	Invitation is rejected and not delivered.
Demo reset	Reproducible state is restored; online balances remain untouched.

Keep trust boundaries visible and explicit.

The present contract records attendance. It does not escrow funds, shuffle cards or settle casino winnings.

Wallet and attendance - W3-01 / P1

Support an injected EVM wallet, account changes, disconnect, wrong-network detection and rejected signatures. Configuration must identify supported chain, contract address, ABI and explorer. Revalidate after account or network changes. Wallet connection alone must not authorize a server account or modify a game balance.

For attendance, read event availability and joined status before submission. Display awaiting signature, submitted, confirmed, reverted and unknown states. Persist the transaction hash and reconcile after refresh. Treat a submitted transaction as pending until the agreed confirmation policy is met. If RPC status is unavailable, show uncertainty rather than retrying a value-changing action blindly.

Contract handoff - W3-02

Review the existing organizer-only event creation and public join functions. Deliver source, reproducible compiler configuration, ABI, deployment script, unit tests and deployment manifest for the selected testnet. Confirm duplicate join prevention, time windows, capacity boundaries, invalid event creation and organizer permissions. Never include private keys in source or the ZIP.

Optional escrow and fair dealing - W3-03 / P2

Estimate separately: deposit/withdrawal accounting, settlement authority, replay protection, emergency controls, finality and reconciliation, user receipts and recovery procedures. Define who can authorize payouts and what evidence resolves a dispute before implementing a contract. The existing local escrow demo must not be presented as an audited payment system.

The seed hash lab is a concept demonstration, not proof of fair gameplay. A production fairness design must specify shuffle derivation, private-card secrecy, seed contribution, reveal timing, withholding behavior and an independently reproducible verifier. Commit/reveal alone does not solve all these requirements.

Acceptance: verify confirmed attendance on the chosen testnet, rejected signature, wrong chain, full event, duplicate join, reverted transaction and RPC interruption. Local demo receipts and real transaction hashes must have visibly different presentation.

Chain selection, confirmation count and any real-value launch conditions remain owner decisions. Independent contract review and deployment authorization are separate gates, not implied by alpha acceptance.

Make the experience operable after handoff.

Proposed architecture - BE-01

Retain Vite, React and TypeScript for the client. Add an authenticated HTTP API for profiles, events and history; a real-time transport for rooms and presence; and a transactional database for users, registrations, game outcomes and the chip ledger. The server owns authority. Choose specific backend/database vendors in discovery with a written rationale and recurring cost estimate.

Entity	Minimum records / invariants
User / session	Stable ID, profile, identity links, session expiry and account status.
Room / hand / action	Rule version, participants, state version, ordered accepted actions and outcome.
Event / registration	Schedule, immutable published rules, capacity, entry status and check-in.
Ledger / reward	Append-only amount, reason, reference ID and unique idempotency key.
Message / report	Channel permissions, sender, timestamps and moderation status.
Transaction	Chain, hash, related event, observed status and reconciliation timestamp.

Operator workspace - OP-01

Provide a separate protected management area to draft/publish/cancel events, inspect room health, review reports, suspend accounts and investigate reward or transaction failures. Define player, moderator and organizer/admin permissions. Log privileged actions with actor, time, target and reason. Operators may not edit an active deck or retrospectively alter an accepted hand.

Observability and recovery - OP-02

Record structured errors and correlation IDs across client, API and room service. Track failed joins, queue duration, reconnect rate, game settlement failures and transaction reconciliation backlog. Exclude secrets and unrevealed cards from general logs. Document backup, restore, deployment rollback and interrupted-event handling.

Acceptance

A clean environment can be started from the README and example configuration. Database migrations and seed data are reproducible. Unauthorized role actions fail. A repeated reward job cannot double-credit an account. A recovery exercise demonstrates restoring persistent data and reconciling a pending operation.

Prove behavior, not just screenshots.

These are proposed acceptance targets. Confirm representative devices, hosting region and load profile during discovery before fixing performance commitments.

Quality area	Proposed target / verification
Rendering	Target 60 fps on agreed mid-range desktop and at least 30 fps on agreed mobile during table play. Measure effects enabled and reduced-motion mode.
Responsiveness	Layouts verified at 390, 768 and 1440 px; no horizontal page scroll or obscured legal actions.
Input feedback	Local control acknowledgement within 100 ms; pending state clearly separates a click from server acceptance.
Network	Measure p95 accepted-action update under the agreed regional load; proposed budget 500 ms excluding deliberate animation.
Initial payload	Proposed lobby transfer budget 5 MB compressed; lazy-load table and character media. Report actual build sizes.
Accessibility	Keyboard navigation, visible focus, readable contrast, non-color status cues, reduced motion and accessible modal focus.
Security	Server authorization, validation, rate limiting and secret management; clients cannot read opponent private cards.
Reliability	No duplicate debits, payouts or claims under retry, refresh and reconnect scenarios.

Required evidence

Unit tests: evaluator, action legality, split allocation, ledger invariants and reward idempotency. **Integration tests:** concurrent joins, registration capacity, event lifecycle and transaction reconciliation. **End-to-end tests:** four-player hand, event participation, social permissions and recovery after disconnection.

Visual review: approved screenshots and short recordings of all player states, selection, table transitions and mobile controls. **Load exercise:** propose and document a baseline of 25 concurrent four-seat rooms, then report resource usage and failure rates; larger scale is separately priced.

Release gate

No unresolved defect that loses or duplicates chips, exposes private information, blocks the core journey or crashes table play. Minor visual defects require a written list and owner acceptance. Deliver test results, known limitations and a reproducible build with the milestone submission.

Price the work in reviewable outcomes.

Milestone	Deliverable / exit criterion
M1 · Discovery	Repository review, confirmed rulebook, scope matrix, architecture, device targets, asset plan and itemized estimate. Owner resolves the decision register.
M2 · Art and UX	Editable lobby, selector and table designs; component system; character animation sample; mobile compositions. Visual direction approved before full asset production.
M3 · Visual demo	Implemented responsive scene, three characters, all action states and complete demo walkthrough. Existing mechanics pass regression checks.
M4 · Online core	Accounts, authoritative four-seat poker, queue/private rooms and reconnect. Independent sessions complete the acceptance flow.
M5 · Club systems	Events, live circuit, friends/parties/chat, reward ledger and basic operator tools. Capacity and duplicate-claim scenarios pass.
M6 · Web3 and release	Testnet attendance lifecycle, contract handoff, QA evidence, deployment/runbook and documented release package.

Final delivery package

Git repository and clean source ZIP; reproducible frontend and server builds; contract source/tests/scripts/ABI; database migrations and sample data; environment variable guide; API and real-time event documentation; editable design and licensed asset sources; setup, deployment, rollback and troubleshooting guides; test report and known-issues list.

Working method

Use a shared backlog with requirement IDs from this document. Each milestone submission includes a preview, a concise change list, test evidence and unresolved decisions. Changes to rules, asset quantities or platform support require a written impact estimate before entering the committed milestone. A defect fails an agreed requirement; a new requirement changes the scope.

Commercial assumptions

Budget, delivery dates, weekly availability, review turnaround and post-handoff support period are not set. Bidders should propose them per milestone, with assumptions, dependencies and separate optional pricing. Do not blend recurring hosting, asset licenses or independent audit fees into an unexplained total.

What the right partner should bring.

Suggested job title

Senior React Game Developer / Small Team for a 3D-Style Social Poker & Web3 Platform

Post-ready overview

We have a Vite, React and TypeScript casino game prototype and need an experienced developer or small team to take it to a polished online alpha. The priority is a professional game experience: an immersive poker scene, animated human characters, a refined lobby and clear feedback for every player action.

The engagement includes character selection, responsive game UI, real multiplayer, matchmaking, scheduled events, a scored tournament circuit, social features and an optional EVM wallet flow. Existing demo features provide a starting point; several are local simulations and need proper backend implementation. Initial delivery uses play money, with testnet attendance integration. Any real-value settlement is a separate phase.

Please read the attached functional scope and quote the milestones separately. We value demonstrated game interaction quality, reliable real-time systems, clear communication and maintainable code.

Required experience

Strong React/TypeScript/Vite delivery; polished animation and responsive UI; server-authoritative multiplayer; persistent transactional data; automated testing and deployment. Solidity/EVM expertise is required for the contract milestone. A team may divide design, backend and contract responsibilities, but must identify who owns each.

Include in your proposal

1. Two relevant playable examples and your exact contribution; include an animation or multiplayer sample.
2. A short assessment of the prototype, the largest risks and what you would preserve.
3. Your recommended lightweight character-animation approach, with asset and licensing assumptions.
4. A milestone estimate with effort, calendar duration, price, exclusions and recurring costs.
5. Your approach to reconnection, private-card secrecy, duplicate reward prevention and transaction confirmation.
6. Availability, team roles and the proposed handoff/support period.

Candidate review: prioritize relevant delivery evidence, visual craft and multiplayer correctness. Ask shortlisted applicants to explain an existing implementation. Any new evaluation task should be small, clearly scoped and paid.

Resolve these choices before the fixed bid.

ID / decision	Proposed baseline	Why it matters
D01 · First release	Play-money online alpha.	Determines economy, architecture and release gates.
D02 · Poker rules	Keep simplified demo rules; quote full rules separately.	Side pots and blinds materially change testing and tournaments.
D03 · Characters	Three existing identities, lightweight layered/sprite animation.	Sets asset production and runtime budget.
D04 · Event format	Four players, three scored rounds; defined tie allocation.	Fixes scoring, scheduling and reward logic.
D05 · Platforms	Responsive desktop/tablet/mobile web; browser matrix agreed in M1.	Controls layout, media and performance scope.
D06 · Accounts	Authenticated accounts plus guest practice; wallet linking optional.	Defines identity recovery and persistence.
D07 · Blockchain	One EVM testnet; attendance only.	Fixes chain configuration, finality and deployment tasks.
D08 · Hosting / region	One initial service region with selectable queue labels.	Global infrastructure is not implied by the UI.
D09 · Social scope	Friends, parties and text chat; no voice/video.	Defines moderation and operating burden.
D10 · Delivery terms	Milestone contract; dates, budget and support to be proposed.	Prevents an ambiguous fixed-price commitment.

Priority and ownership

The product owner approves rules, art direction and commercial boundaries. The contractor proposes implementation, documents tradeoffs and supplies acceptance evidence. Chain, settlement and production release decisions remain explicit owner approvals. The initial bid must flag any departure from the proposed baseline.

Document typography

Adobe Fonts recommendations informed this document's type choices: Fira Sans Bold for headings, by Carrois Corporate and Edenspiekermann AG (Mozilla); Roboto for body text, by David Berlow and Christian Robertson (Google). The game itself may use a more expressive display face while preserving readable controls.

Font references: Fira Sans on Adobe Fonts · Roboto on Adobe Fonts

Prepared for River Club contractor selection. Proposed scope and acceptance criteria require confirmation during discovery.