

Computer Science Course Notes — 1st Semester

Dario Loi

Contents

Models of Computation	1
First Lesson	1
Contact Information	1
Course Contents	1
Set Definition	1
Bactus Normal Form	2
Beta Reduction	2
Types of Variables	3
Extra Rules	4
Second Lecture	4
Alpha Reduction	4
Arithmetic Expressions	4
Combinators	5
Third Lecture	6
Fourth Lecture	6
Fifth Lecture	6
Sixth Lecture	7
Transformation Algorithm	8
Example of application	8

Models of Computation

First Lesson

Contact Information

Prof email: piperno@di.uniroma1.it

Actual lecture times:

- Wednesday 13:30 - 15:00
- Thursday 16:00 - 17:30, or 16:15 - 17:55

Course Contents

The course content will focus on **functional programming** and λ -calculus.

The course contains practical exercises that should be done by pen and paper, so do not rely on *just* these notes.

The main application of these languages is that of *function application*, these languages are devoid of *assignment* semantics, and are therefore called *pure*.

The main ingredients of our programs will be:

- Variables, which are usually denoted by lowercase letters
- Starting from these, you obtain the set of all programs, which are called λ -terms, this set is denoted as Λ .

Set Definition

We can provide an inductive definition of a set of λ -terms, Λ :

$$\frac{x \in V}{x \in \Lambda} \quad (\text{var})$$

$$\frac{M \in \Lambda \quad N \in \Lambda}{(MN) \in \Lambda} \quad (\text{app})$$

$$\frac{M \in \Lambda \quad x \in V}{\lambda x.M \in \Lambda} \quad (\text{abs})$$

Applying these inductive rules (variables, application, abstraction).

Bactus Normal Form

Another way of describing a set of lambda terms is by using Bactus Normal Form (BNF).

$$\Lambda :: Var | \Lambda \Lambda | \lambda Var. \Lambda$$

Which is essentially a grammar for the set of lambda terms.

Lambda calculus is left-associative:

$$((xy)z) = xyz \neq x(yz)$$

All functions are unary (we assume currying). For example, the function $f(x, y)$ is represented as:

$$\lambda x. \lambda y. fxy$$

.

Functions in lambda calculus can be applied to other functions or themselves, they can also return functions.

Beta Reduction

The main operation in lambda calculus is *beta reduction*, which is the application of a function to an argument.

$$\frac{(\lambda x.M)N}{\text{redex}} \rightarrow_{\beta} M[N/x]$$

Where $M[N/x]$ is the result of substituting all occurrences of x in M with N .

Some other examples:

$$(\lambda x.x)y \rightarrow_{\beta} y$$

$$(\lambda x.xx)y \rightarrow_{\beta} yy$$

$$(\lambda xy.yx)(\lambda u.u) \rightarrow_{\beta} \lambda y.y(\lambda u.u)$$

$$(\lambda x y. y x)(\lambda t. y) \rightarrow_{\beta} \lambda y. y(\lambda t. y)$$

This rule can be applied in any context in which it appears.

Formal Substitution Definition

We give a formal definition of substitution, $M[N/x]$:

$$x[N/x] = N$$

$$y[N/x] = y$$

$$(M_1 M_2)[N/x] = M_1[N/x] M_2[N/x]$$

$$(\lambda t. P)[N/x] = \lambda t. (P[N/x])$$

As observed, substitution is always in place of *free* variables, therefore the abstraction is *not* replaced in the last rule.

If we had an abstraction of type $\lambda x. P$ where $x \in P$, it would be best to rename x in order to avoid name clashes.

Types of Variables

We distinguish two kinds of variables:

- Free variables: variables that are not bound by an abstraction
- Bound variables: variables that are bound by an abstraction

For example, in the term $\lambda x. x y$, y is a free variable, while x is a bound variable.

Bound variables can be renamed, whereas for free variables the naming is relevant.

$$\begin{cases} FV(x) &= \{x\} \\ FV(MN) &= FV(M) \cup FV(N) \\ FV(\lambda x. M) &= FV(M) - \{x\} \end{cases}$$

A set of lambda terms where $LM(\Lambda) =$ is called *closed*.

Extra Rules

$$\begin{aligned}
 (\mu) \quad & \frac{M \rightarrow_{\beta} M'}{NM \rightarrow_{\beta} NM'} \\
 (\nu) \quad & \frac{M \rightarrow_{\beta} M'}{MN \rightarrow_{\beta} M'N} \\
 (\xi) \quad & \frac{M \rightarrow M'}{\lambda x.M \rightarrow \lambda x.M'}
 \end{aligned}$$

These rules allow us to select redexes in a context-free manner in the middle of our lambda term. We can then choose the order of evaluation of our redexes, while still taking care of the left-associative order of precedence. Our calculus is therefore not *determinate* but is still *deterministic*, meaning that there may be multiple reduction strategies but they all lead to the same result.

This corollary is called the *Church Rosser Theorem*, discovered in 1936.

In general, a call-by-value-like semantic is preferable when choosing evaluation paths, as it clears the most amount of terms as early as possible.

- Call By Value is *efficient*
- Call By Name is *complete*, if the lambda term is normalizable

Second Lecture

Alpha Reduction

Alpha reduction is the renaming of bound variables in a lambda term.

$$\lambda x.M \rightarrow_{\alpha} \lambda y.M[y/x]$$

This rule is used to avoid name clashes between bound variables.

Arithmetic Expressions

The set of all valid arithmetic expressions has a very precise syntax. In general, a syntax can be viewed either as a tool for checking validity or as a generator of valid expressions (a grammar).

We proceed to give a definition for arithmetic expressions

$$\begin{aligned}
 & \frac{x \in \mathbb{N}}{x \in \text{Expr}} \quad (\text{num}) \\
 & \frac{X \in \text{Expr} \quad Y \in \text{Expr}}{X + Y \in \text{Expr}} \quad (\text{add})
 \end{aligned}$$

$$\frac{X \in \text{Expr} \quad Y \in \text{Expr}}{X \times Y \in \text{Expr}} \quad (\text{mul})$$

Etc, etc... for all the other binary operations.

From this, we can successfully decompose any arithmetic expression into a syntactic tree. With this set of rules, we have a slight problem: we can't represent negative numbers. We could solve this either by adding a rule for unary minus, or by specifying the num rule over \mathbb{Z} instead of \mathbb{N} .

Combinators

We define three combinators:

$$S = \lambda xyz.xz(yz)$$

$$K = \lambda xy.x$$

$$I = \lambda u.u$$

We have that $SKy \rightarrow_{\beta} I$

Exercise 1.1: β -reduce $S(KS)S$

This reduces to $\lambda zbc.z(bc)$, which is the B combinator (composition).

Exercise 1.2: β -reduce $S(BBS)(KK)$.

This reduces to $\lambda zcd.zdc$, which is the C combinator (permutation).

For exercise this, we show a step-by-step reduction:

$$\begin{aligned} & S(BBS)(KK) \\ \rightsquigarrow & \lambda z.(BBS)z((KK)z) \\ \rightsquigarrow & \lambda z.(\lambda c.B(Sc))z((KK)z) \\ \rightsquigarrow & \lambda z.(\lambda c.B(Sc))zK \\ \rightsquigarrow & \lambda z.B(Sz)K \\ \rightsquigarrow & \lambda z.(\lambda c.(Sz)(Kc)) \\ \rightsquigarrow & \lambda zc.Sz(Kc) \\ \rightsquigarrow & \lambda zcd.zd(Kcd) \\ \rightsquigarrow & \lambda zcd.zdc \quad \square. \end{aligned}$$

Third Lecture

Recupera!!!

Fourth Lecture

First we do a simple exercise, β -reduce $\lambda uv.(\lambda z.zz)(\lambda t.tuv)$.

$$\begin{aligned} & \lambda uv.(\lambda z.zz)(\lambda t.tuv) \\ \rightarrow_{\beta} & \lambda uv.(\lambda t.tuv)(\lambda t.tuv) \\ \rightarrow_{\beta} & (\lambda t.tuv)(\lambda t.tuv) \\ \rightarrow_{\beta} & \lambda uv.(\lambda t.tuv)uv \\ \rightarrow_{\beta} & \lambda uv.uuvv \quad \square. \end{aligned}$$

Find a term X s.t $Xx = \lambda t.t(Xx)$

$$\begin{aligned} Xx &= \lambda t.t(Xx) \\ X &= (\lambda fxy.t(fx))X \\ X &= Y(\lambda fxy.t(fx)) \end{aligned}$$

Find a term H s.t $H(\lambda x_1x_2x_3.P) = \lambda ax_3x_2x_1.ax_1x_2x_3$

Fifth Lecture

Today we will try to be more precise about the *fixed point* operator.

The first question is:

Find X s.t:

$$XMN = MI(MN) \quad \forall M, N \in \Lambda$$

By substitution, we have:

$$X = \lambda xy.xI(xy)$$

This can be verified by beta reduction (we skip it since it's trivial).

Now, the core question is to replicate the same result with an expression that is *recursive* in nature.

For example: find $X \in \Lambda$ s.t:

$$XMN = M(XMN) \quad \forall M, N \in \Lambda$$

Sixth Lecture

This lecture will focus on *Combinatory Logic*, which is a simpler version of lambda calculus, where we only use combinators.

Here we have: * Application * Variables * *No* Abstraction

This means that *all* variables are *free*!

We have some *constants* (we define them using abstraction with a slight abuse of notation): * $S = \lambda xyz.xz(yz)$ * $K = \lambda xy.x$ * $I = \lambda x.x$ * $B = \lambda xyz.x(yz)$ * $C = \lambda xyz.xzy$

(Where SK is a sufficient base for all combinators, and the other combinators are syntactic sugar).

We define the CL set inductively, as follows:

$$\frac{x \in V}{x \in CL} \quad (\text{var})$$

$$\frac{X \in \text{const}}{X \in CL} \quad (\text{const})$$

$$\frac{X \in CL \quad Y \in CL}{(XY) \in CL} \quad (\text{app})$$

In the same way as lambda calculus, we use left-associative application.

$$((UV)W) = UVW \neq U(VW)$$

Our constants have *computational behavior*, as explained by the abstraction rules. We can give explicit definitions for constant computations in order to completely remove the abstraction rules.

- $SXYZ \triangleright XZ(YZ)$
- $KXY \triangleright X$
- $IX \triangleright X$
- $BXYZ \triangleright X(YZ)$
- $CXYZ \triangleright XZY$

Showing that these combinators map to lambda terms is trivial (we can just apply the definitions). Showing the opposite is a bit more complex, but it can be done.

We essentially want to *implement* the abstraction behavior from combinatory logic, so that we can transpose *any* lambda term (not just trivial combinators) into combinatory logic.

$$\lambda x.P \quad [x]P \quad (\text{abstraction of } x \text{ in } P)$$

For instance

$$\lambda xy.yx \quad [x]([y]yx)$$

Transformation Algorithm

Our aim is to produce an algorithm that performs this transformation:

$$([x]P)x \rightarrow P$$

We do this by creating a set of rules that we then apply iteratively (effectively performing a closure of the initial expression over the transformation set).

We define indicators U, V s.t:

$$\begin{cases} U & x \notin FV(U) \\ W, V & x \in FV(V) \end{cases}$$

Then we define the following rules:

- I. $[x]Ux = U$
- II. $[x]x = I$
- III. $[x]U = KU$
- IV. $[x](UW) = BU([x]W)$
- V. $[x][VU] = C([x]V)U$
- VI. $[x](VW) = S([x]V)([x]W)$

The order of the rules is *important*. This kind of algorithm is called a *markov algorithm*, which is a class of algorithms in which a set of rules is applied iteratively, with a priority order, until a fixed point is reached.

Example of application

Let's give an example of application by transforming

$$\lambda xy.ytx$$

We start by applying the rules:

$$\begin{aligned}
&\lambda xy.ytx \\
&\quad [x]([y](yt)x) \\
&\quad [x](C([y]yt)x) \\
&\quad [x](C(C([y]y)t)x) \\
&\quad [x](C(C(I)t)x) \\
&\quad [x]C(CIt)x \\
&\quad C(CIt)x
\end{aligned}$$

Now we can apply this combinatory logic expression to xy :

$$\begin{aligned}
C(CIt)xy &\triangleright C(CIt)yx \\
&\triangleright CIt yx \\
&\triangleright I ytx \\
&\triangleright ytx \quad \square.
\end{aligned}$$

In order to show that our result is

