

My solutions to
Deep Learning: Foundations and Concepts

Dario Miro Konopatzki

5 Single-Layer Networks: Classification

5.1

For all $1 \leq k \leq K$:

$$\begin{aligned}\mathbb{E}[T_k|X=x] &= \sum_{t \in \{0,1\}} t p_{T_k|X=x}(t) \\ &= 0 \cdot p_{T_k|X=x}(0) + 1 \cdot p_{T_k|X=x}(1) \\ &= p_{T_k|X=x}(1) \\ &= \begin{cases} 1 & \text{if class of } x \text{ is } c_k \\ 0 & \text{otherwise} \end{cases} \\ &= p_{C|X=x}(c_k)\end{aligned}$$

Hence $\mathbb{E}[T|X=x] = (p_{C|X=x}(c_k))_{1 \leq k \leq K}$.

5.2

Assume the convex hulls intersect, i.e. t.e. (α_n) and (β_m) s.t.

$$z := \sum_n \alpha_n x_n = \sum_m \beta_m y_m$$

Now assume the sets are linearly separable, i.e. t.e. \hat{w}, w_0 s.t. $\hat{w}^\top x_n + w_0 > 0$ for all x_n and $\hat{w}^\top y_m + w_0 < 0$ for all y_m . Then

$$\hat{w}^\top z + w_0 = \hat{w}^\top \left(\sum_n \alpha_n x_n \right) + w_0$$

$$\begin{aligned}
&= \sum_n \alpha_n \hat{w}^\top x_n + w_0 \\
&> \sum_n \alpha_n (-w_0) + w_0 \quad \alpha_n \geq 0 \text{ f.a. } n \\
&= -w_0 \sum_n \alpha_n + w_0 \\
&= -w_0 \cdot 1 + w_0 \quad \sum_n \alpha_n = 1 \\
&= 0
\end{aligned}$$

but also, $\hat{w}^\top z + w_0 < 0$ by the analogous argument via $z = \sum_m \beta_m y_m$, which is a contradiction.

The converse statement, that if the two sets of points are not linearly separable, then their convex hulls intersect, follows immediately from the contrapositive of the separating hyperplane theorem.