

Simulation and Analysis of 1D Wave Propagation under Various Physical Models

Dario Liotta



UNIVERSITÀ
DEGLI STUDI
DI PADOVA




Dipartimento
di Fisica
e Astronomia
Galileo Galilei

September 6th 2025


Course of **Quantum Information and Computing**
Academic Year 2024/2025

Numerical methods for differential equations

Ordinary Differential Equations




Partial Differential Equations




Numerical methods for differential equations

Ordinary Differential Equations



Partial Differential Equations



Introduction to the problem

Solving a **PDE** means to find a function u such that

$$\mathcal{L}u = f$$

where \mathcal{L} is a differential operator and f is a source term.

The equation holds in a domain Ω and is completed by prescribing **boundary conditions** on $\partial\Omega$.

In most physical applications \mathcal{L} is a second-order operator

- Poisson equation: $\mathcal{L} = -\Delta$
- Heat equation: $\mathcal{L} = \frac{\partial}{\partial t} - \Delta$
- Wave equation: $\mathcal{L} = \frac{\partial^2}{\partial t^2} - c^2 \Delta$

Introduction to the problem

Solving a **PDE** means to find a function u such that

$$\mathcal{L}u = f$$

where \mathcal{L} is a differential operator and f is a source term.

The equation holds in a domain Ω and is completed by prescribing **boundary conditions** on $\partial\Omega$.

In most physical applications \mathcal{L} is a second-order operator

- **Poisson** equation: $\mathcal{L} = -\Delta$
- **Heat** equation: $\mathcal{L} = \frac{\partial}{\partial t} - \Delta$
- **Wave** equation: $\mathcal{L} = \frac{\partial^2}{\partial t^2} - c^2 \Delta$

Weak formulation

Galerkin methods rely on a **weak formulation**

- Multiply by a test function v and integrate over the entire domain

$$-\int_{\Omega} (\Delta u) v d\Omega = \int_{\Omega} f v d\Omega$$

- Integrate by parts the left hand side

$$-\int_{\Omega} (\Delta u) v d\Omega = \int_{\Omega} \nabla u \cdot \nabla v d\Omega - \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds$$

- Substitute and get the new expression

$$\int_{\Omega} \nabla u \cdot \nabla v d\Omega = \int_{\Omega} f v d\Omega + \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds$$

Weak formulation

Galerkin methods rely on a **weak formulation**

- Multiply by a test function v and integrate over the entire domain

$$-\int_{\Omega} (\Delta u) v d\Omega = \int_{\Omega} f v d\Omega$$

- Integrate by parts the left hand side

$$-\int_{\Omega} (\Delta u) v d\Omega = \int_{\Omega} \nabla u \cdot \nabla v d\Omega - \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds$$

- Substitute and get the new expression

$$\int_{\Omega} \nabla u \cdot \nabla v d\Omega = \int_{\Omega} f v d\Omega + \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds$$

Weak formulation

Galerkin methods rely on a **weak formulation**

- Multiply by a test function v and integrate over the entire domain

$$-\int_{\Omega} (\Delta u) v d\Omega = \int_{\Omega} f v d\Omega$$

- Integrate by parts the left hand side

$$-\int_{\Omega} (\Delta u) v d\Omega = \int_{\Omega} \nabla u \cdot \nabla v d\Omega - \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds$$

- Substitute and get the new expression

$$\int_{\Omega} \nabla u \cdot \nabla v d\Omega = \int_{\Omega} f v d\Omega + \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds$$

Weak formulation

Galerkin methods rely on a **weak formulation**

- Multiply by a test function v and integrate over the entire domain

$$-\int_{\Omega} (\Delta u) v d\Omega = \int_{\Omega} f v d\Omega$$

- Integrate by parts the left hand side

$$-\int_{\Omega} (\Delta u) v d\Omega = \int_{\Omega} \nabla u \cdot \nabla v d\Omega - \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds$$

- Substitute and get the new expression

$$\int_{\Omega} \nabla u \cdot \nabla v d\Omega = \int_{\Omega} f v d\Omega + \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds$$

About the test function

The test function v is introduced to check whether the PDE is satisfied on average throughout the domain.

The problem becomes to find u such that

$$a(u, v) = F(v) \quad \forall v \in V$$

where

$$a(u, v) = \int_{\Omega} \nabla u \cdot \nabla v d\Omega \quad \text{is a } \underline{\text{bilinear form}}$$

$$F(v) = \int_{\Omega} f v d\Omega + \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds \quad \text{is a } \underline{\text{linear functional}}$$

About the test function

The test function v is introduced to check whether the PDE is satisfied on average throughout the domain.

The problem becomes to find u such that

$$a(u, v) = F(v) \quad \forall v \in V$$

where

$$a(u, v) = \int_{\Omega} \nabla u \cdot \nabla v d\Omega \quad \text{is a } \underline{\text{bilinear form}}$$

$$F(v) = \int_{\Omega} f v d\Omega + \int_{\partial\Omega} \frac{\partial u}{\partial n} v ds \quad \text{is a } \underline{\text{linear functional}}$$

Benefits of the weak formulation

Strong formulation

$$u \in C^2(\Omega)$$

Holds pointwise in Ω

Derivatives exist classically

Weak formulation

$$u, v \in H^1(\Omega)^*$$

Holds on average on Ω

Derivatives exist in the distributional sense

In short: weak formulation requires **less regularity**

* $H^1(\Omega)$ is a **Sobolev space** of functions with square-integrable first derivatives:

$$w \in H^1(\Omega) = \left\{ w \in L^2(\Omega) \mid \nabla w \in L^2(\Omega)^d \right\}$$

Benefits of the weak formulation

Strong formulation

$$u \in C^2(\Omega)$$

Holds pointwise in Ω

Derivatives exist classically

Weak formulation

$$u, v \in H^1(\Omega)^*$$

Holds on average on Ω

Derivatives exist in the distributional sense

In short: weak formulation requires **less regularity**

* $H^1(\Omega)$ is a **Sobolev space** of functions with square-integrable first derivatives:

$$w \in H^1(\Omega) = \left\{ w \in L^2(\Omega) \mid \nabla w \in L^2(\Omega)^d \right\}$$

On boundary conditions

Another difference lies in the boundary condition prescription.



$v = 0$ on $\partial\Omega \Rightarrow$ cancels boundary term
 (no information available on $\frac{\partial u}{\partial n}$)


v free on $\partial\Omega$

$u = g$ enforced on $\partial\Omega$ (final solution)

$\frac{\partial u}{\partial n} = h$ naturally enters weak form

On boundary conditions

Another difference lies in the boundary condition prescription.



Dirichlet becomes
essential condition

$v = 0$ on $\partial\Omega \Rightarrow$ cancels boundary term
 (no information available on $\frac{\partial u}{\partial n}$)

$u = g$ enforced on $\partial\Omega$ (final solution)



Neumann becomes
natural condition

v free on $\partial\Omega$

$\frac{\partial u}{\partial n} = h$ naturally enters weak form

On boundary conditions

Another difference lies in the boundary condition prescription.



$v = \mathbf{0}$ on $\partial\Omega \Rightarrow$ cancels boundary term
 (no information available on $\frac{\partial u}{\partial n}$)

v free on $\partial\Omega$

$u = g$ enforced on $\partial\Omega$ (final solution)

$\frac{\partial u}{\partial n} = h$ naturally enters weak form

Shape functions

Galerkin methods allow to find an approximate solution

$$u_h \in V_h \subset H^1(\Omega) \quad \text{where } V_h \text{ is a **finite-dimensional** space}$$

In this framework, the goal is to find u_h such that

$$a(u_h, v_h) = F(v_h) \quad \forall v_h \in V_h$$

A basis of function $\{\phi_i\}$ is chosen to express u_h and to use it as test:

$$u_h = \sum_{j=1}^N u_j \phi_j \implies a\left(\sum_{j=1}^N u_j \phi_j, \phi_i\right) = F(\phi_i) \quad \forall i = 1, \dots, N$$

Functions ϕ_i model the solution \longrightarrow **shape functions**

Shape functions

Galerkin methods allow to find an approximate solution

$$u_h \in V_h \subset H^1(\Omega) \quad \text{where } V_h \text{ is a **finite-dimensional** space}$$

In this framework, the goal is to find u_h such that

$$a(u_h, v_h) = F(v_h) \quad \forall v_h \in V_h$$

A **basis of function** $\{\phi_i\}$ is chosen to express u_h and to use it as test:

$$u_h = \sum_{j=1}^N u_j \phi_j \implies a\left(\sum_{j=1}^N u_j \phi_j, \phi_i\right) = F(\phi_i) \quad \forall i = 1, \dots, N$$

Functions ϕ_i model the solution \longrightarrow **shape functions**

Shape functions

Galerkin methods allow to find an approximate solution

$$u_h \in V_h \subset H^1(\Omega) \quad \text{where } V_h \text{ is a **finite-dimensional** space}$$

In this framework, the goal is to find u_h such that

$$a(u_h, v_h) = F(v_h) \quad \forall v_h \in V_h$$

A **basis of function** $\{\phi_i\}$ is chosen to express u_h and to use it as test:

$$u_h = \sum_{j=1}^N u_j \phi_j \implies a\left(\sum_{j=1}^N u_j \phi_j, \phi_i\right) = F(\phi_i) \quad \forall i = 1, \dots, N$$

Functions ϕ_i model the solution → **shape functions**

Final expression

By linearity of $a(\cdot, \cdot)$, the problem reduces to a **finite linear system**:

$$\sum_{j=1}^N u_j a(\phi_j, \phi_i) = F(\phi_i) \quad \forall i = 1, \dots, N$$

↓

$$A\mathbf{u} = \mathbf{F}$$

where

$$A_{i,j} = a(\phi_j, \phi_i)$$

form the **stiffness matrix**

$$\mathbf{u} = (u_1, \dots, u_N)^T$$

is the **vector of unknowns**

$$\mathbf{F} = (F(\phi_1), \dots, F(\phi_N))^T$$

is the **load vector**

Final expression

By linearity of $a(\cdot, \cdot)$, the problem reduces to a **finite linear system**:

$$\sum_{j=1}^N u_j a(\phi_j, \phi_i) = F(\phi_i) \quad \forall i = 1, \dots, N$$

\Downarrow

$$A\mathbf{u} = \mathbf{F}$$

where

$$A_{i,j} = a(\phi_j, \phi_i)$$

form the **stiffness matrix**

$$\mathbf{u} = (u_1, \dots, u_N)^T$$

is the **vector of unknowns**

$$\mathbf{F} = (F(\phi_1), \dots, F(\phi_N))^T$$

is the **load vector**

Mesh discretization

FEM approach consists in the subdivision of the domain in a so-called **mesh**

This choice brings several advantages:


- Good approximation of **complex geometries**
- Better capture of **local effects**
- Possibility of **adaptive refinement**
- Natural construction of a **global solution**

Mesh discretization


FEM approach consists in the subdivision of the domain in a so-called **mesh**

This choice brings several advantages:


- Good approximation of **complex geometries**
- Better capture of **local effects**
- Possibility of **adaptive refinement**
- Natural construction of a **global solution**




Elements



Elements




Elements



Finite Element Method

Application examples




Manual mesh refinement of a wrench using different element types

Image from COMSOL Multiphysics Encyclopedia, "Finite Element Mesh Refinement", 21st of February 2017

Mesh of a wheel rim composed of tetrahedrons in green, bricks in blue and prisms in pink

Image from COMSOL Multiphysics Blog, "Meshing Your Geometry: When to Use the Various Element Types", Walter Frei, 4th of November 2013



Choise of the base

Mesh division into sub-domains



Choice of a **local basis functions**



Exploitation of compact support



- Leads to sparse matrices
- Allows local interpolation
- Enhances numerical stability
- Enables efficient parallelization

Choise of the base

Mesh division into sub-domains



Choice of a **local basis functions**



Exploitation of compact support



- Leads to sparse matrices
- Allows local interpolation
- Enhances numerical stability
- Enables efficient parallelization

Choise of the base

Mesh division into sub-domains



Choice of a **local basis functions**



Exploitation of compact support



- Leads to sparse matrices
- Allows local interpolation
- Enhances numerical stability
- Enables efficient parallelization

Choise of the base

Mesh division into sub-domains




Choice of a local basis functions



- Exploitation of **compact support**



- Leads to **sparse matrices**
 - Allows **local interpolation**
 - Enhances **numerical stability**
 - Enables **efficient parallelization**



FEniCS library

A leading software platform for finite element computations is **FEniCS**.

- Open-source and freely available
- Multi-language support (C++ and Python APIs)
- Parallel computing with MPI support

FEniCS package: $\left\{ \begin{array}{ll} \text{DOLFIN} & (\text{backend core engine and PETSc interface}) \\ \text{UFL} & (\text{symbolic language}) \\ \text{FIAT} & (\text{shape functions tabulator}) \\ \text{FFC} & (\text{C++ compiler for efficient local assembly}) \\ \text{MSHR} & (\text{mesh generator}) \end{array} \right.$

FEniCS library

A leading software platform for finite element computations is **FEniCS**.

- **Open-source** and freely available
- **Multi-language support** (C++ and Python APIs)
- **Parallel computing** with MPI support



FEniCS package: $\left\{ \begin{array}{ll} \text{DOLFIN} & (\text{backend core engine and PETSc interface}) \\ \text{UFL} & (\text{symbolic language}) \\ \text{FIAT} & (\text{shape functions tabulator}) \\ \text{FFC} & (\text{C++ compiler for efficient local assembly}) \\ \text{MSHR} & (\text{mesh generator}) \end{array} \right.$

FEniCS library

A leading software platform for finite element computations is **FEniCS**.

- **Open-source** and freely available
- **Multi-language support** (C++ and Python APIs)
- **Parallel computing** with MPI support



FEniCS package: $\left\{ \begin{array}{ll} \text{DOLFIN} & (\text{backend core engine and PETSc interface}) \\ \text{UFL} & (\text{symbolic language}) \\ \text{FIAT} & (\text{shape functions tabulator}) \\ \text{FFC} & (\text{C++ compiler for efficient local assembly}) \\ \text{MSHR} & (\text{mesh generator}) \end{array} \right.$

A minimal FEniCS example: setup

Setup of a Poisson equation with Neumann boundary conditions in FEniCS:

- Generation of the mesh

```
domain = mesh.create_interval(MPI.COMM_WORLD, nx, [0.0, L])
```

- Definition of the finite element function space

```
V = functionspace(domain, ("Lagrange", 1))
```

- Definition of trial function and test function

```
u = ufl.TrialFunction(V)
v = ufl.TestFunction(V)
```

- Definition of the source term

```
f = fem.Constant(domain, default_scalar_type(-6))
```

A minimal FEniCS example: solution

Solving Poisson equation with Neumann boundary conditions in FEniCS:

- Weak formulation

```
a = ufl.dot(ufl.grad(u), ufl.grad(v)) * ufl.dx
F = f * v * ufl.dx
```

- Solution of the linear system

```
problem = LinearProblem(a, F,
                        petsc_option = {"ksp_type": "preonly",
                                      "pc_type" : "lu"
                                    })
u_h = problem.solve()
```

Approach to the classical wave equation


Our first goal is to approximate the solution of

$$\frac{\partial^2 u}{\partial t^2} - c^2 \frac{\partial^2 u}{\partial x^2} = 0 \quad \leftarrow \text{d'Alembert equation}$$

Approach to the classical wave equation

Our first goal is to approximate the solution of

$$\frac{\partial^2 u}{\partial t^2} - c^2 \frac{\partial^2 u}{\partial x^2} = 0 \quad \leftarrow \text{d'Alembert equation}$$



$$\int_0^L \frac{\partial^2 u}{\partial x^2} v dx = \left. \frac{\partial u}{\partial x} v \right|_0^L - \int_0^L \frac{\partial u}{\partial x} \frac{\partial v}{\partial x} dx$$

$$\frac{\partial^2 u}{\partial t^2} \simeq \frac{u^{(n+1)} - 2u^{(n)} + u^{(n-1)}}{\Delta t^2}$$

From PDE to ODEs

To do so, a **separable base** must be chosen:

$$u_h(x, t) = \sum_{j=1}^N u_j(t) \phi_j(x)$$

Managing the boundary term separately, the weak formulation goes as

$$\int_0^L \frac{\partial^2 u}{\partial t^2} v dx + c^2 \int_0^L \frac{\partial u}{\partial x} \frac{\partial v}{\partial x} dx = 0 \quad \forall v \in H^1([0, L])$$



$$\sum_{j=1}^N \frac{d^2 u_j}{dt^2} \int_0^L \phi_j \phi_i dx + c^2 \sum_{j=1}^N u_j \int_0^L \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx = 0 \quad \forall i = 1, \dots, N$$

From PDE to ODEs

To do so, a **separable base** must be chosen:

$$u_h(x, t) = \sum_{j=1}^N u_j(t) \phi_j(x)$$

Managing the boundary term separately, the weak formulation goes as

$$\int_0^L \frac{\partial^2 \textcolor{blue}{u}}{\partial t^2} \textcolor{green}{v} dx + c^2 \int_0^L \frac{\partial \textcolor{blue}{u}}{\partial x} \frac{\partial \textcolor{green}{v}}{\partial x} dx = 0 \quad \forall v \in H^1([0, L])$$



$$\sum_{j=1}^N \frac{d^2 u_j}{dt^2} \int_0^L \phi_j \phi_i dx + c^2 \sum_{j=1}^N u_j \int_0^L \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx = 0 \quad \forall i = 1, \dots, N$$

From PDE to ODEs

To do so, a **separable base** must be chosen:

$$u_h(x, t) = \sum_{j=1}^N u_j(t) \phi_j(x)$$

Managing the boundary term separately, the weak formulation goes as

$$\int_0^L \frac{\partial^2 \textcolor{blue}{u}}{\partial t^2} \textcolor{green}{v} dx + c^2 \int_0^L \frac{\partial \textcolor{blue}{u}}{\partial x} \frac{\partial \textcolor{green}{v}}{\partial x} dx = 0 \quad \forall v \in H^1([0, L])$$



$$\sum_{j=1}^N \frac{d^2 \textcolor{blue}{u}_j}{dt^2} \int_0^L \phi_j \phi_i dx + c^2 \sum_{j=1}^N u_j \int_0^L \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx = 0 \quad \forall i = 1, \dots, N$$

Matrix formulation

Let's define

$$M : M_{i,j} = \int_0^L \phi_j \phi_i dx \quad \leftarrow \text{Mass matrix}$$

$$A : A_{i,j} = \int_0^L \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx \quad \leftarrow \text{Stiffness matrix}$$



$$M \frac{d^2 u}{dt^2} + c^2 A u = 0$$

Matrix formulation

Let's define

$$M : M_{i,j} = \int_0^L \phi_j \phi_i dx \quad \leftarrow \text{Mass matrix}$$

$$A : A_{i,j} = \int_0^L \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx \quad \leftarrow \text{Stiffness matrix}$$



$$M \frac{d^2 \mathbf{u}}{dt^2} + c^2 A \mathbf{u} = 0$$

Time discretization

Let's apply **implicit central difference scheme**:

$$M \frac{\mathbf{u}^{(n+1)} - 2\mathbf{u}^{(n)} + \mathbf{u}^{(n-1)}}{\Delta t^2} + c^2 A \mathbf{u}^{(n+1)} = 0$$



$$\left(\frac{1}{\Delta t^2} M + c^2 A \right) \mathbf{u}^{(n+1)} = \frac{2}{\Delta t^2} M \mathbf{u}^{(n)} - \frac{1}{\Delta t^2} M \mathbf{u}^{(n-1)}$$

Time discretization

Let's apply **implicit central difference scheme**:

$$M \frac{\mathbf{u}^{(n+1)} - 2\mathbf{u}^{(n)} + \mathbf{u}^{(n-1)}}{\Delta t^2} + c^2 A \mathbf{u}^{(n+1)} = 0$$



$$\left(\frac{1}{\Delta t^2} M + c^2 A \right) \mathbf{u}^{(n+1)} = \frac{2}{\Delta t^2} M \mathbf{u}^{(n)} - \frac{1}{\Delta t^2} M \mathbf{u}^{(n-1)}$$


Analytical solutions

Solutions are known since 1747 due to d'Alembert himself.

- Dirichlet boundary conditions: $u(0, t) = u(L, t) = 0$

$$u(x, t) = \sum_{n=1}^{\infty} A_n \cos\left(\frac{n\pi}{L}ct\right) \sin\left(\frac{n\pi}{L}x\right)$$

with $A_n = \frac{2}{L} \int_0^L f(x) \sin\left(\frac{n\pi}{L}x\right) dx$.




Analytical solutions

Solutions are known since 1747 due to d'Alembert himself.

- **Neumann** boundary conditions: $\frac{\partial u}{\partial x}\Big|_{x=0} = \frac{\partial u}{\partial x}\Big|_{x=L} = 0$

$$u(x, t) = A_0 + \sum_{n=1}^{\infty} A_n \cos\left(\frac{n\pi}{L}ct\right) \cos\left(\frac{n\pi}{L}x\right)$$

with $A_0 = \frac{1}{L} \int_0^L f(x)dx$, $A_n = \frac{2}{L} \int_0^L f(x) \cos\left(\frac{n\pi}{L}x\right) dx$.



Approximate solutions

The selection of discretization steps should* take into account

$$\text{CFL stability condition : } \frac{c\Delta t}{\Delta x} \lesssim 1$$

Choosing first-order Lagrange polynomials as $\{\phi_i\}$:

*While for implicit schemes it is only a recommendation, for explicit ones it is mandatory.


Approximate solutions

The selection of discretization steps should* take into account


$$\text{CFL stability condition : } \frac{c\Delta t}{\Delta x} \lesssim 1$$

Choosing first-order Lagrange polynomials as $\{\phi_i\}$:

Dirichlet



Neumann



* While for implicit schemes it is only a recommendation, for explicit ones it is mandatory.

Energy loss

A strong indicator of numerical correctness is **energy conservation**.

$$\text{Energy: } E = \underbrace{\frac{T}{2c^2} \int_0^L \left(\frac{\partial u}{\partial t} \right)^2 dx}_{\text{Kinetic}} + \underbrace{\frac{T}{2} \int_0^L \left(\frac{\partial u}{\partial x} \right)^2 dx}_{\text{Potential}}$$

T is the *tension*, which can be arbitrarily set to 1.

Numerical energy decay is *independent* of the CFL number, being entirely caused by the **implicit scheme** itself.

Energy loss

A strong indicator of numerical correctness is **energy conservation**.

$$\text{Energy: } E = \underbrace{\frac{T}{2c^2} \int_0^L \left(\frac{\partial u}{\partial t} \right)^2 dx}_{\text{Kinetic}} + \underbrace{\frac{T}{2} \int_0^L \left(\frac{\partial u}{\partial x} \right)^2 dx}_{\text{Potential}}$$

T is the *tension*, which can be arbitrarily set to 1.

Numerical energy decay is *independent* of the CFL number, being entirely caused by the **implicit scheme** itself.


Energy loss

A strong indicator of numerical correctness is **energy conservation**.


$$\text{Energy: } E = \underbrace{\frac{T}{2c^2} \int_0^L \left(\frac{\partial u}{\partial t} \right)^2 dx}_{\text{Kinetic}} + \underbrace{\frac{T}{2} \int_0^L \left(\frac{\partial u}{\partial x} \right)^2 dx}_{\text{Potential}}$$

T is the *tension*, which can be arbitrarily set to 1.


CFL = 0.05



CFL = 0.25



CFL = 0.50



Numerical energy decay is *independent* of the CFL number, being entirely caused by the **implicit scheme** itself.

What if $c = c(x)$?

If c is not constant, its square must be interpolated as the wave function:

$$c(2x) \longrightarrow c_h^2(x) = \sum_{k=1}^N c_k^{(2)} \psi_k(x)$$

Velocity must be included in the stiffness matrix A :

$$A_{i,j} = \int_0^L \left(\sum_{k=1}^N c_k^{(2)} \psi_k(x) \right) \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx$$



$$M \frac{d^2 u}{dt^2} + A u = 0$$

What if $c = c(x)$?

If c is not constant, its square must be interpolated as the wave function:

$$c(2x) \longrightarrow c_h^2(x) = \sum_{k=1}^N c_k^{(2)} \psi_k(x)$$

Velocity must be included in the stiffness matrix A :

$$A_{i,j} = \int_0^L \left(\sum_{k=1}^N c_k^{(2)} \psi_k(x) \right) \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx$$



$$M \frac{d^2 u}{dt^2} + A u = 0$$

What if $c = c(x)$?

If c is not constant, its square must be interpolated as the wave function:

$$c(2x) \longrightarrow c_h^2(x) = \sum_{k=1}^N c_k^{(2)} \psi_k(x)$$

Velocity must be included in the stiffness matrix A :

$$A_{i,j} = \int_0^L \left(\sum_{k=1}^N c_k^{(2)} \psi_k(x) \right) \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx$$



$$M \frac{d^2 \mathbf{u}}{dt^2} + A \mathbf{u} = 0$$


Piecewise constant velocity

One simple example is the **piecewise constant function**:


$$c(x) = \begin{cases} c_1 & x \leq x_0 \\ c_2 & x > x_0 \end{cases}$$

Placing initial pulse on the left with $c_1 = 1, c_2 = 3$:

Dirichlet



Neumann




Piecewise constant velocity

One simple example is the **piecewise constant function**:


$$c(x) = \begin{cases} c_1 & x \leq x_0 \\ c_2 & x > x_0 \end{cases}$$

Placing initial pulse on the left with $c_1 = 3$, $c_2 = 1$:

Dirichlet



Neumann



Fresnel coefficients

In this case, the analytical reference values are the **Fresnel coefficients**.

$$T = \frac{2c_1}{c_1 + c_2} \quad R = \frac{c_2 - c_1}{c_1 + c_2}$$

T and R are numerically evaluated as the ratio of the transmitted and reflected waves to the incident one.

Smaller velocity \rightarrow Smaller coefficient \rightarrow Higher sensitivity to numerical errors


Fresnel coefficients

In this case, the analytical reference values are the **Fresnel coefficients**.


$$T = \frac{2c_1}{c_1 + c_2} \quad R = \frac{c_2 - c_1}{c_1 + c_2}$$

T and R are numerically evaluated as the ratio of the **transmitted** and **reflected** waves to the **incident** one.

$$c_1 < c_2$$



$$c_1 > c_2$$




Smaller velocity → Smaller coefficient → Higher sensitivity to numerical errors


Energy variation

Right after the wave crosses the interface, a clear **non-conservation of energy** emerges.

$$c_1 = 1 \quad c_2 = 3$$




$$c_1 = 3 \quad c_2 = 1$$




Energy variation

Right after the wave crosses the interface, a clear **non-conservation of energy** emerges.

$$c_1 = 1 \quad c_2 = 6$$




$$c_1 = 6 \quad c_2 = 1$$




Energy variation

Right after the wave crosses the interface, a clear **non-conservation of energy** emerges.

$$c_1 = 1 \quad c_2 = 9$$




$$c_1 = 9 \quad c_2 = 1$$



Energy variation

Right after the wave crosses the interface, a clear **non-conservation of energy** emerges.



Approach to the Schrödinger equation

Moving in the quantum realm, our next goal is to approximate the solution of a **1D time-dependent Schrödinger equation**:

$$i\hbar \frac{\partial \psi}{\partial t} = -\frac{\hbar^2}{2m} \frac{\partial^2 \psi}{\partial x^2} + V(x)\psi(x, t)$$



$$\underbrace{i\hbar \sum_{j=1}^N \frac{d\psi_j}{dt} \int_{-L}^L \phi_j \phi_i dx}_{i\hbar M \frac{d\psi}{dt}} = \underbrace{\frac{\hbar^2}{2m} \sum_{j=1}^N \psi_j \int_{-L}^L \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx}_{\frac{\hbar^2}{2m} A\psi} + \sum_{j=1}^N \psi_j \int_{-L}^L V \phi_j \phi_i dx$$

Approach to the Schrödinger equation

Moving in the quantum realm, our next goal is to approximate the solution of a **1D time-dependent Schrödinger equation**:

$$i\hbar \frac{\partial \psi}{\partial t} = -\frac{\hbar^2}{2m} \frac{\partial^2 \psi}{\partial x^2} + V(x)\psi(x, t)$$



$$\underbrace{i\hbar \sum_{j=1}^N \frac{d\psi_j}{dt} \int_{-L}^L \phi_j \phi_i dx}_{i\hbar M \frac{d\psi}{dt}} = \underbrace{\frac{\hbar^2}{2m} \sum_{j=1}^N \psi_j \int_{-L}^L \frac{\partial \phi_j}{\partial x} \frac{\partial \phi_i}{\partial x} dx}_{\frac{\hbar^2}{2m} A\psi} + \sum_{j=1}^N \psi_j \int_{-L}^L V \phi_j \phi_i dx$$

Potential matrix

In the equation it appears a linear term.

We must then introduce a new matrix, that can be called **potential matrix**, which is nothing different than a **weighted mass matrix**:

$$V : V_{i,j} = \int_{\Omega} V(x) \phi_j(x) \phi_i(x) dx$$



$$i\hbar M \frac{d\psi}{dt} = \frac{\hbar^2}{2m} A\psi + V\psi$$



$$\boxed{M \frac{d\psi}{dt} = -\frac{i}{\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi}$$

Potential matrix

In the equation it appears a linear term.

We must then introduce a new matrix, that can be called **potential matrix**, which is nothing different than a **weighted mass matrix**:

$$V : V_{i,j} = \int_{\Omega} V(x) \phi_j(x) \phi_i(x) dx$$



$$i\hbar M \frac{d\psi}{dt} = \frac{\hbar^2}{2m} A\psi + V\psi$$



$$\boxed{M \frac{d\psi}{dt} = -\frac{i}{\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi}$$

Potential matrix

In the equation it appears a linear term.

We must then introduce a new matrix, that can be called **potential matrix**, which is nothing different than a **weighted mass matrix**:

$$V : V_{i,j} = \int_{\Omega} V(x) \phi_j(x) \phi_i(x) dx$$



$$i\hbar M \frac{d\psi}{dt} = \frac{\hbar^2}{2m} A\psi + V\psi$$



$$\boxed{M \frac{d\psi}{dt} = -\frac{i}{\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi}$$

Potential matrix

In the equation it appears a linear term.

We must then introduce a new matrix, that can be called **potential matrix**, which is nothing different than a **weighted mass matrix**:

$$V : V_{i,j} = \int_{\Omega} V(x) \phi_j(x) \phi_i(x) dx$$



$$i\hbar M \frac{d\psi}{dt} = \frac{\hbar^2}{2m} A\psi + V\psi$$



$$M \frac{d\psi}{dt} = -\frac{i}{\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi$$

Application of the Crank-Nicholson method

In this case, the PDE is of first order in time.

The most suitable method to use is the **Crank-Nicholson** scheme:

$$M \frac{\psi^{(n+1)} - \psi^{(n)}}{\Delta t} = -\frac{i}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi^{(n+1)} - \frac{i}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi^{(n)}$$



$$\boxed{\left[M + \frac{i\Delta t}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \right] \psi^{(n+1)} = \left[M - \frac{i\Delta t}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \right] \psi^{(n)}}$$

Application of the Crank-Nicholson method

In this case, the PDE is of first order in time.

The most suitable method to use is the **Crank-Nicholson** scheme:

$$M \frac{\psi^{(n+1)} - \psi^{(n)}}{\Delta t} = -\frac{i}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi^{(n+1)} - \frac{i}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi^{(n)}$$



$$\boxed{\left[M + \frac{i\Delta t}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \right] \psi^{(n+1)} = \left[M - \frac{i\Delta t}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \right] \psi^{(n)}}$$

Application of the Crank-Nicholson method

In this case, the PDE is of first order in time.

The most suitable method to use is the **Crank-Nicholson** scheme:

$$M \frac{\psi^{(n+1)} - \psi^{(n)}}{\Delta t} = -\frac{i}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi^{(n+1)} - \frac{i}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \psi^{(n)}$$



$$\left[M + \frac{i\Delta t}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \right] \psi^{(n+1)} = \left[M - \frac{i\Delta t}{2\hbar} \left(\frac{\hbar^2}{2m} A + V \right) \right] \psi^{(n)}$$

How to handle imaginary part

The imaginary unit implies that the wavefunction is complex-valued.
 In order to work with standard real-valued FEM solvers, we apply a **real-imaginary splitting**:

$$\psi^{(i)} = \mathbf{u}^{(i)} + i\mathbf{w}^{(i)}$$

Setting $\alpha = \frac{\Delta t}{2\hbar}$ and $H = \frac{\hbar^2}{2m}A + V$:

$$(M + i\alpha H) (\mathbf{u}^{(n+1)} + i\mathbf{w}^{(n+1)}) = (M - i\alpha H) (\mathbf{u}^{(n)} + i\mathbf{w}^{(n)})$$



$$\begin{cases} M\mathbf{u}^{(n+1)} - \alpha H\mathbf{w}^{(n+1)} = M\mathbf{u}^{(n)} + \alpha H\mathbf{w}^{(n)} \\ \alpha H\mathbf{u}^{(n+1)} + M\mathbf{w}^{(n+1)} = -\alpha H\mathbf{u}^{(n)} + M\mathbf{w}^{(n)} \end{cases}$$

How to handle imaginary part

The imaginary unit implies that the wavefunction is complex-valued.
 In order to work with standard real-valued FEM solvers, we apply a **real-imaginary splitting**:

$$\psi^{(i)} = \mathbf{u}^{(i)} + i\mathbf{w}^{(i)}$$

Setting $\alpha = \frac{\Delta t}{2\hbar}$ and $H = \frac{\hbar^2}{2m}A + V$:

$$(M + i\alpha H) (\mathbf{u}^{(n+1)} + i\mathbf{w}^{(n+1)}) = (M - i\alpha H) (\mathbf{u}^{(n)} + i\mathbf{w}^{(n)})$$



$$\begin{cases} M\mathbf{u}^{(n+1)} - \alpha H\mathbf{w}^{(n+1)} = M\mathbf{u}^{(n)} + \alpha H\mathbf{w}^{(n)} \\ \alpha H\mathbf{u}^{(n+1)} + M\mathbf{w}^{(n+1)} = -\alpha H\mathbf{u}^{(n)} + M\mathbf{w}^{(n)} \end{cases}$$

How to handle imaginary part

The imaginary unit implies that the wavefunction is complex-valued.
 In order to work with standard real-valued FEM solvers, we apply a **real-imaginary splitting**:

$$\psi^{(i)} = \mathbf{u}^{(i)} + i\mathbf{w}^{(i)}$$

Setting $\alpha = \frac{\Delta t}{2\hbar}$ and $H = \frac{\hbar^2}{2m}A + V$:

$$(M + i\alpha H) (\mathbf{u}^{(n+1)} + i\mathbf{w}^{(n+1)}) = (M - i\alpha H) (\mathbf{u}^{(n)} + i\mathbf{w}^{(n)})$$



$$\begin{cases} M\mathbf{u}^{(n+1)} - \alpha H\mathbf{w}^{(n+1)} = M\mathbf{u}^{(n)} + \alpha H\mathbf{w}^{(n)} \\ \alpha H\mathbf{u}^{(n+1)} + M\mathbf{w}^{(n+1)} = -\alpha H\mathbf{u}^{(n)} + M\mathbf{w}^{(n)} \end{cases}$$

How to handle imaginary part

The imaginary unit implies that the wavefunction is complex-valued.
 In order to work with standard real-valued FEM solvers, we apply a **real-imaginary splitting**:

$$\psi^{(i)} = \mathbf{u}^{(i)} + i\mathbf{w}^{(i)}$$

Setting $\alpha = \frac{\Delta t}{2\hbar}$ and $H = \frac{\hbar^2}{2m}A + V$:

$$(M + i\alpha H) (\mathbf{u}^{(n+1)} + i\mathbf{w}^{(n+1)}) = (M - i\alpha H) (\mathbf{u}^{(n)} + i\mathbf{w}^{(n)})$$



$$\begin{cases} M\mathbf{u}^{(n+1)} - \alpha H\mathbf{w}^{(n+1)} = M\mathbf{u}^{(n)} + \alpha H\mathbf{w}^{(n)} \\ \alpha H\mathbf{u}^{(n+1)} + M\mathbf{w}^{(n+1)} = -\alpha H\mathbf{u}^{(n)} + M\mathbf{w}^{(n)} \end{cases}$$

Block matrix formulation

Concatenating real and imaginary components in a single vector, the final expression is

$$\begin{pmatrix} M & -\alpha H \\ \alpha H & M \end{pmatrix} \begin{pmatrix} \mathbf{u}^{(n+1)} \\ \mathbf{w}^{(n+1)} \end{pmatrix} = \begin{pmatrix} M & \alpha H \\ -\alpha H & M \end{pmatrix} \begin{pmatrix} \mathbf{u}^{(n)} \\ \mathbf{w}^{(n)} \end{pmatrix}$$

As before, the problem is recast as a **linear system of equations**.

Free particle scenario

If $V(x) = 0$, the solution of the Schrödinger equation describes a system called **free particle**.

A gaussian $\mathcal{G}(x|x_0, \sigma_0)$ can be chosen as *initial wave packet*:

$$\psi(x, 0) = (\pi\sigma_0^2)^{-\frac{1}{4}} e^{-\frac{(x-x_0)^2}{2\sigma_0^2} + ik_0 x}$$

We know the analytical solution of the equation:

$$\boxed{\psi(x, t) = \frac{1}{\sigma_t \sqrt{\pi}} e^{-\frac{(x-x_0 - \frac{\hbar k_0}{m} t)^2}{\sigma_t^2}} \quad \text{where } \sigma_t = \sigma_0 \sqrt{1 + \left(\frac{\hbar t}{m \sigma_0^2}\right)^2}}$$

Free particle scenario

If $V(x) = 0$, the solution of the Schrödinger equation describes a system called **free particle**.

A gaussian $\mathcal{G}(x|x_0, \sigma_0)$ can be chosen as *initial wave packet*:


$$\psi(x, 0) = (\pi\sigma_0^2)^{-\frac{1}{4}} e^{-\frac{(x-x_0)^2}{2\sigma_0^2} + ik_0 x}$$

We know the analytical solution of the equation:

$$\psi(x, t) = \frac{1}{\sigma_t \sqrt{\pi}} e^{-\frac{(x-x_0 - \frac{\hbar k_0}{m} t)^2}{\sigma_t^2}} \quad \text{where } \sigma_t = \sigma_0 \sqrt{1 + \left(\frac{\hbar t}{m \sigma_0^2}\right)^2}$$

Numerical simulation

Numerical simulation using FEM confirms the theoretical predictions.



Ballistic spreading

The numerical σ follows the same **ballistic behaviour** up until the time when the wavefunction reaches the boundary.


$$\sigma(t) \propto \frac{t}{\sigma_0} \longrightarrow \text{Bigger } \sigma_0, \text{ slower spreading}$$

Ballistic spreading


The numerical σ follows the same **ballistic behaviour** up until the time when the wavefunction reaches the boundary.

$\sigma(t) \propto \frac{t}{\sigma_0} \rightarrow$ Bigger σ_0 , slower spreading


$$\sigma_0 = 0.10$$



$$\sigma_0 = 0.15$$



$$\sigma_0 = 0.20$$



Smaller error with larger σ_0 at equal times

Kronig-Penney model

The introduction of a **periodic potential** leads to what is called a **Kronig-Penney-like model**, which is used to describe electrons in a crystal lattice.

Bloch's theorem states that solutions to the Schrödinger equation in a periodic potential can be expressed as *plane waves* modulated by *periodic functions* $u(x)$ with the same periodicity as the crystal:

$$\psi(x) = e^{ikx}u(x)$$

Kronig-Penney model

The introduction of a **periodic potential** leads to what is called a **Kronig-Penney-like model**, which is used to describe electrons in a crystal lattice.

Bloch's theorem states that solutions to the Schrödinger equation in a periodic potential can be expressed as *plane waves* modulated by *periodic functions* $u(x)$ with the same periodicity as the crystal:

$$\psi(x) = e^{ikx}u(x)$$

Bloch waves


A periodic potential $V(x) = V_0 \cos\left(\frac{2\pi}{a}x\right)$ couples plane waves which differ of multiples of $\frac{2\pi}{a}$, and the resulting superpositions form the **Bloch waves**.

Projection onto periodic plane waves




Formation of **lattice harmonics**


$$a = 1.0$$



$$a = 1.5$$



$$a = 2.0$$



Effective mass

With the periodic potential, the allowed energies are no longer continuous, but split into separate **bands**, each associated with different values of the *crystal momentum* k .

Taylor expansion around k_0 :

$$E(k) = E(k_0) + \frac{dE}{dk} \Big|_{k_0} (k - k_0) + \frac{1}{2} \frac{d^2E}{dk^2} \Big|_{k_0} (k - k_0)^2 + \dots$$

In the lowest bound, $k_0 = 0$ is the *minimum*:

$$E(k) \simeq E_0 + \frac{1}{2} \frac{d^2E}{dk^2} \Big|_{k=0} k^2$$

Comparing with the energy of a free particle, an **effective mass** can be found:

$$E(k) = E_0 + \frac{\hbar^2 k^2}{2m^*} \implies m^* = \hbar^2 \left(\frac{d^2E}{dk^2} \Big|_{k=0} \right)^{-1}$$

Effective mass

With the periodic potential, the allowed energies are no longer continuous, but split into separate **bands**, each associated with different values of the *crystal momentum* k .

Taylor expansion around k_0 :

$$E(k) = E(k_0) + \frac{dE}{dk} \Big|_{k_0} (k - k_0) + \frac{1}{2} \frac{d^2 E}{dk^2} \Big|_{k_0} (k - k_0)^2 + \dots$$

In the lowest bound, $k_0 = 0$ is the *minimum*:

$$E(k) \simeq E_0 + \frac{1}{2} \frac{d^2 E}{dk^2} \Big|_{k=0} k^2$$

Comparing with the energy of a free particle, an **effective mass** can be found:

$$E(k) = E_0 + \frac{\hbar^2 k^2}{2m^*} \implies m^* = \hbar^2 \left(\frac{d^2 E}{dk^2} \Big|_{k=0} \right)^{-1}$$

Effective mass

With the periodic potential, the allowed energies are no longer continuous, but split into separate **bands**, each associated with different values of the *crystal momentum* k .

Taylor expansion around k_0 :

$$E(k) = E(k_0) + \frac{dE}{dk} \Big|_{k_0} (k - k_0) + \frac{1}{2} \frac{d^2 E}{dk^2} \Big|_{k_0} (k - k_0)^2 + \dots$$

In the lowest bound, $k_0 = 0$ is the *minimum*:

$$E(k) \simeq E_0 + \frac{1}{2} \frac{d^2 E}{dk^2} \Big|_{k=0} k^2$$

Comparing with the energy of a free particle, an **effective mass** can be found:

$$E(k) = E_0 + \frac{\hbar^2 k^2}{2m^*} \implies m^* = \hbar^2 \left(\frac{d^2 E}{dk^2} \Big|_{k=0} \right)^{-1}$$

Effective mass

With the periodic potential, the allowed energies are no longer continuous, but split into separate **bands**, each associated with different values of the *crystal momentum* k .

Taylor expansion around k_0 :

$$E(k) = E(k_0) + \frac{dE}{dk} \Big|_{k_0} (k - k_0) + \frac{1}{2} \frac{d^2 E}{dk^2} \Big|_{k_0} (k - k_0)^2 + \dots$$

In the lowest bound, $k_0 = 0$ is the *minimum*:

$$E(k) \simeq E_0 + \frac{1}{2} \frac{d^2 E}{dk^2} \Big|_{k=0} k^2$$


Comparing with the energy of a free particle, an **effective mass** can be found:

$$E(k) = E_0 + \frac{\hbar^2 k^2}{2m^*} \implies m^* = \hbar^2 \left(\frac{d^2 E}{dk^2} \Big|_{k=0} \right)^{-1}$$

Sub-ballistic spreading

Around the *minimum of a band*, a quantum system in a periodic lattice behaves like a free particle with an effective mass m^* .

Since $\sigma \propto \frac{1}{m}$, a slower spreading is expected for a periodic lattice where $m^* > m$, due to the **parabolic approximation** of the band energy.



Addition of a linear term

The mean value, on the contrary, does not change.


In order to induce a *net drift*, we must add a linear potential
 $V(x) = Fx$.

The plot shows how dispersion causes interference effects to gradually *fade*.

Addition of a linear term


The mean value, on the contrary, does not change.

In order to induce a *net drift*, we must add a **linear potential**
 $V(x) = Fx$.




The plot shows how dispersion causes interference effects to gradually fade.


Average shift




$$V_0 = 1.00, F = 1.00$$



$$V_0 = 1.00, F = 1.25$$



$$V_0 = 1.00, F = 1.50$$



$$V_0 = 1.00, F = 2.00$$

Conclusions

Some final considerations:

- FEM provides a suitable approach for **second-order PDEs**
- Even though it has been used for very simple domains, in principle it can be applied to very **complex geometries**
- To handle time evolution, FEM must be coupled with **finite difference schemes** or other temporal integration methods
- The choice of spatial mesh and time step must satisfy some **stability and accuracy criteria** (like CFL condition or norm conservation)
- FEM allows easy incorporation of **boundary conditions**

In summary, our examples show that FEM is a very **robust** and **versatile** tool for spatial discretization, but time evolution requires appropriate temporal schemes.

Conclusions

Some final considerations:

- FEM provides a suitable approach for **second-order PDEs**
- Even though it has been used for very simple domains, in principle it can be applied to very **complex geometries**
- To handle time evolution, FEM must be coupled with **finite difference schemes** or other temporal integration methods
- The choice of spatial mesh and time step must satisfy some **stability and accuracy criteria** (like CFL condition or norm conservation)
- FEM allows easy incorporation of **boundary conditions**

In summary, our examples show that FEM is a very **robust** and **versatile** tool for spatial discretization, but time evolution requires appropriate temporal schemes.

Conclusions

Some final considerations:

- FEM provides a suitable approach for **second-order PDEs**
- Even though it has been used for very simple domains, in principle it can be applied to very **complex geometries**
- To handle time evolution, FEM must be coupled with **finite difference schemes** or other temporal integration methods
- The choice of spatial mesh and time step must satisfy some **stability and accuracy criteria** (like CFL condition or norm conservation)
- FEM allows easy incorporation of **boundary conditions**

In summary, our examples show that FEM is a very **robust** and **versatile** tool for spatial discretization, but time evolution requires appropriate temporal schemes.

Conclusions

Some final considerations:

- FEM provides a suitable approach for **second-order PDEs**
- Even though it has been used for very simple domains, in principle it can be applied to very **complex geometries**
- To handle time evolution, FEM must be coupled with **finite difference schemes** or other temporal integration methods
- The choice of spatial mesh and time step must satisfy some **stability and accuracy criteria** (like CFL condition or norm conservation)
- FEM allows easy incorporation of **boundary conditions**

In summary, our examples show that FEM is a very **robust** and **versatile** tool for spatial discretization, but time evolution requires appropriate temporal schemes.

Conclusions

Some final considerations:

- FEM provides a suitable approach for **second-order PDEs**
- Even though it has been used for very simple domains, in principle it can be applied to very **complex geometries**
- To handle time evolution, FEM must be coupled with **finite difference schemes** or other temporal integration methods
- The choice of spatial mesh and time step must satisfy some **stability** and **accuracy criteria** (like CFL condition or norm conservation)
- FEM allows easy incorporation of **boundary conditions**

In summary, our examples show that FEM is a very **robust** and **versatile** tool for spatial discretization, but time evolution requires appropriate temporal schemes.

Conclusions

Some final considerations:

- FEM provides a suitable approach for **second-order PDEs**
- Even though it has been used for very simple domains, in principle it can be applied to very **complex geometries**
- To handle time evolution, FEM must be coupled with **finite difference schemes** or other temporal integration methods
- The choice of spatial mesh and time step must satisfy some **stability** and **accuracy criteria** (like CFL condition or norm conservation)
- FEM allows easy incorporation of **boundary conditions**

In summary, our examples show that FEM is a very **robust** and **versatile** tool for spatial discretization, but time evolution requires appropriate temporal schemes.

Conclusions

Some final considerations:

- FEM provides a suitable approach for **second-order PDEs**
- Even though it has been used for very simple domains, in principle it can be applied to very **complex geometries**
- To handle time evolution, FEM must be coupled with **finite difference schemes** or other temporal integration methods
- The choice of spatial mesh and time step must satisfy some **stability** and **accuracy criteria** (like CFL condition or norm conservation)
- FEM allows easy incorporation of **boundary conditions**

In summary, our examples show that FEM is a very **robust** and **versatile** tool for spatial discretization, but time evolution requires appropriate temporal schemes.

Thank you for your attention!