

Base de datos

- - Habilitar la extensión para generar UUIDs automáticamente
CREATE EXTENSION IF NOT EXISTS "uuid-osspl";

- - =====
-- 1. NÚCLEO SAAS Y PLANES
-- =====

```
CREATE TABLE plans (  
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),  
  name VARCHAR(50) NOT NULL, -- Ej: 'Gratis', 'Pro', 'Team'  
  price DECIMAL(10, 2) NOT NULL DEFAULT 0.00,  
  features_config JSONB NOT NULL, -- Ej: {"max_tx": 200, "ai_limit": 50,  
    "can_export": true}  
  created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP  
);  
  
CREATE TABLE users (  
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),  
  email VARCHAR(255) UNIQUE NOT NULL,  
  password_hash VARCHAR(255), -- Nullable si usas OAuth (Google)  
  full_name VARCHAR(100) NOT NULL,  
  created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP,  
  updated_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP  
);  
  
CREATE TABLE subscriptions (  
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),  
  user_id UUID NOT NULL REFERENCES users(id) ON DELETE CASCADE,  
  plan_id UUID NOT NULL REFERENCES plans(id),  
  stripe_sub_id VARCHAR(255) UNIQUE, -- Para integración con pasarela de  
    pago  
  status VARCHAR(50) NOT NULL DEFAULT 'active', -- active, canceled,  
    past_due  
  current_period_end TIMESTAMP WITH TIME ZONE,  
  created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP  
);
```

```
CREATE TABLE workspaces (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  owner_id UUID NOT NULL REFERENCES users(id),
  name VARCHAR(100) NOT NULL, -- Ej: 'Finanzas Personales', 'Mi Startup'
  created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);
```

```
CREATE TABLE workspace_members (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
  user_id UUID NOT NULL REFERENCES users(id) ON DELETE CASCADE,
  role VARCHAR(50) NOT NULL DEFAULT 'viewer', -- admin, editor, viewer
  created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP,
  UNIQUE(workspace_id, user_id)
);
```

- - =====
 -- 2. CORE FINANCIERO
 -- =====

```
CREATE TABLE currencies (
  id SERIAL PRIMARY KEY,
  iso_code VARCHAR(3) UNIQUE NOT NULL, -- Ej: 'PEN', 'USD', 'EUR'
  symbol VARCHAR(5) NOT NULL
);
```

```
CREATE TABLE accounts (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
  currency_id INT NOT NULL REFERENCES currencies(id),
  name VARCHAR(100) NOT NULL,
  type VARCHAR(50) NOT NULL, -- bank, cash, credit_card
  balance DECIMAL(15, 2) NOT NULL DEFAULT 0.00,
  created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);
```

```
CREATE TABLE categories (
  id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
  workspace_id UUID REFERENCES workspaces(id) ON DELETE CASCADE, --
  NULL significa que es global/sistema
```

```

name VARCHAR(100) NOT NULL,
type VARCHAR(20) NOT NULL, -- expense, income
icon_name VARCHAR(50),
is_system BOOLEAN NOT NULL DEFAULT FALSE,
created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

CREATE TABLE transactions (
id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE
CASCADE,
account_id UUID NOT NULL REFERENCES accounts(id) ON DELETE CASCADE,
category_id UUID REFERENCES categories(id) ON DELETE SET NULL,
amount DECIMAL(15, 2) NOT NULL,
type VARCHAR(20) NOT NULL, -- expense, income, transfer
description TEXT,
transaction_date DATE NOT NULL,
source VARCHAR(20) NOT NULL DEFAULT 'manual', -- manual, ai, api, ocr
created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP,
updated_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

```

- - Índices para optimizar las consultas del Dashboard
CREATE INDEX idx_transactions_workspace_date ON
transactions(workspace_id, transaction_date);
CREATE INDEX idx_transactions_account ON transactions(account_id);
- - =====
-- 3. ETIQUETAS, ARCHIVOS Y AUDITORÍA
-- =====

```

CREATE TABLE tags (
id UUID PRIMARY KEY DEFAULT uuid_generate_v4(),
workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE
CASCADE,
name VARCHAR(50) NOT NULL,
created_at TIMESTAMP WITH TIME ZONE DEFAULT CURRENT_TIMESTAMP
);

CREATE TABLE transaction_tags (
transaction_id UUID NOT NULL REFERENCES transactions(id) ON DELETE

```

CASCADE,

tag_id UUID NOT NULL REFERENCES tagsNormally I can help with things like this, but I don't seem to have access to that content. You can try again or ask me for something else.

https://miro.com/app/board/uXjVH_PyaPY=/