

Localization Algorithms for Passive Sensor Networks

by

Darya Ismailova

B.Eng., University of Astrakhan, 2010

A Thesis Submitted in Partial Fulfillment of the
Requirements for the Degree of

MASTER OF APPLIED SCIENCE

in the Department of Electrical and Computer Engineering

© Darya Ismailova, 2016

University of Victoria

All rights reserved. This thesis may not be reproduced in whole or in part, by photocopying or other means, without the permission of the author.

Localization Algorithms for Passive Sensor Networks

by

Darya Ismailova

B.Eng., University of Astrakhan, 2010

Supervisory Committee

Dr. Wu-Sheng Lu, Supervisor
(Department of Electrical and Computer Engineering)

Dr. Pan Agathoklis, Departmental Member
(Department of Electrical and Computer Engineering)

Supervisory Committee

Dr. Wu-Sheng Lu, Supervisor
(Department of Electrical and Computer Engineering)

Dr. Pan Agathoklis, Departmental Member
(Department of Electrical and Computer Engineering)

ABSTRACT

...

Contents

Supervisory Committee	ii
Abstract	iii
Table of Contents	iv
List of Abbreviations	v
List of Tables	vi
List of Figures	vii
1 Least Squares Localization by Sequential Convex Relaxation	1
1.1 Second Order Cone Programming	1
1.2 Range-based localization	1
1.3 Range-Difference Localization	3
Bibliography	4

List of Abbreviations

LS	Least Squares
ML	Maximum Likelihood
MDS	Multidimensional Scaling
DW-MDS	Distributed Weighted-Multidimensional Scaling
SR-LS	
SRD-LS	
PDF	Probability Density Function
SPF	standard fixed point
SWLS	sequential weighted least squares
WSR-LS	weighted squared range based least squares (WSR-LS)
WSRD-LS	weighted squared range-difference based least squares (WSR-LS)
GTRS	
IRWSR-LS	
IRWSRD-LS	
MSE	
TDOA	
TOA	
WCDMA	
LTE	
O-TDOA	
CRLB	Cramér-Rao lower bound
NLLS	Non-Linear Least Squares
SMACOF	Scaling by MAjorizing a COmplicated Function
RSS	Received Signal Strength
NLOS	Non-Line Of Sight
UWB	Ultra Wide Band
SDP	SemiDefinite Programming
DC	Difference of Convex
PCCP	Penalty Convex Concave Procedure
CCP	Convex Concave Procedure
LP	Linear Program

List of Tables

List of Figures

Chapter 1

Least Squares Localization by Sequential Convex Relaxation

1.1 Second Order Cone Programming

1.2 Range-based localization

Problem: Given sensor array $\mathbf{a}_i, i = 1, 2, \dots, m$ and noisy range measurements r_i find the true *unknown* location of \mathbf{x} as

$$\text{minimize } \sum_i^m (\|\mathbf{x} - \mathbf{a}_i\| - r_i)^2 \quad (1.1)$$

which can be (equivalently) written as

$$\begin{aligned} & \text{minimize}_{\mathbf{x}, \mathbf{z}} \sum_i^m (z_i - r_i)^2 \\ & \text{subject to: } \|\mathbf{x} - \mathbf{a}_i\| = z_i, i = 1, 2, \dots, m \end{aligned} \quad (1.2)$$

The constraint in 5.2 is hard to suffice, therefore we allow a relaxation:

$$\begin{aligned} & \text{minimize}_{\mathbf{x}, \mathbf{z}} \sum_i^m (z_i - r_i)^2 \\ & \text{subject to: } \|\mathbf{x} - \mathbf{a}_i\| \leq (1 + \gamma)z_i \\ & \|\mathbf{x} - \mathbf{a}_i\| \geq (1 - \gamma)z_i, \quad i = 1, 2, \dots, m \end{aligned} \quad (1.3)$$

where γ is small, typically $0 < \gamma < 0.5$. This would yield an approximate solution to 5.2 and therefore to 5.1. By allowing γ to sequentially/monotonically decrease from some small $0 < \gamma_0 < 0.5$ to 0 solution of 5.3 will converge to 5.2. *Proof* Let $\gamma(k)$ be monotonically decreasing, where k is an iteration count and $0 < \gamma_0 < 0.5$. Then $\lim_{\gamma \rightarrow 0} (1 + \gamma)z_i = z_i$ and $\lim_{\gamma \rightarrow 0} (1 - \gamma)z_i = z_i$. Therefore as γ approaches 0, the feasible region of the problem in 5.3 will become equivalent to that in 5.2. As iterations proceed, the objective in 5.3 will not be monotonically decreasing but it will converge to the critical point.

Problem in 5.3 is nonconvex due to nonconvexity of one of its inequality constraint. The constraint in 5.3b $\|\mathbf{x} - \mathbf{a}_i\| \leq (1 + \gamma)z_i$ is convex, the constraint in 5.3c is not, because

$$\|\mathbf{x} - \mathbf{a}_i\| \geq (1 - \gamma)z_i \iff \underbrace{-\|\mathbf{x} - \mathbf{a}_i\|}_{\text{nonconvex}} \leq -(1 - \gamma)z_i$$

From convexity of the norm $\|\mathbf{x} - \mathbf{a}_i\|$ it follows that for some *known* \mathbf{x}_k

$$\|\mathbf{x} - \mathbf{a}_i\| \geq \|\mathbf{x}_k - \mathbf{a}_i\| + \partial\|\mathbf{x}_k - \mathbf{a}_i\|^T(\mathbf{x} - \mathbf{a}_i)$$

Hence the constraint in 5.3c can be convexified by replacing it with its affine approximation

$$-\|\mathbf{x}_k - \mathbf{a}_i\| - \partial\|\mathbf{x}_k - \mathbf{a}_i\|^T(\mathbf{x} - \mathbf{a}_i) \leq -(1 - \gamma)z_i$$

At the k th iteration when the iterate \mathbf{x}_k is known, the nonconvex problem in 5.3 can be relaxed to an SOCP problem

$$\underset{\mathbf{x}, \mathbf{z}}{\text{minimize}} \sum_i^m (z_i - r_i)^2 \quad (1.4)$$

$$\text{subject to: } \|\mathbf{x} - \mathbf{a}_i\| \leq (1 + \gamma)z_i \quad (1.4)$$

$$-\|\mathbf{x}_k - \mathbf{a}_i\| - \partial\|\mathbf{x}_k - \mathbf{a}_i\|^T(\mathbf{x} - \mathbf{a}_i) \leq -(1 - \gamma)z_i \quad (1.4)$$

$$i = 1, 2, \dots, m$$

The relaxation parameter γ controls the size of the convex hull that defines a feasibility region of the problem 5.4. γ needs to be monotonically decreasing with increase of the iteration count. Start with some $0 < \gamma_0 < 0.5$, typically $\gamma_0 = 0.3$ or 0.2 is good. After k th iteration update γ_{k+1} linearly as

$$\gamma_{k+1} = \gamma_0 - k \frac{\gamma_0}{K_{max} - 1}$$

or quadratically as

$$\gamma_{k+1} = \gamma_0 \frac{(K_{max} - 1 - k)^2}{(K_{max} - 1)^2}$$

1.3 Range-Difference Localization

Measurement model

$$d_i = \|\mathbf{x} - \mathbf{a}_i\| - \|\mathbf{x}\| + noise$$

Least-squares formulation

$$\text{minimize} \sum_{i=1}^m (\|\mathbf{x} - \mathbf{a}_i\| - \|\mathbf{x}\| - d_i)^2$$

write an equivalent form

$$\begin{aligned} &\text{minimize} \sum_{i=1}^m (z_i - y - d_i)^2 \\ &\text{subject to: } \|\mathbf{x} - \mathbf{a}_i\| = z_i \\ &\quad \|\mathbf{x}\| = y, i = 1, 2, \dots, m \end{aligned}$$

Denote $\hat{\mathbf{x}} = [\mathbf{x}^T \ y \ z_1 \dots z_m]^T$. At the k th iterations with $\hat{\mathbf{x}}_k$ *known* update $(\mathbf{x}_k, y_k, \mathbf{z}_k)$ to

$$\mathbf{x}_{k+1} = \mathbf{x}_k + \sigma_x$$

$$y_{k+1} = y_k + \sigma_y$$

$$\mathbf{z}_{k+1} = \mathbf{z}_k + \sigma_z$$

Then the objective can be written as ...
and the constraints ..

Bibliography

- [1] J. O. Smith and J. S. Abel, "Closed-form least-squares source location estimation from range-difference measurements," *IEEE Trans. on Acoustic, Speech Signal Proc.*, vol. 12, pp. 1661–1669, Dec. 1987.
- [2] H. Schau and A. Robinson, "Passive source localization employing intersecting spherical surfaces from time-of-arrival differences," *IEEE Trans. on Acoustic, Speech Signal Proc.*, vol. ASSP-35, pp. 1223–1225, Aug. 1987.
- [3] K. Yao, R. Hudson, C. Reed, D. Chen, and F. Lorenzelli, "Blind beamforming on a randomly distributed sensor array system," *IEEE J. Select. Areas Commun.*, vol. 16, pp. 1555–1567, Oct. 1998.
- [4] M. A. Sprito, "On the accuracy of cellular mobile station location estimation," *IEEE Trans. on Veh. Technol.*, vol. 50, pp. 674–685, May 2001.
- [5] Y. Huang, J. Benesty, G. W. Elko, and R. M. Mersereau, "Realtime passive source localization: A practical linear correction least-squares approach," *IEEE Trans. on Speech Audio Proc.*, vol. 9, no. 8, pp. 943–956, Nov. 2002.
- [6] K. W. Cheung, H. C. So, W. K. Ma, and Y. T. Chan, "Least squares algorithms for time-of-arrival-based mobile location," *IEEE Trans. on Signal Proc.*, vol. 52, no. 4, pp. 1121–1228, Apr. 2004.
- [7] D. Li and H. Hu, "Energy-Based Collaborative Source Localization Using Acoustic Microsensor Array," in *EURASIP Journal on Applied Signal Proc.*, vol. 4, 321–337, 2003.
- [8] X. Sheng and Y.-H. Hu, "ML Multiple-source localization using acoustic energy measurements with wireless sensor networks," *IEEE Trans. on Signal Proc.*, vol. 53, no.1, pp. 44–53, Jan. 2005.

- [9] Z. M. Saric, D. D. Kukolj, and N. D. Teslic, “Acoustic source localization in wireless sensor network”, *Circuits Syst Signal Proc.*, vol. 29, pp. 837–856, 2010.
- [10] L.Lu, H.-C. Wu, K.Yan, and S.Iyengar, “Robust expectation maximization algorithm for multiple wideband acoustic source localization in the presence of nonuniform noise variances,” *IEEE Sensors J.*, vol. 11, no. 3, pp. 536–544, Mar. 2011.
- [11] K.W. Cheung, W.K. Ma, and H.C. So, “Accurate approximation algorithm for TOA-based maximum-likelihood mobile location using semidefinite programming,” in *Proc. ICASSP*, vol. 2, pp. 145–148, 2004.
- [12] A. H. Sayed, A. Tarighat, and N. Khajehnouri, “Network-based wireless location,” *IEEE Signal Proc. Mag.*, vol. 22, no. 4, pp. 24–40, July 2005.
- [13] Y. T. Chan, H. Y. C. Hang, and P. C. Ching, “Exact and approximate maximum likelihood localization algorithms,” *IEEE Trans. on Veh. Technol.*, vol. 55, no. 1, pp. 10–16, Jan. 2006.
- [14] P. Stoica and J. Li, “Source localization from range-difference measurements,” *IEEE Signal Proc. Mag.*, vol. 23, pp. 63–65,69, Nov. 2006.
- [15] A. Beck, P. Stoica and J. Li, “Exact and approximate solutions of source localization problems,” *IEEE Trans. on Signal Proc.*, vol. 56, no. 5, pp. 1770–1777, May 2008.
- [16] A. Beck, M. Teboulle, and Z. Chikishev, “Iterative minimization schemes for solving the single source localization problem,” *SIAM J. Optim.*, vol. 19, no. 3, pp. 1397–1416, Nov. 2008.
- [17] I. Daubechies, R. DeVore, M. Fornasier, and C. S. Güntürk, “Iteratively reweighted least squares minimization for sparse recovery,” *Comm. Pure Appl. Math.*, vol. 63, pp. 1–38, 2010.
- [18] A. Beck, and D. Pan, “On the solution of the GPS localization and circle fitting problems,” *SIAM J. Optim.*, vol. 22, no. 1, pp. 108–134, Jan. 2012.
- [19] A. Beck, “On the convergence of alternating minimization for convex programming with applications to iteratively re-weighted least squares and decomposition schemes,” *SIAM J. Optim.*, vol. 25, no. 1, pp. 185–209, Jan. 2015.

- [20] J.J. More, “Generalizations of the trust region subproblem,” *Optim. Methods Softw.*, vol. 2, pp. 189–209, 1993.
- [21] C. Fortin and H. Wolkowicz, “The trust region subproblem and semidefinite programming,” *Optim. Methods Softw.*, vol. 19, no.1, pp. 41–67, 2004.
- [22] D.P. O’Leary, “Robust regression computation using iteratively reweighted least squares,” *SIAM J. Matrix Anal. Appl.*, vol. 11, no. 3, pp. 466–480, 1990.
- [23] N. Bissantz, L. Dümbgen, A. Munk, and B. Stratmann, “Convergence analysis of generalized iteratively reweighted least squares algorithms on convex function spaces,” *SIAM J. Optim.*, vol. 19, no. 4, pp 1828–1845, 2009.
- [24] K. W. Cheung and H. C. So, “A multidimensional scaling framework for mobile location using time-of-arrival measurements,” *IEEE Trans. on Signal Proc.*, vol. 53, no. 2, pp. 460–470, Feb. 2005.
- [25] S. Qin, Q. Wan, and L.-F. Duan, “Fast and efficient multidimensional scaling algorithm for mobile positioning,” *IET Signal Processing*, vol. 6, no. 9, pp. 857–861, March 2012.
- [26] J.A. Costa, N. Patwari, and A. O. Hero, “Distributed weighted-multidimensional scaling for node localization in sensor networks,” *ACD Trans. Sens. Netw.*, vol. 2, no. 1, pp. 39–64, 2006.
- [27] H.C. So and F.K.W. Chan, “Generalized Subspace Approach for Mobile Positioning With Time-of-Arrival Measurements,” *IEEE Trans. on Signal Proc.*, vol. 55, no. 10, pp. 5103–5107, October 2007.
- [28] H. Liu, H. Darabi, P. B, and J. Liu, “Survey of Wireless Indoor Positioning Techniques and Systems,” *IEEE Trans. on Systems, Man and Cybernetics. Part C: Applications and Reviews*, vol. 37, no. 6, pp. 1067–1080, Nov. 2007.
- [29] Y. Liu, Y.H. Hu, and Q. Pan, “Distributed, Robust Acoustic Source Localization in a Wireless Sensor Network,” *IEEE Trans. on Signal Proc.*, vol. 60, no. 8, pp. 4350–4359, Aug. 2012.
- [30] W. Kim, J. Lee, and G. Jee, “The interior-point method for an optimal treatment of bias in trilateration location,” *IEEE Trans. Veh. Technol.*, vol. 55, no. 4, pp. 1291–1301, Jul. 2006.

- [31] T. Qiao, S. Redfield, A. Abbasi, Z. Su, and H. Liu, “Robust coarse position estimation for TDOA localization,” *IEEE Wireless Commun. Lett.*, vol. 2, no. 6, pp. 623–626, Dec. 2013.
- [32] A. L. Yuille and A. Rangarajan, “The concave-convex procedure,” *Neural Computation*, vol. 15, no. 4, pp. 915–936, 2003.
- [33] T. Lipp and S. Boyd, “Variations and extensions of the convex-concave procedure,” *Research Report*, Stanford University, Aug. 2014.
- [34] G. R. Lanckreit and B. K. Sriperumbudur, “On the convergence of the concave-convex procedure,” in *Advances in Neural Information Proc. Systems*, pp. 1759–1767, 2009.
- [35] Y. Kang, Z. Zhang, and W.-J. Li, “On the global convergence of majorization minimization algorithms for nonconvex optimization problems,” in *arXiv:1504.07791v2*, 2015.
- [36] M. R. Gholami, S. Gezici, and E. G. Ström, “TW-TOA based positioning in the presence of clock imperfections,” *Digital Signal Processing*, vol. 59, pp. 19–30, 2016.
- [37] M. R. Gholami, E. G. Ström, F. Sottile, D. Dardari, A. Conti, S. Gezici, M. Rydström, and M. A. Spirito, “Static positioning using UWB range measurements,” in *Future Network and Mobile Summit Conference Proceedings*, pp. 1–10, 2010.
- [38] D. Dardari, A. Conti, U. J. Ferner, A. Giorgetti, and M. Z. Win, “Ranging with ultrawide bandwidth signals in multipath environments,” *Proceedings of the IEEE*, vol. 97, pp. 427–450, 2009.
- [39] M. R. Gholami, E. G. Ström, and M. Rydström, “Indoor sensor node positioning using UWB range measurements,” in *17th European Signal Processing Conference (Eusipco)*, pp. 1943–1947, 2009.
- [40] L. Vandenberghe and S. Boyd, “Semidefinite programming,” *SIAM Rev.*, vol. 38, no. 1, pp. 40–95, Mar. 1996.
- [41] P. Hartman, “On functions representable as a difference of convex functions,” *Pacific Journal of Math*, vol. 9, no. 3, pp. 707–713, 1959.

- [42] A. Antoniou and W.-S. Lu, *Practical Optimization: Algorithms and Engineering Applications*, Springer, New-York, 2007.
- [43] Y. Nesterov, *Introductory Lectures on Convex Optimization*, Kluwer Academic Publishers, Boston, 2004.
- [44] C. Gentile, N. Alsindi, R. Raulefs, and C. Teolis, *Geolocation Techniques: Principles and Applications*, Springer, New-York, 2013.
- [45] CVX Research, <http://cvx.com/cvx>, August 2012.
- [46] The Mathworks Inc., <http://mathworks.com>, 2015.
- [47] “Iterative re-weighting”
- [48] “Penalty Convex-Concave Procedure of Source Localization Problem,”