Storage Log AI Analyzer — User Guide

Version 0.2.0 · Suresh Kumar Darisi

Project website · GitHub · Download PDF

1. What the tool does

Analyze exported Pure Storage, Dell EMC, and HPE logs locally. The tool identifies known storage and security patterns, groups evidence into findings, and creates terminal, JSON, or Markdown reports. An optional AI mode assesses a redacted finding summary.

This is a command-line tool. It does not connect directly to your arrays, collect logs continuously, repair faults, or provide a hosted upload service. Treat results as an operational aid and confirm findings against the original evidence and vendor tools.

2. Requirements

- Python 3.10 or newer; Git for the source-install workflow.
- Permission to read the exported logs and write your chosen report directory.
- Internet access for initial installation. Ordinary local analysis does not require internet access.
- Optional AI requires the AI package extra, API access, and a configured key. API usage may incur charges.

3. Install on macOS or Linux

```
git clone https://github.com/darisisuresh/storage-log-ai-analyzer.git
cd storage-log-ai-analyzer
python3 -m venv .venv
source .venv/bin/activate
python -m pip install --upgrade pip
python -m pip install -e .
storage-log-analyzer --version
```

Expected version output: `storage-log-analyzer 0.2.0`. The base analyzer has no third-party runtime dependencies. To reproduce this release, check out tag `v0.2.0` before installing.

4. Install on Windows PowerShell

```
git clone https://github.com/darisisuresh/storage-log-ai-analyzer.git
cd storage-log-ai-analyzer
py -3 -m venv .venv
.\.venv\Scripts\python.exe -m pip install --upgrade pip
.\.venv\Scripts\python.exe -m pip install -e .
.\.venv\Scripts\storage-log-analyzer.exe --version
```

This workflow does not require activating PowerShell scripts. For the remaining examples, either activate the environment or replace `storage-log-analyzer` with `.\.venv\Scripts\storage-log-analyzer.exe`.

5. Try the synthetic sample first

Run these from the repository directory:

```
storage-log-analyzer vendors
```

```
storage-log-analyzer validate samples/mixed-storage.log
storage-log-analyzer summary samples/mixed-storage.log
storage-log-analyzer analyze samples/mixed-storage.log --fail-on never
```

The bundled sample has five events across three vendor families. Expected analysis starts with `Overall risk: CRITICAL` and `Events: 5 | Files: 1`. It includes drive failure, authentication failure, path failure, capacity, and replication findings. These are synthetic examples, not a benchmark of detection accuracy.

`--fail-on never` prevents a detected risk from returning exit code 2. It does not hide findings or suppress input errors.

6. Prepare your own logs

Export logs through your vendor's supported process. Keep originals read-only and work with a copy outside the source repository. Use a case directory containing text, syslog text, CSV, JSON, or JSON Lines exports.

Directory scanning includes `.log`, `.txt`, `.csv`, `.json`, and `.jsonl`, recursively. Do not scan a directory that also contains generated reports: JSON report files may otherwise be treated as new inputs. Compressed or proprietary support bundles must be extracted and converted to supported text exports first.

JSON accepts one event object, an array, or an object with an `events` array. Common fields include `timestamp` or `time`, `message` or `msg` or `description`, and `severity` or `level`.

```
{"events": [{"timestamp": "2026-01-01T00:00:00Z", "severity": "critical", "message": "HPE Alletra drive 7 failed"}]}
```

7. Validate and summarize

Replace `"/path/to/storage-logs"` with your case directory. Quote paths containing spaces.

```
storage-log-analyzer validate "/path/to/storage-logs"
storage-log-analyzer validate "/path/to/storage-logs" --strict
storage-log-analyzer summary "/path/to/storage-logs" --format json -o reports/summary.json
```

Strict validation returns exit code 2 when any event has an unknown vendor or severity. It is a recognition check, not a guarantee that every vendor field is understood. Empty or unreadable input returns exit code 1.

To force a known vendor, use `--vendor pure`, `--vendor emc`, or `--vendor hpe`. Version 0.2.0 gives this explicit choice precedence over text detection.

8. Analyze and export reports

```
storage-log-analyzer analyze "/path/to/storage-logs"
storage-log-analyzer analyze "/path/to/storage-logs" --vendor pure --format markdown -o reports/incident.md
storage-log-analyzer analyze "/path/to/storage-logs" --format json -o reports/incident.json
storage-log-analyzer analyze "/path/to/storage-logs" --min-severity high --fail-on critical
```

`--format` accepts `text`, `json`, or `markdown`. `--output` and `-o` select a destination; missing parent directories are created. Existing output files can be overwritten, so use a new case-specific filename when preserving prior reports.

`--min-severity` filters findings before the overall report risk and failure threshold are calculated. Do not interpret a filtered report as a complete assessment of the original dataset.

9. Read and triage findings

JSON and Markdown reports include evidence and recommended actions. The terminal report emphasizes matched rules and recommended actions. The overall risk is the highest severity among the included findings.

- `STO-001`: drive or media failure.
- `STO-002`: path or port failure.
- `STO-003`: critically high capacity.
- `STO-004`: controller or node degradation.
- `STO-005`: replication or snapshot failure.
- `STO-006`: latency or performance degradation.
- `SEC-001`: authentication failure.
- `SEC-002`: possible ransomware or destructive activity.

Preserve the original evidence, confirm the affected component, check redundancy and recovery points, and involve the storage/security team. A rule match is not proof of root cause or compromise. No matching findings does not prove that a system is healthy.

10. Redact before sharing

```
storage-log-analyzer redact "/path/to/pure-alerts.log" -o sanitized/pure-alerts.log
```

The command refuses to overwrite the input file. It masks common IPv4 addresses, email addresses, labeled storage identifiers, and long hexadecimal IDs. Redaction is heuristic: review hostnames, usernames, paths, customer names, IPv6 addresses, and free-form messages yourself.

Local reports may retain original event evidence and file paths. Ordinary report generation does not automatically sanitize all output.

11. Optional AI assessment

From your source checkout and virtual environment:

```
python -m pip install --upgrade -e '.[ai]'
export OPENAI_API_KEY='your-key'
export STORAGE_LOG_AI_MODEL='gpt-5-mini'
storage-log-analyzer analyze "/path/to/storage-logs" --ai --format markdown -o reports/ai-assessment.md
```

In Windows PowerShell, configure variables with `$env:OPENAI_API_KEY='your-key'` and `$env:STORAGE_LOG_AI_MODEL='gpt-5-mini'`. Do not commit real keys or copy them into issues.

Model choice can also be passed with `--model`. Use a model available to your account. The tool sends a bounded, redacted summary of findings to the configured API rather than the original full log file. Review your data policy and redacted data first. The request uses `store=False`; this disables response storage but does not guarantee zero provider retention. The SDK has a 60-second request timeout and up to two retries, so total elapsed time can exceed 60 seconds.

If AI fails, check connectivity, key configuration, model access, and API quota. Run again without `--ai` to obtain the local report. No real API call is needed for the automated regression tests.

12. Exit codes and automation

For `analyze`:

- `0`: completed; no finding reaches the selected failure threshold, or `--fail-on never` was used.
- `1`: input, output, or AI assessment error.
- `2`: reported risk reaches `--fail-on` (default `high`).

For strict `validate`, exit code `2` means unknown vendors or severities. Argument errors also use the standard CLI exit code `2`; distinguish those using the command and error message.

```
storage-log-analyzer analyze "/path/to/storage-logs" --format json -o reports/latest.json --fail-on high
result=$?
case "$result" in
  0) echo "Completed below the selected risk threshold" ;;
  1) echo "Input, output, or assessment error" ;;
  2) echo "Review findings or command arguments" ;;
esac
```

13. Update and verify

```
git pull
python -m pip install --upgrade -e .
# For users of optional AI:
python -m pip install --upgrade -e '.[ai]'
storage-log-analyzer --version
```

Version 0.2.0 requires OpenAI SDK 3.42.1 or newer, below 4, for the AI extra. Use a separate environment if another application needs an older SDK. GitHub release assets are available; this project has not published a package to PyPI as part of this release.

14. Troubleshooting

- Command not found: activate the environment or run `python -m storage_log_analyzer --help` using the installed environment's Python.
- No supported events: check the path, supported extensions, readable permissions, and whether the file is empty.
- JSON must contain an object or array: correct the input structure; an `events` field must contain an array.
- Unknown vendor: use the correct `--vendor` or submit a synthetic example through the issue form.
- Exit code 2 after a report: inspect findings and the selected failure threshold; the report may have completed normally.
- Permission denied: choose a readable input and writable report directory; do not default to elevated privileges.
- AI unavailable: install `.[ai]` in the same environment, configure a key, or use local analysis without `--ai`.

15. Further help

Run `storage-log-analyzer --help` or `storage-log-analyzer analyze --help`. See the operator procedure, release notes, and changelog. Report ordinary bugs using the GitHub issue template with synthetic evidence. Report sensitive vulnerabilities privately to darisi.suresh@ieee.org as described in SECURITY.md.