



Cheet Sheet v0.1 (tested with vagrant v1.6.5)

Boxes

List all boxes:

% vagrant box list

Add new box (local *.box or name/url):

% vagrant box add <name, url, or path>

Remove box:

% vagrant box remove <name>

Finding more boxes:

<https://atlas.hashicorp.com/boxes/search>

Projects/Control

Each project has a configuration file named 'Vagrantfile' and it is using ruby programming language.

By default project directory is shared inside virtual machine under /vagrant.

Create a vagrant project in current directory:

% vagrant init [name [url]]

% vagrant init precise64

<http://files.vagrantup.com/precise64.box>

Start the machine:

% vagrant up [name]

Connect to the virtual machine:

% vagrant ssh [name]

Show the machine status:

% vagrant status [name]

Suspend the virtual machine:

To resume the VM, simply run 'vagrant up' or 'vagrant resume'

% vagrant suspend [name]

Shutdown the VM:

It will try graceful shutdown first and if it fails it just powers it off.

Append '--force' to force power off.

% vagrant halt

Destroy the machine:

% vagrant destroy [name]

VM Configuration

Box name:

config.vm.box = "precise64"

Box url (optional):

config.vm.box_url =

"http://files.vagrantup.com/precise64.box"

Shared folder location:

'/sfolder' - path inside virtual machine

'.' - path on host machine

To set the owner or group append:

owner: "root", group: "root"

To disable share:

disabled: true

Multiple shared folders can be defined.

config.vm.synced_folder ".", "/sfolder"

Port forwarding:

By default it listens on all host interfaces, to change that, append:

ip:"127.0.0.1"

config.vm.network "forwarded_port", guest: 80, host: 8080

Reload vm configuration:

% vagrant reload [vm-name]

Provisioning

Run shell script during vm creation:

Simply add configuration option to vm config.

No need to use 'sudo' inside the shell script since it runs as root by default.

Example script:

```
#!/usr/bin/env bash
```

```
apt-get install -y apache2 >/dev/null 2>&1
```

config.vm.provision "shell", path: "provision.sh"

Use puppet provisioning:

Manifests should be under manifests folder. Vagrant will run the default.pp manifest in that folder.

Sample manifest (manifests/default.pp):

```
exec { "apt-get update":
  command => "/usr/bin/apt-get update",
}
```

```
package { "apache2":
  require => Exec["apt-get update"],
}
```

config.vm.provision "puppet"

Chef provisioning:

Vagrant will run chef script located in:

./cookbooks/test/recipes/default.rb

config.vm.provision "chef_solo", run_list: ["test"]

Multiple provisioners can be used at the same time.

Inline provisioning:

config.vm.provision "shell", inline: "apt-get install -y nmap"

Networking (advanced)

Forward udp port:

config.vm.network "forwarded_port", guest: 80, host: 8080, protocol: "udp"

Assign different port if no avail:

To configure range: **config.vm.usable_port_range = (2200..2250)**

config.vm.network "forwarded_port", guest: 80, host: 8080, auto_correct: true

Configure host-only networking:

Machine can be reached from your host:

```
% ping 192.168.33.10
```

```
PING 192.168.33.10 (192.168.33.10): 56 data bytes
```

```
64 bytes from 192.168.33.10: icmp_seq=0 ttl=64 time=0.547 ms
```

```
64 bytes from 192.168.33.10: icmp_seq=1 ttl=64 time=0.381 ms
```

Can still use 'vagrant ssh' to ssh into vm.

config.vm.network "private_network", ip: "192.168.33.10"

Configure bridged networking:

Vagrant will ask upon initialization to which device to bridge. This can also be specified by adding bridge

```
option:
`config.vm.network "public_network", bridge: 'en1: Wi-
Fi (AirPort)'\`
```

config.vm.network "public_network"

Multiple network adapters (host-only or bridge) can be specified. Vagrant by default creates one NAT interface, which is used for port forwarding.

Multiple VMs:

Sample configuration for two machines:
Set *autostart* option in order to prevent machine from starting up on `vagrant up` command.

```
Vagrant.configure("2") do |config|
  config.vm.provision "shell", inline: "echo Hello"

  config.vm.define "web" do |web|
    web.vm.box = "hashicorp/precise32"
  end

  config.vm.define "db", autostart: false do |db|
    db.vm.box = "hashicorp/precise32"
  end
end
```

To connect to 'db' machine:

```
% vagrant ssh db
```

Start all machines:

```
% vagrant up
```

Start single machine:

```
% vagrant up web
```

Configure host-only networking for both machines:

```
Vagrant.configure("2") do |config|
  config.vm.provision "shell", inline: "echo Hello"

  config.vm.define "web" do |web|
    web.vm.box = "hashicorp/precise32"
    web.vm.network "private_network", ip:
"192.168.33.10"
  end

  config.vm.define "db", autostart: false do |db|
    db.vm.box = "hashicorp/precise32"
    db.vm.network "private_network", ip:
"192.168.33.12"
  end
end
```

Vagrant Settings/Defaults:

Default location for vagrant boxes and configuration:
It can be changed by setting \$VAGRANT_HOME environment variable.

```
~/ .vagrant.d
```

To change the name of vagrant project configuration file set \$VAGRANT_VAGRANTFILE variable (default: Vagrantfile)