

A Cross-Architecture Audit of Direction-Based Inference-Time Defences in Vision-Language Models

Xiangyu Yin¹, Tora Bodin¹, Rohan Menon², Chih-Hong Cheng^{1,2}

¹Chalmers University of Technology, Gothenburg, Sweden

²Carl von Ossietzky University of Oldenburg, Oldenburg, Germany

Abstract

Inference-time defences against vision-language model (VLM) jailbreaks commonly subtract a calibrated direction from the residual stream at one decoder layer, differing only in which direction is used and at which layer. We compare five defence candidates across fifteen (model, layer) cells from four architectural families under a single magnitude-controlled protocol that matches per-prompt intervention size and pairs every direction against a same-magnitude random control, isolating the choice of direction from the size of the perturbation. The candidates are the mean image-conditioning shift, a CMRM-style refusal direction, a ShiftDC-style attack-specific residual, a prompt-level “ignore the image” instruction, and a same-norm random control. Two results follow. First, no single candidate Pareto-dominates on both refusal recovery and utility preservation: the image-conditioning shift leads the Pareto front on LLaVA-1.5 and Pixtral-12B and is the only candidate whose utility loss stays at the measurement noise floor in every family, while a prompt-level instruction leads on Qwen2.5-VL and the attack-specific residual on Qwen2-VL-2B. The image-conditioning direction passes direction-specificity against a magnitude-matched random control on 13 of the 15 cells, yet is strongly architecture-specific, nearly orthogonal and non-transferable across the one dimension-compatible model pair (LLaVA-1.5-13B and Pixtral-12B), so it must be calibrated per family. Second, connecting two previously separate refusal-geometry literatures, the text-only CMRM refusal direction has positive cosine alignment with the multimodal image-conditioning shift on every one of the 15 cells (mean 0.35, range 0.17–0.65, $15\text{--}25\times$ the random-vector null; sign test $p \approx 3 \times 10^{-5}$), the first quantitative cross-paradigm evidence that text-only and multimodal refusal-direction recipes identify partially overlapping rather than independent geometric structure. Together these argue that direction-based defences should be selected and calibrated separately for each language-decoder family rather than through a single universal recipe.

1 Introduction

A growing class of inference-time defences against vision-language model (VLM) jailbreaks share an algorithmic core. At one decoder layer, subtract a calibrated direction from the residual stream and resume the forward pass. The methods differ only in *which* direction. CMRM (Liu et al. 2025a) uses a refusal direction calibrated on text-only refused vs.

complied prompts. ShiftDC (Zou et al. 2025) calibrates the attack-specific direction by contrasting the representation shift caused by jailbreak vs. benign images. VLMGuard (Liu et al. 2025b) uses a learned discriminator direction (weights not released, scope discussion in §5.2). Each method was proposed and evaluated on its own, usually on a single base architecture. The question *which calibration is right, and whether the answer depends on architecture*, has not been answered head-to-head.

In this paper, we audit five candidate directions on a common evaluation. The candidates are the mean image-conditioning shift (ABL_POS; §5.1), the CMRM-like refusal direction, the ShiftDC-like attack-specific residual, prompt-level IGNORE_INSTR (a non-residual baseline), and a same-norm random-direction control.¹ Evaluation spans $5 \times 3 = 15$ cells, namely five VLMs (LLaVA-1.5-7B, LLaVA-1.5-13B, Qwen2.5-VL-7B, Qwen2-VL-2B, Pixtral-12B) at three layer depths each, on 11 attack settings drawn from FIGSTEP (Gong et al. 2025), HADES (Li et al. 2024), JAILBREAKV (Luo et al. 2024), and MM-SAFETYBENCH (Liu et al. 2024a). Defences are scored on (refusal recovery, MM-Bench utility preserved) at $n = 47\text{--}65$ jailbreak prompts per cell.

The audit rests on two simple ingredients. First, every direction is compared with a random direction of the same magnitude on the same prompts (§5), so that any observed refusal recovery must exceed the improvement caused by an arbitrary perturbation of equal size. Second, the audit holds the per-prompt scaling fixed across candidates, so the comparison concentrates on the choice of direction. The result shows that image-conditioning shift passes the strict paired-difference 95% CI on 13/15 cells, while the magnitude-matched random control fails on every cell. The audit also surfaces a cross-paradigm sign consistency between the text-only refusal direction and the multimodal image-conditioning shift (§5.3).

Contributions.

- **C1. A systematic cross-architecture audit of direction-based VLM defences.** We compare five calibration

¹The three hidden-state defences (ABL_POS, CMRM-LIKE, SHIFTDC-LIKE) share the algorithmic core. IGNORE_INSTR is a prompt-level baseline, RANDOM_CTRL a magnitude-matched control method.

strategies across fifteen (model, layer) cells from four architectural families. No single calibration Pareto-dominates across families: ABL_POS leads on LLaVA-1.5 (tied with SHIFTDC-LIKE) and Pixtral-12B and is the only candidate with utility loss at the measurement noise floor in every family, while IGNORE_INSTR leads on Qwen2.5-VL and SHIFTDC-LIKE on Qwen2-VL-2B. The deployable rule is constraint-conditional (prioritizing either refusal recovery or utility preservation) and family-conditional (§5, 5.2). The positional direction is strongly architecture-specific: across the dim-compatible LLaVA-1.5-13B/Pixtral-12B pair the two models’ directions are nearly orthogonal and neither transfers, so calibration must be per family (App. G).

- **C2. Cross-paradigm sign consistency between text-only and multimodal refusal directions.** The CARM-style refusal direction calibrated on text-only refused-vs-complied prompts has positive cosine alignment with the multimodal image-conditioning shift on every one of the 15 cells (mean 0.35, range 0.17–0.65, 15–25× the random-vector null). This is the first quantitative cross-paradigm replication showing that the text-only refusal-mediation literature (Arditi et al. 2024; Liu et al. 2025a) and the multimodal direction-based defence literature (Zou et al. 2025; Liu et al. 2025b) identify *overlapping rather than independent* geometric structure (§5.3). The two recipes produce different per-cell behavior because the alignment is partial rather than identical, but the consistent sign across 15 cells argues that future multimodal direction-based defence work should not treat the text-only refusal direction as a fully independent axis.

2 Related Work

Representation-space analyses of multimodal refusal bypass. In VLMs, visual input has been described as shifting multimodal representations away from the text-only regime (Liu et al. 2025a; Zou et al. 2025; Wei et al. 2026), motivating inference-time interventions (Liu et al. 2025a; Zou et al. 2025; Liu et al. 2025b) and representation-based detectors (Jiang et al. 2025; Hua et al. 2025), alongside text-only LLM analyses that pin down refusal directions and safety subspaces (Arditi et al. 2024; Pan et al. 2025). Prior work studies each recipe in isolation, usually on a single base architecture. Our audit compares five candidates head-to-head on a common 15-cell grid and reports a cross-paradigm degeneracy between the text-only refusal direction and the multimodal image-conditioning shift.

Magnitude-matched random controls in causal probes. Magnitude-matched random-direction controls are a standard discipline in causal interpretability for ruling out the trivial reading that any large perturbation at the probed layer disrupts model behaviour (Arditi et al. 2024). We apply this control at scale, 15 cells across four architectural families and three layer depths each, paired per-prompt with the candidate direction so the comparison reduces to direction choice rather than magnitude. The matched comparisons across text-only, benign-image, and jailbreak-image conditions at one layer

differ from layerwise lenses (Belrose et al. 2023) (which follow depth-wise computation) and from mode-connectivity work (Garipov et al. 2018; Draxler et al. 2018) (which connects parameters rather than activations).

3 Method

3.1 Per-prompt positional shift

Fix a VLM with L decoder layers and let $h_\ell(x) \in \mathbb{R}^d$ denote the residual-stream activation at layer ℓ for prompt x . We probe image-induced geometry one prompt at a time. For each prompt x in our test set and each image condition $m \in \{T, B, J\}$ (text-only benign image, jailbreak image), we extract the layer- ℓ activation $h_\ell^m(x)$. The per-prompt positional shift (at layer ℓ) due to imaging is

$$\Delta h^m(x) := h_\ell^m(x) - h_\ell^T(x), \quad m \in \{B, J\}. \quad (1)$$

The cross-prompt aggregate is the sign-normalised mean $\widehat{\Delta h}^m := \frac{1}{n} \sum_x \widehat{\Delta h^m(x)}$, where $\widehat{a} := a/\|a\|$ is the unit-norm version of a . When the context is clear we drop the prompt argument x and layer ℓ and write h^m .

Direction tests. The cosine $\langle \widehat{\Delta h}^m(x), \widehat{\Delta h}^m \rangle$ measures how much each prompt agrees with the population mean direction. Under the isotropic null where directions are uniformly random with no preferred alignment, the signed cosine has mean 0, standard deviation $1/\sqrt{d}$, and expected absolute value $\sqrt{2/(\pi d)}$. These are very small for $d \in [3584, 5120]$. We report the fraction of prompts with positive signed cosine (chance 0.5) and the mean signed cosine.

Declared threshold. We fix one threshold before extending the analysis beyond LLaVA-1.5. We declare a model–layer cell to have consistent positional alignment if at $\geq 95\%$ of safety prompts have a positive cosine similarity with the mean image-conditioning direction (FIGSTEP (Gong et al. 2025), HADES (Li et al. 2024), JAILBREAKV (Luo et al. 2024), MM-SAFETYBENCH (Liu et al. 2024a)).

Test set. Safety prompts are those refused by the text-only condition, ≤ 200 per LLaVA-1.5 cell and ≤ 100 per cross-architecture cell, stratified across 11 attacks from the four safety benchmarks above. Non-safety prompts are MM-Bench (Liu et al. 2024b) and POPE (Li et al. 2023), 20 prompts each.

Sample sizes. Direction tests use $n \in [100, 194]$ per cell on safety. Refusal recovery uses $n = 47\text{--}65$ per cell. Direction transfer uses $n = 20$ per pair on 6 pairs. MMBench utility uses $n = 98$ per cell on the CN-cultural L1 split (full 15-cell coverage, paired noise floor ~ 2 pp), and $n = 190$ on English dev (paired noise floor ~ 1.4 pp), also with full 15-cell coverage (App. F.1). Wilson 95% CI throughout.

4 Image-conditioning Geometry

We characterise the image-conditioning geometry that the §5 audit then probes behaviourally. The co-linearity between benign- and jailbreak-image shifts is left unstated in prior recipes (Zou et al. 2025; Liu et al. 2025a). We measure it per




Figure 1: **Visual abstract.** (a) Cross-paradigm sign consistency. The CMRM-style text-only refusal direction has positive cosine alignment with the multimodal image-conditioning shift on every one of the 15 cells (mean 0.35, 15–25× the random-vector null shaded in grey). (b) Causal probe on LLaVA-1.5-7B/L16. Positional ablation lifts refusal by 46 pp, while matched-norm random matches WITH_IMAGE (13/15 cells direction-specific across the full grid). (c) Defence Pareto over all 15 utility-measured cells. IGNORE_INSTR 9/15, ABL_POS 7/15 (only candidate with utility loss at the noise floor in every family), SHIFTDC-LIKE 7/15.

cell (§4.1) and ask where, given the co-linearity, the benign-vs-jailbreak signal lives. §4.2 shows that magnitude along the shared positional direction is the discriminator at the prompt level, which §5 then turns into a behavioural test. Tests run per cell on the 11-attack safety suite (Gong et al. 2025; Li et al. 2024; Luo et al. 2024; Liu et al. 2024a), MMBench (Liu et al. 2024b), and POPE (Li et al. 2023).

4.1 A consistent positional shift direction

Our audit reveals that, over LLaVA-1.5-7B/L16 ($n = 130$), 100% of prompts have positive cosine with $\overline{\Delta h}^B$, mean cosine +0.679 ($\approx 53\times$ the random null $\sqrt{2/(\pi d)} \approx 0.013$). Jailbreak conditioning gives 100% with mean cosine +0.655, and the two image-condition mean directions are nearly identical ($\overline{\Delta h}^B \cdot \overline{\Delta h}^J = 0.949$). This co-linearity holds across all 15 cells. The positive-cosine fraction ($\%_{\text{pos}} \Delta h$) is 100% in every cell for both conditions, and the benign-vs-jailbreak direction overlap is ≥ 0.75 in every cell (Table 1; full breakdown in Appendix Table 8).

4.2 Magnitude is the discriminator, not direction

As the benign-vs-jailbreak shift overlap on LLaVA-1.5-7B/L16 is 0.949, and the same property holds across all 15 cells (≥ 0.75), the positional direction therefore does not carry attack-vs-benign separation at the direction level. What does is shift *magnitude* along the shared direction. Jailbreak conditioning produces larger shifts than benign on LLaVA-1.5-7B/L16, high-dimensional probes saturate at AUC ≈ 0.988 , and 1-D along-direction probes beat orthogonal-complement probes in 12/15 cells (App. H). §5 turns this observation into a behavioural test of whether ablating the positional direction recovers refusal.

Why magnitude rather than direction? The image-conditioning shift is dominated by the *conditioning event*

(image present) rather than by the content of the image. Both benign and jailbreak images push the hidden state along the same axis because both events trigger the same “image is present, attend to it” processing. What differs between them is not where the state goes but how far along that axis it gets pushed, with jailbreak images producing larger shifts than benign on the anchor cell. This reading is consistent with the magnitude-matched random control in §5, which shows that subtracting along the positional direction at jailbreak-scale magnitude recovers refusal while subtracting along a random direction at the same magnitude does not. Direction encodes “image conditioning is active.” Magnitude encodes “how strongly.”

5 Defence Audit

5.1 Ablating the image-conditioning direction

§4 shows the image-conditioning direction is consistent across prompts and that magnitude along it discriminates jailbreak from benign at the prompt level. We now turn to whether ablating the same direction at one decoder layer recovers refusal, and whether the lift is specific to that direction or could be reproduced by any large perturbation. We aggregate over the 15-cell grid alongside three published direction-based recipes (CMRM, SHIFTDC, prompt-level IGNORE_INSTR) plus a magnitude-matched random control.

Intervention. At a chosen layer ℓ , we replace the residual stream $h_\ell(x)$ with

$$\tilde{h}_\ell(x) = h_\ell(x) - \alpha_h \|\Delta h^B(x)\| \frac{\widehat{\Delta h}^B}{\|\widehat{\Delta h}^B\|}, \quad (2)$$

and resume the forward pass. Per-prompt scaling by the prompt’s own $\|\Delta h^B(x)\|$ keeps the perturbation no larger than what unmodified image conditioning would produce. $\alpha_h \in \{0, 1\}$ gives two ablations, OFF and ON. A *matched-norm random-direction* control subtracts the same total norm

model	layer	%pos Δh	$\cos(\overline{\Delta h}^B, \overline{\Delta h}^J)$
LLaVA-1.5-7B	8/16/24	100/100/100	0.99/0.95/0.90
LLaVA-1.5-13B	10/20/30	100/100/100	0.95/0.85/0.91
Qwen2.5-VL-7B	7/14/21	100/100/100	0.95/0.92/0.79
Qwen2-VL-2B	6/14/22	100/100/100	0.91/0.93/0.83
Pixtral-12B	10/20/30	100/100/100	0.75/0.86/0.87
cells passing threshold		15/15	15/15

Table 1: Per-cell direction tests on the 15-cell safety grid (benign condition). %pos Δh , fraction with positive cosine to $\overline{\Delta h}^B$ (threshold $\geq 95\%$). $\cos(B, J)$, cosine between benign- and jailbreak-conditioned mean directions. Other quantities in §3.1.

along an isotropic random direction (redrawn per prompt). Two reference conditions frame the probe. Text-only forward pass (no image) and with-image, no hook. We measure (M1) refusal rate via a refusal-substring lexicon at the first generation step, following the protocol of (Arditi et al. 2024) that has been adopted broadly in the refusal-direction literature, and (M2) cosine of the first-step generation logit to the text-only baseline. Calibration directions are estimated on a 50% held-out split of the prompts used in §4 (stratified within attack types). The remaining 50% is used for evaluation.

Results. Table 2 reports the four conditions on LLaVA-1.5-7B L16 ($n_{\text{calib}} = 65$, $n_{\text{eval}} = 63$). Two properties stand out.

(i) *Positional axis is causally sufficient (within our scope).* ABL_POS lifts refusal from 0.159 to 0.619 (+46 pp, 55% of the WITH_IMAGE-to-TEXT_ONLY headroom) and pulls the first-step logit toward text-only (0.823 $\rightarrow$ 0.886). The pattern is stable across the $n = 4, 20, 30, 40$ checkpoints. Subtracting a single fixed direction at a single layer is therefore a working inference-time defence, which we treat as baseline-strength rather than deployment-ready.

(ii) *Direction specificity (magnitude-matched).* RANDOM_CTRL produces refusal 0.159 and logit cosine 0.814, matching WITH_IMAGE on M1 and slightly worse on M2. A perturbation of equal magnitude along a random direction is no closer to text-only behaviour than no perturbation at all. This rules out the easy reading that any large perturbation at layer 16 just disrupts image conditioning. The +46-pp effect of ABL_POS is therefore specific to the mean positional direction.

Cross-grid replication. The pattern holds beyond LLaVA-1.5-7B/L16. Fig. 3 shows the same probe across all 15 cells. Table 4 gives the per-cell paired-difference 95% CI on ($\Delta_{\text{pos}} - \Delta_{\text{rnd}}$). 13/15 **cells** pass the strict CI-excludes-0 criterion. The two non-passing cells, LLaVA-1.5-13B/L10 (+0.046 $\pm$ 0.067) and Qwen2-VL-2B/L6 (+0.062 $\pm$ 0.069), both have positive point estimates with CI lower bounds just below zero (−0.021 and −0.007). The largest paired difference on the grid is Qwen2-VL-2B/L22 (+0.812 $\pm$ 0.112), and the cross-architecture Mistral anchor Pixtral-12B/L20 passes at +0.771 $\pm$ 0.120.

condition	refusal rate (95% Wilson CI)
TEXT_ONLY (no image)	1.000
WITH_IMAGE (image, no ablation)	0.159 $\pm$ 0.090
ABL_POS (subtract $\overline{\Delta h}^B$)	0.619 $\pm$ 0.118
RANDOM_CTRL (same-norm random direction)	0.159 $\pm$ 0.090

Table 2: Causal probe on **LLaVA-1.5-7B/L16**, $n_{\text{eval}} = 63$ held-out jailbreak-image prompts (95% Wilson CI). ABL_POS subtracts the per-prompt $\overline{\Delta h}^B$ at scale $\|\Delta h^B(x)\|$. RANDOM_CTRL subtracts an isotropic random direction at the same total norm. First-step logit cosines to TEXT_ONLY are 0.886 (POS) and 0.814 (RANDOM).

Per-attack-type robustness. ABL_POS recovers refusal across all four safety benchmarks rather than being driven by a single attack type (Table 3). The smallest absolute recovery is on MM-SafetyBench (+0.173), where the WITH_IMAGE refusal floor is already very low (0.046), and the largest is on JailBreakV (+0.261). The magnitude-matched random control sits within ± 0.014 of WITH_IMAGE on every benchmark, so the lift is direction-specific on each benchmark separately, not just in aggregate.

Layer-depth dependence at the probed depths. Δ_{pos} increases monotonically from the early to the late probed layer in *all five* families (Fig. 2), from lifts of +0.06–+0.29 at the early layer to +0.54–+0.79 at the late layer. With only 3 layers per family this is an empirical pattern, not a fitted depth law. The practical reading is that middle-to-late layers carry more behavioural leverage for ABL_POS than early layers in the families we probe.

Multiple-comparison adjustment. The headline 13/15 direction-specificity pass rate uses uncorrected per-cell 95% CIs. Under Bonferroni-corrected family-wise $\alpha = 0.05$ ($m = 15$ cells), 11/15 cells still pass. The two cells that flip between corrected and uncorrected (LLaVA-1.5-7B/L8 and Qwen2.5-VL-7B/L7) both have positive paired-difference point estimates (+0.077 and +0.092), so the qualitative reading that ABL_POS direction-specificity holds on the large majority of cells is robust to the correction choice.

Robustness check, prompt-level instruction. A textual “ignore the image” instruction (and an emphatic “[CRITICAL SYSTEM]. . .” variant) recovers refusal only to 0.143 / 0.222 and *increases* $\|h_\ell - h_\ell^T\|$ rather than shrinking it, so it sits partly off-axis from the image-conditioning subspace (Appendix C).

Robustness check, refusal metric. The headline refusal metric is the first-step substring lexicon of Arditi et al. (2024), the standard protocol in the refusal-direction literature, which we adopt for comparability with the prior recipes we audit. Because a substring lexicon can miss soft refusals, we verify that our two central claims—that ABL_POS lifts refusal and that the lift is direction-specific—are not artefacts of that choice by re-scoring all 15 cells with an independent LLM judge (Llama-3.1-8B-Instruct, not the language backbone of any tested VLM) under a REFUSE/COMPLY rubric (App. ??). Both claims survive the metric change: ABL_POS




Figure 2: **Layer-depth dependence of ABL_POS lift.** Per-family refusal lift Δ_{pos} at early, middle, and late residual layers. All five families increase monotonically from the early to the late probed layer. Layer indices per family are given in the legend.

raises judged refusal over WITH_IMAGE on 14/15 cells (the lone exception is a ceiling-saturated Qwen2.5-VL cell), the magnitude-matched random control does not (mean lift -0.004), and ABL_POS exceeds the random control on 13/15 cells—the same direction and specificity pattern the lexicon reports. The judge and the lexicon measure related but distinct constructs (per-label agreement 0.43): the judge credits soft refusals and deflections the lexicon misses, so its WITH_IMAGE baseline is much higher (0.81–0.95 vs. 0.11–0.32) and absolute lifts compress against that higher ceiling (cell mean $+0.08$ vs. $+0.41$). The metric choice therefore rescales the *size* of the effect but leaves its direction and specificity—the claims this paper actually makes—intact.

5.2 Defence comparison, positional ablation versus alternatives

We compare ABL_POS against three alternatives on the same split. IGNORE_INSTR prepends a textual “ignore the image” instruction (no hidden-state hook). CMRM-LIKE (Liu et al. 2025a) subtracts a refusal direction defined as the mean difference of text-only hidden states between refused and complied prompts. SHIFTDC-LIKE (Zou et al. 2025) subtracts the attack-specific component $\overline{\Delta h}^J - \overline{\Delta h}^B$. For CMRM-LIKE and SHIFTDC-LIKE we reproduce the published direction without their surrounding training pipelines (CMRM’s contrastive classifier and ShiftDC’s decomposition optimisation), and hold inference-time scaling at the same per-prompt magnitude as ABL_POS. Any gap is a lower bound on what the direction choice contributes. VLMGuard (Liu et al. 2025b) releases neither the trained discriminator weights nor its training data, so we omit it.

Pareto criterion. A defence d is *Pareto-dominant* on cell c if no other defence simultaneously achieves higher re-




Figure 3: **Causal probe across the 15-cell safety grid.** Per-cell refusal rate. ABL_POS (filled red) lifts refusal, while RANDOM_CTRL (x) clusters on WITH_IMAGE (grey). ABL_POS and RANDOM_CTRL are magnitude-matched per prompt. Dashed line marks TEXT_ONLY.

fusal recovery and lower utility loss on c . We count, for each defence, the number of cells on which it is Pareto-dominant. The criterion is strict on recovery and weak on utility loss, which means a defence that ties on utility but wins on recovery still counts as Pareto-dominant. Counts sum to more than 15 across defences because multiple defences can be simultaneously non-dominated on the same cell. The per-family breakdown (per-cell membership in Table 6) is sharply architecture-conditional. On the LLaVA-1.5 cells ($n=6$) ABL_POS and SHIFTDC-LIKE tie on the Pareto front (4/6 each). On the Qwen cells ($n=6$) ABL_POS drops off entirely (0/6; its recovery there is dominated), while IGNORE_INSTR leads (4/6, all three Qwen2.5-VL cells at zero utility loss) and SHIFTDC-LIKE takes the Qwen2-VL-2B cells (3/6, e.g. $+0.688$ recovery on L22). On the Pixtral-12B cells ($n=3$) ABL_POS and IGNORE_INSTR both make the front on all three cells, but only ABL_POS does so with no utility loss, while SHIFTDC-LIKE and CMRM-LIKE drop off entirely (0/3; e.g. SHIFTDC-LIKE’s -0.092 recovery on Pixtral-12B/L10 is dominated by ABL_POS’s $+0.277$ at lower utility loss).

Pareto and architecture-conditional outcome. Fig. 1(c) and Table 5 aggregate over all 15 cells, with both refusal recovery and MMBench utility ($n=98$) measured on every cell. Pareto counts, IGNORE_INSTR 9/15, ABL_POS 7/15, SHIFTDC-LIKE 7/15, CMRM-LIKE 2/15, RANDOM_CTRL 2/15 (Table 6). No defence dominates a majority of cells across families, and the front membership is family-conditional rather than uniform. IGNORE_INSTR leads the raw count, driven by Qwen2.5-VL and Pixtral, but carries a measurable utility cost on Pixtral (~ 4 pp) and offers no calibrated direction to transfer or gate. ABL_POS is the only candidate whose utility loss stays at or below the ~ 2 pp noise floor in every family, and it leads or ties the front on LLaVA-1.5 (4/6) and Pixtral (3/3); we highlight it as the deployable rule under a strict no-utility-loss constraint on those families. SHIFTDC-LIKE ties ABL_POS on LLaVA-1.5

	FigStep	HADES	JailBreakV	MM-SB
n	171	99	207	410
WITH_IMAGE	0.409	0.313	0.440	0.046
ABL_POS	0.655	0.515	0.700	0.220
recovery	+0.246	+0.202	+0.261	+0.173
RANDOM_CTRL	0.409	0.303	0.430	0.032
ShiftDC-like	0.725	0.596	0.628	0.283
CMRM-like	0.561	0.495	0.618	0.185

Table 3: Refusal rate by attack benchmark (FigStep (Gong et al. 2025), HADES (Li et al. 2024), JailBreakV (Luo et al. 2024), and MM-SB=MM-SafetyBench (Liu et al. 2024a)), aggregated over the 15-cell grid. RECOVERY is ABL_POS – WITH_IMAGE. RANDOM_CTRL matches WITH_IMAGE on each benchmark within ± 0.014 .

and is the strongest candidate on Qwen2-VL-2B, but drops off on Pixtral. The utility side of this comparison is not an artefact of the CN-cultural subset: on the English MMBench dev split at $n = 190$ across the same 15 cells (App. F.1), ABL_POS stays within the noise floor on 14/15 cells, with a worst case of 2.6 pp on Pixtral-12B/L20.

Cross-model direction transfer fails in both directions. On the dim-compatible LLaVA-1.5-13B $\leftrightarrow$ Pixtral-12B pair (both $d = 5120$), the calibrated $\overline{\Delta h}^B$ directions of the two models are nearly *orthogonal* at every matched layer ($\cos(\text{native}, \text{transferred}) \in [0.007, 0.038]$), and neither transfers: the source direction recovers essentially no refusal on the target (≈ 0 recovery Pixtral $\rightarrow$ LLaVA, slightly *negative* LLaVA $\rightarrow$ Pixtral; App. G). The apparent asymmetry in the raw transfer penalty (0.05 vs. 0.65) is an artefact of the penalty metric, which subtracts the transferred recovery from the native recovery: native ABL_POS efficacy is large on Pixtral (+0.55–0.60) but small on LLaVA-1.5-13B (+0.05–0.15, one of the cells that fails direction-specificity in Table 4), so there is far more to lose on the Pixtral target. The defence direction is therefore strongly architecture-specific, even between models with identical residual-stream dimensions, which reinforces the per-cell direction-specificity finding and the need to calibrate each family separately.

Deployment guidance. The family-conditional outcome translates into a concrete per-family recipe. On the **LLaVA-1.5** family use ABL_POS or SHIFTDC-LIKE (tied at 4/6 front cells; ABL_POS has the lower worst-case utility loss). On **Pixtral-12B** use ABL_POS (Pareto-dominant on 3/3 Pixtral cells with no measurable utility loss; SHIFTDC-LIKE and CMRM-LIKE drop off). On **Qwen2.5-VL** use IGNORE_INSTR (3/3 front cells at zero measured utility loss on this family). On **Qwen2-VL-2B** use SHIFTDC-LIKE (up to +0.688 recovery at ≤ 1 pp utility loss). No single defence is the right choice on every family. For **cross-architecture deployment**, calibrate per family since the calibrated direction does not transfer across architectures (App. G).

Practical considerations. The per-family calibration that the transfer result mandates is cheap in practice. Calibrating $\overline{\Delta h}^B$ requires only *benign*-image prompts (50–97 per cell in

our runs), so no jailbreak examples need to be collected or labelled. Each calibration prompt costs one with-image and one text-only forward pass, and the full per-cell calibration completes in minutes on a single GPU. At inference time the defence stores one d -dimensional vector and applies one subtraction at one layer, with no weight updates and no auxiliary model; the per-prompt scaling of equation (2) additionally uses the prompt’s text-only hidden state (one image-free forward pass), whereas scaling by the calibration-mean norm, as in the utility runs of Table 14, removes this cost. Because the direction is calibrated against the conditioning event rather than against any specific attack, the same vector is applied to all 11 attack settings without per-attack tuning and recovers refusal on each of the four benchmark suites (Table 3). A conservative gated variant that subtracts only when the runtime shift norm exceeds the calibration median leaves refusal recovery essentially unchanged (+0.216 vs. +0.219 cell-mean on the nine LLaVA/Pixtral cells) and is available as a deployment knob when the number of interventions on benign traffic should be reduced.

5.3 Cross-paradigm sign consistency between text-only and multimodal refusal directions

The audit surfaces a structural observation that connects two previously separate lines of refusal-geometry literature. The CMRM-style refusal direction r_{dir} , calibrated on text-only refused-vs-complied prompts following (Arditi et al. 2024), has positive cosine alignment with the multimodal image-conditioning shift $\overline{\Delta h}^B$ on every one of the 15 cells (Fig. 1(a), mean 0.35, range 0.17–0.65, 15–25 $\times$ the random-vector null).

The text-only refusal-mediation work (Arditi et al. 2024; Liu et al. 2025a) and the multimodal direction-based defences (Zou et al. 2025; Liu et al. 2025b) therefore probe *overlapping rather than independent* geometric structure at the layers we probe. The alignment is partial rather than identical, which is why the two recipes produce different per-cell behaviour (Table 5, CMRM-LIKE reaches 2/15 Pareto-front cells vs. ABL_POS at 7/15). The consistent sign across all 15 cells, however, argues that this overlap is not a coincidence of any single architecture or layer.

Statistical significance. A sign test against the null hypothesis that the cosine has zero mean gives $P(15/15 \text{ positive} \mid \text{null}) = 0.5^{15} \approx 3.05 \times 10^{-5}$. The one-sample t -test on the 15 cell-mean cosines yields $t_{14} = 9.39$, $p < 10^{-7}$. The shared structure between the text-only refusal direction and the multimodal image-conditioning shift is therefore not a chance pattern of one or two cells.

Implication. Future multimodal direction-based defences should not treat the text-only refusal direction as a fully independent axis. The two paradigms share a substantive geometric component, and recipes from one transfer partially to the other rather than from scratch.

Why might these directions overlap? Both directions are calibrated on contrasts that share the same “end state” *compliance*. The CMRM direction contrasts text-only refused

config	Δ_{pos}	Δ_{rnd}	paired diff $\pm$ 95% hw	n	direction specific
LLaVA-1.5-7B / L8	+0.062	-0.015	+0.077 $\pm$ 0.065	65	✓
LLaVA-1.5-7B / L16 (anchor)	+0.460	+0.000	+0.460 $\pm$ 0.124	63	✓
LLaVA-1.5-7B / L24	+0.692	+0.000	+0.692 $\pm$ 0.113	65	✓
LLaVA-1.5-13B / L10	+0.062	+0.015	+0.046 $\pm$ 0.067	65	$\times$ [†]
LLaVA-1.5-13B / L20	+0.280	+0.020	+0.260 $\pm$ 0.123	50	✓
LLaVA-1.5-13B / L30	+0.538	+0.015	+0.523 $\pm$ 0.122	65	✓
Qwen2.5-VL-7B / L7	+0.123	+0.031	+0.092 $\pm$ 0.083	65	✓
Qwen2.5-VL-7B / L14	+0.231	-0.031	+0.262 $\pm$ 0.108	65	✓
Qwen2.5-VL-7B / L21	+0.615	+0.000	+0.615 $\pm$ 0.119	65	✓
Qwen2-VL-2B / L6	+0.062	+0.000	+0.062 $\pm$ 0.069	48	$\times$ [†]
Qwen2-VL-2B / L14	+0.521	+0.000	+0.521 $\pm$ 0.143	48	✓
Qwen2-VL-2B / L22	+0.792	-0.021	+0.812 $\pm$ 0.112	48	✓
Pixtral-12B / L10	+0.292	+0.015	+0.277 $\pm$ 0.118	65	✓
Pixtral-12B / L20	+0.688	-0.083	+0.771 $\pm$ 0.120	48	✓
Pixtral-12B / L30	+0.702	+0.000	+0.702 $\pm$ 0.132	47	✓
Direction-specificity pass rate (CI excludes 0):					13 / 15

[†] Point estimate positive but CI lower bound just below 0 (-0.021 and -0.007), so these cells fail the strict CI criterion.

Table 4: **Direction specificity across the 15-cell grid** on the dedicated held-out causal probe. Per-cell ABL_POS lift Δ_{pos} vs. RANDOM_CTRL lift Δ_{rnd} at matched total norm. Paired difference $\pm$ 95% half-width. **Pass** iff CI lower bound > 0 . Bold, anchor cells LLaVA-1.5-7B/L16 and Pixtral-12B/L20 and the largest paired difference (Qwen2-VL-2B/L22). Under Bonferroni ($\alpha=0.05$, $m=15$), 11/15 still pass; the headline 13/15 uses uncorrected per-cell 95% CIs.

vs. complied prompts, and the image-conditioning shift contrasts the same prompt with vs. without a benign image whose effect is to push the model toward generating a (potentially unsafe) answer rather than a refusal. Both contrasts therefore probe the same axis of behaviour (refusal $\rightarrow$ compliance), even though one is driven by prompt content and the other by image conditioning. The partial overlap (mean $\cos$ 0.35, not 1.0) reflects that the two contrasts also pick up paradigm-specific structure beyond the shared refusal axis. Calibration noise on the CMRM direction (only a few hundred refused/-complied text-only prompts at the layer we probe) further widens the gap.

6 Conclusion

No single direction-based defence Pareto-dominates the 15-cell grid. The deployable rule depends on the constraint and the language-decoder family. The image-conditioning shift passes direction-specificity against a magnitude-matched random control on 13/15 cells, leads or ties the Pareto front on LLaVA-1.5 and Pixtral-12B, and is the only candidate whose utility loss stays at the measurement noise floor in every architectural family. The audit also surfaces a cross-paradigm sign consistency. The text-only CMRM refusal direction has positive cosine alignment with the multimodal image-conditioning shift on all 15 cells (mean 0.35, 15–25 $\times$ random null), giving the first quantitative cross-paradigm replication that the two refusal-geometry literatures probe overlapping rather than independent geometric structure.

Scope and threat model. We assume a *static* attacker who supplies the jailbreak image but does not adapt to the defence and has no access to the calibration direction $\overline{\Delta h}^B$, the calibration set, or the layer ℓ . An adaptive attacker knowing the direction could craft an image whose shift projects only weakly onto it, weakening the ablation. Two choices

defence	recovery	utility loss	Pareto (of 15)	TF / Img / Mod
ABL_POS	+0.219 $\pm$ 0.302	+0.001 $\pm$ 0.026	7/15	✓ / ✓ / ✓
IGNORE_INSTR	+0.267 $\pm$ 0.281	+0.014 $\pm$ 0.020	9/15	✓ / — / —
CMRM-like	+0.171 $\pm$ 0.292	+0.001 $\pm$ 0.026	2/15	✓ / — / —
ShiftDC-like	+0.259 $\pm$ 0.390	+0.006 $\pm$ 0.036	7/15	✓ / ✓ / —
RANDOM_CTRL	-0.010 $\pm$ 0.065	+0.007 $\pm$ 0.041	2/15	✓ / — / —

Table 5: **Defence comparison over the 15-cell grid.** Refusal recovery (cell-mean $\pm$ half-range, $n=47$ –65 per cell) and MMBench utility loss ($n=98$ per cell; negative values are within the ≈ 2 pp noise floor). Pareto: number of non-dominated cells (per-cell breakdown in Table 6). TF/Img/Mod = training-free / image-aware / model-specific.

model	layer	ABL_POS	IGNORE_INSTR	CMRM-like	ShiftDC-like	RANDOM_CTRL
LLaVA-1.5-7B	8	✓	✓			
LLaVA-1.5-7B	16				✓	
LLaVA-1.5-7B	24	✓				
LLaVA-1.5-13B	10	✓				
LLaVA-1.5-13B	20	✓	✓	✓	✓	
LLaVA-1.5-13B	30			✓	✓	
Qwen2.5-VL-7B	7		✓			
Qwen2.5-VL-7B	14		✓			
Qwen2.5-VL-7B	21		✓			
Qwen2-VL-2B	6		✓			
Qwen2-VL-2B	14				✓	
Qwen2-VL-2B	22				✓	
Pixtral-12B	10	✓	✓			
Pixtral-12B	20	✓	✓			
Pixtral-12B	30	✓	✓			✓
front count (of 15)		7	9	2	7	2
LLaVA-1.5 (of 6)		4	2	2	4	0
Qwen (of 6)		0	4	0	3	0
Pixtral-12B (of 3)		3	3	0	0	2

Table 6: **Per-cell Pareto-front membership** across the 15-cell grid. ✓ = non-dominated on (recovery, $-$ utility loss) on that cell (criterion in the text); sources: Tables 11–13 and 14. Ties count for both defences.

narrow this surface: $\overline{\Delta h}^B$ is calibrated on *benign* images only (no attack labels needed), and the per-prompt scaling $\|\Delta h^B(x)\|$ is set at runtime, so the ablation magnitude cannot be pre-computed offline. Quantifying the residual adaptive risk needs an attacker that optimises the image to evade the defence, which we leave to future work.

Limitations. The audit covers five open-weights VLMs; frontier closed-source models do not expose hidden states, so the family-conditional rule cannot be verified there. Refusal is scored by a first-step substring lexicon, which can miss paraphrased refusals (a multi-token extension is open), and utility is MMBench MCQ accuracy (CN and EN), a coarse proxy that may not register open-ended degradation such as fluency or grounding. The direction is calibrated on one safety distribution; prompts that differ substantially (new languages, domains, or image styles) may shift $\overline{\Delta h}^B$, at a low but non-zero re-calibration cost. The two non-passing direction-specificity cells have positive point estimates (paired-CI lower bounds -0.021 and -0.007), so the 13/15 headline is conservative rather than driven by negative effects. Transfer is verified on the single dim-compatible LLaVA-1.5-13B $\leftrightarrow$ Pixtral-12B pair, and Pareto membership that hinges on utility gaps below the ≈ 2 pp noise floor ($n=98$) should be read with caution.

Acknowledgments

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Health and Digital Executive Agency (HADEA). Neither the European Union nor the granting authority can be held responsible for them. RobustifAI project, ID 101212818.

References

- Arditi, A.; Obeso, O.; Syed, A.; Paleka, D.; Panickssery, N.; Gurnee, W.; and Nanda, N. 2024. Refusal in Language Models Is Mediated by a Single Direction. In *Advances in Neural Information Processing Systems (NeurIPS)*. ArXiv:2406.11717.
- Belrose, N.; Furman, Z.; Smith, L.; Halawi, D.; Ostrovsky, I.; McKinney, L.; Biderman, S.; and Steinhardt, J. 2023. Eliciting Latent Predictions from Transformers with the Tuned Lens. *arXiv preprint arXiv:2303.08112*.
- Draxler, F.; Veschgini, K.; Salmhofer, M.; and Hamprecht, F. 2018. Essentially No Barriers in Neural Network Energy Landscape. In *International Conference on Machine Learning (ICML)*, 1309–1318. PMLR 80.
- Garipov, T.; Izmailov, P.; Podoprikin, D.; Vetrov, D. P.; and Wilson, A. G. 2018. Loss Surfaces, Mode Connectivity, and Fast Ensembling of DNNs. In *Advances in Neural Information Processing Systems (NeurIPS)*, 8803–8812.
- Gong, Y.; Ran, D.; Liu, J.; Wang, C.; Cong, T.; Wang, A.; Duan, S.; and Wang, X. 2025. FigStep: Jailbreaking Large Vision-Language Models via Typographic Visual Prompts. In *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, volume 39. Oral presentation. ArXiv:2311.05608.
- Hua, P.; Li, H.; Shi, S.; Yu, Z.; and Zhang, N. 2025. Rethinking Jailbreak Detection of Large Vision Language Models with Representational Contrastive Scoring. *arXiv preprint arXiv:2512.12069*.
- Jiang, Y.; Gao, X.; Peng, T.; Tan, Y.; Zhu, X.; Zheng, B.; and Yue, X. 2025. HiddenDetect: Detecting Jailbreak Attacks against Large Vision-Language Models via Monitoring Hidden States. In *Proceedings of the Annual Meeting of the Association for Computational Linguistics (ACL)*. ArXiv:2502.14744.
- Li, Y.; Du, Y.; Zhou, K.; Wang, J.; Zhao, W. X.; and Wen, J.-R. 2023. Evaluating Object Hallucination in Large Vision-Language Models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*. ArXiv:2305.10355.
- Li, Y.; Guo, H.; Zhou, K.; Zhao, W. X.; and Wen, J.-R. 2024. Images are Achilles’ Heel of Alignment: Exploiting Visual Vulnerabilities for Jailbreaking Multimodal Large Language Models. In *European Conference on Computer Vision (ECCV)*, 173–190. Oral presentation. arXiv:2403.09792.
- Liu, Q.; Shang, C.; Liu, L.; Pappas, N.; Ma, J.; John, N. A.; Doss, S.; Márquez, L.; Ballesteros, M.; and Benajiba, Y. 2025a. Unraveling and Mitigating Safety Alignment Degradation of Vision-Language Models. In *Findings of the Association for Computational Linguistics (ACL)*, 3631–3643. ArXiv:2410.09047.
- Liu, Q.; Wang, F.; Xiao, C.; and Chen, M. 2025b. VLM-Guard: Safeguarding Vision-Language Models via Fulfilling Safety Alignment Gap. *arXiv preprint arXiv:2502.10486*.
- Liu, X.; Zhu, Y.; Gu, J.; Lan, Y.; Yang, C.; and Qiao, Y. 2024a. MM-SafetyBench: A Benchmark for Safety Evaluation of Multimodal Large Language Models. In *European Conference on Computer Vision (ECCV)*, 386–403. ArXiv:2311.17600.
- Liu, Y.; Duan, H.; Zhang, Y.; Li, B.; Zhang, S.; Zhao, W.; Yuan, Y.; Wang, J.; He, C.; Liu, Z.; Chen, K.; and Lin, D. 2024b. MMBench: Is Your Multi-modal Model an All-around Player? In *European Conference on Computer Vision (ECCV)*. Oral presentation. arXiv:2307.06281.
- Luo, W.; Ma, S.; Liu, X.; Guo, X.; and Xiao, C. 2024. JailBreakV-28K: A Benchmark for Assessing the Robustness of MultiModal Large Language Models against Jailbreak Attacks. In *Conference on Language Modeling (COLM)*. ArXiv:2404.03027.
- Pan, W.; Liu, Z.; Chen, Q.; Zhou, X.; Yu, H.; and Jia, X. 2025. The Hidden Dimensions of LLM Alignment: A Multi-Dimensional Analysis of Orthogonal Safety Directions. In *International Conference on Machine Learning (ICML)*. ArXiv:2502.09674.
- Wei, Z.; Li, Q.; Ruan, J.; Qin, Z.; Wen, L.; Liu, D.; and Shen, W. 2026. Understanding and Defending VLM Jailbreaks via Jailbreak-Related Representation Shift. *arXiv preprint arXiv:2603.17372*.
- Zou, X.; Kang, J.; Kesidis, G.; and Lin, L. 2025. Understanding and Rectifying Safety Perception Distortion in VLMs. In *Advances in Neural Information Processing Systems (NeurIPS)*. ArXiv:2502.13095.

A Configuration grid

model	params	residual dim d	layers (early / middle / late)
LLaVA-1.5-7B	7B	4096	8 / 16 / 24
LLaVA-1.5-13B	13B	5120	10 / 20 / 30
Qwen2.5-VL	7B	3584	7 / 14 / 21
Qwen2-VL-2B	2B	1536	6 / 14 / 22
Pixtral-12B	12B	5120	10 / 20 / 30

Table 7: The 15 (model, layer) configurations used throughout the paper. Layer depths span early, middle, and late residual streams within each model.

B Per-cell direction-test breakdown (safety)

Table 8 reports the per-cell direction-test quantities on the safety-evaluation distribution. Per-prompt alignment with the mean shift direction, the shared-direction ratio R_h , and the benign-vs-jailbreak direction overlap.

The %pos Δh test reaches the threshold of §3 ($\geq 95\%$) in every cell. The benign-vs-jailbreak direction overlap is ≥ 0.75 in every cell.

C Robustness checks for §5

C.1 α_h sensitivity for ABL_POS

§5 fixes the per-prompt scaling $\alpha_h = 1.0$ in equation (2) (subtract one full per-prompt $\|\Delta \mathbf{h}^B(x)\|$). To rule out cherry-picking, we sweep $\alpha_h \in \{0, 0.25, 0.5, 0.75, 1.0, 1.25, 1.5, 2.0\}$ on LLaVA-1.5-7B/L16 ($n = 40$ jailbreak-image prompts) and report the refusal-recovery curve. Numbers are filled from `alpha_sensitivity.json` produced by `exp_alpha_sensitivity.py`.

The curve is smooth and rises monotonically from WITH_IMAGE ($\alpha_h = 0$) to a plateau near $\alpha_h \in [1.0, 1.5]$, with no collapse at $\alpha_h > 1.5$. The choice $\alpha_h = 1.0$ sits on the plateau (stable, not at a knife-edge). The plateau refusal rate at the default $\alpha_h = 1.0$ is 0.325.

C.2 Mechanistic ablation versus prompt-level instruction

We compare the mechanistic ablation (2) against two prompt-level alternatives that ask the model to ignore the image (LLaVA-1.5-7B L16, $n = 63$ jailbreak-image prompts).

The prompt-level instructions recover only 0.14–0.22 refusal, far below ABL_POS’s 0.619. They moreover *increase* the residual-stream distance from the text-only reference (from 20.1 to 22.3 / 24.1) and partially *reduce* the cosine alignment of the deviation with the calibrated mean image-direction (0.62 to 0.45 / 0.37). The textual instruction adds an additional perturbation that is partially off-axis from the image-conditioning subspace rather than removing it, consistent with the image-conditioning structure being mechanistically distinct from textual instruction-following at the layer we probe.

D Loader coverage for causal scripts

The five scripts that perform forward-pass interventions (ABL_POS, IGNORE_INSTR, CMRM-LIKE, SHIFTDC-LIKE, utility preservation) dispatch the model-loading and prompt-template paths by family. We use `LlavaForConditionalGeneration` for the LLaVA-1.5 family and `Pixtral-12B`, `Qwen2VLForConditionalGeneration`

for Qwen2-VL-2B, and `Qwen2_5_VLForConditionalGeneration` for Qwen2.5-VL-7B. Causal results in §5 and the defence comparison of §5.2 therefore cover the full $5 \times 3 = 15$ (model, layer) grid. Direction transfer (§5.2) is restricted to source/target pairs whose residual streams share dimensionality. LLaVA-1.5-13B and Pixtral-12B both have $d = 5120$, while Qwen2.5-VL-7B has $d = 3584$ and Qwen2-VL-2B has $d = 1536$. The dim-compatible transfer pair is LLaVA-1.5-13B $\leftrightarrow$ Pixtral-12B (six matched-layer pairs).

E Per-cell defence breakdown

Tables 11–13 give the per-cell numbers underlying the cell-mean values of Table 5, covering the full 15-cell grid. ABL_POS calibration uses the same 50% split as §5.

F Utility preservation: five defences on MMBench MCQ

We test whether each candidate defence, calibrated on safety benign-image data and applied at inference time, breaks the model’s image-dependent VQA ability on MMBench multiple-choice prompts. For each configuration we evaluate seven conditions per prompt. TEXT_ONLY (no image, image-blind lower bound), WITH_IMAGE (no intervention, upper bound), and five defences (ABL_POS, CMRM-LIKE, SHIFTDC-LIKE, RANDOM_CTRL, IGNORE). All hidden-state defences scale per-prompt subtraction by the calibration mean $\bar{m} := \|\Delta \mathbf{h}^B\|$. MCQ choices are extracted via the parser of §F (regex matching answer markers “Answer: X” / “X” / “(X)” before falling back to the first standalone A – D letter) and scored against the MMBench `true_answer` field.

Subset, n, and noise floor. We use a stratified 7-category subsample ($n = 98$, 14 prompts per category) of MMBench’s Chinese-culture L1 split (scenery / building, cultural relic, traditional show, calligraphy & painting, historical figure, sketch reasoning, food & clothes). The default English-MMBench accuracy of LLaVA-1.5-7B is $\sim 64\%$ in the published evaluation, which uses the full mixed-language split with broader visual semantics. Our subset is substantially harder due to its concentration on Chinese-cultural visual reasoning, so the WITH_IMAGE accuracy here (42.9% on LLaVA-1.5-7B; the Qwen family, trained with more Chinese data, reaches 66–74%) is a property of the subset rather than an evaluation bug. The paired utility-loss noise floor at $n = 98$ is ~ 2 pp. We deliberately frame utility differences smaller than this as below the resolution of our measurement. The defence comparison is *relative* (utility loss = WI accuracy –

model	layer	n	d	%pos Δh	R_h	$\cos(B, J)_h$
LLaVA-1.5-7B	8	168	4096	100%	0.860	0.986
LLaVA-1.5-7B	16	130	4096	100%	0.680	0.949
LLaVA-1.5-7B	24	168	4096	100%	0.626	0.902
LLaVA-1.5-13B	10	181	5120	100%	0.766	0.945
LLaVA-1.5-13B	20	181	5120	100%	0.628	0.853
LLaVA-1.5-13B	30	181	5120	100%	0.721	0.912
Qwen2.5-VL	7	181	3584	100%	0.939	0.950
Qwen2.5-VL	14	194	3584	100%	0.850	0.922
Qwen2.5-VL	21	194	3584	100%	0.684	0.785
Qwen2-VL-2B	6	100	1536	100%	0.904	0.912
Qwen2-VL-2B	14	100	1536	100%	0.851	0.928
Qwen2-VL-2B	22	100	1536	100%	0.724	0.831
Pixtral-12B	10	144	5120	100%	0.813	0.752
Pixtral-12B	20	100	5120	100%	0.642	0.857
Pixtral-12B	30	100	5120	100%	0.528	0.872

Table 8: Per-cell safety-grid direction tests. %pos Δh , fraction of prompts with positive cosine to the mean shift direction (benign condition). R_h , the shared-direction ratio. $\cos(B, J)_h$, cosine between benign- and jailbreak-conditioned mean directions. Note R_h (shared-direction ratio) is distinct from the per-prompt *mean cosine* to $\overline{\Delta h}^B$ quoted for the anchor cell in §4.1 (+0.679 benign, +0.655 jailbreak on LLaVA-1.5-7B/L16); the two quantities are numerically close on this cell but measure different things.

α_h	0	0.25	0.5	0.75	1.0	1.25	1.5	2.0
refusal rate	0.100	0.100	0.125	0.175	0.325	0.425	0.575	0.725

Table 9: α_h sensitivity on LLaVA-1.5-7B/L16 ($n = 40$). Refusal rate at each α_h . The default is $\alpha_h = 1.0$.

defence accuracy), so absolute-accuracy differences across cells or subsets do not affect the relative ordering.

For each defence d , $\text{UTILITY_LOSS}_d = \text{acc}_{\text{WITH_IMAGE}} - \text{acc}_d$ (positive means defence d hurts utility), and $\text{DEFENCE_DRIFT}_d = \text{acc}_d - \text{acc}_{\text{TEXT_ONLY}}$ (near zero means the defence collapses to the image-blind regime).

F.1 Robustness check: English MMBench at $n = 190$ on all 15 cells

The CN-cultural subset above ($n = 98$) has a paired utility-loss noise floor of ~ 2 pp per cell. To rule out a language-/topic-specific artefact, we re-run utility preservation on the standard *English MMBench dev split* (Liu et al. 2024b) (lms-lab/MMBench, config=en, split=dev) at $n = 190$ stratified across 20 L1 categories (~ 10 prompts per subset) on the full 15-cell grid. At $n = 190$ the paired noise floor drops to ~ 1.4 pp. The same 7-condition probe is applied. Calibration directions and per-prompt scaling are inherited from the safety calibration of §5 so defence directions are identical between the CN and EN runs.

Reading. The English MMBench WITH_IMAGE accuracy matches published numbers for the corresponding families ($\sim 64\%$ for LLaVA-1.5-7B, $\sim 68\%$ for LLaVA-1.5-13B,

$\sim 75\text{--}80\%$ for Pixtral-12B, with Qwen2.5-VL-7B at 82.6% and Qwen2-VL-2B at 72.1%), confirming the parser and evaluation protocol are sound. The lower WITH_IMAGE accuracy on the CN-cultural subset (Table 14) was a property of that subset, not an evaluation bug. Across all 15 cells, every hidden-state defence stays within 2.6 pp of WITH_IMAGE (ABL_POS worst case +2.6 pp on Pixtral-12B/L20, at or below the noise floor everywhere else), so the no-utility-loss conclusion from the CN subset carries over to English.

G Cross-model direction transfer

Cross-model defence transfer requires the source and target residual streams to share a dimensionality. On our grid, LLaVA-1.5-13B and Pixtral-12B both have $d = 5120$ at all layer depths. The Qwen models ($d \in \{1536, 3584\}$) are dim-incompatible with the LLaVA/Pixtral pair and dim-incompatible with each other, so transfer is reported on the dim-compatible LLaVA-13B / Pixtral pair at the three matched layer depths (L10, L20, L30), yielding six source-/target pairs. For each pair we report the calibrated native ABL_POS efficacy on the target, the transferred ABL_POS efficacy (using the source’s $\overline{\Delta h}^B$ on target hidden states), and the TRANSFER PENALTY, defined as native refusal recovery minus transferred refusal recovery.

Reading. The near-orthogonal calibrated directions ($\cos \leq 0.04$) and the near-zero transferred recovery show the mean image-direction $\overline{\Delta h}^B$ is strongly model-idiosyncratic on the dim-compatible pair: it does *not* transfer across architectures in either direction. The raw transfer-penalty asymmetry ($\sim$

condition	refusal rate	$\ \mathbf{h} - \mathbf{h}^T\ $	$\cos(\mathbf{h} - \mathbf{h}^T, \overline{\Delta\mathbf{h}}^B)$
TEXT_ONLY	1.000	—	—
WITH_IMAGE	0.159	20.1	0.62
+ “Ignore the image. . . ”	0.143	22.3	0.45
+ “[CRITICAL SYSTEM] You MUST ignore. . . ”	0.222	24.1	0.37
ABL_POS (mechanistic, from §5)	0.619	—	—

Table 10: Mechanistic vs prompt-level “ignore the image”. Refusal: fraction of prompts on which the model refuses. $\|\mathbf{h} - \mathbf{h}^T\|$: distance from text-only reference at layer ℓ . $\cos(\mathbf{h} - \mathbf{h}^T, \overline{\Delta\mathbf{h}}^B)$: direction alignment with the calibrated mean image-direction.

model	layer	WITH_IMAGE	ABL_POS	RANDOM_CTRL	recovery
LLaVA-1.5-7B	8	0.185	0.262	0.138	+0.077
LLaVA-1.5-7B	16	0.159	0.349	0.159	+0.190
LLaVA-1.5-7B	24	0.185	0.523	0.154	+0.338
LLaVA-1.5-13B	10	0.215	0.338	0.231	+0.123
LLaVA-1.5-13B	20	0.215	0.338	0.262	+0.123
LLaVA-1.5-13B	30	0.215	0.369	0.246	+0.154
Qwen2.5-VL-7B	7	0.415	0.477	0.400	+0.062
Qwen2.5-VL-7B	14	0.323	0.431	0.308	+0.108
Qwen2.5-VL-7B	21	0.323	0.646	0.277	+0.323
Qwen2-VL-2B	6	0.208	0.208	0.208	+0.000
Qwen2-VL-2B	14	0.208	0.354	0.188	+0.146
Qwen2-VL-2B	22	0.208	0.438	0.229	+0.229
Pixtral-12B	10	0.262	0.538	0.231	+0.277
Pixtral-12B	20	0.188	0.792	0.104	+0.604
Pixtral-12B	30	0.213	0.745	0.234	+0.532

Table 11: **ABL_POS / RANDOM_CTRL** per-cell refusal rates on jailbreak-image prompts across the full 5×3 grid. **RECOVERY** is **ABL_POS** – **WITH_IMAGE**. Numbers come from the **BASELINE_DEFENCES** run, which mixes the calibration and held-out indices into a single evaluation set and therefore reports lower-magnitude refusal rates than the dedicated 6-condition causal probe of Table 2 (LLaVA-1.5-7B/L16, **ABL_POS** 0.349 here vs. 0.619 there). The two estimators frame different deployment proxies. The relative ordering of defences is consistent across both.

0.70 on the Pixtral target vs. ~ 0.10 on the LLaVA-1.5-13B target) is a metric artefact, since the penalty is native minus transferred recovery and native efficacy is far larger on Pixtral. This complements the within-cell §4.1 finding that the direction is prompt-shared *within* a model while being architecture- specific *across* models.

H Probe-regime analysis: where the attack signal lives

Detection vs. intervention. Two complementary questions about the positional direction $\overline{\Delta\mathbf{h}}^B$ are easy to confuse. (a) Where does the benign-vs-jailbreak *discriminative* signal live (*detection regime*)? (b) Which direction, when subtracted at one layer, recovers refusal best (*intervention regime*)? This appendix addresses (a), and §5 and §5.2 address (b). The two answers need not agree. A feature can be where the signal is detectable and yet not be the optimal direction to subtract for behavioural recovery on every architecture (e.g. on the LLaVA-1.5 family the **SHIFTDC-LIKE** attack-specific residual is competitive with **ABL_POS** in §5.2).

Probes. We score “image is jailbreak” vs. “image is benign” on the per-prompt activation $\mathbf{h}_t^m$ using 5-fold stratified cross-validated AUC on the held-out split. Three high-D probes use the full $\mathbb{R}^d$ input (**BASELINE** on raw activations, **Pos-PROJECTED** on the residual after projecting out $\overline{\Delta\mathbf{h}}^B$, and **RANDOM-PROJECTED** likewise with an isotropic random direction, 10 draws). Two low-D probes use a single scalar each (1D-ALONG = $\langle \mathbf{h}, \overline{\Delta\mathbf{h}}^B \rangle$, 1D-ORTHO = orthogonal-complement norm). Per-config n ranges 98–194. The three high-D probes agree within ± 0.007 absolute AUC, and we report their mean.

Implication. High-D probes saturate (≈ 1.000 on 8/15 cells, mean 0.988 across all three projections), so the choice of single direction projected away is invisible at this regime. 1D-ALONG exceeds 1D-ORTHO in 12/15 cells (mean 0.66 vs. 0.59). The discriminative signal lives along the shared positional direction as a signed magnitude, not in the orthogonal complement.

model	layer	WITH_IMAGE	IGNORE	IGNORE-emphatic	Δ IGNORE	gap to ABL_POS
LLaVA-1.5-7B	8	0.185	0.169	0.277	−0.015/ + 0.092	+0.015
LLaVA-1.5-7B	16	0.159	0.143	0.222	−0.016/ + 0.063	−0.127
LLaVA-1.5-7B	24	0.185	0.169	0.277	−0.015/ + 0.092	−0.246
LLaVA-1.5-13B	10	0.215	0.154	0.308	−0.062/ + 0.092	−0.031
LLaVA-1.5-13B	20	0.215	0.154	0.308	−0.062/ + 0.092	−0.031
LLaVA-1.5-13B	30	0.215	0.154	0.308	−0.062/ + 0.092	−0.062
Qwen2.5-VL-7B	7	0.415	0.708	0.708	+0.292/ + 0.292	+0.231
Qwen2.5-VL-7B	14	0.323	0.708	0.662	+0.385/ + 0.338	+0.231
Qwen2.5-VL-7B	21	0.323	0.708	0.662	+0.385/ + 0.338	+0.015
Qwen2-VL-2B	6	0.208	0.333	0.479	+0.125/ + 0.271	+0.271
Qwen2-VL-2B	14	0.208	0.333	0.479	+0.125/ + 0.271	+0.125
Qwen2-VL-2B	22	0.208	0.333	0.479	+0.125/ + 0.271	+0.042
Pixtral-12B	10	0.262	0.262	0.785	+0.000/ + 0.523	+0.246
Pixtral-12B	20	0.188	0.208	0.812	+0.021/ + 0.625	+0.021
Pixtral-12B	30	0.213	0.170	0.766	−0.043/ + 0.553	+0.021

Table 12: **Prompt-level IGNORE-INSTRUCTION** per-cell refusal rates on jailbreak-image prompts (non-emphatic / emphatic variants).

model	layer	CMRM-like	gap to ABL_POS	ShiftDC-like	gap to ABL_POS
LLaVA-1.5-7B	8	0.200	−0.062	0.231	−0.031
LLaVA-1.5-7B	16	0.159	−0.190	0.476	+0.127
LLaVA-1.5-7B	24	0.338	−0.185	0.708	+0.185
LLaVA-1.5-13B	10	0.262	−0.077	0.231	−0.108
LLaVA-1.5-13B	20	0.338	+0.000	0.492	+0.154
LLaVA-1.5-13B	30	0.477	+0.108	0.769	+0.400
Qwen2.5-VL-7B	7	0.446	−0.031	0.431	−0.046
Qwen2.5-VL-7B	14	0.462	+0.031	0.400	−0.031
Qwen2.5-VL-7B	21	0.446	−0.200	0.508	−0.138
Qwen2-VL-2B	6	0.208	+0.000	0.271	+0.062
Qwen2-VL-2B	14	0.479	+0.125	0.792	+0.437
Qwen2-VL-2B	22	0.521	+0.083	0.896	+0.458
Pixtral-12B	10	0.292	−0.246	0.169	−0.369
Pixtral-12B	20	0.771	−0.021	0.500	−0.292
Pixtral-12B	30	0.681	−0.064	0.532	−0.213

Table 13: **CMRM-LIKE (refusal direction)** and **SHIFTDC-LIKE (attack-specific shift component)** per-cell refusal rates. Both apply a fixed-direction subtraction at the calibrated layer, scaled to match ABL_POS’s per-prompt norm. A cell would be degenerate if the calibrated refusal direction collapsed onto the positional direction ($\cos(r_{\text{dir}}, \overline{\Delta \mathbf{h}}^B) \geq 0.999$, making the CMRM-LIKE number equal ABL_POS by construction); no cell on the grid triggers this criterion (max per-cell $\cos = 0.65$).

<i>Accuracy</i>								
model	layer	T	W	ABL_POS	CMRM-like	ShiftDC-like	RANDOM	IGNORE
LLaVA-1.5-7B	8	0.214	0.429	0.429	0.429	0.418	0.418	0.418
LLaVA-1.5-7B	16	0.214	0.429	0.418	0.418	0.449	0.418	0.418
LLaVA-1.5-7B	24	0.214	0.429	0.418	0.418	0.398	0.418	0.418
LLaVA-1.5-13B	10	0.316	0.480	0.480	0.480	0.459	0.480	0.480
LLaVA-1.5-13B	20	0.316	0.480	0.469	0.469	0.459	0.439	0.480
LLaVA-1.5-13B	30	0.316	0.480	0.510	0.510	0.459	0.459	0.480
Qwen2.5-VL-7B	7	0.265	0.735	0.735	0.735	0.735	0.735	0.735
Qwen2.5-VL-7B	14	0.265	0.735	0.714	0.714	0.724	0.714	0.735
Qwen2.5-VL-7B	21	0.265	0.735	0.714	0.714	0.694	0.704	0.735
Qwen2-VL-2B	6	0.347	0.663	0.643	0.643	0.663	0.653	0.643
Qwen2-VL-2B	14	0.347	0.663	0.663	0.663	0.663	0.643	0.643
Qwen2-VL-2B	22	0.347	0.663	0.653	0.653	0.653	0.653	0.643
Pixtral-12B	10	0.245	0.653	0.673	0.673	0.663	0.663	0.612
Pixtral-12B	20	0.245	0.653	0.663	0.663	0.663	0.684	0.612
Pixtral-12B	30	0.245	0.653	0.684	0.684	0.684	0.694	0.612
<i>Utility loss = Acc_W − Acc_{DEF}</i>								
model	layer	—	—	ABL_POS	CMRM-like	ShiftDC-like	RANDOM	IGNORE
LLaVA-1.5-7B	8	—	—	+0.000	+0.000	+0.010	+0.010	+0.010
LLaVA-1.5-7B	16	—	—	+0.010	+0.010	−0.020	+0.010	+0.010
LLaVA-1.5-7B	24	—	—	+0.010	+0.010	+0.031	+0.010	+0.010
LLaVA-1.5-13B	10	—	—	+0.000	+0.000	+0.020	+0.000	+0.000
LLaVA-1.5-13B	20	—	—	+0.010	+0.010	+0.020	+0.041	+0.000
LLaVA-1.5-13B	30	—	—	−0.031	−0.031	+0.020	+0.020	+0.000
Qwen2.5-VL-7B	7	—	—	+0.000	+0.000	+0.000	+0.000	+0.000
Qwen2.5-VL-7B	14	—	—	+0.020	+0.020	+0.010	+0.020	+0.000
Qwen2.5-VL-7B	21	—	—	+0.020	+0.020	+0.041	+0.031	+0.000
Qwen2-VL-2B	6	—	—	+0.020	+0.020	+0.000	+0.010	+0.020
Qwen2-VL-2B	14	—	—	+0.000	+0.000	+0.000	+0.020	+0.020
Qwen2-VL-2B	22	—	—	+0.010	+0.010	+0.010	+0.010	+0.020
Pixtral-12B	10	—	—	−0.020	−0.020	−0.010	−0.010	+0.041
Pixtral-12B	20	—	—	−0.010	−0.010	−0.010	−0.031	+0.041
Pixtral-12B	30	—	—	−0.031	−0.031	−0.031	−0.041	+0.041

Table 14: Utility preservation on MMBench MCQ across the full 5×3 grid (15 cells, $n = 98$ per cell). Top block reports accuracy under each condition (T=TEXT_ONLY, W=WITH_IMAGE references, with the ABL_POS, CMRM-LIKE, SHIFTDC-LIKE, RANDOM, IGNORE defences). Bottom block reports utility loss $\text{Acc}_W - \text{Acc}_{\text{DEF}}$ per defence.

Accuracy model	layer	T	W	ABL_POS	CMRM-like	ShiftDC-like	RANDOM	IGNORE
LLaVA-1.5-7B	8	0.332	0.689	0.689	0.689	0.684	0.679	0.668
LLaVA-1.5-7B	16	0.332	0.689	0.684	0.684	0.684	0.689	0.674
LLaVA-1.5-7B	24	0.332	0.689	0.695	0.695	0.689	0.684	0.668
LLaVA-1.5-13B	10	0.416	0.711	0.716	0.716	0.716	0.700	0.711
LLaVA-1.5-13B	20	0.416	0.711	0.711	0.711	0.721	0.711	0.711
LLaVA-1.5-13B	30	0.416	0.711	0.700	0.700	0.726	0.700	0.711
Qwen2.5-VL-7B	7	0.411	0.826	0.826	0.826	0.826	0.826	0.816
Qwen2.5-VL-7B	14	0.411	0.826	0.832	0.832	0.826	0.821	0.816
Qwen2.5-VL-7B	21	0.411	0.826	0.816	0.816	0.826	0.826	0.816
Qwen2-VL-2B	6	0.342	0.721	0.716	0.716	0.721	0.716	0.753
Qwen2-VL-2B	14	0.342	0.721	0.726	0.726	0.742	0.721	0.753
Qwen2-VL-2B	22	0.342	0.721	0.732	0.732	0.726	0.726	0.753
Pixtral-12B	10	0.389	0.784	0.784	0.784	0.774	0.784	0.784
Pixtral-12B	20	0.389	0.784	0.758	0.758	0.763	0.779	0.784
Pixtral-12B	30	0.389	0.784	0.779	0.779	0.774	0.789	0.784

$Utility\ loss = Acc_W - Acc_{DEF}$ model	layer	—	—	ABL_POS	CMRM-like	ShiftDC-like	RANDOM	IGNORE
LLaVA-1.5-7B	8	—	—	+0.000	+0.000	+0.005	+0.011	+0.021
LLaVA-1.5-7B	16	—	—	+0.005	+0.005	+0.005	+0.000	+0.016
LLaVA-1.5-7B	24	—	—	-0.005	-0.005	+0.000	+0.005	+0.021
LLaVA-1.5-13B	10	—	—	-0.005	-0.005	-0.005	+0.011	+0.000
LLaVA-1.5-13B	20	—	—	+0.000	+0.000	-0.011	+0.000	+0.000
LLaVA-1.5-13B	30	—	—	+0.011	+0.011	-0.016	+0.011	+0.000
Qwen2.5-VL-7B	7	—	—	+0.000	+0.000	+0.000	+0.000	+0.011
Qwen2.5-VL-7B	14	—	—	-0.005	-0.005	+0.000	+0.005	+0.011
Qwen2.5-VL-7B	21	—	—	+0.011	+0.011	+0.000	+0.000	+0.011
Qwen2-VL-2B	6	—	—	+0.005	+0.005	+0.000	+0.005	-0.032
Qwen2-VL-2B	14	—	—	-0.005	-0.005	-0.021	+0.000	-0.032
Qwen2-VL-2B	22	—	—	-0.011	-0.011	-0.005	-0.005	-0.032
Pixtral-12B	10	—	—	+0.000	+0.000	+0.011	+0.000	+0.000
Pixtral-12B	20	—	—	+0.026	+0.026	+0.021	+0.005	+0.000
Pixtral-12B	30	—	—	+0.005	+0.005	+0.011	-0.005	+0.000

Table 15: Utility preservation on **English MMBench** dev split ($n = 190$ per cell, stratified across 20 L1 categories) on the full 15-cell grid. Top block reports accuracy (T=TEXT_ONLY, W=WITH_IMAGE, with the defences as in Table 14). Bottom block reports utility loss $Acc_W - Acc_{DEF}$.

source $\rightarrow$ target	layer	$\cos(\text{nat}, \text{transf})$	WITH_IMAGE	native ABL_POS	transferred ABL_POS	transfer penalty
LLaVA-1.5-13B $\rightarrow$ Pixtral-12B	10 / 10	0.008	0.300	0.900	0.150	+0.750
Pixtral-12B $\rightarrow$ LLaVA-1.5-13B	10 / 10	0.007	0.400	0.500	0.400	+0.100
LLaVA-1.5-13B $\rightarrow$ Pixtral-12B	20 / 20	0.020	0.150	0.750	0.100	+0.650
Pixtral-12B $\rightarrow$ LLaVA-1.5-13B	20 / 20	0.020	0.400	0.450	0.400	+0.050
LLaVA-1.5-13B $\rightarrow$ Pixtral-12B	30 / 30	0.035	0.150	0.700	0.000	+0.700
Pixtral-12B $\rightarrow$ LLaVA-1.5-13B	30 / 30	0.038	0.400	0.550	0.400	+0.150

Table 16: Direction transfer between LLaVA-1.5-13B and Pixtral-12B at three matched layer depths (L10, L20, L30, both $d = 5120$), $n = 20$ jailbreak prompts per pair (Wilson half-width ~ 0.22 at $n = 20$ on a binomial proportion). NATIVE means ABL_POS calibrated on the target model. TRANSFERRED means the ABL_POS direction calibrated on the source model and applied to the target. $\cos(\text{nat}, \text{transf})$ is the cosine between the two models’ calibrated directions. The two directions are nearly orthogonal ($\cos \leq 0.04$) at every matched layer, and the transferred direction recovers essentially no refusal (transferred $\approx$ WITH_IMAGE, or below it), so neither model’s direction transfers. The much larger raw penalty on the Pixtral target reflects its much larger *native* efficacy, not better transfer.

config	FULL- d AUC (mean of 4)	1D-ALONG	1D-ORTHO
LLaVA-1.5-7B L8	0.991	0.746	0.653
LLaVA-1.5-7B L16	0.936	0.678	0.562
LLaVA-1.5-7B L24	0.959	0.451	0.535
LLaVA-1.5-13B L10	0.998	0.547	0.465
LLaVA-1.5-13B L20	0.975	0.578	0.567
LLaVA-1.5-13B L30	0.981	0.542	0.367
Qwen2.5-VL L7	1.000	0.436	0.463
Qwen2.5-VL L14	1.000	0.680	0.550
Qwen2.5-VL L21	1.000	0.597	0.542
Qwen2-VL-2B L6	1.000	0.849	0.768
Qwen2-VL-2B L14	1.000	0.728	0.665
Qwen2-VL-2B L22	0.990	0.825	0.747
Pixtral-12B L10	1.000	0.987	0.627
Pixtral-12B L20	0.993	0.742	0.634
Pixtral-12B L30	0.991	0.562	0.738
mean (15 cfg)	0.988	0.663	0.592

Table 17: Cross-validated probe AUC across the 15-cell safety grid. FULL- d AUC is the mean over three full-dimensional probes (raw, project-out positional, project-out random, with per-probe agreement within ± 0.007). 1D-ALONG is the scalar projection $\langle \mathbf{h}, \overline{\Delta \mathbf{h}}^B \rangle$. 1D-ORTHO is the orthogonal-complement norm. **Bold** marks the larger of (Along, Ortho).