

Onboarding — Vnotice

Six steps to get set up and ship your first change.

1. Get access

- Clone the repo: `git clone https://github.com/darkhager/vnotice.git`
- Ask the team for the SSH login to the production server (`vnotice@10.4.150.57`). Never put that password in a file — keep it in your own password manager.
- On Windows, install **PuTTY** — deployment uses its `plink`/`pscp` tools (see step 5), not OpenSSH.

2. Run it locally

Backend (SQLite, no Docker needed):

```
cd backend
.\setup_local.ps1      # creates venv, installs deps, writes .env, starts uvicorn
# API:      http://localhost:8000
# Swagger:  http://localhost:8000/docs
```

Frontend (separate terminal):

```
cd frontend
npm install
npm run dev                # http://localhost:3000
```

If a run fails with `table user_configs` has no column named `...`, delete `backend/cvedb.sqlite` and restart — the dev DB gets recreated with the current schema.

3. Read the map before touching code

- `CLAUDE.md` — architecture, routes, schema, what's built vs. missing.
- `backend/main.py` — every API route.
- `backend/rss_parser.py` — feed/NVD fetchers.
- `frontend/src/components/Dashboard.tsx` — nearly the whole UI (one big file — see `CLAUDE.md`'s P4 for the planned split).

4. Know the production layout

Bare-metal on `10.4.150.57` (no Docker, no root — the `vnotice` user isn't a sudoer):

Service	Port	Unit
Backend (uvicorn, plain HTTP)	8080	<code>vnotice-backend.service</code>

Frontend (Next.js, plain HTTP)	4000	vnotice-frontend.service
--------------------------------	------	--------------------------

Both are systemd --user services (lingering enabled, so they survive logout/reboot without a login session). Both serve plain HTTP (no TLS) — open `http://10.4.150.57:4000`.

5. Ship a change

There's no CI/CD yet — deploys are manual, from Windows via PuTTY's CLI tools (git bash recommended).

Backend:

```
# 1. Syntax-check locally first
py -c "import ast; ast.parse(open('backend/main.py', encoding='utf-8').read())"

# 2. Upload
"/c/Program Files/PuTTY/pscp.exe" -batch -pw '<password>' backend/main.py \
  vnotice@10.4.150.57:/home/vnotice/vnotice/backend/

# 3. Restart (MSYS_NO_PATHCONV=1 stops git-bash mangling the /run/user/... path)
MSYS_NO_PATHCONV=1 "/c/Program Files/PuTTY/plink.exe" -ssh -batch -pw '<password>' \
  vnotice@10.4.150.57 "XDG_RUNTIME_DIR=/run/user/\$(id -u) systemctl --user restart
  vnotice-backend"

# 4. Verify
curl -s http://10.4.150.57:8080/health/
```

Frontend: same upload step, then on the server run `npm run build` (needs `nvm use 20` first) before restarting `vnotice-frontend` — Next.js needs a rebuild, unlike the backend which just re-executes the `.py` file.

Gotcha: never `kill -f 'uvicorn main:app'` over SSH — the pattern matches the SSH shell's own command line and kills your connection (exit 128). Use `systemctl --user stop/restart` instead.

6. Commit

Nothing auto-commits. Stage, commit, and push yourself when a change is ready — ask before pushing if you're unsure it's wanted yet.