

Class Dictionary

Jean-Philippe Miguel-Gagnon, Jérémy Gaouette, Raphaël Rail

Thursday, 31th of march 2022



Presented to : Charles Jacob

Contents

1	Introduction	3
2	Models	4
2.1	Classe Piece	4
2.1.1	Fields	4
2.1.2	Methods	4
2.1.3	Properties	5
2.2	Class StartingPiece : Piece	6
2.2.1	Fields	6
2.2.2	Methods	6
2.2.3	Properties	6
2.3	Class Pawn : StartingPiece	7
2.3.1	Fields	7
2.3.2	Methods	7
2.3.3	Properties	7
2.4	Class Rook : StartingPiece	8
2.4.1	Fields	8
2.4.2	Methods	8
2.4.3	Properties	8
2.5	Class King : StartingPiece	9
2.5.1	Fields	9
2.5.2	Methods	9
2.5.3	Properties	9
2.6	Class Knight : Piece	10
2.6.1	Fields	10
2.6.2	Methods	10
2.6.3	Properties	10
2.7	Class Bishop : Piece	11
2.7.1	Fields	11
2.7.2	Methods	11
2.7.3	Properties	11
2.8	Class Queen : Piece	12
2.8.1	Fields	12
2.8.2	Methods	12
2.8.3	Properties	12
2.9	Class Match	13
2.9.1	Fields	13
2.9.2	Methods	14
2.9.3	Properties	15
2.10	Class Board	16
2.10.1	Fields	16
2.10.2	Methods	16
2.11	Class Cell	19

2.11.1	Fields	19
2.11.2	Methods	19
2.12	Class Player	21
2.12.1	Fields	21
3	Controllers	22
3.1	Class Chess	22
3.1.1	Fields	22
3.1.2	Methods	22
3.2	Class GameController	24
3.2.1	Fields	24
3.2.2	Methods	25
3.3	Class PlayerController	27
3.3.1	Fields	27
3.3.2	Methods	27
4	Views	28
4.1	Class FormSelection	28
4.1.1	Fields	28
4.1.2	Methods	28
4.2	Class FormMenu	29
4.2.1	Fields	29
4.2.2	Methods	29
4.3	Class FormPromotion	30
4.3.1	Fields	30
4.3.2	Methods	30
4.4	Class FormMatch	31
4.4.1	Fields	31
4.4.2	Methods	31
4.5	Class FormLeaderboard	33
4.5.1	Fields	33
4.5.2	Methods	33

1 Introduction

The goal of this document is to inform the programmer about classes used to create a C# OOP Chess game.

We'll go through this with the MVC model approach to make it clearer for the programmer where to implement his code.

2 Models

2.1 Classe Piece

This is an abstract class for a base piece for the game.

(Abstract) Piece
-_colour : Colour
+CanCollide() : bool
+ValidMove(int x1, int y1, int x2, int y2) : bool
+ToString() : string
+CanPromote() : bool
+IsEssential() : bool

2.1.1 Fields

Field Name	Type	Visibility
_colour	Colour	Private

Description : This field represent the colour a piece, wich can only be black or white as it is for a regular chess game.

2.1.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : The method returns true if the piece can move to the 2nd position.

Method Name	Parameters	Returned Type	Visibility
CanCollide	None	bool	Public

Description : Returns true if the piece can't go over other pieces, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : Empty method to be overridden by child classes.

Method Name	Parameters	Returned Type	Visibility
CanPromote	None	bool	Public

Description : Returns true if the piece is promotable.

Method Name	Parameters	Returned Type	Visibility
IsEssential	None	bool	Public

Description : Returns true if the piece is essential.

2.1.3 Properties

Property Name	Parameters	Returned Type	Visibility
Colour	None	Colour	Public

Description : Gets the colour of a piece.

2.2 Class StartingPiece : Piece

Another abstract Class that inherits to the base Class Piece. This Class is for pieces that have different behaviour after they have moved for the first time.

(Abstract) StartingPiece
-_hasMoved : bool

2.2.1 Fields

Field Name	Type	Visibility
_hasMoved	bool	Private

Description : This field is used to tell if the piece has already made its first move.

2.2.2 Methods

Same as Class Piece.

2.2.3 Properties

Property Name	Parameters	Returned Type	Visibility
HasMoved	None	bool	Public

Description : Gets or Sets the property _hasMoved of a piece to true or false.

2.3 Class Pawn : StartingPiece

This Class inherits the Class StartingPiece. It represents the pawn piece of a regular chess game.

Pawn
+ValidMove(x1, y1, x2, y2) : bool
+CanPromote() : bool
+ToString() : string

2.3.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.3.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method checks if the move provided is valid considering the basic moves of a pawn which are 1 or 2 cells ahead, or 1 diagonal cell if an opponent piece is present. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
CanPromote	None	bool	Public

Description : Returns true if the piece can promote.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "p" if the piece is white and upper "P" if it is black.

2.3.3 Properties

Same as parent.

2.4 Class Rook : StartingPiece

This Class inherits the Class StartingPiece. It represents the rook piece of a regular chess game.

Rook
+ValidMove(x1, y1, x2, y2) : bool
+ToString() : string

2.4.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.4.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method checks if the move provided is valid considering the basic moves of a rook which are forward, backward or sideways to any empty cell. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "r" if the piece is white and upper "R" if it is black.

2.4.3 Properties

Same as parent.

2.5 Class King : StartingPiece

This Class inherits the Class StartingPiece. It represents the king piece of a regular chess game.

King
+ValidMove(x1, y1, x2, y2) : bool
+IsEssential() : bool
+ToString() : string

2.5.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.5.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method checks if the move provided is valid considering the basic moves of a king which are one square horizontally, vertically, or diagonally unless the square is already occupied by a friendly piece or the move would place the king in check. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
IsEssential	None	bool	Public

Description : Returns true if the piece is essential.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "k" if the piece is white and upper "K" if it is black.

2.5.3 Properties

Same as parent.

2.6 Class Knight : Piece

This Class inherits the Class Piece. It represents the knight piece of a regular chess game.

Knight
+ValidMove(x1, y1, x2, y2) : bool
+CanCollide() : bool
+ToString() : string

2.6.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.6.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method checks if the move provided is valid considering the basic moves of a knight which are "L-shape"—that is, they can move two squares in any direction vertically followed by one square horizontally, or two squares in any direction horizontally followed by one square vertically. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
CanCollide	None	bool	Public

Description : Returns true if the piece can collide.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "n" if the piece is white and upper "N" if it is black.

2.6.3 Properties

Same as parent.

2.7 Class Bishop : Piece

This Class inherits the Class Piece. It represents the bishop piece of a regular chess game.

Bishop
+ValidMove(x1, y1, x2, y2) : bool
+ToString() : string

2.7.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.7.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method checks if the move provided is valid considering the basic moves of a bishop which are any direction diagonally with no limit of cells unless there is another piece obstructing its path. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "b" if the piece is white and upper "B" if it is black.

2.7.3 Properties

Same as parent.

2.8 Class Queen : Piece

This Class inherits the Class Piece. It represents the queen piece of a regular chess game.

Queen
+ValidMove(x1, y1, x2, y2) : bool
+ToString() : string

2.8.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.8.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method checks if the move provided is valid considering the basic moves of a bishop which are any direction diagonally with no limit of cells unless there is another piece obstructing its path. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "q" if the piece is white and upper "Q" if it is black.

2.8.3 Properties

Same as parent.

2.9 Class Match

This Class represents the model of a chess match which compose the GameController. It will keep all changes that the game controller will return.

Match
-_board : Board
-_current : Colour
-_history : string[]
-_turnNumber : int
+ExportBoard() : string
+ExportHistory() : string[]
+ValidTurn(int origin, int target) : bool
+MakeTurn(int origin, int target) : void
+ValidSelection(int cell, bool firstClick) : bool
+HasPromotable(int target) : bool
+Check() : bool
+Checkmate() : bool
+Stalemate() : bool
+Castle(int origin, int target) : void
+GetAssailants(Colour) : List< int >

2.9.1 Fields

Field Name	Type	Visibility
_board	Board	Private

Description : This field represent the board of a match which compose the match. Its type is Board which is the next class to discuss.

Field Name	Type	Visibility
_current	Colour	Private

Description : This field tells us which piece colour is currently playing, white or black.

Field Name	Type	Visibility
_history	string[]	Private

Description : This field is a table that contains strings that represent previous board states to keep track of what has been played. For example, the first string would look like that :

"RNBKQBNRPPPPPPPP.....pppppppprnkqbnr".

Field Name	Type	Visibility
_turnNumber	int	Private

Description : This field tracks the number of turns that have been played.

2.9.2 Methods

Method Name	Parameters	Returned Type	Visibility
ExportBoard	none	string	Public

Description : The method returns the the board as a string of 64 char.

Method Name	Parameters	Returned Type	Visibility
ExportHistory	none	string[]	Public

Description : The method returns the table _history.

Method Name	Parameters	Returned Type	Visibility
ValidTurn	int origin, int target	bool	Public

Parameters : Parameter origin represents the cell where the piece is before the move and target is the targeted cell.

Description : The method returns true if the turn is valid.

Method Name	Parameters	Returned Type	Visibility
MakeTurn	int origin, int target	void	Public

Parameters : Parameter origin represents the cell where the piece is before the move and target is the targeted cell.

Description : The method makes all changes to the board in order to make the turn.

Method Name	Parameters	Returned Type	Visibility
ValidSelection	int cell, bool firstClick	bool	Public

Parameters : Parameter cell represents the cell where the player clicks and the parameter firstClick is a bool that returns true if its the first click.

Description : The method checks if the selection made in the board is valid.

Method Name	Parameters	Returned Type	Visibility
HasPromotable	int target	bool	Public

Parameters : The parameter target represents the targeted cell for a piece move. **Description :** This method returns true if the cell contains a promotable piece.

Method Name	Parameters	Returned Type	Visibility
Check	none	bool	Public

Description : This method returns true if the current turn makes a check.

Method Name	Parameters	Returned Type	Visibility
Checkmate	none	bool	Public

Description : This method returns true if the current turn makes a checkmate.

Method Name	Parameters	Returned Type	Visibility
Stalemate	none	bool	Public

Description : This method returns true if the current turn makes a Stalemate.

Method Name	Parameters	Returned Type	Visibility
Castle	int origin, int target	bool	Public

Description : This method returns true if the move will make a castle.

Method Name	Parameters	Returned Type	Visibility
GetAsaillants	Colour colour	List<int>	Public

Parameters : The parameter colour represents the piece colour specified. **Description :** This method returns a list of all possible asaillants by the index of their cell.

2.9.3 Properties

Property Name	Parameters	Returned Type	Visibility
Current	None	Colour	Public

Description : Gets or Sets the property _current of a match (Colour white or black).

2.10 Class Board

This Class represents the model of a chess board which compose the match. It will return all changes to the match.

Board
-_cells : Cell[]
+ToString() : string
+Collision(int origin, int target) : bool
+SameColour (int cell, Colour colour) : bool
+ValidMove(int origin, int target) : bool
+MoveCellTo(int origin, int target) : void
+GenerateBoard(string board) : void
+IsEssentialExposed(Colour colour) : bool
+HasPromotable(int target) : bool
+GetAssailants(Colour colour) : List<int>
-GetEssentialPiece(Colour colour) : int
-GetAttackingPieces(Colour colour, int target) : List<int>
-HasAttackersAroundEssential(Colour colour) : bool

2.10.1 Fields

Field Name	Type	Visibility
_cells	Cell[]	Private

Description : This field represent all 64 cells on a chess board. Each cell will contain a piece or be empty.

2.10.2 Methods

Method Name	Parameters	Returned Type	Visibility
Collision	int origin, int target	bool	Public

Parameters : Parameter origin represents the cell where the piece is before the move and target is the targeted cell.

Description : This method returns true if it detects a possible collision in the path to the targeted cell.

Method Name	Parameters	Returned Type	Visibility
SameColour	int cell, Colour colour	bool	Public

Parameters : Parameter cell represents the index of one of the 64 cells that is selected and colour is the colour of the selected cell.

Description : This method returns true the cell selected contains a piece at the same colour of the current turn.

Method Name	Parameters	Returned Type	Visibility
ValidMove	int origin, int target	bool	Public

Parameters : Parameter origin represents the index of the origin cell and the target parameter is the cell targeted.

Description : This method returns true if the move is valid.

Method Name	Parameters	Returned Type	Visibility
MoveCellTo	int origin, int target	bool	Public

Parameters : Parameter origin represents the index of the origin cell and the target parameter is the cell targeted.

Description : This method swaps cells origin and target.

Method Name	Parameters	Returned Type	Visibility
GenerateBoard	string board	void	Public

Parameters : Board parameter is a 64 char string that represent a board state(tells where the pieces are supposed to be).

Description : This method takes a string as board and transforms each of the 64 char as the content of each of the 64 cells.

Method Name	Parameters	Returned Type	Visibility
IsEssentialExposed	Colour colour	bool	Public

Parameters : The parameter colour represent the colour to test.

Description : Checks if the essential piece of the colour white or black is exposed.

Method Name	Parameters	Returned Type	Visibility
HasPromotable	int target	bool	Public

Parameters : The parameter target represent the targeted cell.

Description : Checks if the targeted cell has the promotable attribute.

Method Name	Parameters	Returned Type	Visibility
GetAsaillants	Colour colour	List<int>	Public

Parameters : The parameter colour represents the piece colour specified. **Description :** This method returns a list of all possible asaillants by the index of their cell.

Method Name	Parameters	Returned Type	Visibility
GetEssentialPiece	Colour colour	int	Public

Parameters : The parameter colour represents the piece colour specified. **Description :** This method returns the index of the cell that contains the essential piece.

Method Name	Parameters	Returned Type	Visibility
GetAttackingPieces	Colour colour, int target	List<int>	Public

Parameters : The parameter colour represents the piece colour specified and target is the targeted piece. **Description :** This method returns a list of all attacking pieces.

Method Name	Parameters	Returned Type	Visibility
HasAttackersAroundEssential	Colour colour	bool	Public

Parameters : The parameter colour represents the piece colour specified. **Description :** This method returns true if there's attackers around the essential piece.

2.11 Class Cell

This Class represents the model of a chess cell and its content.

Cell
-_piece : Nullable<Piece>
+IsEmpty() : bool
+HasCollision() : bool
+HasPromotable() : bool
+HasEssential() : bool
+ValidMove(int x1, int y1, int x2, int y2) : bool
+Colour() : Colour

2.11.1 Fields

Field Name	Type	Visibility
_piece	Nullable<Piece>	Private

Description : This field represents the content of a cell if it is a piece or null if it's empty.

2.11.2 Methods

Method Name	Parameters	Returned Type	Visibility
IsEmpty	none	bool	Public

Description : This method returns true if the _piece is null, so it's empty.

Method Name	Parameters	Returned Type	Visibility
HasCollision	none	bool	Public

Description : This method returns true if the cell contains a piece that can collide.

Method Name	Parameters	Returned Type	Visibility
HasPromotable	none	bool	Public

Description : This method returns true if the cell contains a promotable piece.

Method Name	Parameters	Returned Type	Visibility
HasEssential	none	bool	Public

Description : This method returns true if the cell contains a piece that is essential.

Method Name	Parameters	Returned Type	Visibility
ValidMove	int x1, int y1, int x2, int y2	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method returns true if the move is valid.

Method Name	Parameters	Returned Type	Visibility
Colour	none	Colour	Public

Description : This method returns the colour if the field _piece is not null.

2.12 Class Player

This Class represents a player in a chess game.

Player
-_name : string
-_points : int

2.12.1 Fields

Field Name	Type	Visibility
_name	string	Private

Description : This field is the name of the player.

Field Name	Type	Visibility
_points	int	Private

Description : This field is the points that the player collects during a game.

3 Controllers

3.1 Class Chess

Chess
-_listGames : List<GameController>
+main() : void
+NewGame() : void
+StartGame(Player[2] players) : void
+ManagePlayers() : void
+Exit() : void

3.1.1 Fields

Field Name	Type	Visibility
_listGames	List<GameController>	Private

Description : This field is a list of the active games.

3.1.2 Methods

Method Name	Parameters	Returned Type	Visibility
main	none	void	Public

Description : This is the entry point of the program.

Method Name	Parameters	Returned Type	Visibility
NewGame	none	void	Public

Description : This method creates a new game with its own GameController, Match, Board etc...

Method Name	Parameters	Returned Type	Visibility
StartGame	Player[2] players	void	Public

Description : This method starts the game with the players given.

Method Name	Parameters	Returned Type	Visibility
ManagePlayers	none	void	Public

Description : This method makes the link between FormMenu and FormLeaderboard.

Method Name	Parameters	Returned Type	Visibility
Exit	none	void	Public

Description : This is the exit point method.

3.2 Class GameController

GameController
-_main : Chess
-.selected : int
-.match : Match
-.playerA : Player
-.playerB : Player
-.tieCounter : int
-.view : FormMatch
-Rules(int origin, int target) : void
-Check() : bool
-Checkmate() : bool
-Castle() : bool
-Stalemate() : bool
-FiftyTurns() : bool
-SameBoard() : bool
-Turn(int origin, int target) : void
+Selection(int cell) : void
+Resign() : void

3.2.1 Fields

Field Name	Type	Visibility
_main	Chess	Private

Description : This field represent the chess which the game controller will talk to.

Field Name	Type	Visibility
_.selected	int	Private

Description : This field represent the selected cell.

Field Name	Type	Visibility
_.match	Match	Private

Description : This field represent the match of a game.

Field Name	Type	Visibility
_.playerA	Player	Private

Description : This field represent the first player in the game.

Field Name	Type	Visibility
_playerB	Player	Private

Description : This field represent the second player in the game.

Field Name	Type	Visibility
_tieCounter	int	Private

Description : This field counts the number of ties in the game.

Field Name	Type	Visibility
_view	FormMatch	Private

Description : This field represent the view to paint in a match.

3.2.2 Methods

Method Name	Parameters	Returned Type	Visibility
Rules	int origin, int target	void	Private

Parameters : Origin and target represent the index of the origin cell and the targeted cell for the path. **Description :** This method calls Check(), Checkmate(), Castle() and Stalemate() to check the state of the game if the move is valid.

Method Name	Parameters	Returned Type	Visibility
Check	none	bool	Public

Description : This method returns true if the match has a check.

Method Name	Parameters	Returned Type	Visibility
Checkmate	None	bool	Private

Description : This method returns true if the match has a checkmate.

Method Name	Parameters	Returned Type	Visibility
Castle	None	bool	Private

Description : This method returns true if the match has a Castle.

Method Name	Parameters	Returned Type	Visibility
Stalemate	None	bool	Private

Description : This method returns true if the match has a stalemate.

Method Name	Parameters	Returned Type	Visibility
FiftyTurns	None	bool	Private

Description : This method returns true if the match has 50 turns to count.

Method Name	Parameters	Returned Type	Visibility
SameBoard	None	bool	Private

Description : This method returns true if history list of boards has 3 same boards.

Method Name	Parameters	Returned Type	Visibility
Turn	int origin, int target	void	Private

Parameters : Origin and target represent the index of the origin cell and the targeted cell for the path. **Description :** Makes the turn, and send it to the view.

Method Name	Parameters	Returned Type	Visibility
Selection	int cell	void	Public

Parameters : Parameeter cell is the index of the cell to be selected. **Description :** Selects the cell.

Method Name	Parameters	Returned Type	Visibility
Resign	none	void	Public

Description : Make the end and exit the game.

3.3 Class PlayerController

PlayerController
-_main : Chess
-_list : List<Player>
+Add() : void
+Remove() : void

3.3.1 Fields

Field Name	Type	Visibility
_main	Chess	Private

Description : This field represent the chess which the game controller will talk to.

Field Name	Type	Visibility
_list	List<Player>	Private

Description : This field represent the list of all players.

3.3.2 Methods

Method Name	Parameters	Returned Type	Visibility
Add	none	void	Public

Description : This method adds the player to the list.

Method Name	Parameters	Returned Type	Visibility
Remove	none	void	Public

Description : This method removes the player to the list.

4 Views

4.1 Class FormSelection

FormSelection
-_controller : Chess
+OpenLeaderboard() : void
+Start() : Player[2]
+Cancel() : void

4.1.1 Fields

Field Name	Type	Visibility
_controller	Chess	Private

Description : This field is the controller of the selection menu, it helps to access the list of players.

4.1.2 Methods

Method Name	Parameters	Returned Type	Visibility
OpenLeaderboard	none	void	Public

Description : This method opens a form listing all the best players.

Method Name	Parameters	Returned Type	Visibility
Start	none	void	Public

Description : This method returns a table of 2 players and starts the game.

Method Name	Parameters	Returned Type	Visibility
Cancel	none	void	Public

Description : This method cancels the player selection.

4.2 Class FormMenu

FormMenu
-_main : Chess
+Start(object sender, System.EventArgs e) : void
+Exit(object sender, System.EventArgs e) : void
+ManagePlayers(object sender, System.EventArgs e) : void

4.2.1 Fields

Field Name	Type	Visibility
_main	Chess	Private

Description : This field makes the link between the menu and the chess game.

4.2.2 Methods

Method Name	Parameters	Returned Type	Visibility
Start	object sender, System.EventArgs e	void	Public

Description : Parameter sender is the button and e is the event listener.

Description : This method is for the start button. Starts the game.

Method Name	Parameters	Returned Type	Visibility
Exit	object sender, System.EventArgs e	void	Public

Description : Parameter sender is the button and e is the event listener.

Description : This method is for the exit button. Stops the game.

Method Name	Parameters	Returned Type	Visibility
ManagePlayers	object sender, System.EventArgs e	void	Public

Description : Parameter sender is the button and e is the event listener.

Description : This method is to manage players, add or remove.

4.3 Class FormPromotion

FormPromotion
-_controller : GameController
+Submit(object sender, System.EventArgs e) : void

4.3.1 Fields

Field Name	Type	Visibility
_controller	GameController	Private

Description : This field makes the link between the promotion form and the players.

4.3.2 Methods

Method Name	Parameters	Returned Type	Visibility
ManagePlayers	object sender, System.EventArgs e	void	Public

Description : Parameter sender is the button and e is the event listener.

Description : This method is to submit changes to players.

4.4 Class FormMatch

FormMatch
-_controller : GameController
+GridClick(object sender, System.EventArgs e) : void
+DrawBoard(string board) : void
+DrawSelection(int cell) : void
+ShowMessage(string message) : void
+VictoryMessage() : void

4.4.1 Fields

Field Name	Type	Visibility
_controller	GameController	Private

Description : This field makes the link between the match form and the chess game.

4.4.2 Methods

Method Name	Parameters	Returned Type	Visibility
GridClick	object sender, System.EventArgs e	void	Public

Description : Parameter sender is the button and e is the event listener.

Description : This method sends the coordinates of the cell clicked on the match board to the game controller.

Method Name	Parameters	Returned Type	Visibility
DrawBoard	string board	void	Public

Description : Parameter board is a string that represents a board as each char represents a cell.

Description : This method paints the board with all pieces at the right places.

Method Name	Parameters	Returned Type	Visibility
DrawSelection	int cell	void	Public

Description : Parameter cell is a index of a cell that represents the selected cell.

Description : This method paints the selected cell as selected.

Method Name	Parameters	Returned Type	Visibility
ShowMessage	string message	void	Public

Description : Parameter message is a string that represents a specific message depending on the situation.

Description : This method paints the message.

Method Name	Parameters	Returned Type	Visibility
VictoryMessage	none	void	Public

Description : Parameter message is a string that represents a specific message depending on the situation.

Description : This method paints the victory message.

4.5 Class FormLeaderboard

FormLeaderboard
-_controller : PlayerController
+ShowList(List<Player>) : void
+Add() : void
+Remove() : void
+Back() : void

4.5.1 Fields

Field Name	Type	Visibility
_controller	PlayerController	Private

Description : This field is the controller for the leader board.

4.5.2 Methods

Method Name	Parameters	Returned Type	Visibility
ShowList	List<Player>	void	Public

Description : Parameter List is a list of players.

Description : This method paints the list of all players.

Method Name	Parameters	Returned Type	Visibility
Add	none	void	Public

Description : Adds a player to list.

Method Name	Parameters	Returned Type	Visibility
Remove	none	void	Public

Description : Removes a player from list.

Method Name	Parameters	Returned Type	Visibility
Back	none	void	Public

Description : Gets back to main menu.