

Class Dictionary

Jean-Philippe Miguel-Gagnon, Jérémy Gaouette, Raphaël Rail

Thursday, 31th of march 2022



Presented to : Charles Jacob

Contents

1	Introduction	2
2	Models	3
2.1	Classe Piece	3
2.1.1	Fields	3
2.1.2	Methods	3
2.1.3	Properties	4
2.2	Class StartingPiece : Piece	4
2.2.1	Fields	4
2.2.2	Methods	4
2.2.3	Properties	5
2.3	Class Pawn : StartingPiece	5
2.3.1	Fields	5
2.3.2	Methods	5
2.3.3	Properties	6
2.4	Class Rook : StartingPiece	6
2.4.1	Fields	6
2.4.2	Methods	6
2.4.3	Properties	7
2.5	Class King : StartingPiece	7
2.5.1	Fields	7
2.5.2	Methods	7
2.5.3	Properties	8
2.6	Class Knight : Piece	8
2.6.1	Fields	8
2.6.2	Methods	8
2.6.3	Properties	9

1 Introduction

The goal of this document is to inform the programmer about classes used to create a C# OOP Chess game.

We'll go through this with the MVC model approach to make it clearer for the programmer where to implement his code.

2 Models

2.1 Classe Piece

This is an abstract class for a base piece for the game.

(Abstract) Piece
- _colour : Colour
+CanCollide() : bool
+ValidMove(int x1, int y1, int x2, int y2) : bool
+ToString()

2.1.1 Fields

Field Name	Type	Visibility
_colour	Colour	Private

Description : This field represent the colour a piece, wich can only be black or white as it is for a regular chess game.

2.1.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : The method returns true if the piece can move to the 2nd position.

Method Name	Parameters	Returned Type	Visibility
CanCollide	None	bool	Public

Description : Returns true if the piece can't go over other pieces, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : Empty method to be overridden by child classes.

2.1.3 Properties

Property Name	Parameters	Returned Type	Visibility
Colour	None	Colour	Public

Description : Returns the colour of a piece.

2.2 Class StartingPiece : Piece

Another abstract Class that inherits to the base Class Piece. This Class is for pieces that have different behaviour after they have moved for the first time.

(Abstract) StartingPiece
- _hasMoved : bool
+ValidMove(int x1, int y1, int x2, int y2) : bool
+ToString()

2.2.1 Fields

Field Name	Type	Visibility
_hasMoved	bool	Private

Description : This field is used to tell if the piece has already made its first move.

2.2.2 Methods

Same as Class Piece.

2.2.3 Properties

Property Name	Parameters	Returned Type	Visibility
HasMoved	None	bool	Public

Description : Gets or Sets the property `_hasMoved` of a piece to true or false.

2.3 Class Pawn : StartingPiece

This Class inherits the Class StartingPiece. It represents de pawn piece of a regular chess game.

Pawn
+ValidMove(x1, y1, x2, y2) : bool
+ToString() : string

2.3.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.3.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method is overridden to check specifically if the move provided is valid considering the basic moves of a pawn which are 1 or 2 cells ahead, or 1 diagonal cell if an opponent piece is present. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "p" if the piece is white and upper "P" if it is black.

2.3.3 Properties

Same as parent.

2.4 Class Rook : StartingPiece

This Class inherits the Class StartingPiece. It represents de rook piece of a regular chess game.

Rook
+ValidMove(x1, y1, x2, y2) : bool
+ToString() : string

2.4.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.4.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method is overridden to check specifically if the move provided is valid considering the basic moves of a rook which are forward, backward or sideways to any empty cell. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "r" if the piece is white and upper "R" if it is black.

2.4.3 Properties

Same as parent.

2.5 Class King : StartingPiece

This Class inherits the Class StartingPiece. It represents de rook piece of a regular chess game.

King
+ValidMove(x1, y1, x2, y2) : bool
+ToString() : string

2.5.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.5.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method is overridden to check specifically if the move provided is valid considering the basic moves of a king which are one square horizontally, vertically, or diagonally unless the square is already occupied

by a friendly piece or the move would place the king in check. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "k" if the piece is white and upper "K" if it is black.

2.5.3 Properties

Same as parent.

2.6 Class Knight : Piece

This Class inherits the Class Piece. It represents the knight piece of a regular chess game.

Knight
+ValidMove(x1, y1, x2, y2) : bool
+ToString() : string

2.6.1 Fields

Description : This Class doesn't provide a new field. It just inherits the fields of its parent.

2.6.2 Methods

Method Name	Parameters	Returned Type	Visibility
ValidMove	x1, y1, x2, y2 : int	bool	Public

Parameters : x1 and y1 represent the coordinates of the position before a possible move and x2 and y2 are the coordinates of the position after the move. These are all of Integer(16) type.

Description : This method is overridden to check specifically if the move provided is valid considering the basic moves of a king which are “L-shape”—that is, they can move two squares in any direction vertically followed by one square horizontally, or two squares in any direction horizontally followed by one square vertically. In those cases it returns true, otherwise it returns false.

Method Name	Parameters	Returned Type	Visibility
ToString	None	String	Public

Description : This method overrides ToString virtual method and returns minus "n" if the piece is white and upper "N" if it is black.

2.6.3 Properties

Same as parent.