


Content Security Policy (CSP) Quick Reference Guide






Content Security Policy Reference

The *new* Content-Security-Policy HTTP response header helps you reduce XSS risks on modern browsers by declaring what dynamic resources are allowed to load via a HTTP Header.

 Tweet (<https://twitter.com/intent/tweet?url=http%3A%2F%2Fcontent-security-policy.com%2F>)

 Edit on Github (<https://github.com/foundeo/content-security-policy.com/>)

Browser Support

Header					
Content-Security-Policy CSP Level 2	40+ Full January 2015	31+ <i>Partial</i> July 2014	10+	-	Edge 15 build 15002+
Content-Security-Policy CSP 1.0	25+	23+	7+	-	Edge 12 build 10240+
X-Content-Security-Policy Deprecated	-	4+	-	10+ <i>Limited</i>	12+ <i>Limited</i>

Header					
X-Webkit-CSP Deprecated	14+	-	6+	-	-

Sources: caniuse.com/contentsecuritypolicy (<http://caniuse.com/contentsecuritypolicy>),
caniuse.com/contentsecuritypolicy2 (<http://caniuse.com/contentsecuritypolicy2>) & Mozilla
(<https://hacks.mozilla.org/2013/05/content-security-policy-1-0-lands-in-firefox-aurora/>)





















Try our CSP Browser Test ([browser-test/](#)) to test your browser.



























Note: It is known that having both Content-Security-Policy and X-Content-Security-Policy or X-Webkit-CSP causes unexpected behaviours on certain versions of browsers. Please avoid using deprecated x-* headers.

Directive Reference

The Content-Security-Policy header value is made up of one or more directives (defined below), multiple directives are separated with a semicolon ;

This documentation is provided based on the Content Security Policy 1.0 W3C Candidate Recommendation (<http://www.w3.org/TR/2012/CR-CSP-20121115/>)

Directive	Example Value	Description
default-src	'self' cdn.example.com	<p>The default-src is the default policy for loading content such as JavaScript, Images, CSS, Fonts, AJAX requests, Frames, HTML5 Media. See the Source List Reference for possible values.</p> <div> CSP Level 1  25+  23+  7+  12+ </div>
script-src	'self' js.example.com	<p>Defines valid sources of JavaScript.</p> <div> CSP Level 1  25+  23+  7+  12+ </div>
style-src	'self' css.example.com	<p>Defines valid sources of stylesheets.</p> <div> CSP Level 1  25+  23+  7+  12+ </div>
img-src	'self' img.example.com	<p>Defines valid sources of images.</p> <div> CSP Level 1  25+  23+  7+  12+ </div>
connect-src	'self'	<p>Applies to XMLHttpRequest (AJAX), WebSocket or EventSource . If not allowed the browser emulates a 400 HTTP status code.</p> <div> CSP Level 1  25+  23+  7+  12+ </div>

Directive	Example Value	Description
font-src	font.example.com	<p>Defines valid sources of fonts.</p> <div> CSP Level 1  25+  23+  7+  12+ </div>
object-src	'self'	<p>Defines valid sources of plugins, eg <object>, <embed> or <applet>.</p> <div> CSP Level 1  25+  23+  7+  12+ </div>
media-src	media.example.com	<p>Defines valid sources of audio and video, eg HTML5 <audio>, <video> elements.</p> <div> CSP Level 1  25+  23+  7+  12+ </div>
frame-src	'self'	<p>Defines valid sources for loading frames. child-src is preferred over this deprecated directive.</p> <div> Deprecated </div>
sandbox	allow-forms allow-scripts	<p>Enables a sandbox for the requested resource similar to the iframe sandbox attribute. The sandbox applies a same origin policy, prevents popups, plugins and script execution is blocked. You can keep the sandbox value empty to keep all restrictions in place, or add values: allow-forms allow-same-origin allow-scripts allow-popups, allow-modals, allow-orientation-lock, allow-pointer-lock, allow-presentation, allow-popups-to-escape-sandbox, and allow-top-navigation</p> <div> CSP Level 1  25+  50+  7+  12+ </div>
report-uri	/some-report-uri	<p>Instructs the browser to POST reports of policy failures to this URI. You can also append -Report-Only to the HTTP header name to instruct the browser to only send reports (does not block anything).</p> <div> CSP Level 1  25+  23+  7+  12+ </div>
child-src	'self'	<p>Defines valid sources for web workers and nested browsing contexts loaded using elements such as <frame> and <iframe></p> <div> CSP Level 2  40+  45+  15+ </div>
form-action	'self'	<p>Defines valid sources that can be used as a HTML <form> action.</p> <div> CSP Level 2  40+  36+  15+ </div>

Directive	Example Value	Description
frame-ancestors	'none'	Defines valid sources for embedding the resource using <code><frame></code> <code><iframe></code> <code><object></code> <code><embed></code> <code><applet></code> . Setting this directive to 'none' should be roughly equivalent to X-Frame-Options: DENY <div> <div>CSP Level 2</div> <div>🔒 39+</div> <div>🔒 33+</div> <div>🔒 15+</div> </div>
plugin-types	application/pdf	Defines valid MIME types for plugins invoked via <code><object></code> and <code><embed></code> . To load an <code><applet></code> you must specify <code>application/x-java-applet</code> . <div> <div>CSP Level 2</div> <div>🔒 40+</div> <div>🔒 15+</div> </div>

Source List Reference

All of the directives that end with `-src` support similar values known as a source list. Multiple source list values can be space separated with the exception of 'none' which should be the only value..

Source Value	Example	Description
*	<code>img-src *</code>	Wildcard, allows any URL except <code>data: blob: filesystem: schemes</code> .
'none'	<code>object-src 'none'</code>	Prevents loading resources from any source.
'self'	<code>script-src 'self'</code>	Allows loading resources from the same origin (same scheme, host and port).
<code>data:</code>	<code>img-src 'self' data:</code>	Allows loading resources via the data scheme (eg Base64 encoded images).
<i>example.com</i>	<code>img-src example.com</code>	Allows loading resources from the specified domain name.
<i>*.example.com</i>	<code>img-src *.example.com</code>	Allows loading resources from any subdomain under <i>example.com</i> .
<i>https://cdn.com</i>	<code>img-src https://cdn.com</code>	Allows loading resources only over HTTPS matching the given domain.
<code>https:</code>	<code>img-src https:</code>	Allows loading resources only over HTTPS on any domain.
'unsafe-inline'	<code>script-src 'unsafe-inline'</code>	Allows use of inline source elements such as <code>style</code> attribute, <code>onclick</code> , or <code>script</code> tag bodies (depends on the context of the source it is applied to) and <code>javascript: URIs</code>
'unsafe-eval'	<code>script-src 'unsafe-eval'</code>	Allows unsafe dynamic code evaluation such as JavaScript <code>eval()</code>

Source Value	Example	Description
'nonce- '	script-src 'nonce-2726c7f26c'	Allows script or style tag to execute if the nonce attribute value matches the header value. For example: <script nonce="2726c7f26c">alert("hello");</script>
'sha256- '	script-src 'sha256-qzn...ng='	Allow a specific script or style to execute if it matches the hash. Doesn't work for javascript: URIs. For example: sha256-qznLcsR0x4GACP2dm0UCKCzCG+HiZ1guq6ZZDob/Tng= will allow alert('Hello, world.');

Content-Security-Policy Examples

Here a few common scenarios for content security policies:

Allow everything but only from the same origin

```
default-src 'self';
```

Only Allow Scripts from the same origin

```
script-src 'self';
```

Allow Google Analytics, Google AJAX CDN and Same Origin

```
script-src 'self' www.google-analytics.com ajax.googleapis.com;
```

Starter Policy

This policy allows images, scripts, AJAX, and CSS from the same origin, and does not allow any other resources to load (eg object, frame, media, etc). It is a good starting point for many sites.

```
default-src 'none'; script-src 'self'; connect-src 'self'; img-src 'self'; style-src 'self';
```

Content-Security-Policy Error Messages

In Chrome when a Content Security Policy Script Violation happens you get a message like this one in the *Chrome Developer Tools*:

```
Refused to load the script 'script-uri' because it violates the following Content Security Policy
```

In Firefox you might see messages like this in the *Web Developer Tools*:

```
Content Security Policy: A violation occurred for a report-only CSP policy ("An attempt to execute
```

In addition to a console message, a `securitypolicyviolation` event is fired on the window. See <https://www.w3.org/TR/CSP2/#firing-securitypolicyviolationevent-events> (<https://www.w3.org/TR/CSP2/#firing-securitypolicyviolationevent-events>).

Server Side Configuration

Any server side programming environment should allow you to send back a custom HTTP response header. You can also use your web server to send back the header.

Apache Content-Security-Policy Header

Add the following to your `httpd.conf` in your `VirtualHost` or in an `.htaccess` file:

```
Header set Content-Security-Policy "default-src 'self';"
```

Nginx Content-Security-Policy Header

In your `server {}` block add:

```
add_header Content-Security-Policy "default-src 'self';";
```

You can also append `always` to the end to ensure that nginx sends the header regardless of response code.

IIS Content-Security-Policy Header

You can use the HTTP Response Headers GUI in IIS Manager or add the following to your `web.config`:

```
<system.webServer>
  <httpProtocol>
    <customHeaders>
      <add name="Content-Security-Policy" value="default-src 'self';" />
    </customHeaders>
  </httpProtocol>
</system.webServer>
```

CSP Resources

Want more info on CSP, checkout these links:

- CSP 1.0 Spec (<http://www.w3.org/TR/CSP1/>)
- CSP Level 2 Spec (*W3C Candidate Recommendation, 21 July 2015*) (<http://www.w3.org/TR/CSP2/>)
- CSP Presentations / Slides ([presentations/](#))
- Mozilla Tutorial: Implementing Content Security Policy (<https://hacks.mozilla.org/2016/02/implementing-content-security-policy/>)
- Mozilla MDN Docs (https://developer.mozilla.org/en-US/docs/Web/Security/CSP/CSP_policy_directives)

© Foundeo Inc. (<https://foundeo.com/>) 2012-2016 - Contact Us (<https://foundeo.com/contact/>)