600



Q600 shown with TRU-Balance® Power Positioning System and Q-Logic drive controls

Available with 4-pole high-speed motors for a top speed of up to 6 mph



Specifications

DRIVE WHEELS	1 4" programatic or called / VI = 1 4" called
	14" pneumatic or solid / XL: 14" solid
OMNI-CASTERS	Front: 5" solid Rear: 6" solid
SUSPENSION	ATX Suspension (Active-Trac® with extra stability)
	(Active-flac with extra Stability)
MAXIMUM SPEED ¹	Up to 5 mph or 6 mph ² / XL: 4 mph
BRAKES	Intelligent braking
CROUND OF EADANGE 3	(electronic, regenerative disc brakes) 3"
GROUND CLEARANCE 3	
TURNING RADIUS 3	20"
OVERALL SIZE ³	Length: 36.5"/XL: 37.5" Width: 23"
SEATING	Synergy [®] Seat
	Adjustable Width: 10"-20" / XL: 10"-24"
	Adjustable Depth: 10"-20" / XL: 10"-24"
	TRU-Balance® Power Positioning System 4
	Adjustable Width: 14"-20" / XL: 14"-24"
	Adjustable Depth: 14"-20" / XL: 14"-24"
	High-back Seat (22" x 20" max. dim.) /
	XL: (24" x 24" max. dim.)
DRIVE TRAIN	2-motor (GLIDE), Mid-Wheel 6®
BATTERIES	Two 12 volt, deep cycle NF-22
RANGE PER CHARGE 1	Up to 20 miles / XL: Up to 15 miles
BATTERY CHARGER	5A, off-board (standard)
AVAILABLE	75A, NE
ELECTRONICS	75A, NE+
	80A, Q-Logic EX ⁵
WEIGHT CAPACITY	300 lbs. maximum (user weight) / XL: 400 lbs.
BASE WEIGHT	129 lbs.
BATTERY WEIGHT 7	38 lbs. (each)
WARRANTY	Lifetime limited warranty on frame;
	2-year warranty on electronics;
	18-month warranty on drive motor

Shroud Colors

METALLIC COLORS



SOLID COLORS





(US) 866-800-2002 (Canada) 888-570-1113 www.guantumrehab.com

Features

- Mid-Wheel 6® allows six wheels on the ground for maximum stability
- Compatible with TRU-Balance® Power Positioning
- Patent pending OMNI-Casters (nylon, spherical-shaped casters) on front and rear prevent wheel hang-ups
- Side-mounted, easily accessible freewheel levers
- Patent pending ATX Suspension (Active-Trac® with extra stability) incorporates front OMNI-Casters for enhanced performance over more varied terrain
- Easy front access to batteries
- Powerful GLIDE motors for added power and torque
- Offers smallest turning radius in its class at 20"

Options

- Solid tires (standard on XL version)
- Swing-away joystick
- Multi-axis joystick mount
- Elevating leg rests
- Oxygen tank holder
- Neoprene leg rest sleeves
- Gel adductor buttons
- Angle-adjustable footplates
- 70° drop-in footrests
- Q-Logic Drive Control System
- 4-pole high-speed motors ⁶
- Available with TRU-Balance® positioning systems

FOOTNOTES:

- Range and speed vary with user weight, terrain type, battery charge, battery condition and tire pressure.
- 2) 6 mph with 4-pole high speed motor package.
- Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3 %.
- 4) TRU-Balance® Power Recline not compatible with XL model. Tilt requires TB1 Tilt System.
- 5) 100 amp Q-Logic controller required with high-speed motors.
- 6) Not available on Q600XL
- 7) Battery weight may vary based on manufacturer