Liquid-Tite Connectors

Steel Electric Products

Straight





Catal	og Number	Size
Insulated	Insulated with Ground	Size
SLT47T	SLT47ALT	3/8"
SLT27T	SLT27ALT	1/2"
SLT28T	SLT28ALT	3/4"
SLT29T	SLT29ALT	1"
SLT30T	SLT30ALT	1-1/4"
SLT31T	SLT31ALT	1-1/2"
SLT32T	SLT32ALT	2"
SLT33T	SLT33ALT	2-1/2"
SLT34T	SLT34ALT	3″
SLT60T	SLT60ALT	3-1/2"
SLT61T	SLT61ALT	4"
SLT62T	SLT62ALT	5″
SLT63T	SLT63ALT	6"

45 Degree





To begine				
	Catalog Number		Size	
	Insulated	Insulated with Ground	Size	
	SLT25-45T	SLT25-45ALT	3/8″	
	SLT35-45T	SLT35-45ALT	1/2"	
	SLT36-45T	SLT36-45ALT	3/4"	
	SLT37-45T	SLT37-45ALT	1"	
	SLT38-45T	SLT38-45ALT	1-1/4"	
	SLT39-45T	SLT39-45ALT	1-1/2"	
	SLT40-45T	SLT40-45ALT	2"	
	SLT65-45T	SLT65-45ALT	2-1/2"	
	SLT66-45T	SLT66-45ALT	3"	
	SLT67-45T	SLT67-45ALT	3-1/2"	
	SLT68-45T	SLT68-45ALT	4"	

90 Degree





Ca	Catalog Number	
Insulated	Insulated with Ground	Size
SLT25T	SLT25ALT	3/8"
SLT35T	SLT35ALT	1/2"
SLT36T	SLT36ALT	3/4"
SLT37T	SLT37ALT	1"
SLT38T	SLT38ALT	1-1/4"
SLT39T	SLT39ALT	1-1/2"
SLT40T	SLT40ALT	2"
SLT65T	SLT65ALT	2-1/2"
SLT66T	SLT66ALT	3″
SLT67T	SLT67ALT	3-1/2"
SLT68T	SLT68ALT	4"

- Tapered Threaded Male Hub (NPT)
- Compact, Slim Diameter with Small Turning Radius
- Furnished with Steel Locknut and Sealing Ring
- Long Ferrule Prevents Pullout and Tight Bend "pop-out"
- Liquidtight Raintight Oiltight

- Malleable Iron/Zinc Plated
- Steel Ferrule/Zinc Plated
- Aluminum Grounding Lug

