

Flexible Conduit

Liquid-tite Flexible Conduit

Catalog Number	Size	Standard Length
CSALT-3/8	3/8"	30 / 150 Meters
CSALT-1/2	1/2"	30 / 150 / 300 Meters
CSALT-3/4	3/4"	30 / 150 / 300 Meters
CSALT-1	1"	30 / 150 Meters
CSALT-1-1/4	1-1/4"	15 / 75 Meters
CSALT-1-1/2	1-1/2"	15 / 61 Meters
CSALT-2	2"	15 Meters
CSALT-2-1/2	2-1/2"	8 Meters **
CSALT-3	3"	8 Meters **
CSALT-4	4"	8 Meters **

**Cut Lengths Available



Aluminum Flexible Conduit

Catalog Number	Size	Standard Length
ALFCSA-3/8	3/8"	30 / 75 / 300 Meters
ALFCSA-7/16	7/16"	75 Meters
ALFCSA-1/2	1/2"	30 / 150 / 300 Meters
ALFCSA-3/4	3/4"	30 / 150 / 300 Meters
ALFCSA-1	1"	15 / 30 / 150 / meters
ALFCSA-1-1/4	1-1/4"	15 / 30 / 150 Meters
ALFCSA-1-1/2	1-1/2"	8 / 15 / 91.5 Meters
ALFCSA-2	2"	8 / 15 Meters
ALFCSA-2-1/2	2-1/2"	16 Meters **
ALFCSA-3	3"	16 Meters **
ALFCSA-4	4"	16 Meters **

**Cut Lengths Available



Flexible Conduit Connectors

Catalog Number				Size
Straight		90 Degree		
Zinc Die Cast	Malleable Iron	Zinc Die Cast	Malleable Iron	
C25Z				3/8"
C27Z		C35Z		1/2"
C28Z		C36Z		3/4"
C29Z		C37Z		1"
C30Z		C38Z		1-1/4"
C31Z		C39Z		1-1/2"
C32Z		C40Z		2"
	C33		C65	2-1/2"
	C34		C66	3"
	C61		C68	4"



Liquid-Tite Connectors

Steel Electric Products

Straight



Catalog Number		Size
Insulated	Insulated with Ground	
SLT47T	SLT47ALT	3/8"
SLT27T	SLT27ALT	1/2"
SLT28T	SLT28ALT	3/4"
SLT29T	SLT29ALT	1"
SLT30T	SLT30ALT	1-1/4"
SLT31T	SLT31ALT	1-1/2"
SLT32T	SLT32ALT	2"
SLT33T	SLT33ALT	2-1/2"
SLT34T	SLT34ALT	3"
SLT60T	SLT60ALT	3-1/2"
SLT61T	SLT61ALT	4"
SLT62T	SLT62ALT	5"
SLT63T	SLT63ALT	6"

45 Degree



Catalog Number		Size
Insulated	Insulated with Ground	
SLT25-45T	SLT25-45ALT	3/8"
SLT35-45T	SLT35-45ALT	1/2"
SLT36-45T	SLT36-45ALT	3/4"
SLT37-45T	SLT37-45ALT	1"
SLT38-45T	SLT38-45ALT	1-1/4"
SLT39-45T	SLT39-45ALT	1-1/2"
SLT40-45T	SLT40-45ALT	2"
SLT65-45T	SLT65-45ALT	2-1/2"
SLT66-45T	SLT66-45ALT	3"
SLT67-45T	SLT67-45ALT	3-1/2"
SLT68-45T	SLT68-45ALT	4"

90 Degree



Catalog Number		Size
Insulated	Insulated with Ground	
SLT25T	SLT25ALT	3/8"
SLT35T	SLT35ALT	1/2"
SLT36T	SLT36ALT	3/4"
SLT37T	SLT37ALT	1"
SLT38T	SLT38ALT	1-1/4"
SLT39T	SLT39ALT	1-1/2"
SLT40T	SLT40ALT	2"
SLT65T	SLT65ALT	2-1/2"
SLT66T	SLT66ALT	3"
SLT67T	SLT67ALT	3-1/2"
SLT68T	SLT68ALT	4"

- Tapered Threaded Male Hub (NPT)
- Compact, Slim Diameter with Small Turning Radius
- Furnished with Steel Locknut and Sealing Ring
- Long Ferrule Prevents Pullout and Tight Bend "pop-out"
- Liquidtight • Raintight • Oiltight

- Malleable Iron/Zinc Plated
- Steel Ferrule/Zinc Plated
- Aluminum Grounding Lug

