

Explosion Proof

SparkSafe

Explosion Proof Reducing Bushings



Catalog Number		Size
Steel	Aluminum	
RB75-50S	RB75-50A	3/4" x 1/2"
RB100-50S	RB100-50A	1" x 1/2"
RB100-75S	RB100-75A	1" x 3/4"
RB125-50S	RB125-50A	1-1/4" x 1/2"
RB125-75S	RB125-75A	1-1/4" x 3/4"
RB125-100S	RB125-100A	1-1/4" x 1"
RB150-50S	RB150-50A	1-1/2" x 1/2"
RB150-75S	RB150-75A	1-1/2" x 3/4"
RB150-100S	RB150-100A	1-1/2" x 1"
RB150-125S	RB150-125A	1-1/2" x 1-1/4"
RB200-50S	RB200-50A	2" x 1/2"
RB200-75S	RB200-75A	2" x 3/4"
RB200-100S	RB200-100A	2" x 1"
RB200-125S	RB200-125A	2" x 1-1/4"
RB200-150S	RB200-150A	2" x 1-1/2"

- Class I, Division 1 & 2, Groups A, B, C & D
- Class I, Zone 1 & 2, Groups IIC, IIB & IIA
- Class II, Division 1 & 2, Groups E, F & G
- Class III, Division 1 & 2



Explosion Proof Conduit Unions



Catalog Number		Size
Steel	Aluminum	
Male		
UM50S	UM50A	1/2"
UM75S	UM75A	3/4"
UM100S	UM100A	1"
Female		
UF50S	UF50A	1/2"
UF75S	UF75A	3/4"
UF100S	UF100A	1"

- Class I, Division 1 & 2, Groups A, B, C & D
- Class I, Zone 1 & 2, Groups IIC, IIB & IIA
- Class II, Division 1 & 2, Groups E, F & G
- Class III, Division 1 & 2



Explosion Proof

Flexible Couplings

Catalog Number	Size	Length	Catalog Number	Size	Length
EXFC-14	1/2"	4"	EXFC-310	1"	10"
EXFC-16	1/2"	6"	EXFC-312	1"	12"
EXFC-18	1/2"	8"	EXFC-315	1"	15"
EXFC-110	1/2"	10"	EXFC-318	1"	18"
EXFC-112	1/2"	12"	EXFC-321	1"	21"
EXFC-115	1/2"	15"	EXFC-324	1"	24"
EXFC-118	1/2"	18"	EXFC-327	1"	27"
EXFC-121	1/2"	21"	EXFC-330	1"	30"
EXFC-124	1/2"	24"	EXFC-333	1"	33"
EXFC-127	1/2"	27"	EXFC-336	1"	36"
EXFC-130	1/2"	30"			
EXFC-133	1/2"	33"	EXFC-412	1-1/4"	12"
EXFC-136	1/2"	36"	EXFC-415	1-1/4"	15"
			EXFC-418	1-1/4"	18"
EXFC-24	3/4"	4"	EXFC-421	1-1/4"	21"
EXFC-26	3/4"	6"	EXFC-424	1-1/4"	24"
EXFC-28	3/4"	8"	EXFC-427	1-1/4"	27"
EXFC-210	3/4"	10"	EXFC-430	1-1/4"	30"
EXFC-212	3/4"	12"	EXFC-433	1-1/4"	33"
EXFC-215	3/4"	15"	EXFC-436	1-1/4"	36"
EXFC-218	3/4"	18"			
EXFC-221	3/4"	21"	EXFC-512	1-1/2"	12"
EXFC-224	3/4"	24"	EXFC-515	1-1/2"	15"
EXFC-227	3/4"	27"	EXFC-518	1-1/2"	18"
EXFC-230	3/4"	30"	EXFC-521	1-1/2"	21"
EXFC-233	3/4"	33"	EXFC-524	1-1/2"	24"
EXFC-236	3/4"	36"	EXFC-527	1-1/2"	27"
			EXFC-530	1-1/2"	30"
EXFC-36	1"	6"	EXFC-533	1-1/2"	33"
EXFC-38	1"	8"	EXFC-536	1-1/2"	36"



- Larger Sizes May Be Available, please call

EXFC couplings are for use in hazardous atmospheres where a flexible connection is required for motor and equipment installation where movement and vibration are present. Also for difficult bends and connections.

- Class I, Groups A,B,C,D;
- Class II, Groups E,F,G;
- Nema 7 & 9
- Brass and Bronze End Fittings
- Bronze Wire Flexible Braid over Flexible Bronze Core with Insulating Liner

