

Retractable Cords

Autac

Retractable Cords

Catalog Number	Retracted Length (inches)	Number of Conductors	U.L. Type	Maximum Voltage	Conductor Amp Rating
----------------	---------------------------	----------------------	-----------	-----------------	----------------------

18 AWG

710182	12,24,36,48	10	SEOW/STOW	600	7
72180	12,24,36,48	2	SVEO/STEO	300	7
72181	12,24,36,48	2	SJEOOW/SJTOOW	300	7
73181	12,24,36,48	3	SJEOW/SJTOW	300	7
74181	12,24,36,48	4	SJEOW/SJTOW	300	7
75181	12,24,36,48	5	SJEOW/SJTOW	300	7
77182	12,24,36,48	7	SEOW/STOW	600	7

16 AWG

73161	12,24,36,48	3	SJEOW/SJTOW	300	10
74161	12,24,36,48	4	SJEOW/SJTOW	300	10
74162	12,24,36,48	4	SEOW/STOW	600	10
76162	12,24,36,48	6	SEOW/STOW	600	10
78162	12,24,36,48	8	SEOW/STOW	600	10

14 AWG

73142	12,24,36,48	3	SEOW/STOW	600	12
74172	12,24,36,48	4	SEOW/STOW	600	12

12 AWG

73122	12,24,36,48	3	SEOW/STOW	600	20
74122	12,24,36,48	4	SEOW/STOW	600	20

- Soft Bare Copper, TPE Insulated
- TPR – Black Jacket



Length Chart:

- 12" Retracted Extends to Maximum 5'
- 24" Retracted Extends to Maximum 10'
- 36" Retracted Extends to Maximum 15'
- 48" Retracted Extends to Maximum 20'



Other cords may be available, Please call for availability.