Sealtite Connectors

Malleable Iron - Insulated Throat

Straight		
SLT47T	3/8"	25
SLT27T	1/2"	25
SLT28T	3/4"	10
SLT29T	1"	5
SLT30T	1-1/4"	5
SLT31T	1-1/2"	10
SLT32T	2"	5
SLT33T	2-1/2"	1
SLT34T	3"	1
SLT60T	3-1/2"	1
SLT61T	4"	1
SLT62T	5"	1
SLT63T	6"	1



90 Degree	45 Degree		
SLT25T	SLT25-45T	3/8"	10
SLT35T	SLT35-45T	1/2"	10
SLT36T	SLT36-45T	3/4"	10
SLT37T	SLT37-45T	1"	5
SLT38T	SLT38-45T	1-1/4"	10
SLT39T	SLT39-45T	1-1/2"	10
SLT40T	SLT40-45T	2"	5
SLT65T	SLT65-45T	2-1/2"	1
SLT66T	SLT66-45T	3"	1
SLT67T	SLT67-45T	3-1/2"	1
SLT68T	SLT68-45T	4"	1



Malleable Iron - Insulated Throat - with Aluminum Grounding Lug

	ra		

Ground Lug Capacity

SLT47ALT	#4 - #14	3/8"	
SLT27ALT	#4 - #14	1/2"	
SLT28ALT	#4 - #14	3/4"	
SLT29ALT	#4 - #14	1"	
SLT30ALT	#4 - #14	1-1/4"	
SLT31ALT	#4 - #14	1-1/2"	
SLT32ALT	#4 - #14	2"	
SLT33ALT	1/0 - #8	2-1/2"	
SLT34ALT	1/0 - #8	3"	
SLT60ALT	3/0 - #6	3-1/2"	
SLT61ALT	3/0 - #6	4"	
SLT62ALT	#6 - 250mcm	5"	
SLT63ALT	#6 - 250mcm	6"	



25 25

90 Degree	45 Degree

Ground Lug Capacity

SLT25ALT	SLT25-45ALT	#4 - #14	3/8"	10
SLT35ALT	SLT35-45ALT	#4 - #14	1/2"	10
SLT36ALT	SLT36-45ALT	#4 - #14	3/4"	10
SLT37ALT	SLT37-45ALT	#4 - #14	1"	5
SLT38ALT	SLT38-45ALT	#4 - #14	1-1/4"	10
SLT39ALT	SLT39-45ALT	#4 - #14	1-1/2"	10
SLT40ALT	SLT40-45ALT	#4 - #14	2"	5
SLT65ALT	SLT65-45ALT	1/0 - #8	2-1/2"	1
SLT66ALT	SLT66-45ALT	1/0 - #8	3"	1
SLT67ALT	SLT67-45ALT	3/0 - #6	3-1/2"	1
SLT68ALT	SLT68-45ALT	3/0 - #6	4"	1



Available with Copper Grounging Lugs

Sealtite Connectors

Malleable Iron - Insulated Throat - Mechanical Galvanized

1/2"	25
3/4"	10
1"	5
1-1/4"	5
1-1/2"	10
2"	5
2-1/2"	1
3"	1
3-1/2"	1
4"	1
5"	1
6"	1
	3/4" 1" 1-1/4" 1-1/2" 2" 2-1/2" 3" 3-1/2" 4" 5"



^{*} Hot Dipped Galvanized

90 Degree	45 Degree		
SLT35TMG	SLT35-45TMG	1/2"	10
SLT36TMG	SLT36-45TMG	3/4"	10
SLT37TMG	SLT37-45TMG	1"	5
SLT38TMG	SLT38-45TMG	1-1/4"	1
SLT39TMG	SLT39-45TMG	1-1/2"	1
SLT40TMG	SLT40-45TMG	2"	1
SLT65TG*	SLT65-45TG*	2-1/2"	1
SLT66TG*	SLT66-45TG*	3"	1
SLT67TG*	SLT67-45TG*	3-1/2"	1
SLT68TG*	SLT68-45TG*	4"	1



Malleable Iron - Insulated Throat - Mechanical Galvanized with Copper Grounding Lug

Straight

Ground Lug Capacity

SLT27CLTMG	#4 - #14	1/2"	2
SLT28CLTMG	#4 - #14	3/4"	1
SLT29CLTMG	#4 - #14	1"	
SLT30CLTMG	#4 - #14	1-1/4"	
SLT31CLTMG	#4 - #14	1-1/2"	1
SLT32CLTMG	#4 - #14	2"	
SLT33CLTMG	1/0 - #8	2-1/2"	
SLT34CLTMG	1/0 - #8	3"	
SLT60CLTMG	3/0 - #6	3-1/2"	
SLT61CLTMG	3/0 - #6	4"	
SLT62CLTG*	#6 - 250mcm	5"	
SLT63CLTG*	#6 - 250mcm	6"	



^{*} Hot Dipped Galvanized

ob begies 40 begies	90	Degree	45 Degree
---------------------	----	--------	-----------

Ground Lug Capacity

SLT35CLTMG	SLT35-45CLTMG	#4 - #14	1/2"	
SLT36CLTMG	SLT36-45CLTMG	#4 - #14	3/4"	
SLT37CLTMG	SLT37-45CLTMG	#4 - #14	1"	
SLT38CLTMG	SLT38-45CLTMG	#4 - #14	1-1/4"	
SLT39CLTMG	SLT39-45CLTMG	#4 - #14	1-1/2"	
SLT40CLTMG	SLT40-45CLTMG	#4 - #14	2"	
SLT65CLTG*	SLT65-45CLTG*	1/0 - #8	2-1/2"	
SLT66CLTG*	SLT66-45CLTG*	1/0 - #8	3"	
SLT67CLTG*	SLT67-45CLTG*	3/0 - #6	3-1/2"	
SLT68CLTG*	SLT68-45CLTG*	3/0 - #6	4"	



Available with Aluminum Grounging Lugs

^{*} Hot Dipped Galvanized

^{*} Hot Dipped Galvanized

Sealtite Connectors

Zinc Die Cast - Non Insulated

Straight		
LT47	3/8"	25
LT27	1/2"	25
LT28	3/4"	10
LT29	1"	5
LT30	1-1/4"	5
LT31	1-1/2"	1
LT32	2"	1
LT33	2-1/2"	1
LT34	3"	1
LT60	3-1/2"	1
LT61	4"	1



	_			
C O Y A Y	B V	VA	170	
90	mY:	10	III. = 3	

LT25	3/8"	10
LT35	1/2"	10
LT36	3/4"	10
LT37	1"	5
LT38	1-1/4"	1
LT39	1-1/2"	1
LT40	2"	1
LT65	2-1/2"	1
LT66	3"	1
LT67	3-1/2"	1
LT68	4"	1

