

DevPulse REST API — Hoppscotch Testing Guide

Complete Endpoint Reference with Request URLs, HTTP Methods, JSON Payloads, and Expected Responses

Backend Base URL: http://localhost:5000	Swagger API Docs: http://localhost:5000/docs
Default User: user@devpulse.io / User@SecurePass2026	Admin User: admin@devpulse.io / Admin@SecurePass2026

 **Quick Hoppscotch Setup Steps:**

1. Authenticate: POST /auth/login to receive your JWT accessToken.

3. Content-Type: Set Header Content-Type: application/json and paste JSON body.

2. Set Bearer Token: In Hoppscotch Authorization tab → select **Bearer Token** → paste token.

4. Response Envelope: All standard responses wrap payload in { "success": true, "data": { ... } }.

0. Pre-Requisite: User Authentication

POST /auth/login

Public

Authenticate and receive the signed JWT Bearer token required for all Day 11 reaction endpoints.

Headers: Content-Type: application/json

REQUEST BODY (JSON)

```
{
  "email": "admin@devpulse.io",
  "password": "Admin@SecurePass2026"
}
```

EXPECTED RESPONSE (200 OK)

```
{
  "success": true,
  "data": {
    "accessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
    "user": {
      "id": "6790b8f4...",
      "name": "DevPulse Administrator",
      "email": "admin@devpulse.io",
      "role": "admin"
    }
  }
}
```

1. Post Reaction Engine Lifecycle (POST /reactions)

POST /reactions

Bearer Token Required

Scenario A: Like a Post — Creates a like reaction on an active post and atomically increments post.reactionCounts.like.

Headers: Authorization: Bearer <accessToken>, Content-Type: application/json

REQUEST BODY (JSON)

```
{
  "targetType": "post",
  "targetId": "66e138fc29094e137127e4e0",
  "type": "like"
}
```

EXPECTED RESPONSE (200 OK)

```
{
  "success": true,
  "data": {
    "action": "created",
    "targetType": "post",
    "targetId": "66e138fc29094e137127e4e0",
    "type": "like",
    "reactionCounts": {
      "like": 1,
      "dislike": 0
    }
  }
}
```

POST /reactions

Bearer Token Required

Scenario B: Switch Reaction (Like → Dislike) — Automatically switches active reaction, decrementing like and incrementing dislike atomically.

Headers: Authorization: Bearer <accessToken>, Content-Type: application/json

REQUEST BODY (JSON)

```
{
  "targetType": "post",
  "targetId": "66e138fc29094e137127e4e0",
  "type": "dislike"
}
```

EXPECTED RESPONSE (200 OK)

```
{
  "success": true,
  "data": {
    "action": "switched",
    "targetType": "post",
    "targetId": "66e138fc29094e137127e4e0",
    "type": "dislike",
    "reactionCounts": {
      "like": 0,
      "dislike": 1
    }
  }
}
```

POST

/reactions

Bearer Token Required

Scenario C: Remove Reaction (Toggle Off) — Submitting the active reaction type again removes it, returning to neutral and decrementing the counter.

Headers: Authorization: Bearer <accessToken>, Content-Type: application/json

REQUEST BODY (JSON)

```
{
  "targetType": "post",
  "targetId": "66e138fc29094e137127e4e0",
  "type": "dislike"
}
```

EXPECTED RESPONSE (200 OK)

```
{
  "success": true,
  "data": {
    "action": "removed",
    "targetType": "post",
    "targetId": "66e138fc29094e137127e4e0",
    "type": null,
    "reactionCounts": {
      "like": 0,
      "dislike": 0
    }
  }
}
```

2. Comment & Nested Reply Reactions (POST /reactions)

POST

/reactions

Bearer Token Required

Scenario D: Like a Top-Level Comment — Targets a comment document (targetType: "comment") and atomically increments comment.reactionCounts.like .

Headers: Authorization: Bearer <accessToken>, Content-Type: application/json

REQUEST BODY (JSON)

```
{
  "targetType": "comment",
  "targetId": "66e138fc29094e137127e4e2",
  "type": "like"
}
```

EXPECTED RESPONSE (200 OK)

```
{
  "success": true,
  "data": {
    "action": "created",
    "targetType": "comment",
    "targetId": "66e138fc29094e137127e4e2",
    "type": "like",
    "reactionCounts": {
      "like": 1,
      "dislike": 0
    }
  }
}
```

POST

/reactions

Bearer Token Required

Scenario E: Dislike a Nested Reply — Targets a nested reply comment and atomically increments reply.reactionCounts.dislike .

Headers: Authorization: Bearer <accessToken>, Content-Type: application/json

REQUEST BODY (JSON)

```
{
  "targetType": "comment",
  "targetId": "66e138fc29094e137127e4e3",
  "type": "dislike"
}
```

EXPECTED RESPONSE (200 OK)

```
{
  "success": true,
  "data": {
    "action": "created",
    "targetType": "comment",
    "targetId": "66e138fc29094e137127e4e3",
    "type": "dislike",
    "reactionCounts": {
      "like": 0,
      "dislike": 1
    }
  }
}
```

3. Active User Reactions Hydration (GET /reactions/mine)

GET

/reactions/mine

Bearer Token Required

Scenario F: Fetch All Active User Reactions — Returns a dictionary mapping every reacted targetId to user reaction type ("like" | "dislike").

Headers: Authorization: Bearer <accessToken>

REQUEST PAYLOAD

None (No request body required)

EXPECTED RESPONSE (200 OK)

```
{
  "success": true,
  "data": {
    "66e138fc29094e137127e4e0": "like",
    "66e138fc29094e137127e4e2": "like",
    "66e138fc29094e137127e4e3": "dislike"
  }
}
```

GET

/reactions/mine?targetIds={id1},{id2}

Bearer Token Required

Scenario G: Batch-Filter Reactions by Specific Targets — Efficiently filters reactions for visible posts or comments currently rendered on screen.

URL Example: /reactions/mine?targetIds=66e138fc29094e137127e4e0,66e138fc29094e137127e4e2

REQUEST PAYLOAD

None (Query parameter passed in request URL)

EXPECTED RESPONSE (200 OK)

```
{
  "success": true,
  "data": {
    "66e138fc29094e137127e4e0": "like",
    "66e138fc29094e137127e4e2": "like"
  }
}
```

4. Error Validation & Edge Scenarios

POST /reactions

404 Not Found

Scenario H: Target Not Found — Attempting to react to a non-existent or deleted target returns a standard 404 envelope.

Headers: Authorization: Bearer <accessToken>, Content-Type: application/json

REQUEST BODY (JSON)

```
{
  "targetType": "post",
  "targetId": "66e138fc29094e137127e999",
  "type": "like"
}
```

EXPECTED RESPONSE

(404 NOT FOUND)

```
{
  "success": false,
  "statusCode": 404,
  "message": "Post with ID '66e138fc29094e137127e999' not found",
  "errors": []
}
```

POST /reactions

400 Bad Request

Scenario I: Validation Error — Invalid targetType or reaction type rejected by NestJS class-validator ValidationPipe.

Headers: Authorization: Bearer <accessToken>, Content-Type: application/json

REQUEST BODY (JSON)

```
{
  "targetType": "invalid_type",
  "targetId": "66e138fc29094e137127e4e0",
  "type": "heart"
}
```

EXPECTED RESPONSE

(400 BAD REQUEST)

```
{
  "success": false,
  "statusCode": 400,
  "message": "Validation failed",
  "errors": [
    "targetType must be one of the following values: post, comment",
    "type must be one of the following values: like, dislike"
  ]
}
```

POST /reactions

401 Unauthorized

Scenario J: Unauthorized Access — Missing or expired Bearer token in request headers rejected by JwtAuthGuard.

Headers: No Authorization header supplied

REQUEST BODY (JSON)

```
{
  "targetType": "post",
  "targetId": "66e138fc29094e137127e4e0",
  "type": "like"
}
```

EXPECTED RESPONSE

(401 UNAUTHORIZED)

```
{
  "success": false,
  "statusCode": 401,
  "message": "Unauthorized",
  "errors": []
}
```

5. Day 11 API Endpoint Matrix Summary

METHOD	URL ENDPOINT	AUTH	KEY PAYLOAD / PARAM	ACTION / PURPOSE
POST	/reactions	Bearer	{ targetType: "post", targetId, type: "like" }	Create like reaction on post (action: "created")
POST	/reactions	Bearer	{ targetType: "post", targetId, type: "dislike" }	Switch from like to dislike on post (action: "switched")
POST	/reactions	Bearer	{ targetType: "post", targetId, type: "dislike" }	Toggle off reaction back to neutral (action: "removed")
POST	/reactions	Bearer	{ targetType: "comment", targetId, type: "like" }	Create like reaction on comment/reply (action: "created")
GET	/reactions/mine	Bearer	None	Get all active reactions for authenticated user
GET	/reactions/mine?targetIds={id1},{id2}	Bearer	targetIds query parameter	Batch-filter active reactions for displayed targets