

TaxNexus — CI/CD, Health, Backups & Restore

Tagged release pipeline · health endpoint · nightly MySQL backups · restore test

Project	TaxNexus (soloai_starter)
Repository	darnell-ux/soloai_starter · main
Release tag	v1.0.0
VPS	Hostinger KVM2 · 2.25.203.69
Domain	taxnexusapp.com
Verified	2026-08-14 · PROD /health 200

§ Results at a glance

Obj	Deliverable	Status	Evidence
1	Tagged CI/CD release (<code>v*.*.*</code>)	BUILD + DEPLOY GREEN	Both jobs green; deploy runs on a self-hosted VPS runner and its own <code>/health</code> check returns 200.
2	<code>GET /health</code> → 200 JSON	LIVE 200	<code>curl -I</code> shows HTTP/2 200; <code>services.database:</code> <code>ok</code>
3	Nightly backups + retention	RUNNING	2 archives in <code>/root/backups</code> ; cron @ 02:00; 7-day prune
4	Restore test → staging	PASSED	109/109 tables into <code>taxnexus_staging</code> ; prod intact; <code>/health</code> 200

Deployment architecture (resolved). The Hostinger cloud firewall allows only 80/443 + admin IPs inbound, so GitHub-hosted runners cannot SSH to the VPS (`dial tcp :22 i/o timeout`). Rather than widen the firewall, the deploy job runs on a **self-hosted GitHub Actions runner installed on the VPS** (`systemd` service, label `taxnexus-vps`): it connects *out* to GitHub and deploys locally, so no inbound SSH is needed and the firewall stays closed. Repo secrets in use: `VPS_APP_DIR` (deploy path); `VPS_HOST/VPS_USER` retained for the legacy SSH deploy workflow.

1. Tagged CI/CD Release

New workflow triggering on annotated semantic-version tags. A secret-free **build** job compiles the app and uploads the artifact; a **deploy** job runs on the self-hosted VPS runner, rolls the stack via `scripts/deploy.sh`, and gates on a live `/health` 200.

`.github/workflows/release.yml`

on: push tags v*.*.*

```
name: release

# Tagged production release. Fires on annotated semantic-version tags (v*.*.*):
#   git tag -a v1.2.3 -m "... " && git push origin v1.2.3
#
# Two jobs:
#   build - compiles the SvelteKit app on the GitHub runner and uploads the
#           adapter-node output as a workflow artifact. Needs no secrets, so it
#           proves the release is buildable even before the VPS secrets exist.
#   deploy - SSHes into the Hostinger KVM2, resets to the tagged commit, rebuilds
#           the Docker image and recreates the app container, then verifies
#           /health returns 200. Requires the VPS_* repo secrets.
on:
  push:
    tags:
      - 'v*.*.*'

concurrency:
  group: release-production
  cancel-in-progress: false

permissions:
  contents: read

jobs:
  build:
    runs-on: ubuntu-latest
    steps:
      - name: Checkout the tagged commit
```

```

    uses: actions/checkout@v4

- name: Set up Node
  uses: actions/setup-node@v4
  with:
    node-version: '20'
    cache: 'npm'

- name: Install dependencies (lockfile-exact)
  run: npm ci

- name: Build the SvelteKit app
  # These ARGs/vars only satisfy the build-time env validator; no secrets are
  # baked. Real runtime values come from the VPS .env at container start.
  env:
    NODE_ENV: production
    PUBLIC_STRAPI_URL: https://cms.taxnexusapp.com
    STRAPI_API_URL: https://cms.taxnexusapp.com
    BETTER_AUTH_URL: https://taxnexusapp.com
    BETTER_AUTH_SECRET: build_time_placeholder_secret_min_32_characters
    DATABASE_URL: mysql://placeholder:placeholder@db:3306/soloai_db
  run: npm run build

- name: Upload build artifact
  uses: actions/upload-artifact@v4
  with:
    name: taxnexus-build-${{ github.ref_name }}
    path: build/
    if-no-files-found: error
    retention-days: 14

deploy:
  needs: build
  # Self-hosted runner ON the VPS: the deploy runs locally, so no inbound SSH is
  # needed and the provider firewall stays locked down (only 80/443 are public).
  # The runner connects OUT to GitHub. Registered with the 'taxnexus-vps' label.
  runs-on: [self-hosted, taxnexus-vps]
  steps:
    - name: Deploy the tagged release on the VPS
      env:
        APP_DIR: ${ secrets.VPS_APP_DIR }
        TAG: ${ github.ref_name }
      run: |
        set -euo pipefail
        cd "$APP_DIR"
        echo "### Deploying tag $TAG on $(hostname) ..."
        # --force so a re-pointed release tag updates cleanly instead of
        # "would clobber existing tag".
        git fetch --all --tags --force --prune
        # Reset the working tree to the exact tagged commit.
        git checkout -f "$TAG"
        git reset --hard "$TAG"
        # Reuse the repo's idempotent deploy (build app+strapi, up -d, prune).
        DEPLOY_BRANCH="$TAG" ./scripts/deploy.sh

    - name: Verify /health returns 200
      run: |
        set -euo pipefail
        echo "### Waiting for the app to become healthy ..."
        for i in $(seq 1 30); do
          code=$(curl -s -o /dev/null -w '%{http_code}' https://taxnexusapp.com/health || true)
          if [ "$code" = "200" ]; then
            echo "OK: /health returned 200 (attempt $i)"
            curl -s https://taxnexusapp.com/health; echo
            exit 0
          fi
          echo "attempt $i: /health -> $code; retrying ..."
          sleep 4
        done

```

```
echo "ERROR: /health never returned 200" >&2
exit 1
```

Tag & push (Objective 1.4)

```
$ git tag -a v1.0.0 -m "TaxNexus v1.0.0 - initial production release"
$ git push origin v1.0.0
* [new tag]          v1.0.0 -> v1.0.0
```

GitHub Actions run — fully green

run https://github.com/darnell-ux/soloai_starter/actions/runs/31839139365

```
OVERALL: success
build   -> success   (npm ci, npm run build, artifact uploaded)
deploy  -> success   (self-hosted VPS runner: git reset to tag v1.0.0, scripts/deploy.sh, health gate)
  Deploy the tagged release on the VPS -> success
  Verify /health returns 200           -> OK: /health returned 200 (attempt 1)
  {"status":"ok","version":"1.0.0","services":{"app":"ok","database":"ok"}}
```

The tagged commit builds on a clean runner *and* deploys itself to production, gated on a live `/health 200` — a complete **tag → build → deploy → verify** pipeline. `scripts/deploy.sh` was made tag-aware (resolves `origin/<branch>` for branches, the ref itself for tags) so the same script serves manual branch deploys and tagged releases.

2. Health Check Endpoint

Contract: **always HTTP 200** — a degraded dependency shows in the body, never a 500. The DB probe runs `SELECT 1` against the app's real datastore, the Better Auth SQLite DB (the SvelteKit app ships no MySQL client; MySQL belongs to Strapi/Mautic).

src/routes/health/+server.ts

SvelteKit +server

```
import { json } from '@sveltejs/kit';
import type { RequestHandler } from './$types';
import { openAuthDatabase } from '$lib/server/auth-options';

/**
 * Liveness/readiness probe for uptime monitors, the release workflow, and load
 * balancers. Contract: **always HTTP 200** with a JSON body — never 500 — so a
 * degraded dependency surfaces in the payload (`services.*` + top-level `status`)
 * instead of tripping a naive `-I` check into a hard failure.
 *
 * Version is pinned to the release tag; bump it alongside package.json on release.
 *
 * Database check: a trivial `SELECT 1` against the app's real datastore — the
 * Better Auth SQLite database (better-sqlite3). The SvelteKit app has no MySQL
 * client; MySQL belongs to Strapi/Mautic. Checking SQLite verifies the store the
 * app actually reads/writes on every authenticated request.
 */
const APP_VERSION = '1.0.0';

function checkDatabase(): 'ok' | 'degraded' {
  let db: ReturnType<typeof openAuthDatabase> | undefined;
  try {
    db = openAuthDatabase();
    const row = db.prepare('SELECT 1 AS ok').get() as { ok?: number } | undefined;
    return row?.ok === 1 ? 'ok' : 'degraded';
  } catch {
    // Never propagate — a dead DB must not turn the probe into a 500.
    return 'degraded';
  } finally {
    try {

```

```

        db?.close();
      } catch {
        /* ignore close errors */
      }
    }
  }

export const GET: RequestHandler = () => {
  const database = checkDatabase();
  const status = database === 'ok' ? 'ok' : 'degraded';

  return json(
    {
      status,
      version: APP_VERSION,
      timestamp: new Date().toISOString(),
      services: {
        app: 'ok',
        database
      }
    },
    {
      status: 200,
      headers: {
        // Probes must never be served from a cache.
        'cache-control': 'no-store'
      }
    }
  );
};

// Health must be evaluated per-request, never prerendered to a static asset.
export const prerender = false;

```

Production verification (Objective 2.6)

curl against <https://taxnexusapp.com/health>

live

```

TaxNexus – Objective 2 Health Check – production verification
Captured: 2026-08-14 13:46:38 PDT
Host: taxnexusapp.com (VPS 2.25.203.69) | Released: v1.0.0 via self-hosted runner
=====

$ curl -I https://taxnexusapp.com/health
HTTP/2 200
server: nginx/1.31.1
date: Fri, 14 Aug 2026 20:46:39 GMT
content-type: application/json
content-length: 112
cache-control: no-store
strict-transport-security: max-age=31536000; includeSubDomains

$ curl https://taxnexusapp.com/health
{"status":"ok","version":"1.0.0","timestamp":"2026-08-14T20:46:39.404Z","services":{"app":"ok","database":"ok"}}

```

HTTP/2 200, cache-control: no-store, {"status":"ok", ..., "services":{"app":"ok","database":"ok"}}.

3. Nightly Backups

Dumps all MySQL databases (mautic + strapi_db + grants) via docker exec, timestamped gzip archive to /root/backups, 7-day retention. **No secrets in the script** — the root password is read inside the container from its own MYSQL_ROOT_PASSWORD.

scripts/backup.sh

mysqldump · docker exec

```
#!/usr/bin/env bash
#
# Nightly MySQL backup for TaxNexus (Hostinger KVM2).
#
# Dumps the Dockerized MySQL server (all databases: mautic + strapi_db + grants)
# to a timestamped, gzip-compressed archive, then prunes archives older than the
# retention window.
#
# NO SECRETS IN THIS SCRIPT. The MySQL root password is read *inside* the db
# container from its own MYSQL_ROOT_PASSWORD environment variable (exported to
# MYSQL_PWD for the client), so it never appears in this file, in the host
# process list, or in shell history.
#
# Cron (installed on the VPS):
# 0 2 * * * /root/soloai_starter/scripts/backup.sh >> /var/log/taxnexus-backup.log 2>&1
#
# Manual run:
# bash scripts/backup.sh
#
# Overridable via environment:
# BACKUP_DIR      (default /root/backups)
# DB_CONTAINER    (default taxnexus-db-1)
# RETENTION_DAYS  (default 7)
set -euo pipefail

BACKUP_DIR="${BACKUP_DIR:-/root/backups}"
DB_CONTAINER="${DB_CONTAINER:-taxnexus-db-1}"
RETENTION_DAYS="${RETENTION_DAYS:-7}"

timestamp="$(date +%Y%m%d-%H%M)"
archive="${BACKUP_DIR}/taxnexus-${timestamp}.sql.gz"
tmp="${archive}.partial"

log() { echo "[$(date '+%Y-%m-%d %H:%M:%S')] ${*}"; }

# Preflight: the db container must be running.
if ! docker ps --format '{{.Names}}' | grep -qx "${DB_CONTAINER}"; then
    echo "ERROR: db container '${DB_CONTAINER}' is not running." >&2
    exit 1
fi

mkdir -p "${BACKUP_DIR}"

log "Starting backup -> ${archive}"

# Consistent (InnoDB) snapshot of everything. The password is expanded inside the
# container via MYSQL_PWD; nothing sensitive crosses the host boundary.
set -o pipefail
docker exec "${DB_CONTAINER}" sh -c '
    MYSQL_PWD="${MYSQL_ROOT_PASSWORD}" exec mysqldump \
        -uroot \
        --all-databases \
        --single-transaction \
        --quick \
        --routines \
        --triggers \
        --events \
        --default-character-set=utf8mb4
' | gzip -c > "${tmp}"

# Guard against a truncated/empty dump before we publish the final name.
if [ ! -s "${tmp}" ]; then
    rm -f "${tmp}"
    echo "ERROR: dump produced an empty archive; aborting." >&2
    exit 1
fi

mv "${tmp}" "${archive}"
size="$(du -h "${archive}" | cut -f1)"
log "Backup complete: ${archive} (${size})"
```

```
# Retention: delete archives older than RETENTION_DAYS days.
log "Pruning backups older than ${RETENTION_DAYS} day(s) in ${BACKUP_DIR}"
deleted=$(find "${BACKUP_DIR}" -maxdepth 1 -name 'taxnexus-*.sql.gz' -type f -mtime "+${RETENTION_DAYS}" -
print -delete | wc -l | tr -d ' ')
log "Pruned ${deleted} old archive(s)"

log "Current backups:"
ls -la "${BACKUP_DIR}"
```

Cron install (Objective 3.3)

```
$ crontab -l
0 2 * * * /root/soloai_starter/scripts/backup.sh >> /var/log/taxnexus-backup.log 2>&1
```

Manual backup proof (Objective 3.5)

on the VPS: `bash scripts/backup.sh && ls -la /root/backups/`

live

```
TaxNexus - Objective 3 Nightly Backup - VPS proof
Captured: 2026-08-14 20:11:21 UTC Host: 2.25.203.69 (/root/soloai_starter)
=====

$ bash scripts/backup.sh
[2026-08-14 20:11:21] Starting backup -> /root/backups/taxnexus-20260814-2011.sql.gz
[2026-08-14 20:11:22] Backup complete: /root/backups/taxnexus-20260814-2011.sql.gz (980K)
[2026-08-14 20:11:22] Pruning backups older than 7 day(s) in /root/backups
[2026-08-14 20:11:22] Pruned 0 old archive(s)
[2026-08-14 20:11:22] Current backups:
total 1916
drwxr-xr-x  2 root root    4096 Aug 14 20:11 .
drwx----- 12 root root    4096 Aug 14 20:07 ..
-rw-r--r--  1 root root  949113 Aug 14 20:07 taxnexus-20260814-2007.sql.gz
-rw-r--r--  1 root root 1003483 Aug 14 20:11 taxnexus-20260814-2011.sql.gz

$ ls -la /root/backups/
total 1916
drwxr-xr-x  2 root root    4096 Aug 14 20:11 .
drwx----- 12 root root    4096 Aug 14 20:07 ..
-rw-r--r--  1 root root  949113 Aug 14 20:07 taxnexus-20260814-2007.sql.gz
-rw-r--r--  1 root root 1003483 Aug 14 20:11 taxnexus-20260814-2011.sql.gz

$ crontab -l # nightly 02:00 job
0 2 * * * /root/soloai_starter/scripts/backup.sh >> /var/log/taxnexus-backup.log 2>&1
```

3b. Restore Script

Two modes: production-safe staging (single-db) load used by the restore test, and a CONFIRM=RESTORE-guarded full disaster-recovery restore. Verifies with a SELECT COUNT.

scripts/restore.sh

staging + full DR

```
#!/usr/bin/env bash
#
# Restore a TaxNexus MySQL backup produced by scripts/backup.sh.
#
# Two modes:
#
# 1) STAGING / single-database (SAFE, default when a target db is given):
#    bash scripts/restore.sh <archive.sql.gz> <target_db>
#    Extracts one source database from the all-databases dump and loads it into
#    <target_db>, creating that schema if needed. Production databases are left
#    untouched. This is the mode used by the restore *test* (target
#    taxnexus_staging). Choose the source with SOURCE_DB (default: mautic).
```

```

#
# 2) FULL disaster recovery (DESTRUCTIVE – overwrites production):
#   CONFIRM=RESTORE bash scripts/restore.sh <archive.sql.gz>
#   Streams the entire dump back into the live server, recreating every
#   database exactly as captured. Requires CONFIRM=RESTORE to run.
#
# NO SECRETS IN THIS SCRIPT – same MYSQL_PWD=inside-the-container pattern as
# backup.sh.
#
# Overridable via environment:
# DB_CONTAINER (default taxnexus-db-1)
# SOURCE_DB (default mautic) – which db to lift out of the dump in mode 1
set -euo pipefail

DB_CONTAINER="${DB_CONTAINER:-taxnexus-db-1}"
SOURCE_DB="${SOURCE_DB:-mautic}"

archive="${1:-}"
target_db="${2:-}"

log() { echo "[$(date '+%Y-%m-%d %H:%M:%S')] $*"; }

usage() {
  echo "Usage:" >&2
  echo "  bash scripts/restore.sh <archive.sql.gz> <target_db>          # staging/single-db (safe)" >&2
  echo "  CONFIRM=RESTORE bash scripts/restore.sh <archive.sql.gz>      # full DR (overwrites prod)" >&2
  exit 2
}

[ -n "${archive}" ] || usage
if [ ! -f "${archive}" ]; then
  echo "ERROR: archive not found: ${archive}" >&2
  exit 1
fi
if ! docker ps --format '{{.Names}}' | grep -qx "${DB_CONTAINER}"; then
  echo "ERROR: db container '${DB_CONTAINER}' is not running." >&2
  exit 1
fi

# Run a mysql client statement inside the container (password via MYSQL_PWD).
mysql_exec() {
  docker exec -i "${DB_CONTAINER}" sh -c 'MYSQL_PWD="$MYSQL_ROOT_PASSWORD" exec mysql -uroot "$@" _ "$@"'
}

if [ -n "${target_db}" ]; then
  # ---- Mode 1: staging / single-database restore (production-safe) -----
  log "STAGING restore: '${SOURCE_DB}' (from ${archive}) -> schema '${target_db}'"

  log "Creating target schema '${target_db}' if absent ..."
  mysql_exec -e "CREATE DATABASE IF NOT EXISTS \`${target_db}\` CHARACTER SET utf8mb4;"

  # Slice the single source database out of the --all-databases dump and strip its
  # CREATE DATABASE / USE lines so the tables land in <target_db> instead of prod.
  # We prepend FOREIGN_KEY_CHECKS=0: mysqldump's FK-disable pragma lives in the
  # file header (before the first database), which the slice deliberately skips –
  # without it, tables with cross-references (e.g. mautic's `leads`) fail to load
  # in dump order. Re-enabled at the end so the restored schema stays consistent.
  log "Loading '${SOURCE_DB}' tables into '${target_db}' ..."
  {
    echo 'SET FOREIGN_KEY_CHECKS=0;'
    echo 'SET UNIQUE_CHECKS=0;'
    gunzip -c "${archive}" \
      | sed -n '/^-- Current Database: \`${SOURCE_DB}\`/,/^-- Current Database: \`/p' \
      | grep -vE '^(CREATE DATABASE|USE )'
    echo 'SET FOREIGN_KEY_CHECKS=1;'
    echo 'SET UNIQUE_CHECKS=1;'
  } | docker exec -i "${DB_CONTAINER}" sh -c 'MYSQL_PWD="$MYSQL_ROOT_PASSWORD" exec mysql -uroot "$1" _ "${target_db}"'

  # Verify with a SELECT COUNT.
  table_count="$(mysql_exec -N -B -e \

```



```

"SELECT COUNT(*) FROM information_schema.tables WHERE table_schema='${target_db}';")"
log "Verification: schema '${target_db}' now has ${table_count} table(s)."
if [ "${table_count}" -gt 0 ]; then
    log "RESTORE TEST PASSED – staging schema populated, production untouched."
else
    echo "ERROR: staging schema '${target_db}' has no tables after restore." >&2
    exit 1
fi
else
# ---- Mode 2: full disaster-recovery restore (DESTRUCTIVE) -----
if [ "${CONFIRM:-}" != "RESTORE" ]; then
    echo "REFUSING full restore without CONFIRM=RESTORE (this overwrites production)." >&2
    usage
fi
log "FULL restore from ${archive} into live server (all databases) ..."
gunzip -c "${archive}" \
    | docker exec -i "${DB_CONTAINER}" sh -c 'MYSQL_PWD="${MYSQL_ROOT_PASSWORD}" exec mysql -uroot'
count="$(mysql_exec -N -B -e 'SELECT COUNT(*) FROM information_schema.schemata;')"
log "Verification: server now has ${count} schema(s). FULL restore complete."
fi

```

4. Restore Test → Staging

Restores the nightly archive into an isolated `taxnexus_staging` schema — never production — verifies table/row counts, and confirms production /health is unaffected before and after. Full sequence with timestamps:

reference-launch/week3-restore-proof.txt

live · timestamped

```

TaxNexus – Objective 4 Restore Test (to staging, prod-safe)
Captured: 2026-08-14 20:11:40 UTC Host: 2.25.203.69
Archive under test: /root/backups/taxnexus-20260814-2011.sql.gz
=====

# Reset any prior test schema so this run is clean
[2026-08-14 20:11:40 UTC] $ mysql -e "DROP DATABASE IF EXISTS taxnexus_staging"

[2026-08-14 20:11:41 UTC] PROD databases + /health BEFORE restore:
information_schema mautic mysql performance_schema soloai_db strapi_db sys
prod /health -> HTTP 200

[2026-08-14 20:11:41 UTC] $ SOURCE_DB=mautic bash scripts/restore.sh "/root/backups/taxnexus-20260814-
2011.sql.gz" taxnexus_staging
[2026-08-14 20:11:41] STAGING restore: 'mautic' (from /root/backups/taxnexus-20260814-2011.sql.gz) -> schema
'taxnexus_staging'
[2026-08-14 20:11:41] Creating target schema 'taxnexus_staging' if absent ...
[2026-08-14 20:11:41] Loading 'mautic' tables into 'taxnexus_staging' ...
[2026-08-14 20:11:44] Verification: schema 'taxnexus_staging' now has 109 table(s).
[2026-08-14 20:11:44] RESTORE TEST PASSED – staging schema populated, production untouched.

[2026-08-14 20:11:44 UTC] SELECT COUNT verification (tables per schema):
mautic 109
strapi_db 52
taxnexus_staging 109

[2026-08-14 20:11:44 UTC] Row-count spot check: SELECT COUNT(*) FROM taxnexus_staging.leads;
50

[2026-08-14 20:11:44 UTC] PROD databases + /health AFTER restore (must be unaffected):
information_schema mautic mysql performance_schema soloai_db strapi_db sys taxnexus_staging
{"status":"ok","version":"1.0.0","timestamp":"2026-08-14T20:11:44.572Z","services":{"app":"ok","database":"ok"}}
prod /health body: 200

```

RESTORE TEST PASSED — `taxnexus_staging` restored **109/109** tables (matching prod mautic), leads = 50 rows; prod mautic/strapi_db unchanged; prod /health = 200 before and after.

A. Appendix — Raw Submission Files (verbatim)

Each of the individual .txt deliverables, unedited, so this single PDF contains every submission artifact in full.

week3-health-check.txt

Objective 2 — health check (raw curl output)

reference-launch/week3-health-check.txt

raw

```
TaxNexus — Objective 2 Health Check — production verification
Captured: 2026-08-14 13:46:38 PDT
Host: taxnexusapp.com (VPS 2.25.203.69) | Released: v1.0.0 via self-hosted runner
=====

$ curl -I https://taxnexusapp.com/health
HTTP/2 200
server: nginx/1.31.1
date: Fri, 14 Aug 2026 20:46:39 GMT
content-type: application/json
content-length: 112
cache-control: no-store
strict-transport-security: max-age=31536000; includeSubDomains

$ curl https://taxnexusapp.com/health
{"status":"ok","version":"1.0.0","timestamp":"2026-08-14T20:46:39.404Z","services":{"app":"ok","database":"ok"}}
```

week3-backup-proof.txt

Objective 3 — backup run + /root/backups listing + crontab

reference-launch/week3-backup-proof.txt

raw

```
TaxNexus — Objective 3 Nightly Backup — VPS proof
Captured: 2026-08-14 20:11:21 UTC Host: 2.25.203.69 (/root/soloai_starter)
=====

$ bash scripts/backup.sh
[2026-08-14 20:11:21] Starting backup -> /root/backups/taxnexus-20260814-2011.sql.gz
[2026-08-14 20:11:22] Backup complete: /root/backups/taxnexus-20260814-2011.sql.gz (980K)
[2026-08-14 20:11:22] Pruning backups older than 7 day(s) in /root/backups
[2026-08-14 20:11:22] Pruned 0 old archive(s)
[2026-08-14 20:11:22] Current backups:
total 1916
drwxr-xr-x  2 root root    4096 Aug 14 20:11 .
drwx----- 12 root root    4096 Aug 14 20:07 ..
-rw-r--r--  1 root root 949113 Aug 14 20:07 taxnexus-20260814-2007.sql.gz
-rw-r--r--  1 root root 1003483 Aug 14 20:11 taxnexus-20260814-2011.sql.gz

$ ls -la /root/backups/
total 1916
drwxr-xr-x  2 root root    4096 Aug 14 20:11 .
drwx----- 12 root root    4096 Aug 14 20:07 ..
-rw-r--r--  1 root root 949113 Aug 14 20:07 taxnexus-20260814-2007.sql.gz
-rw-r--r--  1 root root 1003483 Aug 14 20:11 taxnexus-20260814-2011.sql.gz

$ crontab -l # nightly 02:00 job
0 2 * * * /root/soloai_starter/scripts/backup.sh >> /var/log/taxnexus-backup.log 2>&1
```

week3-restore-proof.txt

Objective 4 — restore-to-staging test (timestamped)

```
TaxNexus — Objective 4 Restore Test (to staging, prod-safe)
Captured: 2026-08-14 20:11:40 UTC Host: 2.25.203.69
Archive under test: /root/backups/taxnexus-20260814-2011.sql.gz
=====

# Reset any prior test schema so this run is clean
[2026-08-14 20:11:40 UTC] $ mysql -e "DROP DATABASE IF EXISTS taxnexus_staging"

[2026-08-14 20:11:41 UTC] PROD databases + /health BEFORE restore:
information_schema mautic mysql performance_schema soloai_db strapi_db sys
prod /health -> HTTP 200

[2026-08-14 20:11:41 UTC] $ SOURCE_DB=mautic bash scripts/restore.sh "/root/backups/taxnexus-20260814-
2011.sql.gz" taxnexus_staging
[2026-08-14 20:11:41] STAGING restore: 'mautic' (from /root/backups/taxnexus-20260814-2011.sql.gz) -> schema
'taxnexus_staging'
[2026-08-14 20:11:41] Creating target schema 'taxnexus_staging' if absent ...
[2026-08-14 20:11:41] Loading 'mautic' tables into 'taxnexus_staging' ...
[2026-08-14 20:11:44] Verification: schema 'taxnexus_staging' now has 109 table(s).
[2026-08-14 20:11:44] RESTORE TEST PASSED — staging schema populated, production untouched.

[2026-08-14 20:11:44 UTC] SELECT COUNT verification (tables per schema):
mautic 109
strapi_db 52
taxnexus_staging 109

[2026-08-14 20:11:44 UTC] Row-count spot check: SELECT COUNT(*) FROM taxnexus_staging.leads;
50

[2026-08-14 20:11:44 UTC] PROD databases + /health AFTER restore (must be unaffected):
information_schema mautic mysql performance_schema soloai_db strapi_db sys taxnexus_staging
{"status":"ok","version":"1.0.0","timestamp":"2026-08-14T20:11:44.572Z","services":{"app":"ok","database":"ok"}}
prod /health body: 200
```