

Problem 4.6

Let X be the set $\{1,2,3,4,5\}$ and Y be the set $\{6,7,8,9,10\}$. We describe the functions $f : X \rightarrow Y$ and $g : X \rightarrow Y$ in the following tables. Answer each part and give a reason for each negative answer.

n	$f(n)$
1	6
2	7
3	6
4	7
5	6

n	$g(n)$
1	10
2	9
3	8
4	7
5	6

^A**a.** Is f one-to-one?

b. Is f onto?

c. Is f a correspondence?

^A**d.** Is g one-to-one?

e. Is g onto?

f. Is g a correspondence?

Problem 4.6a Answer

No, $f(1)$ and $f(3)$ are equal.

Problem 4.6b Answer

No, no input for $f(n)$ results in 8, 9, or 10 from set Y .

Problem 4.6c Answer

No, f is neither one to one or onto, therefore it is not a correspondence.

Problem 4.6d Answer

Yes, no value of n in $f(n)$ results in the same answer

Problem 4.6e Answer

Yes, every value of Y is reached.

Problem 4.6f Answer

Yes, both one to one and onto.

Problem 4.13

Let $A = \{ \langle R, S \rangle \mid R \text{ and } S \text{ are regular expressions and } L(R) \subseteq L(S) \}$. Show that A is decidable.

Problem 4.13 Answer

First construct a language $L(C) = \overline{L(S)} \cap L(R)$. Then create DFA's R_{dfa} and S_{dfa} by converting R and S . We can use R_{dfa} and S_{dfa} to construct C_{dfa} . We know that since R is a subset of S , if we intersect the complement of S with R it will result in a language consisting of the empty set. Therefore, C_{dfa} should only accept the empty string. Knowing this, we can run E_{dfa} to check if C recognizes the empty set and accept it if it does. Otherwise, reject.

Problem 4.21

Let $S = \{ \langle M \rangle \mid M \text{ is a DFA that accepts } w^R \text{ whenever it accepts } w \}$. Show that S is decidable.

Problem 4.21 Answer

"On valid input $\langle M \rangle$:

- 1) Construct an NFA M' such that $L(M') = \{ w^R \mid w \in L(M) \}$
- 2) Create DFA M'_{dfa} using M'
- 3) Use EQ_{dfa} to compare $L(M'_{dfa})$ and $L(M)$
- 4) If $L(M'_{dfa}) = L(M)$ accept; otherwise reject.

All steps can be done in a finite amount of time.