

# 1 AdaBoost

AdaBoost is a boosting algorithm developed by Yoav Freund and Robert Schapire in 1996.

## 1.1 Basics of AdaBoost

- The goal of boosting is to use a set of weak learners to create a single strong learner.
- Schapire (1990) introduced simple boosting.
- Freund (1995) built on Schapire (1995) to show that it is possible to simultaneously combine many weak learners.
- AdaBoost was invented in 1996 and the outline of the algorithm was outlined in Freund and Schapire (1997).
- AdaBoost is adaptive as weak learners are adjusted for the instances where misclassification occurred by previous classifiers
- As long as the individual classifiers are better than pure guessing, AdaBoost can provide a strong learner

## 1.2 AdaBoost Algorithm

1. Initialize  $w_i \equiv 1/n$
2. For  $m = 1, \dots, M$ 
  - (a) Fit  $g_m(x)$  on  $\mathcal{D}$ , weighted by  $w_i$
  - (b) Compute  $R_m = \frac{\sum_{i=1}^n w_i \mathbf{1}(Y_i \neq g_m(X_i))}{\sum_{i=1}^n w_i}$
  - (c) Find  $\beta_m = \log((1 - R_m)/R_m)$
  - (d) Set  $w_i \leftarrow w_i \exp\{\beta_m \mathbf{1}(Y_i \neq g_m(X_i))\}$
3. Output:  $g(x) = \text{sgn}\left(\sum_{m=1}^M \beta_m g_m(x)\right)$

*The above algorithm is also known as Discrete AdaBoost since it is using discrete labels.*

### 1.3 Simulation Results

- To illustrate the merits of AdaBoost, we will consider a particularly tricky classification example.
- A diagonal boundary between two groups is difficult for a small classification tree to handle.
- AdaBoost can combine a series of small trees to create a stronger classifier.
- In this example, we will look at "depth 2-stumps" which have no more than four terminal nodes.




Figure 1: Diagonal Decision boundary is typically difficult for classification trees to handle




Figure 2: AdaBoost refining the classification method by adapting to misclassifications




Figure 3: The misclassification rate decreases as the algorithm progresses




Figure 4: A lower misclassification rate is achieved

## 1.4 Real AdaBoost Algorithm

The AdaBoost algorithm can be modified to estimate the contribution of the  $m^{th}$  classifier, rather than the estimated label.

1. Initialize  $w_i \equiv 1/n$
2. For  $m = 1, \dots, M$ 
  - (a) Fit the classifier on  $\mathcal{D}$ , weighted by  $w_i$  and produce  $p_m(x) = \hat{P}_w(Y = 1|x)$
  - (b) Set  $g_m(x) \leftarrow \frac{1}{2} \log(p_m/(1 - p_m(x)))$
  - (c) Set  $w_i \leftarrow w_i \exp\{-Y_i g_m(X_i)\}$
3. Output:  $g(x) = \text{sgn}\left(\sum_{m=1}^M g_m(x)\right)$

## 2 Additive Models

### 2.1 Introduction

- Additive Models are a nonparametric regression method.
- We have previously modeled nonlinearity using constrained linear regression.
- Nonparametric methods form different types of local averages of the Y values of points near each other
- This can work well when p is small
- When p is large, we have to deal with the curse of dimensionality

*The Curse of Dimensionality and methods to counter the issue will be examined in the next set of notes.*