

CS2030/S Programming Methodology
Semester 1 2020/2021

11 November 2020
Problem Set #11 Suggested Answers
Asynchronous Programming

This problem set aims to let students explore the different methods provided by the `CompletableFuture` class in Java 8 or later.

1. Study the given class A below, which uses the methods `incr` and `decr` to imitate slow computations.

```
class A {
    private final int x;

    A() {
        this(0);
    }

    A(int x) {
        this.x = x;
    }

    void sleep() {
        System.out.println(Thread.currentThread().getName() + " " + x);
        try {
            Thread.sleep(1000);
        } catch (InterruptedException e) {
            System.out.println("interrupted");
        }
    }

    A incr() {
        sleep();
        return new A(this.x + 1);
    }

    A decr() {
        sleep();
        if (x < 0) {
            throw new IllegalStateException();
        }
        return new A(this.x - 1);
    }

    public String toString() {
        return "" + x;
    }
}
```

(a) Suppose we have a method

```
A foo(A a) {  
    return a.incr().decr();  
}
```

Convert the method `foo` above to a method that returns a `CompletableFuture` so that the body of the method is **executed asynchronously**. Try different variations by using

- i. `supplyAsync` only;
- ii. `supplyAsync` and **`thenApply`**;
- iii. `supplyAsync` and **`thenApplyAsync`**

Demonstrate how you would retrieve the result of the computation.

See also: `thenRun`, `thenAccept`, `runAsync`

Answer:

```
i. CompletableFuture<A> foo(A a) {  
    return CompletableFuture.supplyAsync(() -> a.incr().decr());  
}  
ii. // same as foo above  
CompletableFuture<A> foo(A a) {  
    return CompletableFuture.supplyAsync(() -> a.incr())  
        .thenApply(x -> x.decr());  
}  
iii. // decr() could be run in another thread  
CompletableFuture<A> foo(A a) {  
    return CompletableFuture.supplyAsync(() -> a.incr())  
        .thenApplyAsync(x -> x.decr());  
}
```

To wait for the result,

```
CompletableFuture<A> a = foo(new A());  
// do something else  
a.join();
```

(b) Suppose now we have another method

```
A bar(A a) {  
    return a.incr();  
}
```

which we would like to invoke using `bar(foo(new A()))`. Convert the computation within `bar` to **run asynchronously as well**. `bar` should **now return a `CompletableFuture`**. In addition, show the equivalent of calling `bar(foo(new A()))` in an asynchronous fashion, using the method `thenCompose`.

See also: `thenCombine`

```

CompletableFuture<A> bar(A a) {
    return CompletableFuture.supplyAsync(() -> a.incr());
}

CompletableFuture<A> b = foo(new A()).thenCompose(x -> bar(x));
System.out.println(b.join());

```

(c) Suppose now we have yet another method

```

A baz(A a, int x) {
    if (x == 0) {
        return new A(0);
    } else {
        return a.incr().decr();
    }
}

```

Convert the computation within `baz` in the `else` clause to run asynchronously. `baz` should now `return a CompletableFuture`. You may find the method `completedFuture` useful.

```

CompletableFuture<A> baz(A a, int x) {
    if (x == 0) {
        return CompletableFuture.completedFuture(new A(0));
    } else {
        return CompletableFuture.supplyAsync(() -> a.incr().decr());
    }
}

```

```

CompletableFuture<A> c = baz(new A(), 1);
System.out.println(c.join());

```

Note that `CompletableFuture` is a monad:

- `completedFuture` is equivalent to `of`,
- `thenCompose` is `flatMap`, and
- `thenApply` is `map`.

(d) Let's now call `foo`, `bar`, `baz` asynchronously. We would like to output the string `"done!"` when *all* three method calls complete. Show how you can use the `allOf()` method to achieve this behavior.

See also: `anyOf`, `runAfterBoth`, `runAfterEither`.

```

CompletableFuture<Void> all = CompletableFuture.allOf(
    foo(new A()),
    bar(new A()),
    baz(new A(), 1));
all.join();
System.out.println("done!");

```

- (e) Calling `new A().decr().decr()` would cause an exception to be thrown, even when it is done asynchronously. Show how you would use the `handle()` method to gracefully handle exceptions thrown (such as printing them out) within a chain of `CompletableFuture` calls.

See also: `whenComplete` and `exceptionally`

```
CompletableFuture<A> exc = CompletableFuture
    .supplyAsync(() -> new A().decr().decr())
    .handle((result, exception) -> {
        if (result == null) {
            System.out.println("ERROR: " + exception);
            return new A();
        } else {
            return result;
        }
    });

System.out.println(exc.join());
```

2. Modify the following sequences of code such that `f`, `g`, `h` and `i` are now invoked asynchronously, via `CompletableFuture`. Assume that `a` has been initialized as

```
A a = new A();
```

- (a) `B b = f(a);`
`C c = g(b);`
`D d = h(c);`

```
CompletableFuture<D> cf = CompletableFuture
    .supplyAsync(() -> f(a))
    .thenApply(b -> g(b))
    .thenApply(c -> h(c));
D d = cf.join();
```

- (b) `B b = f(a);`
`C c = g(b);`
`h(c);` // no return value

```
CompletableFuture<Void> cf = CompletableFuture
    .supplyAsync(() -> f(a))
    .thenApply(b -> g(b))
    .thenAccept(c -> h(c));
cf.join();
```

```
(c) B b = f(a);
    C c = g(b);
    D d = h(b);
    E e = i(c, d);

    CompletableFuture<B> cfb = CompletableFuture
        .supplyAsync(() -> f(a));
    CompletableFuture<C> cfc = cfb
        .thenApply(b -> g(b));
    CompletableFuture<D> cfd = cfb
        .thenApply(b -> h(b));
    CompletableFuture<E> cfe = cfc
        .thenCombine(cfd, (c, d) -> i(c, d));
    cfe.join();
```