

CS2030 Programming Methodology
Semester 1 2020/2021

2 September 2020
Problem Set #2 Suggested Guidance
Inheritance and Polymorphism

1. Study the following Point and Circle classes.

```
class Point {
    private final double x;
    private final double y;

    Point(double x, double y) {
        this.x = x;
        this.y = y;
    }
}

class Circle {

    private final Point centre;
    private final int radius;

    Circle(Point centre, int radius) {
        this.centre = centre;
        this.radius = radius;
    }

    @Override
    public boolean equals(Object obj) {
        System.out.println("equals(Object) called");
        if (obj == this) {
            return true;
        } else if (obj instanceof Circle) {
            Circle circle = (Circle) obj;
            return (circle.centre.equals(centre) && circle.radius == radius);
        } else {
            return false;
        }
    }

    boolean equals(Circle circle) {
        System.out.println("equals(Circle) called");
        return circle.centre.equals(centre) && circle.radius == radius;
    }
}
```

Given the following program fragment,

```
Circle c1 = new Circle(new Point(0, 0), 10);
Circle c2 = new Circle(new Point(0, 0), 10);
Object o1 = c1;
Object o2 = c2;
```

what is the output of the following statements?

- | | |
|-----------------------------|-----------------------------|
| (a) o1.equals(o2); | (e) c1.equals(o2); |
| (b) o1.equals((Circle) o2); | (f) c1.equals((Circle) o2); |
| (c) o1.equals(c2); | (g) c1.equals(c2); |
| (d) o1.equals(c1); | (h) c1.equals(o1); |

```
jshell> o1.equals(o2)
equals(Object) called
...
```

```
jshell> o1.equals((Circle) o2)
equals(Object) called
...
```

```
jshell> o1.equals(c2)
equals(Object) called
...
```

```
jshell> o1.equals(c1)
equals(Object) called
...
```

```
jshell> c1.equals(o2)
equals(Object) called
...
```

```
jshell> c1.equals((Circle) o2);
equals(Circle) called
...
```

```
jshell> c1.equals(c2)
equals(Circle) called
...
```

```
jshell> c1.equals(o1)
equals(Object) called
...
```

Calling the `equals` method though a reference of compile-time type `Object` would invoke the `equals(Object)` method of `Object`. This method is overridden by the overriding method in the sub-class `Circle`.

The only time that the overloaded method `equals(Circle)` can be called is when the method is invoked through a variable of compile-time type `Circle`.

The output of `true` or `false` largely depends on the presence of an overriding `equals` method in the `Point` class.

2. We would like to design a class `Square` that inherits from `Rectangle`. A square has the constraint that the four sides are of the same length.

- (a) How should `Square` be implemented to obtain the following evaluation from `JShell`?

```
jshell> new Square(5)
$3 ==> area 25.00 and perimeter 20.00

class Rectangle {
    private final double width;
    private final double height;

    Rectangle(double width, double height) {
        this.width = width;
        this.height = height;
    }

    double getArea() {
        return width * height;
    }

    double getPerimeter() {
        return 2 * (width + height);
    }

    @Override
    String toString() {
        return "area " + String.format("%.2f", getArea()) +
            " and perimeter " + String.format("%.2f", getPerimeter());
    }
}

class Square extends Rectangle {
    Square(double length) {
        super(length, length);
    }
}
```

- (b) Now implement two separate methods to set the width and height of the rectangle:

```
Rectangle setWidth(double width) { ... }
```

```
Rectangle setHeight(double height) { ... }
```

What **undesirable design issues** would this present?

*A **square can be changed to a rectangle***

```
jshell> new Square(5.0).setHeight(10.0)
$3 ==> area 50.00 and perimeter 30.00
```

- (c) Now implement two overriding methods in the **Square** class

```
@Override
Square setHeight(double height) {
    return new Square(height);
}
```

```
@Override
Square setWidth(double width) {
    return new Square(width);
}
```

Do you think that it is now **sensible for to have Square inherit from Rectangle**? Or should it be the other way around? Or maybe they should not inherit from each other?

*Based on the **substitutability principle**, if **Square inherits from Rectangle**, then **anywhere we expect a Rectangle**, we can **always substitute it with a Square**.*

Consider the following example,

```
jshell> Rectangle[] rects = {new Rectangle(3.0, 5.0), new Square(5.0)}
rects ==> Rectangle[2] { area 15.00 and perimeter 16.00, area 25.00
and perimeter 20.00 }
```

```
jshell> rects[0].setHeight(4.0).setWidth(8.0)
$4 ==> area 32.00 and perimeter 24.00
```

```
jshell> rects[1].setHeight(4.0).setWidth(8.0)
$6 ==> area 64.00 and perimeter 32.00
```

*Notice that setting **rects[1]** (of type **Rectangle**) to a height of 4.0 and a width of 8.0 **does not produce the desired rectangle**.*