- Table of Contents {:toc}

Acknowledgements

- This project is based on the AddressBook-Level3 project created by the SE-EDU initiative.

Setting up, getting started

Refer to the guide *Setting up and getting started*.

Design

💡 **Tip:** The `.puml` files used to create diagrams are in this document `docs/diagrams` folder. Refer to the *PlantUML Tutorial* at se-edu/guides to learn how to create and edit diagrams.

Architecture



The ***Architecture Diagram*** given above explains the high-level design of the App.

Given below is a quick overview of main components and how they interact with each other.

Main components of the architecture

`Main` (consisting of classes `Main` and `MainApp`) is in charge of the app launch and shut down.

- At app launch, it initializes the other components in the correct sequence, and connects them up with each other.
- At shut down, it shuts down the other components and invokes cleanup methods where necessary.

The bulk of the app's work is done by the following four components:

- `UI`: The UI of the App.
- `Logic`: The command executor.
- `Model`: Holds the data of the App in memory.
- `Storage`: Reads data from, and writes data to, the hard disk.

`Commons` represents a collection of classes used by multiple other components.

How the architecture components interact with each other

The *Sequence Diagram* below shows how the components interact with each other for the scenario where the user issues the command `delete 1`.



Each of the four main components (also shown in the diagram above),

- defines its *API* in an `interface` with the same name as the Component.
- implements its functionality using a concrete `{Component Name}Manager` class (which follows the corresponding API `interface` mentioned in the previous point.

For example, the `Logic` component defines its API in the `Logic.java` interface and implements its functionality using the `LogicManager.java` class which follows the `Logic` interface. Other components interact with a given component through its interface rather than the concrete class (reason: to prevent outside component's being coupled to the implementation of a component), as illustrated in the (partial) class diagram below.



The sections below give more details of each component.

UI component

The **API** of this component is specified in `Ui.java`



The UI consists of a `MainWindow` that is made up of several parts such as `CommandBox`, `ResultDisplay`, `PersonListPanel`, `MeetingListPanel`, and `StatusBarFooter`.

All these components, including the `MainWindow`, inherit from the abstract `UiPart` class, which captures the common functionality shared by GUI components.

The `UI` component uses the JavaFx UI framework. The layout of these UI parts are defined in matching `.fxml` files that are in the `src/main/resources/view` folder. For example, the layout of the `MainWindow` is specified in `MainWindow.fxml`

The `UI` component:

- executes user commands using the `Logic` component.
- listens for changes to `Model` data so that the UI can be updated with the modified data.
- switches between different views (`PersonListPanel` and `MeetingListPanel`) based on user interaction.
- keeps a reference to the `Logic` component, because the `UI` relies on the `Logic` to execute commands.
- depends on the `Model` component, as some `UI` component (like `MeetingItem`) needs to find the `Person` referred by a `ParticipantID`.

The `CommandHistory` component:

- keeps track of commands that the user have entered in the `CommandHistory`.
- allows the user to shift through their previously entered commands via `prevCommand()` and `nextCommand()`.

- Usage:
  1. Add commands into the history using `add()`. Internally, this also resets the index to point at the end of the list.
  2. Go to the previous command using `prevCommand()`. Note that the current draft needs to be passed in. This is because the `CommandHistory` keeps track of the user draft (the text that the user is currently editing). Internally, this method simply shifts the index to the previous command.
  3. Go to the next command using `nextCommand()`. The current draft needs to be passed in as well. Internally, this method simply shifts the index to the next command and returns the command at that position OR the draft if `index == list.size()`.
- Example usage:

```
CommandHistory ch = new CommandHistory();

// Assume the user has entered these two commands.
ch.add("first command");
ch.add("second command");

// userDraft is the text in the CommandBox.
String userDraft = "draft command";

userDraft = ch.prevCommand(userDraft); // userDraft becomes "second
command".
userDraft = ch.prevCommand(userDraft); // userDraft becomes "first command".
userDraft = ch.nextCommand(userDraft); // userDraft becomes "second
command".
userDraft = ch.nextCommand(userDraft); // userDraft becomes "draft command".
```

- `CommandHistory` sequence diagram:



Logic component

API : `Logic.java`

Here's a (partial) class diagram of the `Logic` component:



The sequence diagram below illustrates the interactions within the `Logic` component, taking `execute("delete 1")` API call as an example.



:information_source: **Note:** The lifeline for `DeleteCommandParser` should end at the destroy marker (X) but due to a limitation of PlantUML, the lifeline continues till the end of diagram.

How the `Logic` component works:

1. When `Logic` is called upon to execute a command, it is passed to an `AddressBookParser` object which in turn creates a parser that matches the command (e.g., `DeleteCommandParser`) and uses it to parse the command.
2. This results in a `Command` object (more precisely, an object of one of its subclasses e.g., `DeleteCommand`) which is executed by the `LogicManager`.
3. The command can communicate with the `Model` when it is executed (e.g. to delete a person).
   Note that although this is shown as a single step in the diagram above (for simplicity), in the code it can take several interactions (between the command object and the `Model`) to achieve.
4. The result of the command execution is encapsulated as a `CommandResult` object which is returned back from `Logic`.

Here are the other classes in `Logic` (omitted from the class diagram above) that are used for parsing a user command:



How the parsing works:

- When called upon to parse a user command, the `AddressBookParser` class creates an `XYZCommandParser` (`XYZ` is a placeholder for the specific command name e.g., `AddCommandParser`) which uses the other classes shown above to parse the user command and create a `XYZCommand` object (e.g., `AddCommand`) which the `AddressBookParser` returns back as a `Command` object.
- All `XYZCommandParser` classes (e.g., `AddCommandParser`, `DeleteCommandParser`, ...) inherit from the `Parser` interface so that they can be treated similarly where possible e.g, during testing.

Model component

API : `Model.java`



The `Model` component,

- stores the address book data i.e., all `Person` objects (which are contained in a `UniquePersonList` object) and all `Meeting` objects (which are contained in a `UniqueMeetingList` object).
- stores the currently 'selected' `Person` objects (e.g., results of a search query) as a separate *filtered* list which is exposed to outsiders as an unmodifiable `ObservableList<Person>` that can be 'observed' e.g. the UI can be bound to this list so that the UI automatically updates when the data in the list change.
- stores the currently 'selected' `Meeting` objects as a separate *filtered* list which is exposed as an unmodifiable `ObservableList<Meeting>`that can be 'observed'.
- stores a `UserPref` object that represents the user's preferences. This is exposed to the outside as a `ReadOnlyUserPref` objects.
- does not depend on any of the other three components (as the `Model` represents data entities of the domain, they should make sense on their own without depending on other components)

Storage component

API : `Storage.java`



The `Storage` component,

- can save both address book data and user preference data in JSON format, and read them back into corresponding objects.
- inherits from both `AddressBookStorage` and `UserPrefStorage`, which means it can be treated as either one (if only the functionality of only one is needed).
- depends on some classes in the `Model` component (because the `Storage` component's job is to save/retrieve objects that belong to the `Model`)

Common classes

Classes used by multiple components are in the `seedu.address.commons` package.

Implementation

This section describes some noteworthy details on how certain features are implemented.

Adding a person: `add`

The `add` command is used to insert a new person into the contacts list. The name field (`n/NAME`) must always be provided, while at least one contact detail—either phone (`p/PHONE`) or email (`e/EMAIL`)—is required. Tags (`t/TAG`) are optional.

Input processing is performed by `AddCommandParser`, which tokenizes the user input and ensures that the following conditions are met:

- Name is present
- At least one of phone or email is provided

- Required prefixes (e.g. `n/`, `p/`, `e/`, `t/`) are valid
- Preamble is empty
- All field values are valid

If any of these checks fail, a `ParseException` is thrown.

Once the input is successfully parsed, a `Person` object is instantiated. As part of its construction, a `PersonId` is generated automatically, ensuring that each person has a unique identifier.

When the command is executed, `AddCommand` invokes `Model#hasPerson(Person)` to determine if the person already exists in the contacts list. A duplicate is defined as a person with the same name, phone, and email as an existing entry.

- If a duplicate is detected, a `CommandException` is raised
- Otherwise, the person is added via `Model#addPerson(Person)` and a `CommandResult` is returned

The following sequence diagram illustrates the flow of parsing and execution for the `add` command.



Editing a person: `edit`

The `edit` command is used to edit an existing person in the contacts list. The user specifies the index of the person to edit, together with one or more fields to be updated.

Any field of a person can be modified using `edit` -- `n/NAME`, `p/PHONE`, `e/EMAIL@EMAIL.COM`, `t/TAG`.

Using edit with tags (`t/TAG`) will replace all existing tags with the new tags specified in the command. This means that all previous tags will be wiped unless they are listed out while using edit.

The edit person feature is implemented using the following main components:

- `EditCommand`
- `EditCommandParser`
- `EditPersonDescriptor`

When the user enters an edit command, the input is first handled by `AddressBookParser`, which delegates parsing to `EditCommandParser`.

`EditCommandParser` parses:

- the target index of the person to be edited
- the fields the user wants to modify

The parsed values are stored in an `EditPersonDescriptor`, which acts as a container for the optional fields provided by the user. This is necessary because the user may choose to edit only some fields instead of all fields.

After parsing, an `EditCommand` object is created with:

- the target index
- the descriptor containing the edited values

During execution, `EditCommand` retrieves the person at the specified index from the currently displayed person list. It then creates a new edited `Person` object by combining:

- the original person's existing values
- the new values from `EditPersonDescriptor` if they were specified

Fields not provided by the user remain unchanged.

Finally, the command asks the `Model` to replace the original person with the edited person. The updated person list is then reflected in the UI.

The following sequence diagram illustrates the flow of parsing and execution for the `edit` command.



Finding a Person: `find`

The find command allows the user to search for persons whose fields match given keywords. In the implementation, there are two types of find operations that reuse the same predicate `find`.

1. Global find Searches across all supported fields of a person and returns persons where any field matches the given substring

2. Field-specific filtered search Searches only within specified fields and returns persons whose value in that field matches the given substring in that specific field.

This design allows the system to support both broad and targeted searching while keeping the matching logic reusable.

Examples:

- Global find: `find alex`
- Field-specific find: `find n/alex`
- Field-specific find: `find n/alex e/gmail`

A global find checks whether the substring appears in any searchable field, while a field-specific find restricts the search to the specified field only. Field-specific find will find contacts all within the displayed contact list that matches ANY of the keywords of specified fields. For example, `find n/alex e/gmail` will find persons named 'alex' AND persons whose emails have a 'gmail' in it.

The find feature is implemented mainly using the following components:

- `FindCommand`
- `FindCommandParser`
- `PersonMatchesKeywordsPredicate`
- `ModelManager`

When the user enters a find command, `AddressBookParser` identifies the command and passes the input to `FindCommandParser`.

`FindCommandParser` determines which type of search the user is performing:

- If the user provides a plain keyword without a prefix, the parser interprets it as a global find.
- If the user provides a prefixed argument such as n/, p/, e/, or another supported prefix, the parser interprets it as a field-specific filtered search.

After parsing, the command creates a `PersonMatchesKeywordsPredicate`. Although both search modes use the same predicate class, the predicate is configured differently depending on the parsed input.

This predicate is then passed into a `FindCommand`, which updates the model's filtered person list.

The following sequence diagram illustrates the flow of parsing and execution for the `find` command.





Adding a Tag: `addtag`

The `addtag` command is used to assign tags into one or more persons in the contacts list. The index(es) (`INDEX [,INDEX...]`) and tags (`/TAG [/TAG...]`) must always be provided.

Input processing is performed by `AddTagCommandParser`, which tokenizes the user input and ensures that the following conditions are met:

- Preamble contains at least 1 index
- At least 1 tag is included in the command
- All field values are valid

If any of these checks fail, a `ParseException` is thrown.

Once the input is successfully parsed, an `AddTagCommand` instance is created with the set of tags to add and the indices of persons to add to.

The command checks the following conditions:

- If any of the indices are invalid, a `CommandException` is raised
- If no tags are provided, a `CommandException` is raised

When `AddTagCommand` is executed, it gets all the persons referred by the indices, edits their tags, and calls `Model#setPerson(person, personWithAddedTags)` to edit the address book.

The following sequence diagram illustrates the flow of parsing and execution for the `addtag` command.



Adding a Meeting: `addmeeting`

The `addmeeting` command is used to add a meeting into the address book. The meeting description (`d/DESCRIPTION`) and date (`dt/DATE`) must always be provided. Participant indices (`[INDEX,...]`) are optional. The meeting can initially have no participants and edited later using `editmeeting`. For the purpose of a `Meeting`, a "participant" is defined as a `Person` whose ID is included in the `Meeting`.

Input processing is performed by `AddMeetingCommandParser`, which tokenizes the user input and ensures that the following conditions are met:

- Description field exists
- Date field exists
- All field values are valid

If any of these checks fail, a `ParseException` is thrown.

Once the input is successfully parsed, an `AddMeetingCommand` instance is created with the set of participant's indices.

The command checks the following conditions:

- If any of the indices are invalid, a `CommandException` is raised
- If no description is provided, a `CommandException` is raised
- If no date is provided, a `CommandException` is raised

Before the meeting is added, `Model#hasMeeting(Meeting)` will be called to ensure that the meeting has not already existed in the address book. A meeting is considered a duplicate if it has the same description and date as another meeting. **Participants alone do not differentiate two meetings**.

When `AddMeetingCommand` is executed, it gets all the persons referred by the indices, gets their IDs, and adds them into the participant set. It then calls `Model#addMeeting(Meeting)` to add the meeting to the address book.

The following sequence diagram illustrates the flow of parsing and execution for the `addmeeting` command.



Documentation, logging, testing, configuration, dev-ops

- Documentation guide
- Testing guide
- Logging guide
- Configuration guide
- DevOps guide

Appendix: Requirements

Product scope

Target user profile:

- has a need to manage a significant number of contacts
- frequently arranges meetings with people they know
- need to log interactions with contacts
- prefer desktop apps over other types
- can type fast

- prefers typing to mouse interactions
- is reasonably comfortable using CLI apps

Value proposition:

- **Productivity:** Enable users to easily manage their numerous relations in a fast, distraction-free CLI.
- **Organization:** Neatly organizes information like contacts, meetings, and interaction notes all in one place, with efficient filtering and retrieval.
- **Simplicity:** A lightweight app that avoids slow, feature-heavy GUIs. Runs directly in the terminal with minimal setup.
- **Privacy:** Fully local application. No risk of data leakage or delays from network issues.

Not in our scope:

- InternLink does not send emails or messages to the contacts
- InternLink cannot automatically sync with LinkedIn or other platforms
- Internlink cannot manage the internship application

User stories

Priorities: High (must have) - * * *, Medium (nice to have) - * *, Low (unlikely to have) - *

Priority	As a	I want to	So that I can
* * *	general user	add a new person to the contact list	store new contacts
* * *	general user	delete a person from the contact list	remove entries that I no longer need
* * *	general user	list out all people in the contact list	see my saved contacts
* * *	general user	view a person's profile in the contact list with full details	access comprehensive details when needed
* * *	general user	edit information of people in the contact list	keep my records accurate
* * *	general user	add a meeting with people in the contact list	keep track of scheduled interactions
* * *	general user	delete meetings with people in the contact list	remove outdated or cancelled meetings
* * *	general user	find people in the contact list by one or multiple tags	locate people in specific categories
* *	general user	find a person in the contact list by name	locate details without going through the entire list
* *	general user	find people in the contact list by phone or email	locate contacts even without names

Priority	As a	I want to	So that I can
* *	new user	see usage instructions	refer to instructions when I forget how to use the app
* *	general user	add tags to people in the contact list en masse	categorise contacts efficiently
* *	general user	delete tags from people in the contact list en masse	keep tags up to date efficiently
* *	general user	edit a tag for people in the contact list en masse	maintain accurate categorisation efficiently
* *	general user	star or favourite people in the contact list	access important contacts quickly
* *	general user	unstar or remove favourite from people in the contact list	keep priorities updated
* *	general user	edit meetings with people in the contact list	keep meeting details up to date
* *	general user	find meetings by date or description	locate specific meetings easily
* *	general user	delete people in the contact list en masse	remove multiple entries efficiently
* *	general user	see overdue follow-ups for people in the contact list	remember to follow up
*	general user	sort people in the contact list lexicographically	locate contacts more easily
*	general user	sort meetings by date	view meetings in chronological order
*	general user	go to my last command quickly	fix mistakes faster

Use Cases

For all use cases below, the **System** is **Internlink** and the **Actor** is the **user**

Use case: UC1 - Add a contact / meeting

MSS:

1. User requests to add a new contact / meeting by providing details.
2. InternLink checks whether the contact / meeting already exists.
3. InternLink saves the contact / meeting.
4. InternLink updates the contact / meeting list.
5. Internlink reports the successful creation of contact / meeting.

Use case ends.

Extensions:

- 2a. The contact / meeting already exists.
    - 2a1. InternLink notifies the user of the duplicate person / meeting error.

      Use case resumes at step 1.
- 5a. The meeting has a date that is before the device's time.
    - 5a1. Internlink reports the successful creation of contact / meeting, and notes the date has passed.

      Use case ends.

Use case: UC2 - Delete contact(s) / meeting(s)

MSS:

1. User requests to delete one or more contact(s) / meeting(s) by index.
2. InternLink identifies the specified contact(s) / meeting(s) in the current displayed list.
3. InternLink deletes the specified contact(s) / meeting(s).
4. InternLink updates the contact / meeting list.
5. Internlink reports the successful deletion of contact / meeting.

Use case ends.

Extensions:

- 2a. One or more of the specified indices are invalid contact(s) / meeting(s).
    - 2a1. InternLink notifies the user of the invalid index error.

      Use case resumes at step 1.

Use case: UC3 - List contacts / meetings

MSS:

1. User requests to list contacts / meetings.
2. InternLink retrieves all contacts / meetings.
3. InternLink displays the contact / meeting list.

Use case ends.

Extensions:

- 3a. There are no contacts / meetings stored.
    - 3a1. InternLink displays an empty list.

      Use case ends.

Use case: UC4 - Edit contact details

MSS:

1. User requests to edit a contact by index, providing the updated contact details.
2. InternLink identifies the specified contact in the current displayed list.
3. InternLink checks whether the updated contact would duplicate an existing contact.
4. InternLink updates the contact.
5. Internlink reports the successful editing of contact.

Use case ends.

Extensions:

- 2a. The specified index is invalid.
    - 2a1. InternLink notifies the user of the invalid index error.

      Use case resumes at step 1.
- 3a. The updated contact would duplicate an existing contact (same name, email and phone).
    - 3a1. InternLink notifies the user of the duplicate person error.

      Use case resumes at step 1.

Use case: UC5 - Edit a meeting

MSS:

1. User requests to edit a meeting by index, providing the updated meeting details.
2. InternLink identifies the specified meeting in the current displayed meeting list.
3. Internlink identifies the specified contacts in the current displayed contact list.
4. InternLink checks whether the updated meeting would duplicate an existing meeting.
5. InternLink updates the meeting.
6. Internlink reports the successful editing of meeting.

Use case ends.

Extensions:

- 2a. The specified meeting index is invalid.
    - 2a1. InternLink notifies the user of the invalid meeting index error.

      Use case resumes at step 1.
- 3a. One or more specified participant indices are invalid.
    - 3a1. InternLink notifies the user of the invalid contact index error.

      Use case resumes at step 1.

- 3b. One or more specified contacts to remove are not participants in the meeting, and the contacts were specified as added in the same command (e.g., `add/1 del/1`).
    - 3b1. InternLink proceeds without those contacts.

      Use case resumes at step 4.
- 3c. One or more specified contacts to remove are not participants in the meeting, and the contacts were not added in the same command.
    - 3c1. InternLink notifies the user of the non-valid participant error.

      Use case resumes at step 1.
- 4a. The updated meeting would duplicate an existing meeting (same description and date).
    - 4a1. InternLink notifies the user of the duplicate meeting error.

      Use case resumes at step 1.
- 6a. The edited meeting has a date that is before the device's time.
    - 6a1. Internlink reports the successful editing of contact / meeting, and notes the date has passed.

      Use case ends.

Use case: UC6 - Find contacts

MSS:

1. User requests to find contacts and provides search input.
2. InternLink evaluates the current displayed contact list for contacts that have the input as substrings.
3. InternLink filters the displayed contact list to include only matching contacts.
4. InternLink displays the filtered list of contacts.
5. Internlink reports how many contacts are found.

Use case ends.

Extensions:

- 1a. User provides prefix-based input (e.g. `n/NAME`, `e/EMAIL`).
    - 1a1. InternLink restricts the search to the specified fields based on the provided prefixes.

      Use case resumes at step 2.
- 1b. User provides keyword-based input (without prefixes).
    - 1b1. InternLink treats the entire input as a single substring that is searched in contacts' name, phone, and email.

      Use case resumes at step 2.
- 4a. No contacts in the displayed contact list match the search criteria.

    - 4a1. InternLink displays an empty contact list.

      Use case ends.

Use case: UC7 - Find meetings

MSS:

1. User requests to find meetings and provides search inputs (e.g. description, date, or participant indices).
2. InternLink evaluates the current meeting list based on the provided inputs:
    - If participant indices are provided, meetings containing all specified participants are considered matches.
    - If description or date prefixes are provided (e.g. `d/`, `dt/`), meetings whose specified fields contain the given substrings are considered matches.
3. InternLink filters the meeting list to include meetings that match any of the specified prefixes.
4. InternLink displays the filtered list of meetings.
5. Internlink reports how many meetings are found.

Use case ends.

Extensions:

- 2a. One or more specified participant indices are invalid.

    - 2a1. InternLink notifies the user of the invalid index error.

      Use case resumes at step 1.

- 3a. A meeting does not satisfy any of the specified prefix conditions.

    - 3a1. InternLink excludes the meeting from the filtered meeting list.

      Use case resumes at step 4.

- 4a. No meetings in the displayed meeting list match the specified criteria.

    - 4a1. InternLink displays an empty meeting list.

      Use case ends.

Use case: UC8 - Assign tags to contacts

MSS:

1. User requests to assign one or more tags to one or more contacts by index.
2. InternLink identifies the specified contact(s).
3. InternLink adds the specified tag(s) to the selected contact(s).
4. InternLink updates the contact list.
5. InternLink reports the attempted deletion of all specified tags.

Use case ends.

Extensions:

- 2a. One or more specified indices are invalid.
    - 2a1. InternLink notifies the user of the invalid index error.

      Use case resumes at step 1.
- 3a. One or more specified tags already exist on the selected contacts.
    - 3a1. InternLink ignores the duplicate tags and adds only new tags, if any.

      Use case resumes at step 4.

Use case: UC9 - Find contacts by tag

MSS:

1. User requests to find contacts using one or more tags.
2. InternLink checks the current displayed contact list for contacts containing at least one of the specified tags.
3. InternLink filters the contact list to show matching contacts.
4. InternLink displays the matching contacts.
5. Internlink reports all results match at least one of the given tags.

Use case ends.

Extensions:

- 2a. None of the specified tags exist in the displayed contact list.
    - 2a1. InternLink notifies the user that no matching tags were found.

      Use case resumes at step 1.
- 2b. Some specified tags are invalid.
    - 2b1. InternLink ignores the invalid tags and proceeds searching for valid ones.

      Use case resumes at step 3.

Use case: UC10 - Delete tags from contacts

MSS:

1. User requests to delete one or more tags from one or more contacts by index.
2. InternLink identifies the specified contact(s).
3. InternLink removes the specified tag(s) from the selected contact(s).
4. InternLink updates the contact list.
5. InternLink reports the attempted deletion of all specified tags.

Use case ends.

Extensions:

- 2a. One or more specified indices are invalid.

    - 2a1. InternLink notifies the user of the invalid index error.

      Use case resumes at step 1.

- 3a. None of the specified tags exist on any of the selected contacts.

    - 3a1. InternLink notifies the user that the tags are not found.

      Use case resumes at step 1.

- 3b. Some specified tags do not exist on the selected contacts.

    - 3b1. InternLink ignores tags that are not present on the selected contacts and removes only applicable tags, if any.

      Use case resumes at step 4.

Use case: UC11 - Star or unstar a contact

MSS:

1. User requests to star or unstar a contact by contact indexes.
2. InternLink identifies the specified contacts.
3. InternLink updates the contact's starred status (starred or unstarred).
4. InternLink updates the contact list.
5. Internlink reports attempt to star / unstar contacts.

Use case ends.

Extensions:

- 2a. The specified index is invalid.

    - 2a1. InternLink notifies the user of the invalid index error.

      Use case resumes at step 1.

- 2b. All specified contacts are already in the target state (starred / unstarred).

    - 2b1. InternLink notifies the user that all selected contacts are already starred / unstarred.

      Use case resumes at step 1.

- 2c. Only some specified contacts are already in the target state.

    - 2c1. InternLink ignores those contacts and updates only the valid ones.

      Use case resumes at step 3.

Non-Functional Requirements

1. Should work on any *mainstream OS* as long as it has Java 17 or above installed.
2. Should be able to hold up to 1000 contacts without a noticeable sluggishness in performance for typical usage.

3. A user with above average typing speed for regular English text (i.e. not code, not system admin commands) should be able to accomplish most of the tasks faster using commands than using the mouse.
4. Search and filtering operations (including multi-tag filtering) should complete within 1 second for up to 100 contacts.
5. The system should load the application within 2 seconds with 1000 total contacts and meetings.
6. Each contact should be able to support up to 20 tags.
7. The application should automatically save changes after every successful command.
8. The application should prevent data corruption even if the program closes unexpectedly.
9. The application should try to recover all non-corrupted lines in the event of a data corruption.

Glossary

- **Mainstream OS**: Windows, Linux, Unix, MacOS.
- **Contact**: A person stored in the contact list, representing an individual such as a friend, colleague, or acquaintance.
- **Participant**: A contact associated with a meeting. Participant cards can be seen under a meeting, representing the individuals involved in that meeting.
- **Tag**: A label assigned to a contact to categorize or organize them. Examples: `friends`, `cs`, `school`, `project`. A contact may have multiple tags.
- **Meeting**: An event scheduled in the application, which may involve zero or more contacts. Each meeting contains details such as a description and a date.
- **Contact List**: The collection of all contacts currently stored in the application.
- **Displayed Contact List**: The current filtered view of contacts shown to the user (e.g., after using `find` or `findtag`).
- **Meeting List**: The collection of all meetings stored in the application.
- **Displayed Meeting List**: The current filtered view of meetings shown to the user (e.g., after using `findmeeting`).
- **Index**: A number assigned to each item in a displayed list (contacts or meetings), used to reference that item in commands.
- **Prefix**: A marker used in commands to indicate a specific field (e.g., `n/`, `p/`, `e/`, `t/`, `d/`, `dt/`).

Appendix: Effort

Overview

This project required a moderate to high level of effort. Compared to AB3, which manages only a single entity type (Person), adding an additional entity type of Meetings required us to design and integrate a new set of features while ensuring compatibility with the existing system.

Extending the Architecture

One major challenge was implementing support for multiple entity types within a structure originally designed for only one. This included:

- Designing and implementing a new Meeting entity
- Extending the model, logic, and storage components to support meetings
- Creating a separate UI view for meetings and enabling seamless switching between Contacts and Meetings

Entity Relationships

Another key challenge was creating references between entities, specifically linking contacts to meetings. Meetings can involve multiple contacts, which required us to:

- Store and manage references to existing Person objects within Meeting objects, and ensure it remains consistent when contacts are edited or deleted
- Adapt the storage layer so that these relationships can be saved and reconstructed accurately from JSON

Understanding and Adapting AB3

A further difficulty was understanding and adapting the internal architecture of AB3. Much of the effort involved reverse-engineering how entities are handled across layers (Model, Logic, Storage), especially:

- How data is parsed and validated
- How commands interact with the model
- How data is persisted in JSON format

We had to replicate and adapt these mechanisms for the new Meeting entity, including modifying the JSON storage structure (`InternlinkData.json`) to support multiple entity types while maintaining data integrity.

Conclusion

Overall, while AB3 provided a strong foundation, the effort required to extend it into a multi-entity system with additional UI functionality was considerable. As a team of four, we worked collaboratively to design, implement, and refine the application to the best of our abilities.

Appendix: Instructions for manual testing

Given below are instructions to test the app manually.

:information_source: **Note:** These instructions only provide a starting point for testers to work on; testers are expected to do more *exploratory* testing.

Launch and shutdown

1. Initial launch

    1. Download the jar file and copy into an empty folder

    2. Double-click the jar file Expected: Shows the GUI with a set of sample contacts and meetings. The window size may not be optimum.

2. Saving window preferences

    1. Resize the window to an optimum size. Move the window to a different location. Close the window.

    2. Re-launch the app by double-clicking the jar file.
    Expected: The most recent window size and location is retained.

Getting started

1. Launch the application as seen above.

2. Use the help command: `help` Expected: A help message is displayed that provides a link to the user guide.

Adding and managing contacts

1. Add a new contact with minimal required fields: `add n/Alice Tan p/91234567` Expected: A new contact named Alice Tan is added with the phone number shown.

2. Try adding a contact without a name: `add p/91234567` Expected: Error message indicating invalid command format.

3. Add another contact with tags: `add n/Bob Lee e/bob@example.com t/friend t/cs` Expected: Contact is added with email and tags.

4. Edit an existing contact: `edit 1 p/98765432 e/alice@new.com` Expected: Contact 1's phone and email are updated.

5. Try editing without specifying any fields: `edit 1` Expected: Error message indicating that at least one field must be provided.

Working with tags and favourites

1. Add tags to multiple contacts: `addtag 1, 2 / friends / cs` Expected: Tags are added to both contacts.

2. Attempt to use an invalid index: `addtag 0 / friends` Expected: Error message indicating invalid contact index.

3. Rename a tag: `edittag 1, 2 o/cs n/computer science` Expected: Tag is updated for the specified contacts.

4. Try editing a tag without specifying the old tag: `edittag 1, 2 n/computer science` Expected: Error message due to missing old tag.

5. Remove a tag: `deletetag 1 / friends` Expected: Tag is removed from contact 1.

6. Try an incorrectly formatted delete tag command: `deletetag / friends 1` Expected: Error message indicating invalid format.
7. Mark a contact as starred: `star 2` Expected: Contact 2 is marked as starred.
8. Try starring with an invalid index: `star 0` Expected: Error message indicating invalid index.
9. Remove starred marking: `unstar 2` Expected: Contact 2 is no longer marked as starred.

Searching and filtering contacts

1. List all contacts: `list` Expected: Full contact list is displayed.
2. Search for contacts globally: `find Alice` Expected: Contacts matching "Alice" are shown.
3. Try searching without a keyword: `find` Expected: Error message indicating invalid format.
4. Restore the original list with `list`.
5. Search using specific fields: `find n/Alice p/9876` Expected: Contacts matching the name or phone are shown.
6. Try mixing global and field search: `find Alice n/Bob` Expected: Error message due to mixing types of searches.
7. Restore the original list with `list`.
8. Search by tags: `findtag / friends` Expected: Contacts with the tag are displayed.
9. Try searching without specifying tags: `findtag` Expected: Error message indicating invalid format.

Managing meetings

1. Click the tab to switch from the Contacts view to the Meetings view.
2. Create a meeting with contacts: `addmeeting 1, 2 d/Project meeting dt/2026-05-26` Expected: Meeting is added with the given details.
3. Try using an invalid date format: `addmeeting d/Project meeting dt/26-05-2026` Expected: Error message indicating invalid date format.
4. Edit the meeting: `editmeeting 1 d/Updated meeting dt/2026-06-01` Expected: Meeting details are updated.
5. Try editing with an invalid date: `editmeeting 1 dt/01-06-2026` Expected: Error message indicating invalid date format.
6. List all meetings: `listmeeting` Expected: All meetings are displayed.
7. Search for meetings: `findmeeting d/updated` Expected: Matching meetings are shown.
8. Delete a meeting: `deletemeeting 1` Expected: Meeting at index 1 is deleted.

9. Try deleting with an invalid index: `deletemeeting 999` Expected: Error message indicating invalid meeting index.

Cleaning up

1. Click the tab to switch from the Meetings view back to the Contacts view.
2. Delete a contact: `delete 1` Expected: Contact at index 1 is removed.
3. Try deleting with an invalid index: `delete 999` Expected: Error message indicating invalid index.
4. Clear all data: `clear` Expected: All contacts and meetings are removed.
5. Exit the application: `exit` Expected: Application closes successfully.

Saving data

Missing file test

1. Close the application.
2. Delete `data/InternlinkData.json`.
3. Re-launch the application.

Expected: The application starts with sample data and logs that the datafile is missing.

4. Add a person: `add n/Alice Tan p/91234567`

Expected: The datafile will reappear at the same location with the sample data and the added person inside.

Corrupted file test

1. Close the application.
2. Open `data/InternlinkData.json` and introduce invalid JSON (e.g. remove a closing bracket).
3. Re-launch the application.

Expected: The application detects the corrupted file, clears all data, and starts with an empty dataset, logging that the datafile cannot be read. The `data/InternlinkData.json` file should remain untouched until a command is inputted in the application.