

# Representing and Learning Opaque Maps with Strictly Local Functions

Jane Chandlee, Jeffrey Heinz, and Adam Jardine

University of Delaware

There are several current challenges to a formal theory of how the phonological component of grammar is acquired. This research addresses the particular problem of how opaque maps can be learned from finitely many examples. The concrete result is that the learning algorithms of Chandlee [3, et seq.] and Jardine et al. [11] are shown to be able to learn (in a well-defined and provably correct sense) the six cases of under- and over-application opacity discussed in Baković's [1] typology of opaque maps. We also discuss the implications of this result for a theory of phonology, its limitations, and future efforts.

The transformation from input underlying representations to output surface representations [5, 14] can be viewed as a *map* [17]. Chandlee [3] establishes that significant classes of phonological processes belong to a small subset of regular maps. They are *k-Input Strictly Local* (*k-ISL*), so called because of their Markovian property that the output at any given point is completely determined by the most recently read *k* input symbols (cf. [16]). Chandlee [3] and Chandlee et al. [4] show how this property naturally leads to a learning algorithm (ISLFLA) for such processes, a result [11] extends with the algorithm SOSFIA. Like Gildea and Jurafsky [7], ISLFLA modifies Oncina et al.'s [13] state-merging algorithm, but unlike [7], ISLFLA's principled restrictions allows [4] to prove it learns classes of ISL functions.

The present work extends these results to maps traditionally described as the *interaction* of different phonological processes. In particular we show the opaque maps described in Baković (2007)'s typology are also *k-ISL* and therefore learnable by the ISLFLA and SOSFIA algorithms. Take, for instance, Baković's example from Bedouin Arabic, summarized in (1). As a result of the interaction, Rule (1a) is not surface true, because non-final [i]s survive in the output.

(1) Counterfeeding-on-focus in B. Arabic [1]	(2) Examples of (1) as a map
<div style="text-align: right;">/katab/</div> <div style="text-align: left;">a. <math>i \rightarrow \emptyset / \_\sigma</math>      —</div> <div style="text-align: left;">b. <math>a \rightarrow i / \_\sigma</math>      kitab    (*ktab)</div>	<div style="text-align: left;">...iC#      <math>\mapsto</math>    ...iC#</div> <div style="text-align: left;">...aC#      <math>\mapsto</math>    ...aC#</div> <div style="text-align: left;">...iCV...    <math>\mapsto</math>    ...CV...</div> <div style="text-align: left;">...aCV...    <math>\mapsto</math>    ...iCV...</div>

However, this interaction is ISL when viewed as a single map, as in (2) (other vowels and consonants are represented as Cs and Vs). The opaque examples are that /iCV/ (with /i/ being non-final) gets mapped to [CV], whereas /aCV/ is mapped to [iCV]. Both changes are decided on 3-segment input sequences, /iCV/ and /aCV/, respectively, and so the Bedouin map is ISL for  $k = 3$ . ISLFLA, for example, would learn this distinction because it would not merge the states representing the input prefixes /iC/ and /aC/, allowing the output for any /...iCV.../ and /...aCV.../ input sequences to be distinct.

These results challenge the view of phonology as optimization. It is well-known that classical OT and its variants such as Harmonic Grammar (HG) and Harmonic Serialism (HS) cannot represent all opaque maps [10, 1, 2]. In addition, OT also overgenerates: even with simple markedness and faithfulness constraints, OT predicts non-regular maps [2, 6, 15] despite the fact that available evidence suggests all phonological maps are regular [12, 9]. In contrast, the explicit hypothesis that possible phonological maps are determined by computational properties like *k-ISL* provides a better approximation to the attested typology with regard to these issues. On the other hand, like OT (and HG, HS), the current proposal does not distinguish individual processes from interacting ones.

There are limitations to the current approach. First, like other algorithms such as Recursive Constraint Demotion, it assumes the underlying forms are given, and not learned [c.f. 17]. Second, the theoretical result cannot be applied directly to natural language data because it is implicational: *if* the learning sample contains the following information *then* the map is learned. We expect, however, that properly integrating features, natural classes, and/or the output-driven property [17] will help the algorithms find the right kind of information in natural language data [c.f. 7]. Third, long-distance processes are not ISL. We expect that treating long-distance phenomena distinctly from local ones will address this [8].

Despite these limitations, this research shows that a restrictive, learnable theory of phonology that also can represent opaque maps, contra OT and its variants, is viable. This is why we believe this research represents an important step forward in understanding the nature of the phonological component of grammar and how humans come to learn it.

- [1] Eric Baković. A revised typology of opaque generalisations. *Phonology*, 24(2):217–259, 2007.
- [2] Brian Buccola. On the expressivity of Optimality Theory versus ordered rewrite rules. In *Proceedings of Formal Grammar 2012 and 2013*, volume 8036 of *Lecture Notes in Computer Science*, pages 142–158. Berlin: Springer-Verlag, 2013.
- [3] Jane Chandlee. *Strictly Local Phonological Processes*. PhD thesis, U. of Delaware, 2014.
- [4] Jane Chandlee, Rémi Eyraud, and Jeffrey Heinz. Learning strictly local subsequential functions. *Transactions of the Association for Computational Linguistics*, 2:491–503, November 2014.
- [5] Noam Chomsky and Morris Halle. *The Sound Pattern of English*. Harper & Row, 1968.
- [6] Dale Gerdemann and Mans Hulden. Practical finite state Optimality Theory. In *Proceedings of the 10th International Workshop on FSMNLP*, pages 10–19. ACL, July 2012.
- [7] Daniel Gildea and Daniel Jurafsky. Learning bias and phonological-rule induction. *Computational Linguistics*, 24(4), 1996.
- [8] Jeffrey Heinz. Learning long-distance phonotactics. *LI*, 41:623–661, 2010.
- [9] Jeffrey Heinz and William Idsardi. What complexity differences reveal about domains in language. *Topics in Cognitive Science*, 5(1):111–131, 2013.
- [10] William Idsardi. Clarifying opacity. *The Linguistic Review*, 17:199–218, 2000.
- [11] Adam Jardine, Jane Chandlee, Rémi Eyraud, and Jeffrey Heinz. Very efficient learning of structured classes of subsequential functions from positive data. In *ICGI 2014. In JMLR: Workshop and Conference Proceedings*, volume 34, pages 94–108, 2014.
- [12] Ronald Kaplan and Martin Kay. Regular models of phonological rule systems. *Computational Linguistics*, 20:331–78, 1994.
- [13] José Oncina, Pedro García, and Enrique Vidal. Learning subsequential transducers for pattern recognition tasks. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 15:448–458, May 1993.
- [14] Alan Prince and Paul Smolensky. *Optimality Theory: Constraint Interaction in Generative Grammar*. Blackwell Publishing, 2004.
- [15] Jason Riggle. *Generation, Recognition, and Learning in Finite State Optimality Theory*. PhD thesis, UCLA, 2004.
- [16] James Rogers and Geoffrey Pullum. Aural pattern recognition experiments and the subregular hierarchy. In *Tenth Meeting on Mathematics of Language*. UCLA, 2007.
- [17] Bruce Tesar. *Output-Driven Phonology: Theory and Learning*. Cambridge Studies in Linguistics, 2014.