

CS2040 Tutorial 1

Week 3, starting 22 Aug 2022

Q1 Big-O Notation

Big-O time complexity gives us an idea of the growth rate of a function. In other words, for a large input size N , as N increases, in what order of magnitude is the volume of statements executed expected to increase?

Rearrange the following functions in increasing order of their Big-O complexity. Use $<$ to indicate that the function on the left is upper-bounded by the function on the right, and $=$ to indicate that two functions have the same big-O time complexity

$4N^2$	$\log_3 N$	$20N$	$N^{2.5}$
$N^{0.00001}$	$\log(N!)$	N^N	2^N
2^{N+1}	2^{2N}	3^N	$N \log N$
$100N^{2/3}$	$\log((\log N)^2)$	$N!$	$(N-1)!$

Q2 Time Complexity Analysis

Find the tightest big-O time complexity of each of the following code fragments in terms of n

a)

```
for (int i = 1; i <= n; i++) {  
    for (int j = 0; j < n; j++)  
        System.out.print("*");  
    System.out.println();  
}
```

n^2

b)

```
for (int i = 1; i <= n; i++) {  
    for (int j = 0; j < i; j++)  
        System.out.print("*");  
    System.out.println();  
}
```

Step: 1 2 3 ... N
Op: 1 2 3 ... $N = \frac{N}{2}(1+N)$
 $O(n^2)$
 $= O(n^2)$

c)

```
for (int i = 1; i <= n; i *= 2) {  
    for (int j = 0; j < i; j++)  
        System.out.print("*");  
    System.out.println();  
}
```

Step: 1 2 4 ... $2^{\log_2 n}$
Op: 1 2 4 ... n

$O(n) \Leftarrow$

$$= \frac{1(1 - 2^{\log_2 n})}{1 - 2}$$

d)

```
ArrayList<Integer> reverse(ArrayList<Integer> items) {  
    ArrayList<Integer> copy = new ArrayList<>(); int n = items.size();  
    for (int idx = 0; idx < n; idx++) copy.add(0, items.get(idx));  
    return copy;  
}
```

Q3 Analyzing Recursive Algorithms

For recursive problems, draw out the recursive tree. For each node in the tree:

- Identify how many calls are made directly from that node
- Identify how the **problem size** decreases each call
- Indicate how much **work is done per call**, aside from other recursive calls

Calls on the same level usually have similar problem sizes. Therefore, for each level:

- Calculate the work done per level
- Calculate the height of the tree if it helps you

These may help you to evaluate the Big-O time complexity quickly.

Worked Example

```
public static long power(long x, long k, long M) {  
    if (k == 0) return 1;  
    long y = k / 2;  
    if (2 * y == k) { // even power k  
        long half = power(x, y, M); // (x^y) % M  
        return half * half % M; // [(x^y % M) (x^y % M)] % M  
    } else { // k == 2y + 1  
        long next = power(x, 2 * y, M); // (x^2y) % M  
        return x * next % M; // [x (x^2y % M)] % M  
    }  
}
```

Notice, x and M do not change, and are not useful to us. To find the next problem size, y may help.

Substituting k/2 for y and disregarding O(1) statements, the code can be **reduced** to:

```
void powerReduced(long k) {  
    if (k == 0) return; // base case, to identify leaf nodes  
    if (k % 2 == 0) powerReduced(k/2); // even k, recursive call  
    else powerReduced(k-1); // odd k, recursive call  
} // O(1) work done per call (aside from rec. calls)
```

Next, draw out the recursive tree (list, in this case, as only one call is made within another)

We here assume k is a power of 2 (e.g. 64, 1024, ...)

Level	Problem size		# mtd calls in level	Work done per call	Work done in level
	Intuitive	Based on level			
1	k	$2^{\log(k)}$	1	$O(1)$	$O(1)$
2	$k/2$	$2^{\log(k)-1}$	1	$O(1)$	$O(1)$
...					
$h-1$	2	2^1	1	$O(1)$	$O(1)$
Height h	1	2^0	1	$O(1)$	$O(1)$

How much work is done in total?

We can sum the work done in each level to get the answer.

However, since every level does $O(1)$ work, we first need to find the height h , which is $\log(k)+1$.

Therefore, time complexity is **$O(\log(k))$** .

You may ask, what happens if k is not a power of 2?

The worst case occurs when k is a ((power of 2) -1).

Every call to `powerReduced(x)` results in a call to `powerReduced(x-1)` and `powerReduced((x-1)/2)`

Each call does $O(1)$ work aside from other recursive calls

The height (length) of the list is $2\log(k) + 1$

Therefore, the time complexity is still $O(\log(k))$.

Your Turn!

a)

```
boolean lookHere(ArrayList<Integer> items, int value) {
    int n = items.size();
    return lookHere(items, value, 0, n - 1);
}

boolean lookHere(ArrayList<Integer> items, int value, int low, int hi) {
    if (low > hi) return false;
    int mid = (low + hi) / 2;
    // do some O(1) stuff
    if (items.get(mid) > value)
        return lookHere(items, value, low, mid - 1);
    return lookHere(items, value, mid + 1, hi);
}
```

b)

```
void lookHere(ArrayList<Integer> items, int value) {
    int n = items.size();
    lookHere(items, value, 0, n - 1);
}

void lookHere(ArrayList<Integer> items, int value, int low, int hi) {
    if (low > hi) return;
    int mid = (low + hi) / 2;
    // do some O(1) stuff
    lookHere(items, value, low, mid - 1);
    lookHere(items, value, mid + 1, hi);
}
```

Question 4 (Online Discussion) – Unangry Teams

Answers for online discussion questions will NOT be given out. Your tutor may go through this question if there is time. Discuss these questions on piazza before/after the tutorial!

There are **N** people standing in a line and some of them are angry! You are given the array of the anger of these **N** people, `true` being angry. Find the number of groups of adjacent people in which no one angry is inside the group:

```
int numUnangryTeams(boolean[] angryPeople)
```

e.g. `numUnangryTeams({T, F, F, F, T, F, F}) == 9`

What is the time and space complexity of a brute force solution to solve this algorithm?

Can you think of any better solution than the brute force one?