



LEGEND - WALL TYPES	
Reference image	Description
	Wall 01 - Existing Brickwork Varying thickness brickwork at thickness as shown with plaster and paint on both sides (unless specified otherwise) and prepared for final finish as per Wall Finishes Schedule.
	Wall 02 - New Brickwork Varying thickness brickwork at thickness as shown with plaster and paint on both sides (unless specified otherwise) and prepared for final finish as per Wall Finishes Schedule.
	Wall 03 - Gyproc Rhinoboard 1 layer Gyproc Rhinoboard 12.5mm fixed to both sides of the framework using Gyproc Rhinoboard Sharp Point Screws 3.5mm diameter x 25mm at maximum 220mm centres. All joints shall be staggered. In wet areas replace face layer of Gyproc Rhinoboard 12.5mm with Gyproc MoistureResistant 12.5mm. Framework consisting of Dorn UltraSTEEL Studs 63.5mm x 35mm friction fitted into top and bottom Dorn UltraSTEEL Track 63.5mm x 25mm at 600mm centres. Apply Gyproc Rhinotape to all joints and internal corners. Install Dorn Corner Bead to all external corners. Skim all taped joints with Gyproc Rhinoflute, as per manufacturer's specifications. Wall to be prepared for final finish as per Wall Finishes Schedule.
	Wall 04 - Reinforced Concrete New reinforced concrete as per structural engineers details and specifications.

NOTES:

- 1 DRYWALL HEIGHTS (this drawing is to be read in conjunction with the Ceiling Plan)
- 2 REINFORCING OF DRYWALLS
- all drywalls to extend over shopfronts, doors and windows to height as indicated elsewhere, and be reinforced with min. 38mm x stud thickness PAR SA Pine posts and lintols at all openings accommodating windows, doors and shopfronts
- all drywalls to be reinforced with min. 22mm thick plywood to wall void (inside studs and track) where joinery, fittings and fixtures will be fixed into walls

General Notes

- The design on this drawing is copyright and remains the property of SVA International (Pty) Ltd. Reg No 2011/13726807
- All work to be carried out in strict accordance with local authority requirements, National Building Regulations, and the S.A.B.S standards.
- This drawing may not be scaled. Only figured dimensions and levels may be used.
- All relevant details, levels, and dimensions must be checked on site before commencement of work. Any discrepancies to be reported to the Architects office immediately

Revisions	Rev	Date	Issued by	Description
1	2025-10-07	1	Issued for Costing	1 Issued for Team Input
2	2025-10-07	2		

