

Spring boot : AOP

AOP (Aspect Oriented Programming)

- In simple term, It helps to Intercept the method invocation. And we can perform some task before and after the method.
- AOP allow us to focus on business logic by handling boilerplate and repetitive code like logging, transaction management etc.
- So, Aspect is a module which handle this repetitive or boilerplate code.
- Helps in achieving reusability, maintainability of the code.

Used during:

- Logging
- Transaction Management
- Security etc..

Dependency you need to add in pom.xml:


```
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-aop</artifactId>
</dependency>
```

Report Abuse

```
@RestController
@RequestMapping(value = "/api/")
public class Employee {

    @GetMapping(path = "/fetchEmployee")
    public String fetchEmployee(){
        return "item fetched";
    }
}
```

```
2024-06-16T23:03:38.117+05:30 INFO 18746 --- [           main] org.hibernate.Version                    : HHH000412: Hibernate ORM core version 6.4.4.Final
2024-06-16T23:03:38.137+05:30 INFO 18746 --- [           main] o.h.e.i.RegionFactoryInitiator          : HHH000024: Second-level cache disabled
2024-06-16T23:03:38.137+05:30 INFO 18746 --- [           main] o.s.o.j.p.SpringPersistenceUnitInfo      : No LoadTimeWeaver setup: ignoring JPA class transformer
2024-06-16T23:03:38.139+05:30 INFO 18746 --- [           main] o.s.o.t.j.p.TomcatPlatformInitiator       : HHH000499: No JTA platform available (set 'hibernate.transaction.jta.platform' to 'true' if you want to use JBoss Seam's JBoss TransactionManager)
2024-06-16T23:03:38.139+05:30 INFO 18746 --- [           main] j.LocalContainerEntityManagerFactoryBean   : Initialized 'org.hibernate.jpa.EntityManagerFactory' bean with name 'entityManagerFactory' (default)
2024-06-16T23:03:38.440+05:30 WARN 18746 --- [           main] o.s.b.a.CONFIGURATION$PlaceholderConfiguration : spring.jpa.open-in-view is enabled by default. Therefore, database queries may be performed during a view's lifecycle. If this causes problems, set spring.jpa.open-in-view=false in your application configuration.
2024-06-16T23:03:38.452+05:30 INFO 18746 --- [           main] o.s.b.w.embedded.tomcat.TomcatWebServer  : Tomcat started on port 8080 (http) with context path ''
2024-06-16T23:03:38.457+05:30 INFO 18746 --- [           main] o.c.l.SpringbootApplication               : Started SpringbootApplication in 1.577 seconds (process running for 1.727)
```



```
2024-06-16T23:03:38.237+05:30 INFO 18746 --- [           main] o.s.o.j.p.SpringPersistenceUnitInfo      : No LoadTimeWeaver setup: ignoring JPA class transformer
2024-06-16T23:03:38.237+05:30 INFO 18746 --- [           main] o.s.o.t.j.p.TomcatPlatformInitiator       : HHH000499: No JTA platform available (set 'hibernate.transaction.jta.platform' to 'true' if you want to use JBoss Seam's JBoss TransactionManager)
2024-06-16T23:03:38.440+05:30 WARN 18746 --- [           main] o.s.b.a.CONFIGURATION$PlaceholderConfiguration : spring.jpa.open-in-view is enabled by default. Therefore, database queries may be performed during a view's lifecycle. If this causes problems, set spring.jpa.open-in-view=false in your application configuration.
2024-06-16T23:03:38.452+05:30 INFO 18746 --- [           main] o.s.b.w.embedded.tomcat.TomcatWebServer  : Tomcat started on port 8080 (http) with context path ''
2024-06-16T23:03:38.457+05:30 INFO 18746 --- [           main] o.c.l.SpringbootApplication               : Started SpringbootApplication in 1.577 seconds (process running for 1.727)
2024-06-16T23:03:38.457+05:30 INFO 18746 --- [           main] o.s.web.servlet.DispatcherServlet         : Initializing Servlet 'dispatcherServlet'
2024-06-16T23:03:38.457+05:30 INFO 18746 --- [           main] o.s.web.servlet.DispatcherServlet         : Completed initialization in 1 ms
Inside beforeMethod Aspect
```

Some important AOP concepts :

```
@Component
@Aspect
public class LoggingAspect {
    Access-modifiers: optional and can be omitted
    Return type: optional but can not be omitted
    @Before("execution(public String com.conceptandcoding.learningspringboot.Employee.fetchEmployee())")
    public void beforeMethod(){
        System.out.println("inside beforeMethod Aspect");
    }
}
```

This is a pointcut

This @Before and method together is called Advice

Pointcut:

Its an Expression, which tells where an ADVICE should be applied.

Types of Pointcut:

1. Execution: matches a particular method in a particular class.
- ```
@Before("execution(public String com.conceptandcoding.learningspringboot.Employee.fetchEmployee())")
```

→ (\*) wildcard : matches any single item

Matches any return type

```
@Before("execution(* com.conceptandcoding.learningspringboot.Employee.fetchEmployee())")
public void beforeMethod(){
 System.out.println("inside beforeMethod Aspect");
}
```

Matches any method with single parameter String

```
@Before("execution(* com.conceptandcoding.learningspringboot.Employee.*(String))")
public void beforeMethod(){
 System.out.println("inside beforeMethod Aspect");
}
```

Matches fetchEmployee method that take any single parameter

```
@Before("execution(String com.conceptandcoding.learningspringboot.Employee.fetchEmployee(..))")
public void beforeMethod(){
 System.out.println("inside beforeMethod Aspect");
}
```

→ (..) wildcard : matches 0 or More item

Matches fetchEmployee method that take any 0 or More parameters

```
@Before("execution(String com.conceptandcoding.learningspringboot.Employee.fetchEmployee(..))")
public void beforeMethod(){
 System.out.println("inside beforeMethod Aspect");
}
```

Matches fetchEmployee method in 'com.conceptandcoding' package and subpackage classes

```
@Before("execution(String com.conceptandcoding..fetchEmployee(..))")
public void beforeMethod(){
 System.out.println("inside beforeMethod Aspect");
}
```

Matches any method in 'com.conceptandcoding' package and subpackage classes

```
@Before("execution(String com.conceptandcoding..*(..))")
public void beforeMethod(){
 System.out.println("inside beforeMethod Aspect");
}
```

2. Within: matches all method within any class or package.

→ This pointcut will run for each method in the class Employee

```
@Before("within(com.conceptandcoding.learningspringboot.Employee)")
```

→ This pointcut will run for each method in this package and subpackage

```
@Before("within(com.conceptandcoding.learningspringboot..*)")
```

3. @within: matches any method in a class which has this annotation.

```
@RestController
@RequestMapping(value = "/api/")
public class Employee {

 @Autowired
 EmployeeUtil employeeUtil;

 @GetMapping (path = "/fetchEmployee")
 public String fetchEmployee(){
 employeeUtil.employeeHelperMethod();
 return "item fetched";
 }
}
```

```
@Aspect
@Component
public class LoggingAspect {

 @Before("@within(org.springframework.stereotype.Service)")
 public void beforeMethod() {
 System.out.println("inside beforeMethod aspect");
 }
}

@Service
public class EmployeeUtil {

 public void employeeHelperMethod() {
 }
}
```

```
}
```

```
System.out.println("employee helper method called");
}

2024-06-22T11:54:02,459+05:30 INFO 66918 --- [main] c.c.l.SpringBootTestApplication : Started SpringbootApplication in 1.646 s
2024-06-22T11:54:04,070+05:30 INFO 66918 --- [nio-8080-exec-1] o.a.c.c.C.[Tomcat].[localhost].|/ : Initializing Spring DispatcherServlet 'dispatcherServlet'
2024-06-22T11:54:04,070+05:30 INFO 66918 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet'
2024-06-22T11:54:04,070+05:30 INFO 66918 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 0 ms
```

#### 4. `@annotation:` matches any method that is annotated with given annotation

```
@RestController
@RequestMapping(value = "/api/")
public class Employee {

 @GetMapping (path = "/fetchEmployee")
 public String fetchEmployee(){
 return "item fetched";
 }
}
```

```
@Component
@Aspect
public class LoggingAspect {

 @Before("@annotation(org.springframework.web.bind.annotation.GetMapping)")
 public void beforeMethod(){
 System.out.println("inside beforeMethod Aspect");
 }
}
```

#### 5. `Args:` matches any method with particular arguments (or parameters)

```
@Before("args(String,int)")
```

```
@RestController
@RequestMapping(value = "/api/")
public class Employee {

 @Autowired
 EmployeeUtil employeeUtil;

 @GetMapping (path = "/fetchEmployee")
 public String fetchEmployee(){
 employeeUtil.employeeHelperMethod(str: "xyz", val: 123);
 return "item fetched";
 }
}
```

```
@Aspect
@Component
public class LoggingAspect {

 @Before("args(String, int)")
 public void beforeMethod() {
 System.out.println("inside beforeMethod aspect");
 }
}
```

```
@Service
public class EmployeeUtil {

 public void employeeHelperMethod(String str, int val) {
 System.out.println("employee helper method called");
 }
}
```

```
2024-06-22T11:54:27,250+05:30 INFO 66918 --- [main] org.hibernate.jpa.internal.util.LogHelper : HHH000392: Processing PersistenceUnitInfo { name: default, ... }
2024-06-22T11:54:27,250+05:30 INFO 66918 --- [main] org.hibernate.Version : HHH000422: Hibenate Core 6.1.2.Final
2024-06-22T11:54:27,309+05:30 INFO 66918 --- [main] o.a.c.i.Interval_RestrictionInitiator : HHH000032: Second-level cache is enabled
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [main] o.a.c.p.i.SpringPresentationUnitInfo : No LoadTimeResolver setup is present in the application, therefore it's disabled
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [main] o.a.c.p.i.SpringPresentationUnitInfo : No LoadTimeResolver setup is present in the application, therefore it's disabled
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [main] org.hibernate.boot.registry.StandardServiceRegistryBuilder : Initialized ServiceRegistry [StandardServiceRegistryBuilder]
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [main] org.hibernate.jpa.boot.jaxb.ConfigurationAndMetadataBootstrapListener : spring.jpa.open-in-view is active
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [main] o.a.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8080
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [main] o.a.b.w.embedded.tomcat.TomcatWebServer : ContextLoaderListener: contextInitialized()
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [main] o.a.c.c.C.[Tomcat].[localhost].|/ : Initializing Spring DispatcherServlet 'dispatcherServlet'
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet'
2024-06-22T11:54:27,414+05:30 INFO 66918 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 0 ms
```

If instead of primitive type, we need object, then we can give like this

```
@Before("args(com.conceptandcoding.learningspringboot.Employee)")
```

#### 6. `@args:` matches any method with particular parameters and that parameter class is annotated with particular annotation.

```
@Before("args(org.springframework.stereotype.Service)")
```

```
@Service
public class EmployeeUtil {

 public void employeeHelperMethod(EmployeeDAO employeeDAO) {
 System.out.println("employee helper method called");
 }
}
```

```
@Aspect
@Component
public class LoggingAspect {

 @Before("args(org.springframework.stereotype.Service)")
 public void beforeMethod() {
 System.out.println("inside beforeMethod aspect");
 }
}
```

```
@Service
public class EmployeeDAO { }
```

#### 7. `target:` matches any method on a particular instance of a class.

```
@RestController
@RequestMapping(value = "/api/")
public class Employee {

 @Autowired
 EmployeeUtil employeeUtil;

 @GetMapping (path = "/fetchEmployee")
 public String fetchEmployee(){
 employeeUtil.employeeHelperMethod();
 return "item fetched";
 }
}
```

```
@Aspect
@Component
public class LoggingAspect {

 @Before("target(com.conceptandcoding.learningspringboot.EmployeeUtil)")
 public void beforeMethod() {
 System.out.println("inside beforeMethod aspect");
 }
}
```

```
@Component
public class EmployeeUtil {

 public void employeeHelperMethod() {
 System.out.println("employee helper method called");
 }
}
```

Interface

```

 @Before("target(com.conceptandcoding.learningspringboot.IEmployee)")

 @RestController
 @RequestMapping(value = "/api/")
 public class EmployeeController {
 @Autowired
 @Qualifier("tempEmployee")
 IEmployee employeeObj;

 @GetMapping (path = "/fetchEmployee")
 public String fetchEmployee(){
 employeeObj.fetchEmployeeMethod();
 return "item fetched";
 }
 }

 @Aspect
 @Component
 public class LoggingAspect {
 @Before("target(com.conceptandcoding.learningspringboot.IEmployee)")
 public void beforeMethod() {
 System.out.println("inside beforeMethod aspect");
 }
 }

 public interface IEmployee {
 public void fetchEmployeeMethod();
 }

 @Component
 @Qualifier("tempEmployee")
 public class TempEmployee implements IEmployee {
 @Override
 public void fetchEmployeeMethod() {
 System.out.println("in temp Employee fetch method");
 }
 }

 @Component
 @Qualifier("permaEmployee")
 public class PermanentEmployee implements IEmployee {
 @Override
 public void fetchEmployeeMethod() {
 System.out.println("inside permanent fetch employee method");
 }
 }

```

```

2024-06-22T12:12:42.485+05:30 INFO 67695 --- [main] c.c.l.SpringbootApplication : Started SpringbootApplication
2024-06-22T12:12:48.192+05:30 INFO 67695 --- [nio-8080-exec-1] o.a.c.c.C.[Tomcat].[localhost].[] : Initializing Spring DispatcherServlet
2024-06-22T12:12:48.192+05:30 INFO 67695 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet'
2024-06-22T12:12:48.193+05:30 INFO 67695 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 1 ms
inside beforeMethod aspect
in temp Employee fetch method

```

Combining two pointcuts using:

&& (boolean and)  
|| (boolean or)

```

 @RestController
 @RequestMapping(value = "/api/")
 public class EmployeeController {
 @Autowired
 EmployeeUtil employeeUtil;

 @GetMapping (path = "/fetchEmployee")
 public String fetchEmployee(){
 return "item fetched";
 }
 }

 @Aspect
 @Component
 public class LoggingAspect {
 @Before("execution(* com.conceptandcoding.learningspringboot.EmployeeController.*())"
 + " && @within(org.springframework.web.bind.annotation.RestController)")
 public void beforeAndMethod() {
 System.out.println("inside beforeAndMethod aspect");
 }

 @Before("execution(* com.conceptandcoding.learningspringboot.EmployeeController.*())"
 + " || @within(org.springframework.stereotype.Component)")
 public void beforeOrMethod() {
 System.out.println("inside beforeOrMethod aspect");
 }
 }

```

```

2024-06-22T13:02:39.698+05:30 INFO 70500 --- [nio-8080-exec-1] o.a.c.c.C.[Tomcat].[localhost].[] : Initializing Spring DispatcherServlet 'dispatcherServlet'
2024-06-22T13:02:39.698+05:30 INFO 70500 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet'
2024-06-22T13:02:39.699+05:30 INFO 70500 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 1 ms
inside beforeAndMethod aspect
inside beforeOrMethod aspect

```

Named Pointcuts

```

 @RestController
 @RequestMapping(value = "/api/")
 public class EmployeeController {
 @Autowired
 EmployeeUtil employeeUtil;

 @GetMapping (path = "/fetchEmployee")
 public String fetchEmployee(){
 return "item fetched";
 }
 }

 @Aspect
 @Component
 public class LoggingAspect {
 @Pointcut("execution(* com.conceptandcoding.learningspringboot.EmployeeController.*())")
 public void customPointcutName() {
 //always stays empty
 }

 @Before("customPointcutName()")
 public void beforeMethod() {
 System.out.println("inside beforeMethod aspect");
 }
 }

```

localhost:8080/api/fetchEmployee

```

item fetched

```

```

2024-06-22T13:07:37.055+05:30 WARN 70647 --- [main] JpaBaseConfiguration$JpaWebConfiguration : spring.jpa.open-in-view is enabled by default. This warning is displayed for tests using Spring Boot Actuator. @Profile("actuator") or @AutoConfigureTestDatabase(exclude = JpaBaseConfiguration.class) to disable.
2024-06-22T13:07:37.254+05:30 INFO 70647 --- [main] o.s.b.w.embedded.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path ''
2024-06-22T13:07:37.264+05:30 INFO 70647 --- [main] c.c.l.SpringbootApplication : Started SpringbootApplication in 1.526 seconds (�)
2024-06-22T13:07:41.084+05:30 INFO 70647 --- [nio-8080-exec-1] o.a.c.c.C.[Tomcat].[localhost].[] : Initializing Spring DispatcherServlet 'dispatcherServlet'
2024-06-22T13:07:41.085+05:30 INFO 70647 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet'
2024-06-22T13:07:41.085+05:30 INFO 70647 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 0 ms
inside beforeMethod aspect

```

#### Advice:

Its an action, which is taken @Before or @After or @Around the method execution.

```

@Component
@Aspect
public class LoggingAspect {

 @Before("execution(public String com.conceptandcoding.learningspringboot.Employee.fetchEmployee())")
 public void beforeMethod(){
 System.out.println("inside before Method Aspect");
 }
}

```

@Before or @After: its simple and we have already seen

**@Around:**

As the name says, it surrounds the method execution (before and after both).

```

@RestController
@RequestMapping(value = "/api/")
public class EmployeeController {

 @Autowired
 EmployeeUtil employeeUtil;

 @GetMapping (path = "/fetchEmployee")
 public String fetchEmployee(){
 return "item fetched";
 }
}

@Component
public class LoggingAspect {

 @Around("execution(* com.conceptandcoding.learningspringboot.EmployeeUtil.*())")
 public void aroundMethod(ProceedingJoinPoint joinPoint) throws Throwable {
 System.out.println("inside before Method aspect");
 joinPoint.proceed();
 System.out.println("inside after Method aspect");
 }
}

@Component
public class EmployeeUtil {

 public void employeeHelperMethod() {
 System.out.println("employee helper method called");
 }
}

```

localhost:8080/api/fetchEmployee

item fetched

```

2024-06-22T16:25:39.014+05:30 INFO 79523 --- [main] c.c.l.SpringbootApplication : Started SpringbootApplication in 0.014 seconds (JVM: 0.014s)
2024-06-22T16:25:41.031+05:30 INFO 79523 --- [nio-8080-exec-1] o.a.c.c.C.[Tomcat].[localhost].[] : Initializing Spring DispatcherServlet
2024-06-22T16:25:41.031+05:30 INFO 79523 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet'
2024-06-22T16:25:41.032+05:30 INFO 79523 --- [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 1 ms
inside before Method aspect
fetching employee details
inside after Method aspect

```

**Join Point:** Its generally considered a point, where actual method invocation happens.

**By now, few questions we all should have:**

1. How this interception works?
2. What if we have 1000s of pointcut, so whenever I invoke a method, does matching happens with 1000s of pointcuts?

**Let's understand the AOP flow, to get an answer of above doubts:**

1. When Application startup happens
  - Look for @Aspect annotation Classes
  - Parse the Pointcut Expression
    - Done by *PointcutParser.java* class
  - Stored in a efficient data structure or cache after parsing.
- Look for @Component, @Service @Controller etc.. annotation Classes
- For each class, it check if its eligible for interception based on pointcut expression
  - Done by *AbstractAutoProxyCreator.java* class
- If yes, it creates a Proxy using JDK Dynamic proxy or CGLIB proxy
 

This proxy class, has code, which execute advice before the method, then method execution happens and after than advice if any.

Now, when we initiate the Request after application startup, this Proxy class is actually invoked.

### 1. Parse the Pointcut Expression

```

public Pointcut parsePointcutExpression(String expression, Class<?> inScope, PointcutParameter[] formalParameters)
 PointcutExpressionImpl pcExpr = null;

 try {
 Pointcut pc = this.resolvePointcutExpression(expression, inScope, formalParameters);
 pc = this.concretizePointcutExpression(pc, inScope, formalParameters);
 this.validateAgainstSupportedPrimitives(pc, expression);
 pcExpr = new PointcutExpressionImpl(pc, expression, formalParameters, this.getWorld());
 return pcExpr;
 } catch (ParserException var6) {
 throw new IllegalArgumentException(this.buildUserMessageFromParserException(expression, var6));
 } catch (ReflectionWorld.ReflectionWorldException var7) {
 throw new IllegalArgumentException(var7.getMessage());
 }
}

```

### 2. Create Proxy class (either JDK Dynamic proxy or CGLIB proxy) if required for the class


```

protected Object wrapIfNecessary(Object bean, String beanName, Object cacheKey) {
 if (StringUtil.hasLength(beanName) && this.targetSourceBeans.contains(beanName)) {
 targetSourceBeans.size();
 return bean;
 } else if (Boolean.FALSE.equals(this.advisedBeans.get(cacheKey))) {
 return bean;
 } else if (this.isInfrastructureClass(bean.getClass()) && this.shouldSkip(bean.getClass(), beanName)) {
 Object[] specificInterceptors = this.getAdvisorsAndAdvisorsForBean(bean.getClass(), beanName, null);
 if (specificInterceptors != NO_PROXY) {
 this.advisedBeans.put(cacheKey, Boolean.TRUE);
 Object proxy = this.createProxy(bean.getClass(), beanName, specificInterceptors, new SingletonTargetSource(bean));
 specificInterceptors[0].postProcess(proxy, proxy.getClass());
 return proxy;
 } else {
 this.advisedBeans.put(cacheKey, Boolean.FALSE);
 return bean;
 }
 } else {
 this.advisedBeans.put(cacheKey, Boolean.FALSE);
 return bean;
 }
}

```

Application startup success

### 3. Invoke the request, which need Advice to be run.



4. Now, request actually tries to call Proxy Class, so it invokes either CGLIB proxy class or JDK proxy class

