



GR VertiQ
SOLUTION SARL

**THE FUTURE OF
VERTICAL MOBILITY**



About Us



At GR VertiQ, we redefine urban mobility. We are a premier provider of advanced elevators and escalators solutions, dedicated to keeping this rapid world moving smoothly, safely, and efficiently. From architectural marvels to residential spaces, we are engineering seamless vertical transport systems that blend cutting-edge technology with elegant design.

we have Supply, installed, and maintained high-performance elevators and escalators for commercial, residential, and industrial sectors.

Core Strengths



All kinds of passenger elevators



High-speed passenger elevators



Rapid-response service and maintenance team



Eco-friendly public transit escalators

GR **VertiQ**
SOLUTION SARL

Elevator Ride



Safe and Reliable Travel.

Automatic emergency levelling device in case of power failure

When a power off during running, the automatic emergency leveling device can run the car to the nearest level position in a timely manner, so that passengers can safely leave the elevator.

Permanent magnet synchronous gearless traction machine, Reliable and durable

The power capacity is larger, the temperature rise is better than the national standard.

It provides 2.5 times the rated load braking torque, and a higher transmission efficiency.

The brake is tested by 15 million times.

Microcomputer control system, Stable operation

The new generation of dual 32-bit control system adopts CANBUS communication, direct docking, distance control and other technologies, ensuring stable operation, safety and reliability.

Permanent magnet door machine, Rapid and steady

The torque is greater, the efficiency is higher, and the operation stability and sensitivity are better.

The curtain light can make rapid response to any person or object when entering into the detection area.

The door system (door lock+ door machine) has passed 12 million times reliability tests.

Technology of preventing car's unintended movement, Safe leveling

The precision of car leveling detection can be up to millimeter without mistake, so that the passengers easily get in and out. The reliable car leveling memory technology ensures that the elevator stops in advance and the leveling is safe.


Security Components, Full Protection

The safety gear adopts symmetrical wedge block to avoid the occurrence of the car shaking while using unilateral wedge braking, and reduce the damage to the guide rail.

Full load and full speed hydraulic buffer with longer service life.

Car positioning technology, Safe arrival

The abnormal sliding between the wire rope and the traction wheel is effectively eliminated, and the possibility of returning to the home station by accident is reduced to a minimum.





**Commercial
Escalators**



**Heavy Duty
Escalators**

Handrail Color



Black (Standard)



Gray (Optional)

Frame



C-Type Plastic Frame



C-Type Spraying Frame

Balustrade Color




Transparent (Standard)




Gray (Optional)

Comb Teeth



Yellow Plastic (Standard)




Aluminum (Optional)

Skirt Panel Brush Lighting



White (Optional)



Blue (Optional)

Floor Plate



Stainless Steel Square
Patch (Indoor ladder
standard)



Aluminum Patch
(Outdoor optional)

Handrail Lighting



Enclosed along the
handrail (optional)



Silk screen glass sleek
(optional)

Running Direction Indicator



Transparent Plastic LED
Display (Optional)



Black Plastic Dot Matrix
Display (Optional)

Step



Black Stainless Steel C-Type
Plastic Frame (Standard
Configuration for Indoor escalator)




Silver Grey Aluminum Alloy Spraying
C-Type Frame(Standard
Configuration for Outdoor escalator)



Black Aluminum Alloy (Optional)

Arrangements




Single unit arrangement

Particularly suitable for transporting passengers between two floor levels, where passenger flow is in one direction, although on-demand starting can be utilized to allow travel in both two directions.

Continuous arrangement (one travel direction)

Mainly suitable for small department stores, between three sales floor levels. More space required than the interrupted arrangement.




Interrupted arrangement (one travel direction)

Passengers have to make a short detour to the next escalator, strategically placed displays alongside the route of this detour can help to increase sales by encouraging impulse buying.

Multi-level parallel arrangement (interrupted traffic, two travel directions)


Mainly used in department stores and public buildings with a heavy traffic flow. When there are three or more escalators, the possibility to reverse the direction of travel of both escalators depending on the usage or traffic flow. This arrangement is economical, since no decorative truss cladding required.



Multi-level criss-cross arrangement (continuous traffic flow, two travel directions)

Mainly used in major department stores, public buildings and public transport buildings, reduce congestion at the landing area by separating upwards and downwards travelling passengers

General Layout Drawing Data



Standard Specification and Dimension

	a	HL	DL	ML	UL	FL	PL	AH	BH	SH	SL	-	a	b	c	d	e	f	g	h
900	35°	900	2240	14282XH	2665	590	4100	738	738	230	5950+1.4282XT	2	600	1140	1200	838	1718	1200	4	1078
1000	35°	1000	2240	14282XH	2665	540	4100	819	819	230	5950+1.4282XT	2	800	1340	1400	1038	1918	1400	5	1278
	35°	1000	2240	14282XH	2665	540/605	4100	866/881	866/881	230	5950+1.4282XT	2	1000	1540	1600	1238	2118	1600	6	1478
900	35°	900	2640	14282XH	3065	590	4500	738	738	230	6350+1.4282XT	3								
1000	35°	1000	2640	14282XH	3065	540	4500	819	819	230	6350+1.4282XT	3								
	35°	1000	2640	14282XH	3065	540/605	4500	866/881	866/881	200	6350+1.4282XT	3								
900	30°	900	2195	17321XH	2570	590	4300	735	735	200	6554+1.7321XT	2								
1000	30°	1000	2195	17321XH	2570	540	4300	866	866	200	6554+1.7321XT	2								
	30°	1000	2195	17321XH	2570	540/605	4300	913/927	913/927	200	6554+1.7321XT	2								
900	30°	900	2595	17321XH	2970	590	4700	785	785	200	6554+1.7321XT	3								
1000	30°	1000	2595	17321XH	2970	540	4700	866	866	200	6554+1.7321XT	3								
	30°	1000	2595	17321XH	2970	540/605	4700	913/927	913/927	200	6554+1.7321XT	3								

Reacting Force

	(KN)	
600	R1=0.0035xL+15.5 R2=0.0035xL+10 R3=0.0037xL+8	R1=0.0037xL2+15.5 R2=0.0037xL1+10 R3=0.0037xL+8
800	R1=0.004xL+17 R2=0.004xL+10 R3=0.0042xL+9	R1=0.0042xL2+17 R2=0.0042xL1+10 R3=0.0042xL+9
1000	R1=0.0045xL+18.5 R2=0.0045xL+11.5	R1=0.0047xL2+18.5 R2=0.0047xL1+11.5 R3=0.0047xL+10

Standard Functional Feature



Brake detection protection	Brake arm detection switch executes real-time monitor to brake opening / closing. If the brake does not open by the requirements, the system will not start the elevator.
Protection of none door opening outside door zone	Automatic door opening is forbidden under none door zone condition.
Low-speed protection	It prevents elevator from low-speed running outside the control range causing any safety problem(s).
Prompt of overload alarm	Before the elevator shuts the door, if it detects overload signal, the elevator doors keep opening and overload buzzer rings and overload light is on. After it removes overload problem, it re-starts automatically.
Automatic parking in trouble	When the elevator stops in none leveling zone due to any trouble, if it is not caused by safety device action, it executes self-rescue running towards the middle floor direction at low speed. It parks and opens the door at the nearest service floor to prevent from any trapping accident.
Overspeed protection	With the star-delta brake function, the elevator system can limit the speed well even in case of forced brake releasing.
Unintended car movement protection (UCMP)	When the landing door isn't locked and the car door isn't closed, the elevator is equipped with a device which can stop unintended movements of the car leaving the landing caused by any failed part of the traction machine or drive control system for the safe operation of the car.
Checking the short circuit of door locks	It will check whether the landing door lock or car door lock has a short circuit every time when the elevator stops at a landing and opens the door. If any, the elevator will report the failure and stop until the failure is removed.
Fire-fighting return	When the fire-fighting switch closes, the system enters into fire-fighting return. The system will remove all the landing calls and car command signals, and it automatically returns to fire-fighting home landing, and the door keeps open. If the elevator is operating in reverse direction, it will stop at the nearest storey but won't open the door, then back to fire station and no longer running, the door will keep opening.
Home landing elevator locking	When the elevator is under automatic condition, when it shuts home landing locking switch, the elevator will complete all the registered car command services, automatically return to home landing, it enters into parking condition. As soon as locking switch is on, it immediately returns from parking condition and goes into normal running.
Cancellation of the error register	If the passenger presses the car command button at certain floor and has registered it by mistake, (by then the car indicating lamp is bright), if under the condition of none elevator running, the passenger only double-click the car command button at the same floor to cancel the register. (By then the car indicating lamp out.)
Automatic correction of floor signal	If the floor display position has error, after the system detects terminal switch in the travel, it will automatically correct the floor display.
Cancellation of the reverse command(s) in the car	When the elevator travels to the farthest floor and changes the speed, it removes all the car command register.
Self-diagnostic embedded call button	If on certain storey, the call button was pressed over certain time but not disconnected, the system assumes that it is embedded button. It does not register the landing call of the same floor afterwards. Responsive lamp which corresponds to the button keeps flickering for alarming. When the button disconnects, it exits from above condition.
Re-leveling function	If the elevator parks on the current floor, when too many passengers enter into / leave the elevator, the car is separated from the leveling zone because of wire rope extension or shortening. The elevator will then travel to the leveling position at low speed under the condition of door-opening.

Healthy Elevator Ride (Optional)




Car UV Disinfection



After the elevator has been unused for a certain period of time, it communicates and controls with the elevator to automatically light up the ultraviolet lamp for disinfection and sterilization. Ultraviolet rays can disinfection and sterilization various common pathogenic bacteria, with a sterilization rate of more than 99%, providing passengers with a safe and clean elevator environment.





Negative Ion Fresh Air System



Automatically releasing negative ions, adsorbing small dust particles, oxidizing foreign objects in the air, purifying the air, and caring for human health.

Car Air Purifier



Automatic dust removal and sterilization, clean and pollution-free, keeping the air inside the elevator car clean and hygienic at all times. The automatic operation time can be set, which is energy-saving and environmentally friendly.





📍 Cité Mourtada 2 Sipres Bande,
verte lot 104, VDN, Dakar 25000,
Senegal, West Africa.

✉ marketing@grvertiq.com

🌐 www.grvertiq.com

☎ +221 711 200 277